



# Cjevaste stopice

sa plastičnom čahurom  
DIN 46228, dio 4

- Cjevčica: Cu, galvanski pocinčana.
- Bez halogena.

Presjek mm <sup>2</sup>	Boja prema DIN 47002	l <sub>1</sub>	l <sub>2</sub>	d <sub>1</sub>	s <sub>1</sub>	d <sub>2</sub>	s <sub>2</sub>	Art.-Nr.	Pak./kom.
0,50	bijela	12,0	6,0	1,0	0,15	2,6	0,25	<b>557 300 051</b>	500, 1000
		14,0	8,0					<b>557 300 052*</b>	100, 500, 1000
		16,0	10,0					<b>557 300 053</b>	500
0,75	siva	12,0	6,0	1,2	0,15	2,8	0,25	<b>557 300 751</b>	500, 1000
		14,0	8,0					<b>557 300 752*</b>	100, 500, 1000
		16,0	10,0					<b>557 300 753</b>	500, 1000
		18,0	12,0					<b>557 300 754</b>	100
1,00	crvena	12,0	6,0	1,4	0,15	3,0	0,25	<b>557 300 101</b>	500, 1000
		14,0	8,0					<b>557 300 102*</b>	100, 500, 1000
		16,0	10,0					<b>557 300 103</b>	500, 1000
		18,0	12,0					<b>557 300 104</b>	500
1,50	crna	14,0	8,0	1,7	0,15	3,5	0,25	<b>557 300 151*</b>	100, 500, 1000
		16,0	10,0					<b>557 300 152</b>	500, 1000
		24,0	18,0					<b>557 300 153</b>	500
2,50	plava	14,0	8,0	2,2	0,15	4,2	0,25	<b>557 300 251*</b>	100, 500, 1000
		18,0	12,0					<b>557 300 252</b>	500, 1000
		24,0	18,0					<b>557 300 253</b>	500
4,00	siva	17,0	10,0	2,8	0,20	4,8	0,30	<b>557 300 401*</b>	100, 1000
		20,0	12,0					<b>557 300 402</b>	100, 1000
		26,0	18,0					<b>557 300 403</b>	100
6,00	žuta	20,0	12,0	3,5	0,20	6,3	0,30	<b>557 300 601*</b>	100, 500
		26,0	18,0					<b>557 300 602</b>	100, 500
10,00	crvena	22,0	12,0	4,5	0,20	7,6	0,40	<b>557 300 105*</b>	100, 500
		28,0	18,0					<b>557 300 106</b>	100, 500
16,00	plava	24,0	12,0	5,8	0,20	8,8	0,40	<b>557 300 161*</b>	100, 500
		28,0	18,0					<b>557 300 162</b>	100, 500
25,00	žuta	30,0	16,0	7,3	0,20	11,2	0,40	<b>557 300 254*</b>	50, 200
		36,0	22,0					<b>557 300 255</b>	50
35,00	crvena	30,0	16,0	8,3	0,20	12,7	0,40	<b>557 300 351*</b>	50, 200
		39,0	25,0					<b>557 300 352</b>	50
50,00	plava	36,0	20,0	10,3	0,30	15,0	0,50	<b>557 300 501*</b>	50
		40,0	25,0					<b>557 300 502</b>	50

\* Standardna dužina