

Zebra VDE odvijač / EN 60900, IEC 900

▲ 1000 V



- Komadno ispitivanje u vodenoj kupki s ispitnim naponom od 10 kV.
- Za radove pod naponom do 1000 V (AC) odnosno 1500 V (DC).
- Oznaka s godinom proizvodnje. Poštreno ispitivanje na postojanost kod udara u hladnom stanju.



VDE odvijač Ravni

Oštrica: brunirana, izolirana.
 Prihvat: DIN 5264-A, ISO 2380, konusna oštrica.
 Norma: DIN 7437, IEC 900, EN 60900.

 a mm b mm	 A mm	 B/C mm	 b inch A inch	Art.-Nr.	
0,4 x 2,5	80	83/27	3/32 x 3 1/8"	0613 631 025	1
0,5 x 3,0	100	83/27	1/8 x 4"	0613 631 03	
0,6 x 3,5	100	83/27	1/8 x 4"	0613 631 035	
0,8 x 4,0	100	83/27	5/32 x 4"	0613 631 04	
1,0 x 5,5	125	96/31	7/32 x 5"	0613 631 055	
1,2 x 6,5	150	106/35	1/4 x 6"	0613 631 065	
1,2 x 8,0	175	114/38	5/16 x 7"	0613 631 08	
1,6 x 8,0	200	114/38	5/16 x 8"	0613 631 082	
1,6 x 10,0	200	114/38	3/8 x 8"	0613 631 10	



VDE odvijač Krstasti (PH)

Oštrica: brunirana, izolirana.
 Prihvat: DIN 5260-PH, ISO 8764-PH.
 Norma: DIN 7438, IEC 900, EN 60900.

	 A mm	 B/C mm	 A inch	Art.-Nr.	
PH 0	80	83/27	3 1/8"	0613 632 0	1
PH 1	80	96/31	3 1/8"	0613 632 1	
PH 2	100	106/35	4"	0613 632 2	
PH 3	150	114/38	6"	0613 632 3	
PH 4	200	114/38	8"	0613 632 4	