according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BATTERY TERMINAL SPRAY - 150 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 14.03.2024

 13.0
 13.05.2024
 10785796-00016
 Date of first issue: 11.06.2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : BATTERY TERMINAL SPRAY - 150 ML

Product code : 0890104

Unique Formula Identifier

(UFI)

: JGSE-70DN-7001-D6UG

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Professional use product Corrosion inhibitor

Recommended restrictions

on use

Not applicable

1.3 Details of the supplier of the safety data sheet

Company : Adolf Wuerth GmbH & Co. KG

Reinhold-Würth-Str. 12-17

74653 Künzelsau

Telephone : +49 794015 0

Telefax : +49 794015 10 00

E-mail address of person

responsible for the SDS

isi@wuerth.com

1.4 Emergency telephone number

+49 (0)6132 - 84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BATTERY TERMINAL SPRAY - 150 ML

Version Revision Date: SDS Number: Date of last issue: 14.03.2024 13.0 13.05.2024 10785796-00016 Date of first issue: 11.06.2010

Specific target organ toxicity - single ex-

posure, Category 3

H336: May cause drowsiness or dizziness.

Long-term (chronic) aquatic hazard, Cat-

egory 3

H412: Harmful to aquatic life with long lasting ef-

fects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms





Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition

source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

Storage:

P410 + P412 Protect from sunlight. Do not expose to tem-

peratures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

Methyl acetate

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Hydrocarbons, C9, aromatics

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BATTERY TERMINAL SPRAY - 150 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 14.03.2024

 13.0
 13.05.2024
 10785796-00016
 Date of first issue: 11.06.2010

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No.	Classification	Concentration (% w/w)
	Index-No.		(/0/)
	Registration number		
Dimethyl ether	115-10-6	Flam. Gas 1A; H220	>= 30 - < 50
	204-065-8	Press. Gas Liquefied	
	603-019-00-8	gas; H280	
Mothyl gostoto	01-2119472128-37	STOT SE 3; H336 Flam. Liq. 2; H225	>= 10 - < 20
Methyl acetate	79-20-9 201-185-2	Eye Irrit. 2; H319	>= 10 - < 20
	607-021-00-X	STOT SE 3; H336	
	007 021 00 X	EUH066	
Hydrocarbons, C6-C7, n-alkanes,	Not Assigned	Flam. Liq. 2; H225	>= 2,5 - < 10
isoalkanes, cyclics, <5% n-		Skin Irrit. 2; H315	
hexane	01-2119475514-35	STOT SE 3; H336	
		Asp. Tox. 1; H304	
		Aquatic Chronic 2; H411	
Hydrocarbons, C7, n-alkanes,	64742-49-0	Flam. Liq. 2; H225	>= 2,5 - < 10
isoalkanes, cyclics	04742-43-0	Skin Irrit. 2; H315	/= 2,5 - < 10
iodantarios, cycnos	01-2119475515-33	STOT SE 3; H336	
		Asp. Tox. 1; H304	
		Aquatic Chronic 2;	
		H411	
Hydrocarbons, C9, aromatics	128601-23-0	Flam. Liq. 3; H226	>= 2,5 - < 10
		STOT SE 3; H336	
	01-2119455851-35	STOT SE 3; H335	
		Asp. Tox. 1; H304	
		Aquatic Chronic 2; H411	
		EUH066	
		2011000	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BATTERY TERMINAL SPRAY - 150 ML

Version Revision Date: SDS Number: Date of last issue: 14.03.2024 13.0 13.05.2024 10785796-00016 Date of first issue: 11.06.2010

When symptoms persist or in all cases of doubt seek medical

advice.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with plenty of water

for at least 15 minutes while removing contaminated clothing

and shoes.

Get medical attention. Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water

for at least 15 minutes.

If easy to do, remove contact lens, if worn.

Get medical attention.

If swallowed, DO NOT induce vomiting.

Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes skin irritation.

Causes serious eye irritation. May cause drowsiness or dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

: Flash back possible over considerable distance. Vapours may form explosive mixtures with air.

Exposure to combustion products may be a hazard to health.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BATTERY TERMINAL SPRAY - 150 ML

Version Revision Date: SDS Number: Date of last issue: 14.03.2024 13.0 13.05.2024 10785796-00016 Date of first issue: 11.06.2010

If the temperature rises there is danger of the vessels bursting

due to the high vapor pressure.

Hazardous combustion prod- :

ucts

Carbon oxides

5.3 Advice for firefighters

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.

Use personal protective equipment.

Follow safe handling advice (see section 7) and personal pro-

tective equipment recommendations (see section 8).

6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g. by containment or oil

barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.

Soak up with inert absorbent material.

Suppress (knock down) gases/vapours/mists with a water

spray jet.

For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor-

bent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to deter-

mine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BATTERY TERMINAL SPRAY - 150 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 14.03.2024

 13.0
 13.05.2024
 10785796-00016
 Date of first issue: 11.06.2010

certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If advised by assessment of the local exposure potential, use

only in an area equipped with explosion-proof exhaust ventila-

tion.

Advice on safe handling : For outdoor use only

Do not get on skin or clothing.

Avoid breathing spray. Do not swallow. Do not get in eyes.

Wash skin thoroughly after handling.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as-

sessment

Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

Take precautionary measures against static discharges.

Take care to prevent spills, waste and minimize release to the

environment.

Do not spray on an open flame or other ignition source.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye

flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contami-

nated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Store locked up. Keep tightly closed. Keep in a cool, wellventilated place. Store in accordance with the particular national regulations. Do not pierce or burn, even after use. Keep

cool. Protect from sunlight.

Advice on common storage : Do not store with the following product types:

Self-reactive substances and mixtures

Organic peroxides Oxidizing agents Flammable solids Pyrophoric liquids Pyrophoric solids

Self-heating substances and mixtures

Substances and mixtures, which in contact with water, emit

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BATTERY TERMINAL SPRAY - 150 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 14.03.2024

 13.0
 13.05.2024
 10785796-00016
 Date of first issue: 11.06.2010

flammable gases Explosives

Gases

Storage class (TRGS 510) : 2B

Recommended storage tem: :

perature

< 40 °C

Further information on stor-

age stability

Protect from frost, heat and sunlight.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Dimethyl ether	115-10-6	TWA	1.000 ppm	2000/39/EC
			1.920 mg/m3	
	Further inform	nation: Indicative		
		AGW	1.000 ppm	DE TRGS
			1.900 mg/m3	900
	Peak-limit: ex	cursion factor (categ	ory): 8;(II)	
		MAK	1.000 ppm	DE DFG MAK
			1.900 mg/m3	
	Peak-limit: ex	cursion factor (categ	ory): 8; II	
			re no data for an assessmen	t of damage to
	the embryo or	foetus, including de	velopmental neurotoxicity, or	the currently
	available data	are not sufficient for	r classification in one of the g	roups A - C
Methyl acetate	79-20-9	AGW	200 ppm	DE TRGS
			620 mg/m3	900
	Peak-limit: excursion factor (category): 2;(I)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			nd biological
		MAK	100 ppm	DE DFG MAK
			310 mg/m3	
	Peak-limit: ex	cursion factor (categ	ory): 4; I	
	Further inform	nation: Damage to th	e embryo or foetus is unlikely	when the
	MAK value or	the BAT value is ob	served	
Isobutane	75-28-5	AGW	1.000 ppm	DE TRGS
			2.400 mg/m3	900
	Peak-limit: excursion factor (category): 4;(II)			
		MAK	1.000 ppm	DE DFG MAK
			2.400 mg/m3	
	Peak-limit: excursion factor (category): 4; II			

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BATTERY TERMINAL SPRAY - 150 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 14.03.2024

 13.0
 13.05.2024
 10785796-00016
 Date of first issue: 11.06.2010

	Further information: Either there are no data for an assessment of damage to the embryo or foetus, including developmental neurotoxicity, or the currently available data are not sufficient for classification in one of the groups A - C			
Hydrocarbons, C6- C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	Not As- signed	AGW	700 mg/m3	DE TRGS 900
		cursion factor (categ	• , , ,	
	Further inform	nation: Group exposu	ure limit for hydrocarbon solv	
Hydrocarbons, C7, n-alkanes, isoal- kanes, cyclics	64742-49-0	TWA	500 ppm 2.085 mg/m3	2000/39/EC
	Further information: Indicative			
		AGW	500 ppm 2.100 mg/m3	DE TRGS 900
	Peak-limit: excursion factor (category): 1;(I)			
Hydrocarbons, C9, aromatics	128601-23- 0	AGW	50 mg/m3	DE TRGS 900
	Peak-limit: excursion factor (category): 2;(II)			
	Further inform	nation: Group exposi	ure limit for hydrocarbon solv	ent mixtures
Propane	74-98-6	AGW	1.000 ppm 1.800 mg/m3	DE TRGS 900
	Peak-limit: excursion factor (category): 4;(II)			
		MAK	1.000 ppm 1.800 mg/m3	DE DFG MAK
	Peak-limit: excursion factor (category): 4; II Further information: Either there are no data for an assessment of damage to			•
				t of damage to
	the embryo or foetus, including developmental neurotoxicity, or the currently available data are not sufficient for classification in one of the groups A - C			

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Hydrocarbons, C7, n-	64742-49-0	heptan-2,5-dione:	Immediately after	TRGS 903
alkanes, isoalkanes, cy-		250 μg/l	exposure or after	
clics		(Urine)	working hours	

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Methyl acetate	Workers	Inhalation	Long-term systemic effects	610 mg/m3
	Workers	Inhalation	Long-term local effects	305 mg/m3
	Workers	Skin contact	Long-term systemic effects	88 mg/kg bw/day
	Consumers	Inhalation	Acute local effects	131 mg/m3
	Consumers	Inhalation	Long-term local effects	152 mg/m3
	Consumers	Skin contact	Long-term systemic effects	44 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic	44 mg/kg

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BATTERY TERMINAL SPRAY - 150 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 14.03.2024

 13.0
 13.05.2024
 10785796-00016
 Date of first issue: 11.06.2010

			effects	bw/day
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Workers	Inhalation	Long-term systemic effects	2085 mg/m3
	Workers	Skin contact	Long-term systemic effects	300 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	447 mg/m3
	Consumers	Skin contact	Long-term systemic effects	149 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	149 mg/kg bw/day
Dimethyl ether	Workers	Inhalation	Long-term systemic effects	1894 mg/m3
	Consumers	Inhalation	Long-term systemic effects	471 mg/m3
Hydrocarbons, C6- C7, n-alkanes, isoal- kanes, cyclics, <5% n-hexane	Workers	Inhalation	Long-term systemic effects	2035 mg/m3
	Workers	Skin contact	Long-term systemic effects	773 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	608 mg/m3
	Consumers	Skin contact	Long-term systemic effects	699 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	699 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment Value	
Methyl acetate	Fresh water	0,12 mg/l
	Marine water	0,012 mg/l
	Freshwater - intermittent	1,2 mg/l
	Sewage treatment plant	600 mg/l
	Fresh water sediment	0,128 mg/kg dry weight (d.w.)
	Marine sediment	0,013 mg/kg dry weight (d.w.)
	Soil	0,042 mg/kg dry weight (d.w.)
	Oral (Secondary Poisoning)	20,4 mg/kg food
Dimethyl ether	Fresh water	0,155 mg/l
	Marine water	0,016 mg/l
	Intermittent use/release	1,549 mg/l
	Sewage treatment plant	160 mg/l
	Fresh water sediment	0,681 mg/kg dry weight (d.w.)
	Marine sediment	0,069 mg/kg dry weight (d.w.)
	Soil	0,045 mg/kg dry weight (d.w.)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BATTERY TERMINAL SPRAY - 150 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 14.03.2024

 13.0
 13.05.2024
 10785796-00016
 Date of first issue: 11.06.2010

8.2 Exposure controls

Engineering measures

Minimize workplace exposure concentrations.

If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Personal protective equipment

Eye/face protection : Wear the following personal protective equipment:

Safety goggles

Equipment should conform to DIN EN 166

Hand protection

Material : Nitrile rubber
Break through time : 480 min
Glove thickness : 0,45 mm

Directive : Equipment should conform to DIN EN 374

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Wear the following personal protective equipment:

If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic

protective clothing.

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

Respiratory protection : If adequate local exhaust ventilation is not available or expo-

sure assessment demonstrates exposures outside the rec-

ommended guidelines, use respiratory protection.

Equipment should conform to DIN EN 137

Filter type : Self-contained breathing apparatus

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : Aerosol containing a liquefied gas

Propellant : Dimethyl ether, Isobutane, Propane, Butane

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BATTERY TERMINAL SPRAY - 150 ML

Version Revision Date: SDS Number: Date of last issue: 14.03.2024 13.0 13.05.2024 10785796-00016 Date of first issue: 11.06.2010

Colour : dark blue

Odour : characteristic

Odour Threshold : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling :

range

40 °C

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper

flammability limit

32,0 %(V)

Lower explosion limit / Lower

flammability limit

1,1 %(V)

Flash point : -26 °C

Flash point is only valid for liquid portion in the aerosol can.

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : substance/mixture is non-soluble (in water)

Viscosity

Viscosity, kinematic : < 7 mm2/s (40 °C)

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

Not applicable

Vapour pressure : Not applicable

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BATTERY TERMINAL SPRAY - 150 ML

Version Revision Date: SDS Number: Date of last issue: 14.03.2024 13.0 13.05.2024 10785796-00016 Date of first issue: 11.06.2010

Density : 0,84 g/cm³ (20 °C)

Method: DIN 51757

Relative vapour density : Not applicable

Particle characteristics

Particle size : Not applicable

9.2 Other information

Explosives : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Evaporation rate : Not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Extremely flammable aerosol.

Vapours may form explosive mixture with air.

If the temperature rises there is danger of the vessels bursting

due to the high vapor pressure.

Can react with strong oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of : Inhalation

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BATTERY TERMINAL SPRAY - 150 ML

Version Revision Date: SDS Number: Date of last issue: 14.03.2024 13.0 13.05.2024 10785796-00016 Date of first issue: 11.06.2010

exposure Skin contact

Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Components:

Dimethyl ether:

Acute inhalation toxicity : LC50 (Rat): 164000 ppm

Exposure time: 4 h
Test atmosphere: gas

Methyl acetate:

Acute oral toxicity : LD50 (Rat): 6.482 mg/kg

Acute inhalation toxicity : LC50 (Rabbit): > 49,2 mg/l

Exposure time: 4 h Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 25,2 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Acute oral toxicity : LD50 (Rat): > 5.840 mg/kg

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 23,3 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2.800 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: Based on data from similar materials

Hydrocarbons, C9, aromatics:

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BATTERY TERMINAL SPRAY - 150 ML

Version Revision Date: SDS Number: Date of last issue: 14.03.2024 13.0 13.05.2024 10785796-00016 Date of first issue: 11.06.2010

Acute oral toxicity : LD50 (Rat, female): 3.492 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 6,193 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rabbit): > 3.160 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Skin corrosion/irritation

Causes skin irritation.

Components:

Methyl acetate:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rabbit

Method : OECD Test Guideline 404

Result : Skin irritation

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Species : Rabbit Result : Skin irritation

Remarks : Based on data from similar materials

Hydrocarbons, C9, aromatics:

Assessment : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

Methyl acetate:

Species : Rabbit

Method : OECD Test Guideline 405

Result : Irritation to eyes, reversing within 7 days

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rabbit

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BATTERY TERMINAL SPRAY - 150 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 14.03.2024

 13.0
 13.05.2024
 10785796-00016
 Date of first issue: 11.06.2010

Result : No eye irritation

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Species : Rabbit

Result : No eye irritation

Remarks : Based on data from similar materials

Hydrocarbons, C9, aromatics:

Species : Rabbit

Result : No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Test Type : Buehler Test Exposure routes : Skin contact Species : Guinea pig Result : negative

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative

Remarks : Based on data from similar materials

Hydrocarbons, C9, aromatics:

Test Type : Maximisation Test Exposure routes : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Dimethyl ether:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BATTERY TERMINAL SPRAY - 150 ML

Version Revision Date: SDS Number: Date of last issue: 14.03.2024 13.0 13.05.2024 10785796-00016 Date of first issue: 11.06.2010

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Genotoxicity in vivo : Test Type: Sex-linked recessive lethal test in Drosophila mel-

anogaster (in vivo)

Application Route: inhalation (gas)

Result: negative

Methyl acetate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: negative

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Rat

Application Route: Inhalation Method: OECD Test Guideline 474

Result: negative

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Rat

Application Route: inhalation (vapour)

Method: OPPTS 870.5395

Result: negative

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Result: negative

Remarks: Based on data from similar materials

Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BATTERY TERMINAL SPRAY - 150 ML

Version Revision Date: SDS Number: Date of last issue: 14.03.2024 13.0 13.05.2024 10785796-00016 Date of first issue: 11.06.2010

Method: OECD Test Guideline 476

Result: negative

Remarks: Based on data from similar materials

Germ cell mutagenicity- As-

sessment

Classified based on benzene content < 0.1% (Regulation (EC)

1272/2008, Annex VI, Part 3, Note P)

Hydrocarbons, C9, aromatics:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow

cytogenetic test, chromosomal analysis)

Species: Rat

Application Route: inhalation (vapour)

Result: negative

Germ cell mutagenicity- As-

sessment

Classified based on benzene content < 0.1% (Regulation (EC)

1272/2008, Annex VI, Part 3, Note P)

Carcinogenicity

Not classified based on available information.

Components:

Dimethyl ether:

Species : Rat

Application Route : inhalation (vapour)

Exposure time : 2 Years
Result : negative

Methyl acetate:

Species : Rat
Application Route : Inhalation
Exposure time : 18 Months
Result : negative

Remarks : Based on data from similar materials

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Mouse
Application Route : Skin contact
Exposure time : 102 weeks
Result : negative

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Carcinogenicity - Assess- : Classified based on benzene content < 0.1% (Regulation (EC)

ment 1272/2008, Annex VI, Part 3, Note P)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BATTERY TERMINAL SPRAY - 150 ML

Version Revision Date: SDS Number: Date of last issue: 14.03.2024 13.0 13.05.2024 10785796-00016 Date of first issue: 11.06.2010

Hydrocarbons, C9, aromatics:

Carcinogenicity - Assess-

ment

Classified based on benzene content < 0.1% (Regulation (EC)

1272/2008, Annex VI, Part 3, Note P)

Reproductive toxicity

Not classified based on available information.

Components:

Dimethyl ether:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: inhalation (vapour)

Result: negative

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: inhalation (vapour)

Result: negative

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: inhalation (vapour)

Result: negative

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: inhalation (vapour)

Result: negative

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: inhalation (vapour)

Result: negative

Remarks: Based on data from similar materials

Effects on foetal develop-

ment

Test Type: Fertility/early embryonic development

Species: Rat

Application Route: inhalation (vapour)

Result: negative

Remarks: Based on data from similar materials

Hydrocarbons, C9, aromatics:

Effects on fertility : Test Type: Three-generation reproduction toxicity study

Species: Rat

Application Route: inhalation (vapour)

Result: negative

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BATTERY TERMINAL SPRAY - 150 ML

Version Revision Date: SDS Number: Date of last issue: 14.03.2024 13.0 13.05.2024 10785796-00016 Date of first issue: 11.06.2010

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Mouse

Application Route: inhalation (vapour)

Result: negative

STOT - single exposure

May cause drowsiness or dizziness.

Components:

Dimethyl ether:

Assessment : May cause drowsiness or dizziness.

Methyl acetate:

Assessment : May cause drowsiness or dizziness.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Assessment : May cause drowsiness or dizziness.

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Assessment : May cause drowsiness or dizziness.

Hydrocarbons, C9, aromatics:

Assessment : May cause drowsiness or dizziness.

Assessment : May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Dimethyl ether:

Species : Rat NOAEL : 47,11 mg/l

Application Route : inhalation (vapour)

Exposure time : 2 yr

Methyl acetate:

Species : Rat NOAEL : 1,057 mg/l

Application Route : inhalation (dust/mist/fume)

Exposure time : 28 Days

Method : OECD Test Guideline 412

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BATTERY TERMINAL SPRAY - 150 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 14.03.2024

 13.0
 13.05.2024
 10785796-00016
 Date of first issue: 11.06.2010

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rat NOAEL : > 20 mg/l

Application Route : inhalation (vapour)

Exposure time : 13 Weeks

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Species : Rat

NOAEL : 12,47 mg/l Application Route : Inhalation Exposure time : 90 Days

Remarks : Based on data from similar materials

Hydrocarbons, C9, aromatics:

Species : Rat, female NOAEL : 900 mg/m3

Application Route : inhalation (vapour)

Exposure time : 12 Months

Remarks : Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Hydrocarbons, C9, aromatics:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BATTERY TERMINAL SPRAY - 150 ML

Version Revision Date: SDS Number: Date of last issue: 14.03.2024 13.0 13.05.2024 10785796-00016 Date of first issue: 11.06.2010

SECTION 12: Ecological information

12.1 Toxicity

Components:

Dimethyl ether:

Toxicity to fish LC50 (Poecilia reticulata (guppy)): > 4.100 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 4.400 mg/l

Exposure time: 48 h

Toxicity to microorganisms : EC10 (Pseudomonas putida): > 1.600 mg/l

Methyl acetate:

Toxicity to fish LC50 (Danio rerio (zebra fish)): 250 - 350 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 1.026,7 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

ErC50 (Desmodesmus subspicatus (green algae)): > 120 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

EC10 (Desmodesmus subspicatus (green algae)): > 120 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

EC10 (Pseudomonas putida): 1.830 mg/l Toxicity to microorganisms

Exposure time: 16 h

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

LL50 (Pimephales promelas (fathead minnow)): 8,2 mg/l Toxicity to fish

Exposure time: 96 h

Test substance: Water Accommodated Fraction

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 4,5 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

EL50 (Pseudokirchneriella subcapitata (green algae)): 3,1

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BATTERY TERMINAL SPRAY - 150 ML

Version Revision Date: SDS Number: Date of last issue: 14.03.2024 13.0 13.05.2024 10785796-00016 Date of first issue: 11.06.2010

Remarks: Based on data from similar materials

NOELR (Pseudokirchneriella subcapitata (green algae)): 0,5

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chron-

ic toxicity)

NOELR: 2,6 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 13,4 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 203

Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): 3 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

EL50 (Selenastrum capricornutum (green algae)): > 10 - 100

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

NOELR (Selenastrum capricornutum (green algae)): 0,1 mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC: 0,17 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 211

Remarks: Based on data from similar materials

Hydrocarbons, C9, aromatics:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 9,2 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 203

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BATTERY TERMINAL SPRAY - 150 ML

Version Revision Date: SDS Number: Date of last issue: 14.03.2024 13.0 13.05.2024 10785796-00016 Date of first issue: 11.06.2010

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): 3,2 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EL50 (Pseudokirchneriella subcapitata (green algae)): 7,9

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

NOELR (Pseudokirchneriella subcapitata (green algae)): 0,22

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 : > 99 mg/l

Exposure time: 10 min

12.2 Persistence and degradability

Components:

Dimethyl ether:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 5 % Exposure time: 28 d

Method: OECD Test Guideline 301D

Methyl acetate:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 70 % Exposure time: 28 d

Method: OECD Test Guideline 301D

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 77,05 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Biodegradability : Result: Readily biodegradable.

Method: OECD Test Guideline 301F

Remarks: Based on data from similar materials

Hydrocarbons, C9, aromatics:

Biodegradability : Result: Readily biodegradable.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BATTERY TERMINAL SPRAY - 150 ML

Version Revision Date: SDS Number: Date of last issue: 14.03.2024 13.0 13.05.2024 10785796-00016 Date of first issue: 11.06.2010

Biodegradation: 78 % Exposure time: 28 d

Method: OECD Test Guideline 301F

12.3 Bioaccumulative potential

Components:

Dimethyl ether:

Partition coefficient: n-

: log Pow: 0,2

octanol/water

Methyl acetate:

Partition coefficient: n-

octanol/water

log Pow: 0,18

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Partition coefficient: n- : log Pow: 4

octanol/water Remarks: Based on data from similar materials

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Partition coefficient: n- : log Pow: > 4

octanol/water Remarks: Based on data from similar materials

Hydrocarbons, C9, aromatics:

Partition coefficient: n-

octanol/water

log Pow: 3,7 - 4,5

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BATTERY TERMINAL SPRAY - 150 ML

Version Revision Date: SDS Number: Date of last issue: 14.03.2024 13.0 13.05.2024 10785796-00016 Date of first issue: 11.06.2010

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.

According to the European Waste Catalogue, Waste Codes

are not product specific, but application specific.

Waste codes should be assigned by the user, preferably in

discussion with the waste disposal authorities.

Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product. Please ensure aerosol cans are sprayed completely empty

(including propellant)

Waste Code : The following Waste Codes are only suggestions:

used product

16 05 04, gases in pressure containers (including halons)

containing hazardous substances

unused product

16 05 04, gases in pressure containers (including halons)

containing hazardous substances

uncleaned packagings

15 01 10, packaging containing residues of or contaminated

by hazardous substances

Acc. Packaging Act properly emptied packaging: Properly emptied, non-contaminated packaging of nonhazardous products can be supplied to a system for the col-

lection of sales packaging.

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 1950 ADR : UN 1950 RID : UN 1950

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BATTERY TERMINAL SPRAY - 150 ML

Version Revision Date: SDS Number: Date of last issue: 14.03.2024 13.0 13.05.2024 10785796-00016 Date of first issue: 11.06.2010

IMDG : UN 1950 IATA : UN 1950

14.2 UN proper shipping name

ADN : AEROSOLS
ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS

IATA : Aerosols, flammable

14.3 Transport hazard class(es)

Class Subsidiary risks

 ADN
 : 2
 2.1

 ADR
 : 2
 2.1

 RID
 : 2
 2.1

IMDG : 2.1 IATA : 2.1

14.4 Packing group

ADN

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1

ADR

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1 Tunnel restriction code : (D)

RID

Packing group : Not assigned by regulation

Classification Code : 5F Hazard Identification Number : 23 Labels : 2.1

IMDG

Packing group : Not assigned by regulation

Labels : 2.1 EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo : 203

aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

IATA (Passenger)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BATTERY TERMINAL SPRAY - 150 ML

Version Revision Date: SDS Number: Date of last issue: 14.03.2024 13.0 13.05.2024 10785796-00016 Date of first issue: 11.06.2010

Packing instruction (passen: 203

ger aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) Conditions of restriction for the following entries should be considered: Number on list 75

Substance(s) or mixture(s) are listed here according to their appearance in the regulation, irrespective of their use/purpose or the conditions of the restriction. Please refer to the conditions in corresponding Regulation to determine whether an entry is applicable to the placing on the market or not

If you intend to use this product as tattoo ink, please contact your ven-

dor.

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

Not applicable

Regulation (EC) No 1005/2009 on substances that de- : Not applicable

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BATTERY TERMINAL SPRAY - 150 ML

Version Revision Date: SDS Number: Date of last issue: 14.03.2024 13.0 13.05.2024 10785796-00016 Date of first issue: 11.06.2010

plete the ozone layer

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

s subject to authorisation : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

ajor addiadir na <u>-</u> arad iivorinig	•	Quantity 1	Quantity 2
P3a	FLAMMABLE AEROSOLS	150 t	500 t
18	Liquefied flammable gases (including LPG) and natural gas	50 t	200 t
34	Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)	2.500 t	25.000 t

Water hazard class (Germa-

ny)

WGK 2 obviously hazardous to water

Classification according to AwSV, Annex 1 (5.2)

TA Luft List (Germany) : 5.2.1: Total dust:

Not applicable

5.2.2: Inorganic substances in powdered form:

Not applicable

5.2.4: Inorganic substances in gaseous form:

Not applicable

5.2.5: Organic Substances: Class 1: < 0,01 % Methanol 5.2.7.1.1: Carcinogenic substance:

Not applicable

5.2.7.1.1: Quartz fine dust PM4:

Not applicable

5.2.7.1.1: Formaldehyde:

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BATTERY TERMINAL SPRAY - 150 ML

Version Revision Date: SDS Number: Date of last issue: 14.03.2024 13.0 13.05.2024 10785796-00016 Date of first issue: 11.06.2010

Not applicable 5.2.7.1.1: fibres: Not applicable

5.2.7.1.2: Germ cell mutagens:

Not applicable

5.2.7.1.3: Substances toxic to reproduction:

Not applicable

5.2.7.2: Poorly degradable, easily enrichable and highly toxic

organic substances: Not applicable

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 97,17 %, 670 g/l

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Other information : Items where changes have been made to the previous version

are highlighted in the body of this document by two vertical

lines.

Full text of H-Statements

H220 : Extremely flammable gas.

H225 : Highly flammable liquid and vapour. H226 : Flammable liquid and vapour.

H280 : Contains gas under pressure; may explode if heated.

H304 : May be fatal if swallowed and enters airways.

H315 : Causes skin irritation.

H319
H335
H336
Causes serious eye irritation.
May cause respiratory irritation.
May cause drowsiness or dizziness.

H411 : Toxic to aquatic life with long lasting effects.

EUH066 : Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard

Eye Irrit. : Eye irritation

Flam. Gas : Flammable gases

Flam. Liq. : Flammable liquids

Press. Gas : Gases under pressure

Skin Irrit. : Skin irritation

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BATTERY TERMINAL SPRAY - 150 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 14.03.2024

 13.0
 13.05.2024
 10785796-00016
 Date of first issue: 11.06.2010

STOT SE : Specific target organ toxicity - single exposure

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values

DE DFG MAK : Germany. MAK BAT Annex IIa

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

TRGS 903 : TRGS 903 - Biological limit values

2000/39/EC / TWA : Limit Value - eight hours

DE DFG MAK / MAK : MAK value

DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways: ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level: NOELR - No Observable Effect Loading Rate: NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sheet

Sources of key data used to compile the Safety Data

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Classification of the mixture:

Classification procedure:

Aerosol 1 H222, H229 Based on product data or assessment

Skin Irrit. 2 H315 Calculation method

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BATTERY TERMINAL SPRAY - 150 ML

Version 13.0	Revision Date: 13.05.2024	SDS Number: 10785796-00016	Date of last issue: 14.03.2024 Date of first issue: 11.06.2010
Eye lı	rrit. 2	H319	Calculation method
STOT	SE 3	H336	Calculation method
Aqua	tic Chronic 3	H412	Based on product data or assessment

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN