

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



1C COLD WOOD GLUE D4 - 5 KG

Version 8.0 Revision Date: 17.04.2023 SDS Number: 10778451-00010 Date of last issue: 08.02.2023
Date of first issue: 02.01.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : 1C COLD WOOD GLUE D4 - 5 KG
Product code : 0892100225

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Adhesives
Professional use product
Recommended restrictions on use : Not applicable

1.3 Details of the supplier of the safety data sheet

Company : Adolf Wuerth GmbH & Co. KG
Reinhold-Würth-Str. 12-17
74653 Künzelsau
Telephone : +49 794015 0
Telefax : +49 794015 10 00
E-mail address of person responsible for the SDS : prodsafe@wuerth.com

1.4 Emergency telephone number

+49 (0)6132 – 84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)
Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

Additional Labelling

EUH210 Safety data sheet available on request.
EUH208 Contains Formaldehyde. May produce an allergic reaction.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



1C COLD WOOD GLUE D4 - 5 KG

Version 8.0 Revision Date: 17.04.2023 SDS Number: 10778451-00010 Date of last issue: 08.02.2023
Date of first issue: 02.01.2014

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Propylene carbonate	108-32-7 203-572-1 607-194-00-1 01-2119537232-48	Eye Irrit. 2; H319	>= 1 - < 10
Aluminum chloride, basic	1327-41-9 215-477-2 01-2119531563-43	Met. Corr. 1; H290 Eye Dam. 1; H318	>= 1 - < 3
Formaldehyde	50-00-0 200-001-8 605-001-00-5	Flam. Gas 1B; H221 Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 3; H311 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Muta. 2; H341 Carc. 1B; H350 STOT SE 3; H335 <hr/> specific concentration limit Skin Corr. 1B; H314 >= 25 % Skin Irrit. 2; H315 5 - < 25 % Eye Irrit. 2; H319 5 - < 25 % STOT SE 3; H335 >= 5 % Skin Sens. 1A; H317	< 0,1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



1C COLD WOOD GLUE D4 - 5 KG

Version 8.0 Revision Date: 17.04.2023 SDS Number: 10778451-00010 Date of last issue: 08.02.2023
Date of first issue: 02.01.2014

		>= 0,2 %	
		Acute toxicity estimate	
		Acute oral toxicity: 100 mg/kg	
		Acute inhalation toxicity (gas): 100 ppm	
		Acute dermal toxicity: 270 mg/kg	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Protection of first-aiders : No special precautions are necessary for first aid responders.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : Wash with water and soap as a precaution.
Get medical attention if symptoms occur.
- In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : None known.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



1C COLD WOOD GLUE D4 - 5 KG

Version	Revision Date:	SDS Number:	Date of last issue: 08.02.2023
8.0	17.04.2023	10778451-00010	Date of first issue: 02.01.2014

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides
Nitrogen oxides (NO_x)
Metal oxides
Chlorine compounds

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



1C COLD WOOD GLUE D4 - 5 KG

Version 8.0 Revision Date: 17.04.2023 SDS Number: 10778451-00010 Date of last issue: 08.02.2023
Date of first issue: 02.01.2014

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Take care to prevent spills, waste and minimize release to the environment.
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep in properly labelled containers. Store in accordance with the particular national regulations.
- Advice on common storage : Do not store with the following product types:
Strong oxidizing agents
Gases
- Storage class (TRGS 510) : 10
- Recommended storage temperature : 10 - 30 °C
- Further information on storage stability : Protect from frost.

7.3 Specific end use(s)

- Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Propylene carbonate	108-32-7	AGW (Vapour and aerosols)	2 ppm 8,5 mg/m ³	DE TRGS 900

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



1C COLD WOOD GLUE D4 - 5 KG

Version 8.0 Revision Date: 17.04.2023 SDS Number: 10778451-00010 Date of last issue: 08.02.2023
Date of first issue: 02.01.2014

	Peak-limit: excursion factor (category): 1;(I)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
Formaldehyde	50-00-0	TWA	0,3 ppm 0,37 mg/m ³	2004/37/EC
	Further information: Dermal sensitisation, Carcinogens or mutagens			
		STEL	0,6 ppm 0,74 mg/m ³	2004/37/EC
	Further information: Dermal sensitisation, Carcinogens or mutagens			
		AGW	0,3 ppm 0,37 mg/m ³	DE TRGS 900
	Peak-limit: excursion factor (category): 2;(I)			
	Further information: Carcinogenic substance Cat. 1A or 1B or carcinogenic activity or procedure according to § 2 (3) No. 4 of the Hazardous Substances Ordinance - in addition, § 10 GefStoffV must be observed, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child, Substance sensitizing through the skin			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Propylene carbonate	Workers	Inhalation	Long-term systemic effects	70,53 mg/m ³
	Workers	Inhalation	Long-term local effects	20 mg/m ³
	Workers	Skin contact	Long-term systemic effects	20 mg/kg bw/day
	Workers	Skin contact	Long-term local effects	10 mg/cm ²
	Consumers	Inhalation	Long-term systemic effects	17,4 mg/m ³
	Consumers	Inhalation	Long-term local effects	10 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	10 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	10 mg/kg bw/day
	Aluminum chloride, basic	Workers	Inhalation	Long-term systemic effects
Workers		Skin contact	Long-term systemic effects	4,6 mg/kg bw/day
Consumers		Inhalation	Long-term systemic effects	4 mg/m ³
Consumers		Skin contact	Long-term systemic effects	2,32 mg/kg bw/day
Consumers		Ingestion	Long-term systemic effects	2,32 mg/kg bw/day
Formaldehyde		Workers	Inhalation	Long-term systemic effects
	Workers	Inhalation	Long-term local effects	0,375 mg/m ³
	Workers	Inhalation	Acute local effects	0,75 mg/m ³

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



1C COLD WOOD GLUE D4 - 5 KG

Version
8.0

Revision Date:
17.04.2023

SDS Number:
10778451-00010

Date of last issue: 08.02.2023
Date of first issue: 02.01.2014

	Workers	Skin contact	Long-term systemic effects	240 mg/kg bw/day
	Workers	Skin contact	Long-term local effects	0,037 mg/cm2
	Consumers	Inhalation	Long-term systemic effects	3,2 mg/m3
	Consumers	Inhalation	Long-term local effects	0,1 mg/m3
	Consumers	Skin contact	Long-term systemic effects	102 mg/kg bw/day
	Consumers	Skin contact	Long-term local effects	0,012 mg/cm2
	Consumers	Ingestion	Long-term systemic effects	4,1 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Propylene carbonate	Fresh water	0,9 mg/l
	Freshwater - intermittent	9 mg/l
	Marine water	0,09 mg/l
	Marine water - intermittent	0,9 mg/l
	Sewage treatment plant	7400 mg/l
	Soil	0,81 mg/kg dry weight (d.w.)
Aluminum chloride, basic	Fresh water	0,0003 mg/l
	Marine water	0,00003 mg/l
	Sewage treatment plant	20 mg/l
Formaldehyde	Fresh water	0,44 mg/l
	Freshwater - intermittent	4,44 mg/l
	Marine water	0,44 mg/l
	Sewage treatment plant	0,19 mg/l
	Fresh water sediment	2,3 mg/kg dry weight (d.w.)
	Marine sediment	2,3 mg/kg dry weight (d.w.)
	Soil	0,2 mg/kg dry weight (d.w.)

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

Eye/face protection : Please follow all applicable local/national requirements when selecting protective measures for a specific workplace.

Wear the following personal protective equipment:

Safety glasses

Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded.

Equipment should conform to DIN EN 166

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



1C COLD WOOD GLUE D4 - 5 KG

Version	Revision Date:	SDS Number:	Date of last issue: 08.02.2023
8.0	17.04.2023	10778451-00010	Date of first issue: 02.01.2014

Hand protection

Material : Nitrile rubber
Glove thickness : 0,38 mm
Directive : Equipment should conform to DIN EN 374

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!

Skin and body protection : Skin should be washed after contact.

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection. Equipment should conform to DIN EN 14387

Filter type : Combined inorganic gas/vapour and organic vapour type (AB)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid
Colour : white
Odour : slight
Odour Threshold : No data available
Melting point/freezing point : ca. 0 °C
Initial boiling point and boiling range : ca. 100 °C
Flammability (solid, gas) : Not applicable
Flammability (liquids) : No data available
Upper explosion limit / Upper flammability limit : No data available
Lower explosion limit / Lower flammability limit : No data available
Flash point : > 100 °C

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



1C COLD WOOD GLUE D4 - 5 KG

Version	Revision Date:	SDS Number:	Date of last issue: 08.02.2023
8.0	17.04.2023	10778451-00010	Date of first issue: 02.01.2014

Auto-ignition temperature	:	No data available
Decomposition temperature	:	≥ 100 °C
pH	:	2,6 - 3,2 Concentration: 100 % concentrate
Viscosity		
Viscosity, dynamic	:	3.500 - 8.000 mPa.s (20 °C) Method: Brookfield
Viscosity, kinematic	:	> 20,5 mm ² /s (40 °C)
Solubility(ies)		
Water solubility	:	completely miscible
Partition coefficient: n-octanol/water	:	Not applicable
Vapour pressure	:	23 hPa (20 °C)
Density	:	1,02 - 1,1 g/cm ³ (20 °C)
Relative vapour density	:	No data available
Particle characteristics		
Particle size	:	Not applicable

9.2 Other information

Explosives	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Evaporation rate	:	No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	Can react with strong oxidizing agents.
---------------------	---	---

10.4 Conditions to avoid

Conditions to avoid	:	None known.
---------------------	---	-------------

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



1C COLD WOOD GLUE D4 - 5 KG

Version	Revision Date:	SDS Number:	Date of last issue: 08.02.2023
8.0	17.04.2023	10778451-00010	Date of first issue: 02.01.2014

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:

Propylene carbonate:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Aluminum chloride, basic:

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 401
Assessment: The substance or mixture has no acute oral toxicity

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

Formaldehyde:

Acute oral toxicity : Acute toxicity estimate: 100 mg/kg
Method: Expert judgement

Acute inhalation toxicity : Acute toxicity estimate: 100 ppm
Exposure time: 4 h
Test atmosphere: gas
Method: Expert judgement

Acute dermal toxicity : LD50 (Rabbit): 270 mg/kg

Skin corrosion/irritation

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



1C COLD WOOD GLUE D4 - 5 KG

Version 8.0 Revision Date: 17.04.2023 SDS Number: 10778451-00010 Date of last issue: 08.02.2023
Date of first issue: 02.01.2014

Product:

Method : OECD Test Guideline 439
Result : No skin irritation

Components:

Propylene carbonate:

Species : Rabbit
Result : No skin irritation

Aluminum chloride, basic:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Formaldehyde:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Corrosive after 3 minutes to 1 hour of exposure

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Method : OECD Test Guideline 437
Result : No eye irritation

Components:

Propylene carbonate:

Species : Rabbit
Method : OECD Test Guideline 405
Result : Irritation to eyes, reversing within 21 days

Aluminum chloride, basic:

Species : Rabbit
Method : OECD Test Guideline 405
Result : Irreversible effects on the eye

Formaldehyde:

Species : Rabbit
Result : Irreversible effects on the eye

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



1C COLD WOOD GLUE D4 - 5 KG

Version 8.0 Revision Date: 17.04.2023 SDS Number: 10778451-00010 Date of last issue: 08.02.2023
Date of first issue: 02.01.2014

Respiratory sensitisation

Not classified based on available information.

Components:

Aluminum chloride, basic:

Test Type : Local lymph node assay (LLNA)
Exposure routes : Skin contact
Species : Mouse
Result : negative

Formaldehyde:

Test Type : Local lymph node assay (LLNA)
Exposure routes : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : positive

Assessment : Probability or evidence of high skin sensitisation rate in humans

Germ cell mutagenicity

Not classified based on available information.

Components:

Propylene carbonate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative

Aluminum chloride, basic:

Genotoxicity in vitro : Test Type: in vitro micronucleus test
Method: OECD Test Guideline 487
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



1C COLD WOOD GLUE D4 - 5 KG

Version 8.0 Revision Date: 17.04.2023 SDS Number: 10778451-00010 Date of last issue: 08.02.2023
Date of first issue: 02.01.2014

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Formaldehyde:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: positive

Test Type: Chromosome aberration test in vitro
Result: positive

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: Inhalation
Result: positive

Germ cell mutagenicity- Assessment : Positive result(s) from in vivo mammalian somatic cell mutagenicity tests.

Carcinogenicity

Not classified based on available information.

Components:

Propylene carbonate:

Species : Mouse
Application Route : Skin contact
Exposure time : 104 weeks
Result : negative

Formaldehyde:

Species : Rat
Application Route : inhalation (gas)
Exposure time : 28 Months
Result : positive

Carcinogenicity - Assessment : Sufficient evidence of carcinogenicity in animal experiments

Reproductive toxicity

Not classified based on available information.

Components:

Propylene carbonate:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



1C COLD WOOD GLUE D4 - 5 KG

Version 8.0 Revision Date: 17.04.2023 SDS Number: 10778451-00010 Date of last issue: 08.02.2023
Date of first issue: 02.01.2014

Species: Mouse
Application Route: Ingestion
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Mouse
Application Route: Ingestion
Result: negative

Aluminum chloride, basic:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Formaldehyde:

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (gas)
Result: negative

STOT - single exposure

Not classified based on available information.

Components:

Formaldehyde:

Assessment : May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Components:

Formaldehyde:

Exposure routes : inhalation (gas)
Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



1C COLD WOOD GLUE D4 - 5 KG

Version 8.0 Revision Date: 17.04.2023 SDS Number: 10778451-00010 Date of last issue: 08.02.2023
Date of first issue: 02.01.2014

Repeated dose toxicity

Components:

Propylene carbonate:

Species : Rat
NOAEL : > 5.000 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Aluminum chloride, basic:

Species : Rat
NOAEL : 200 mg/kg
LOAEL : 1.000 mg/kg
Application Route : Ingestion
Exposure time : 28 - 53 Days
Method : OECD Test Guideline 422

Formaldehyde:

Species : Rat
NOAEL : 6 ppm
LOAEL : 10 ppm
Application Route : inhalation (gas)
Exposure time : 28 Days

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Propylene carbonate:

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): > 1.000 mg/l
Exposure time: 96 h
Method: Directive 67/548/EEC, Annex V, C.1.

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 1.000 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



1C COLD WOOD GLUE D4 - 5 KG

Version 8.0 Revision Date: 17.04.2023 SDS Number: 10778451-00010 Date of last issue: 08.02.2023
Date of first issue: 02.01.2014

aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (Selenastrum capricornutum (green algae)): > 929 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (Selenastrum capricornutum (green algae)): 929 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (Pseudomonas putida): 25.619 mg/l
Exposure time: 16 h
Method: DIN 38 412 Part 8

Aluminum chloride, basic:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 1 - 10 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 1 - 10 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 : > 1.000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Ecotoxicology Assessment

Chronic aquatic toxicity : No toxicity at the limit of solubility

Formaldehyde:

Toxicity to fish : LC50 : 6,7 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia pulex (Water flea)): 5,8 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 4,89 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 : 34,1 mg/l
Exposure time: 120 h

Toxicity to fish (Chronic toxicity) : NOEC: >= 48 mg/l
Exposure time: 28 d
Species: Oryzias latipes (Orange-red killifish)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



1C COLD WOOD GLUE D4 - 5 KG

Version	Revision Date:	SDS Number:	Date of last issue: 08.02.2023
8.0	17.04.2023	10778451-00010	Date of first issue: 02.01.2014

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: $\geq 6,4$ mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

12.2 Persistence and degradability

Components:

Propylene carbonate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: > 90 %
Exposure time: 28 d
Method: Directive 67/548/EEC Annex V, C.4.A.

Formaldehyde:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 91 %
Exposure time: 14 d
Method: OECD Test Guideline 301C
Remarks: Based on data from similar materials

12.3 Bioaccumulative potential

Components:

Propylene carbonate:

Partition coefficient: n-octanol/water : log Pow: -0,48

Formaldehyde:

Partition coefficient: n-octanol/water : log Pow: 0,35
Remarks: Calculation

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



1C COLD WOOD GLUE D4 - 5 KG

Version 8.0 Revision Date: 17.04.2023 SDS Number: 10778451-00010 Date of last issue: 08.02.2023
Date of first issue: 02.01.2014

(EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- Product : Dispose of in accordance with local regulations. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities. Do not dispose of waste into sewer.
 - Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal. If not otherwise specified: Dispose of as unused product.
 - Waste Code : The following Waste Codes are only suggestions:
 - used product
08 04 10, waste adhesives and sealants other than those mentioned in 08 04 09
 - unused product
08 04 10, waste adhesives and sealants other than those mentioned in 08 04 09
 - uncleaned packagings
20 03 01, mixed municipal wasteAcc. Packaging Act properly emptied packaging:
Properly emptied, non-contaminated packaging of non-hazardous products can be supplied to a system for the collection of sales packaging.
-

SECTION 14: Transport information

14.1 UN number or ID number

- ADN : Not regulated as a dangerous good
- ADR : Not regulated as a dangerous good
- RID : Not regulated as a dangerous good
- IMDG : Not regulated as a dangerous good
- IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



1C COLD WOOD GLUE D4 - 5 KG

Version 8.0 Revision Date: 17.04.2023 SDS Number: 10778451-00010 Date of last issue: 08.02.2023
Date of first issue: 02.01.2014

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.4 Packing group

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA (Cargo) : Not regulated as a dangerous good
IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 75
If you intend to use this product as tattoo ink, please contact your vendor.

Formaldehyde (Number on list 72, 28)

REACH - Candidate List of Substances of Very High : Not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



1C COLD WOOD GLUE D4 - 5 KG

Version	Revision Date:	SDS Number:	Date of last issue: 08.02.2023
8.0	17.04.2023	10778451-00010	Date of first issue: 02.01.2014

Concern for Authorisation (Article 59).

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
Not applicable

Water hazard class (Germany) : WGK 1 slightly hazardous to water
Classification according to AwSV, Annex 1 (5.2)

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: < 0,5 %, < 5,3 g/l
Remarks: VOC content excluding water

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Other information : Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Full text of H-Statements

H221 : Flammable gas.
H290 : May be corrosive to metals.
H301 : Toxic if swallowed.
H311 : Toxic in contact with skin.
H314 : Causes severe skin burns and eye damage.
H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.
H330 : Fatal if inhaled.
H335 : May cause respiratory irritation.
H341 : Suspected of causing genetic defects.
H350 : May cause cancer.

Full text of other abbreviations

Acute Tox. : Acute toxicity

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



1C COLD WOOD GLUE D4 - 5 KG

Version	Revision Date:	SDS Number:	Date of last issue: 08.02.2023
8.0	17.04.2023	10778451-00010	Date of first issue: 02.01.2014

Carc.	:	Carcinogenicity
Eye Dam.	:	Serious eye damage
Eye Irrit.	:	Eye irritation
Flam. Gas	:	Flammable gases
Met. Corr.	:	Corrosive to metals
Muta.	:	Germ cell mutagenicity
Skin Corr.	:	Skin corrosion
Skin Sens.	:	Skin sensitisation
STOT SE	:	Specific target organ toxicity - single exposure
2004/37/EC	:	Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work
DE TRGS 900	:	Germany. TRGS 900 - Occupational exposure limit values.
2004/37/EC / STEL	:	Short term exposure limit
2004/37/EC / TWA	:	Long term exposure limit
DE TRGS 900 / AGW	:	Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



1C COLD WOOD GLUE D4 - 5 KG

Version	Revision Date:	SDS Number:	Date of last issue: 08.02.2023
8.0	17.04.2023	10778451-00010	Date of first issue: 02.01.2014

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN