

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



GLUE FOR PAINTED SURFACES - 500 G

Version	Revision Date:	SDS Number:	Date of last issue: 26.05.2023
3.1	23.10.2023	5792258-00011	Date of first issue: 29.04.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : GLUE FOR PAINTED SURFACES - 500 G

Product code : 089210055

Unique Formula Identifier (UFI) : DY88-10M7-X006-P7JC

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Adhesives
Professional use product

Recommended restrictions on use : Not applicable

1.3 Details of the supplier of the safety data sheet

Company : Adolf Wuerth GmbH & Co. KG
Reinhold-Würth-Str. 12-17
74653 Künzelsau

Telephone : +49 794015 0

Telefax : +49 794015 10 00

E-mail address of person responsible for the SDS : isi@wuerth.com

1.4 Emergency telephone number

+49 (0)6132 – 84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



GLUE FOR PAINTED SURFACES - 500 G

Version 3.1 Revision Date: 23.10.2023 SDS Number: 5792258-00011 Date of last issue: 26.05.2023
Date of first issue: 29.04.2020

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements : H315 Causes skin irritation.
H319 Causes serious eye irritation.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P264 Wash skin thoroughly after handling.
P273 Avoid release to the environment.
P280 Wear protective gloves/ eye protection/ face protection.
Response:
P332 + P313 If skin irritation occurs: Get medical advice/
attention.
P337 + P313 If eye irritation persists: Get medical advice/
attention.
P362 + P364 Take off contaminated clothing and wash it
before reuse.

Additional Labelling

EUH208 Contains Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1), 1,2-Benzisothiazol-3(2H)-one. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Adhesives

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



GLUE FOR PAINTED SURFACES - 500 G

Version
3.1

Revision Date:
23.10.2023

SDS Number:
5792258-00011

Date of last issue: 26.05.2023
Date of first issue: 29.04.2020

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Methylcyclohexane	108-87-2 203-624-3 601-018-00-7 01-2119556887-18	Flam. Liq. 2; H225 Skin Irrit. 2; H315 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 2,5 - < 10
1-Butylpyrrolidin-2-one	3470-98-2 222-437-8 01-2120062728-48	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Acute toxicity estimate Acute oral toxicity: 300,03 mg/kg	>= 1 - < 10
2-Dimethylaminoethanol	108-01-0 203-542-8 603-047-00-0 01-2119492298-24	Flam. Liq. 3; H226 Acute Tox. 4; H302 Acute Tox. 3; H331 Acute Tox. 4; H312 Skin Corr. 1B; H314 Eye Dam. 1; H318 STOT SE 3; H335 specific concentration limit STOT SE 3; H335 >= 5 % Acute toxicity estimate Acute oral toxicity: 1.182 mg/kg Acute inhalation toxicity (vapour): 5,97 mg/l Acute dermal toxicity: 1.214 mg/kg	>= 1 - < 3
1,2-Benzisothiazol-3(2H)-one	2634-33-5 220-120-9 613-088-00-6	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 2; H411	>= 0,025 - < 0,05

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



GLUE FOR PAINTED SURFACES - 500 G

Version
3.1

Revision Date:
23.10.2023

SDS Number:
5792258-00011

Date of last issue: 26.05.2023
Date of first issue: 29.04.2020

				M-Factor (Acute aquatic toxicity): 1
				specific concentration limit Skin Sens. 1A; H317 >= 0,05 %
				Acute toxicity estimate Acute oral toxicity: 454 mg/kg
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	55965-84-9 613-167-00-5		>= 0,0002 - < 0,0015	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071
				M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100
				specific concentration limit Skin Corr. 1C; H314 >= 0,6 % Skin Irrit. 2; H315 0,06 - < 0,6 % Eye Irrit. 2; H319 0,06 - < 0,6 % Skin Sens. 1A; H317 >= 0,0015 % Eye Dam. 1; H318 >= 0,6 % EUH071 >= 0,6 %
				Acute toxicity estimate

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



GLUE FOR PAINTED SURFACES - 500 G

Version 3.1 Revision Date: 23.10.2023 SDS Number: 5792258-00011 Date of last issue: 26.05.2023
Date of first issue: 29.04.2020

		Acute oral toxicity: 64 mg/kg Acute inhalation toxicity (dust/mist): 0,171 mg/l Acute dermal toxicity: 87,12 mg/kg
--	--	--

For explanation of abbreviations see section 16.

Alternative CAS Numbers for some regions

Chemical name	Alternative CAS Number(s)
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	2682-20-4, 26172-55-4

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes skin irritation.
Causes serious eye irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



GLUE FOR PAINTED SURFACES - 500 G

Version	Revision Date:	SDS Number:	Date of last issue: 26.05.2023
3.1	23.10.2023	5792258-00011	Date of first issue: 29.04.2020

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides
Nitrogen oxides (NO_x)

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



GLUE FOR PAINTED SURFACES - 500 G

Version	Revision Date:	SDS Number:	Date of last issue: 26.05.2023
3.1	23.10.2023	5792258-00011	Date of first issue: 29.04.2020

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Do not get on skin or clothing.
Avoid inhalation of vapour or mist.
Do not swallow.
Do not get in eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Take care to prevent spills, waste and minimize release to the environment.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep in properly labelled containers. Store in accordance with the particular national regulations.

Advice on common storage : Do not store with the following product types:
Strong oxidizing agents
Gases

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



GLUE FOR PAINTED SURFACES - 500 G

Version 3.1 Revision Date: 23.10.2023 SDS Number: 5792258-00011 Date of last issue: 26.05.2023
Date of first issue: 29.04.2020

Storage class (TRGS 510) : 10

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Methylcyclohexane	108-87-2	AGW	200 ppm 810 mg/m ³	DE TRGS 900
Peak-limit: excursion factor (category): 2;(II)				

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
1,2-Benzisothiazol-3(2H)-one	Workers	Inhalation	Long-term systemic effects	6,81 mg/m ³
	Workers	Skin contact	Long-term systemic effects	0,966 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	1,2 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	0,345 mg/kg bw/day
1-Butylpyrrolidin-2-one	Workers	Inhalation	Long-term systemic effects	24,1 mg/m ³
	Workers	Skin contact	Long-term systemic effects	10 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	4,29 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	5 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	4 mg/kg bw/day
	Consumers	Ingestion	Acute systemic effects	4 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	7,4 mg/m ³
	Workers	Inhalation	Acute systemic effects	22 mg/m ³
2-Dimethylaminoethanol	Workers	Inhalation	Long-term local effects	7,4 mg/m ³
	Workers	Inhalation	Acute local effects	22 mg/m ³
	Workers	Skin contact	Long-term systemic effects	1,04 mg/kg bw/day
	Workers	Skin contact	Acute systemic effects	5 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



GLUE FOR PAINTED SURFACES - 500 G

Version 3.1 Revision Date: 23.10.2023 SDS Number: 5792258-00011 Date of last issue: 26.05.2023
Date of first issue: 29.04.2020

			fects	bw/day
	Workers	Skin contact	Acute local effects	0,08 mg/cm ²
Methylcyclohexane	Workers	Inhalation	Long-term systemic effects	64,3 mg/m ³
	Workers	Inhalation	Acute systemic effects	1354,6 mg/m ³
	Workers	Skin contact	Long-term systemic effects	1,7 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	16 mg/m ³
	Consumers	Inhalation	Acute systemic effects	1016 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	0,8 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0,4 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
1,2-Benzisothiazol-3(2H)-one	Fresh water	11 µg/l
	Intermittent use/release	0,403 µg/l
	Marine water	1,1 µg/l
	Intermittent use/release	0,0403 µg/l
	Sewage treatment plant	1,03 mg/l
	Fresh water sediment	0,0499 mg/kg dry weight (d.w.)
	Marine sediment	0,00499 mg/kg dry weight (d.w.)
1-Butylpyrrolidin-2-one	Soil	3 mg/kg dry weight (d.w.)
	Fresh water	4 mg/l
	Freshwater - intermittent	1 mg/l
	Marine water	0,4 mg/l
	Marine water - intermittent	0,1 mg/l
2-Dimethylaminoethanol	Sewage treatment plant	30,62 mg/l
	Fresh water sediment	20,168 mg/kg dry weight (d.w.)
	Marine sediment	2,017 mg/kg dry weight (d.w.)
	Soil	1,68 mg/kg dry weight (d.w.)
	Fresh water	0,066 mg/l
Methylcyclohexane	Marine water	0,007 mg/l
	Freshwater - intermittent	0,066 mg/l
	Sewage treatment plant	10 mg/l
	Fresh water sediment	0,053 mg/kg dry weight (d.w.)
	Soil	0,018 mg/kg dry weight (d.w.)
Methylcyclohexane	Fresh water	3,26 µg/l
	Marine water	0,326 µg/l
	Intermittent use/release	32,6 µg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



GLUE FOR PAINTED SURFACES - 500 G

Version 3.1 Revision Date: 23.10.2023 SDS Number: 5792258-00011 Date of last issue: 26.05.2023
Date of first issue: 29.04.2020

	Sewage treatment plant	338 µg/l
	Fresh water sediment	0,088 mg/kg
	Marine water	0,0088 mg/kg
	Soil	0,0237 mg/kg

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

Eye/face protection : Wear the following personal protective equipment:
Safety goggles
Equipment should conform to DIN EN 166

Hand protection

Material : Nitrile rubber
Break through time : 480 min
Glove thickness : > 0,38 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
Equipment should conform to DIN EN 14387

Filter type : Combined particulates, ammonia/amines and organic vapour type (AK-P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Colour : beige

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



GLUE FOR PAINTED SURFACES - 500 G

Version	Revision Date:	SDS Number:	Date of last issue: 26.05.2023
3.1	23.10.2023	5792258-00011	Date of first issue: 29.04.2020

Odour : characteristic

Odour Threshold : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling range : 100 °C

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Ignitable (see flash point)

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Flash point : 165 °C

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : 7 - 8 (20 °C)
Concentration: 100 %

Viscosity
Viscosity, dynamic : 13.000 mPa.s (20 °C)
Method: Brookfield

Viscosity, kinematic : No data available

Solubility(ies)
Water solubility : completely miscible

Partition coefficient: n-octanol/water : Not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



GLUE FOR PAINTED SURFACES - 500 G

Version	Revision Date:	SDS Number:	Date of last issue: 26.05.2023
3.1	23.10.2023	5792258-00011	Date of first issue: 29.04.2020

Vapour pressure : 23 hPa (20 °C)

Relative density : 1,02 (20 °C)

Density : 1,02 g/cm³ (20 °C)

Relative vapour density : No data available

Particle characteristics
Particle size : Not applicable

9.2 Other information

Explosives : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Evaporation rate : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : None known.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : None.

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



GLUE FOR PAINTED SURFACES - 500 G

Version	Revision Date:	SDS Number:	Date of last issue: 26.05.2023
3.1	23.10.2023	5792258-00011	Date of first issue: 29.04.2020

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Components:

Methylcyclohexane:

Acute oral toxicity : LD50 (Rabbit): 4.000 - 4.500 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 26,3 mg/l
Exposure time: 1 h
Test atmosphere: vapour
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

1-Butylpyrrolidin-2-one:

Acute oral toxicity : LD50 (Rat, female): > 300 - < 2.000 mg/kg
Method: OECD Test Guideline 423

Acute inhalation toxicity : LC50 (Rat): > 5,1 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 402

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



GLUE FOR PAINTED SURFACES - 500 G

Version 3.1 Revision Date: 23.10.2023 SDS Number: 5792258-00011 Date of last issue: 26.05.2023
Date of first issue: 29.04.2020

Assessment: The substance or mixture has no acute dermal toxicity

2-Dimethylaminoethanol:

Acute oral toxicity : LD50 (Rat): 1.182 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 5,97 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): 1.214 mg/kg

1,2-Benzisothiazol-3(2H)-one:

Acute oral toxicity : LD50 (Rat): 454 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1):

Acute oral toxicity : LD50 (Rat): 64 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0,171 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: Corrosive to the respiratory tract.

Acute dermal toxicity : LD50 (Rabbit): 87,12 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Components:

Methylcyclohexane:

Result : Skin irritation
Remarks : Based on harmonised classification in EU regulation
1272/2008, Annex VI

1-Butylpyrrolidin-2-one:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Skin irritation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



GLUE FOR PAINTED SURFACES - 500 G

Version	Revision Date:	SDS Number:	Date of last issue: 26.05.2023
3.1	23.10.2023	5792258-00011	Date of first issue: 29.04.2020

2-Dimethylaminoethanol:

Species	:	Rabbit
Method	:	OECD Test Guideline 404
Result	:	Corrosive after 3 minutes to 1 hour of exposure

1,2-Benzisothiazol-3(2H)-one:

Result	:	Skin irritation
--------	---	-----------------

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1):

Species	:	Rabbit
Method	:	OECD Test Guideline 404
Result	:	Corrosive after 1 to 4 hours of exposure

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

Methylcyclohexane:

Species	:	Rabbit
Method	:	Draize Test
Result	:	No eye irritation

1-Butylpyrrolidin-2-one:

Species	:	Rabbit
Method	:	OECD Test Guideline 405
Result	:	Irritation to eyes, reversing within 21 days

2-Dimethylaminoethanol:

Species	:	Rabbit
Result	:	Irreversible effects on the eye

1,2-Benzisothiazol-3(2H)-one:

Species	:	Rabbit
Result	:	Irreversible effects on the eye

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1):

Result	:	Irreversible effects on the eye
Remarks	:	Based on skin corrosivity.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



GLUE FOR PAINTED SURFACES - 500 G

Version 3.1 Revision Date: 23.10.2023 SDS Number: 5792258-00011 Date of last issue: 26.05.2023
Date of first issue: 29.04.2020

Respiratory sensitisation

Not classified based on available information.

Components:

Methylcyclohexane:

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative
Remarks : Based on data from similar materials

1-Butylpyrrolidin-2-one:

Test Type : Local lymph node assay (LLNA)
Exposure routes : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : negative

2-Dimethylaminoethanol:

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative

1,2-Benzisothiazol-3(2H)-one:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : positive

Assessment : Probability or evidence of high skin sensitisation rate in humans

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1):

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Result : positive

Assessment : Probability or evidence of high skin sensitisation rate in humans

Germ cell mutagenicity

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



GLUE FOR PAINTED SURFACES - 500 G

Version 3.1 Revision Date: 23.10.2023 SDS Number: 5792258-00011 Date of last issue: 26.05.2023
Date of first issue: 29.04.2020

Components:

Methylcyclohexane:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

1-Butylpyrrolidin-2-one:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: in vitro micronucleus test
Method: OECD Test Guideline 487
Result: negative

2-Dimethylaminoethanol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: In vitro sister chromatid exchange assay in mam-
malian cells
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative

1,2-Benzisothiazol-3(2H)-one:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: positive

Genotoxicity in vivo : Test Type: Unscheduled DNA synthesis (UDS) test with

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



GLUE FOR PAINTED SURFACES - 500 G

Version 3.1 Revision Date: 23.10.2023 SDS Number: 5792258-00011 Date of last issue: 26.05.2023
Date of first issue: 29.04.2020

mammalian liver cells in vivo
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 486
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

2-Dimethylaminoethanol:

Species : Mouse
Application Route : Ingestion
Exposure time : 105 weeks
Result : negative

Reproductive toxicity

Not classified based on available information.

Components:

Methylcyclohexane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Method: OECD Test Guideline 414
Result: negative
Remarks: Based on data from similar materials

1-Butylpyrrolidin-2-one:

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

2-Dimethylaminoethanol:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 421
Result: negative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



GLUE FOR PAINTED SURFACES - 500 G

Version	Revision Date:	SDS Number:	Date of last issue: 26.05.2023
3.1	23.10.2023	5792258-00011	Date of first issue: 29.04.2020

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Method: OECD Test Guideline 414
Result: negative

Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Method: OPPTS 870.3700
Result: negative

1,2-Benzisothiazol-3(2H)-one:

Effects on fertility : Test Type: Fertility/early embryonic development
Species: Rat
Application Route: Ingestion
Method: OPPTS 870.3800
Result: negative

STOT - single exposure

Not classified based on available information.

Components:

Methylcyclohexane:

Assessment : May cause drowsiness or dizziness.

2-Dimethylaminoethanol:

Assessment : May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Components:

1,2-Benzisothiazol-3(2H)-one:

Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

Repeated dose toxicity

Components:

Methylcyclohexane:

Species : Rat
NOAEL : 1.600 mg/m³
Application Route : inhalation (vapour)
Exposure time : 12 Months

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



GLUE FOR PAINTED SURFACES - 500 G

Version	Revision Date:	SDS Number:	Date of last issue: 26.05.2023
3.1	23.10.2023	5792258-00011	Date of first issue: 29.04.2020

1-Butylpyrrolidin-2-one:

Species	:	Rat
NOAEL	:	>= 500 mg/kg
Application Route	:	Ingestion
Exposure time	:	90 Days
Method	:	OECD Test Guideline 408

1,2-Benzisothiazol-3(2H)-one:

Species	:	Dog
NOAEL	:	5 mg/kg
LOAEL	:	20 mg/kg
Application Route	:	Ingestion
Exposure time	:	90 Days
Method	:	Directive 67/548/EEC, Annex, B.27

Aspiration toxicity

Not classified based on available information.

Components:

Methylcyclohexane:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment	:	The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
------------	---	---

SECTION 12: Ecological information

12.1 Toxicity

Components:

Methylcyclohexane:

Toxicity to fish	:	LC50 (Oryzias latipes (Orange-red killifish)): 2,07 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 0,326 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EC50 (Pseudokirchneriella subcapitata (green algae)): 0,134 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



GLUE FOR PAINTED SURFACES - 500 G

Version	Revision Date:	SDS Number:	Date of last issue: 26.05.2023
3.1	23.10.2023	5792258-00011	Date of first issue: 29.04.2020

Exposure time: 72 h

NOEC (Pseudokirchneriella subcapitata (green algae)):
0,0221 mg/l
Exposure time: 72 h

Toxicity to microorganisms : IC50 : 97 mg/l
Exposure time: 24 h

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

1-Butylpyrrolidin-2-one:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 160 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

EC10 (Pseudokirchneriella subcapitata (green algae)): 110 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC10 (activated sludge): > 315 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Toxicity to fish (Chronic toxicity) : NOEC: 82 mg/l
Exposure time: 33 d
Species: Pimephales promelas (fathead minnow)
Method: OECD Test Guideline 210

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC10: > 100 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

2-Dimethylaminoethanol:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 146,63 mg/l
Exposure time: 96 h
Test substance: Neutralised product

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



GLUE FOR PAINTED SURFACES - 500 G

Version 3.1 Revision Date: 23.10.2023 SDS Number: 5792258-00011 Date of last issue: 26.05.2023
Date of first issue: 29.04.2020

Method: DIN 38412

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 98,37 mg/l
Exposure time: 48 h
Method: Directive 67/548/EEC, Annex V, C.2.

Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): 66,08 mg/l
Exposure time: 72 h

EC10 (Desmodesmus subspicatus (green algae)): 24,49 mg/l
Exposure time: 72 h

Toxicity to microorganisms : EC10 (Pseudomonas putida): 273,8 mg/l
Exposure time: 17 h
Method: DIN 38 412 Part 8

1,2-Benzisothiazol-3(2H)-one:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 1,6 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 2,9 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 110 µg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 40,4 µg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

M-Factor (Acute aquatic toxicity) : 1

Toxicity to microorganisms : NOEC : 10,3 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0,19 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0,16 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (Skeletonema costatum (marine diatom)): 0,0052 mg/l
Exposure time: 48 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



GLUE FOR PAINTED SURFACES - 500 G

Version	Revision Date:	SDS Number:	Date of last issue: 26.05.2023
3.1	23.10.2023	5792258-00011	Date of first issue: 29.04.2020

NOEC (Skeletonema costatum (marine diatom)): 0,00049 mg/l
Exposure time: 48 h

M-Factor (Acute aquatic toxicity) : 100

Toxicity to fish (Chronic toxicity) : NOEC: 0,02 mg/l
Exposure time: 36 d
Species: Pimephales promelas (fathead minnow)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0,10 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)

M-Factor (Chronic aquatic toxicity) : 100

12.2 Persistence and degradability

Components:

Methylcyclohexane:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 0 %
Exposure time: 28 d
Method: OECD Test Guideline 310

1-Butylpyrrolidin-2-one:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 0 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

2-Dimethylaminoethanol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 60,5 %
Exposure time: 14 d
Method: OECD Test Guideline 301C

1,2-Benzisothiazol-3(2H)-one:

Biodegradability : Result: rapidly degradable

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1):

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 62 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



GLUE FOR PAINTED SURFACES - 500 G

Version 3.1 Revision Date: 23.10.2023 SDS Number: 5792258-00011 Date of last issue: 26.05.2023
Date of first issue: 29.04.2020

12.3 Bioaccumulative potential

Components:

Methylcyclohexane:

Bioaccumulation : Species: Cyprinus carpio (Carp)
Bioconcentration factor (BCF): 134 - 237

Partition coefficient: n-octanol/water : log Pow: 3,88

1-Butylpyrrolidin-2-one:

Partition coefficient: n-octanol/water : log Pow: 1,265
Method: OECD Test Guideline 117

2-Dimethylaminoethanol:

Partition coefficient: n-octanol/water : log Pow: -0,55

1,2-Benzisothiazol-3(2H)-one:

Bioaccumulation : Species: Lepomis macrochirus (Bluegill sunfish)
Bioconcentration factor (BCF): 6,62

Partition coefficient: n-octanol/water : log Pow: 0,7

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1):

Partition coefficient: n-octanol/water : log Pow: < 1

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



GLUE FOR PAINTED SURFACES - 500 G

Version	Revision Date:	SDS Number:	Date of last issue: 26.05.2023
3.1	23.10.2023	5792258-00011	Date of first issue: 29.04.2020

levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- Product : Dispose of in accordance with local regulations.
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.
Do not dispose of waste into sewer.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.
- Waste Code : The following Waste Codes are only suggestions:
- used product
08 04 09, waste adhesives and sealants containing organic solvents or other hazardous substances
- unused product
08 04 09, waste adhesives and sealants containing organic solvents or other hazardous substances
- uncleaned packagings
15 01 10, packaging containing residues of or contaminated by hazardous substances
- Acc. Packaging Act properly emptied packaging:
Properly emptied, non-contaminated packaging of non-hazardous products can be supplied to a system for the collection of sales packaging.
-

SECTION 14: Transport information

14.1 UN number or ID number

- ADN : Not regulated as a dangerous good
- ADR : Not regulated as a dangerous good
- RID : Not regulated as a dangerous good
- IMDG : Not regulated as a dangerous good
- IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



GLUE FOR PAINTED SURFACES - 500 G

Version	Revision Date:	SDS Number:	Date of last issue: 26.05.2023
3.1	23.10.2023	5792258-00011	Date of first issue: 29.04.2020

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.4 Packing group

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA (Cargo) : Not regulated as a dangerous good
IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 75, 3

If you intend to use this product as tattoo ink, please contact your vendor.

Substance(s) or mixture(s) are listed here according to their appearance

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



GLUE FOR PAINTED SURFACES - 500 G

Version 3.1 Revision Date: 23.10.2023 SDS Number: 5792258-00011 Date of last issue: 26.05.2023
Date of first issue: 29.04.2020

in the regulation, irrespective of their use/purpose or the conditions of the restriction. Please refer to the conditions in corresponding Regulation to determine whether an entry is applicable to the placing on the market or not.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

The treated article incorporates biocidal products

Active substance : Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
Not applicable

Water hazard class (Germany) : WGK 2 obviously hazardous to water
Classification according to AwSV, Annex 1 (5.2)

TA Luft List (Germany) : 5.2.1: Total dust:
Not applicable
5.2.2: Inorganic substances in powdered form:
Not applicable
5.2.4: Inorganic substances in gaseous form:
Not applicable
5.2.5: Organic Substances:
Not applicable
5.2.7.1.1: Carcinogenic substance:
Not applicable
5.2.7.1.1: Quartz fine dust PM4:
Not applicable
5.2.7.1.1: Formaldehyde:
Not applicable
5.2.7.1.1: fibres:
Not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



GLUE FOR PAINTED SURFACES - 500 G

Version	Revision Date:	SDS Number:	Date of last issue: 26.05.2023
3.1	23.10.2023	5792258-00011	Date of first issue: 29.04.2020

5.2.7.1.2: Germ cell mutagens:

Not applicable

5.2.7.1.3: Substances toxic to reproduction:

Not applicable

5.2.7.2: Poorly degradable, easily enrichable and highly toxic
organic substances:

Not applicable

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial
emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: < 10 %

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Other information : Items where changes have been made to the previous version
are highlighted in the body of this document by two vertical
lines.

Full text of H-Statements

H225 : Highly flammable liquid and vapour.
H226 : Flammable liquid and vapour.
H301 : Toxic if swallowed.
H302 : Harmful if swallowed.
H304 : May be fatal if swallowed and enters airways.
H310 : Fatal in contact with skin.
H312 : Harmful in contact with skin.
H314 : Causes severe skin burns and eye damage.
H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.
H330 : Fatal if inhaled.
H331 : Toxic if inhaled.
H335 : May cause respiratory irritation.
H336 : May cause drowsiness or dizziness.
H400 : Very toxic to aquatic life.
H410 : Very toxic to aquatic life with long lasting effects.
H411 : Toxic to aquatic life with long lasting effects.
EUH071 : Corrosive to the respiratory tract.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard
Asp. Tox. : Aspiration hazard
Eye Dam. : Serious eye damage
Eye Irrit. : Eye irritation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



GLUE FOR PAINTED SURFACES - 500 G

Version	Revision Date:	SDS Number:	Date of last issue: 26.05.2023
3.1	23.10.2023	5792258-00011	Date of first issue: 29.04.2020

Flam. Liq.	:	Flammable liquids
Skin Corr.	:	Skin corrosion
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT SE	:	Specific target organ toxicity - single exposure
DE TRGS 900	:	Germany. TRGS 900 - Occupational exposure limit values.
DE TRGS 900 / AGW	:	Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Classification of the mixture:

Skin Irrit. 2	H315
Eye Irrit. 2	H319
Aquatic Chronic 3	H412

Classification procedure:

Calculation method
Calculation method
Calculation method

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



GLUE FOR PAINTED SURFACES - 500 G

Version	Revision Date:	SDS Number:	Date of last issue: 26.05.2023
3.1	23.10.2023	5792258-00011	Date of first issue: 29.04.2020

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN