according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



2-COMPONENT PUR ADHESIVE - 380 ML / 550 G (comp. B)

Version Revision Date: SDS Number: Date of last issue: 26.04.2023 15.1 28.07.2023 10611609-00012 Date of first issue: 11.06.2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : 2-COMPONENT PUR ADHESIVE - 380 ML / 550 G (comp. B)

Product code : 08921351

Unique Formula Identifier

(UFI)

9WC8-802R-C000-5UCJ

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Adhesives

stance/Mixture Professional use product

Recommended restrictions

on use

: May only be used by trained personnel.

1.3 Details of the supplier of the safety data sheet

Company : Adolf Wuerth GmbH & Co. KG

Reinhold-Würth-Str. 12-17

74653 Künzelsau

Telephone : +49 794015 0

Telefax : +49 794015 10 00

E-mail address of person responsible for the SDS

: isi@wuerth.com

1.4 Emergency telephone number

+49 (0)6132 - 84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Respiratory sensitisation, Category 1 H334: May cause allergy or asthma symptoms or

breathing difficulties if inhaled.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



2-COMPONENT PUR ADHESIVE - 380 ML / 550 G (comp. B)

Version Revision Date: SDS Number: Date of last issue: 26.04.2023 15.1 28.07.2023 10611609-00012 Date of first issue: 11.06.2010

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Carcinogenicity, Category 2 H351: Suspected of causing cancer.

Specific target organ toxicity - single ex-

posure, Category 3

H335: May cause respiratory irritation.

Specific target organ toxicity - repeated

exposure, Category 2

H373: May cause damage to organs through pro-

longed or repeated exposure.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms





Signal word : Danger

Hazard statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

H335 May cause respiratory irritation.H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or

repeated exposure.

Precautionary statements : Prevention:

P201 Obtain special instructions before use.

P260 Do not breathe vapours.

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ protective clothing/ eye protec-

tion/ face protection.

Response:

P304 + P340 + P312 IF INHALED: Remove person to fresh

air and keep comfortable for breathing. Call a POISON

CENTER/ doctor if you feel unwell.

P342 + P311 If experiencing respiratory symptoms: Call a

POISON CENTER/ doctor.

Hazardous components which must be listed on the label:

Diphenylmethane diisocyanate, isomers and homologues 4,4'-Diphenylmethane diisocyanate

Additional Labelling

"As from 24 August 2023 adequate training is required before industrial or pro-

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



2-COMPONENT PUR ADHESIVE - 380 ML / 550 G (comp. B)

Version Revision Date: SDS Number: Date of last issue: 26.04.2023 15.1 28.07.2023 10611609-00012 Date of first issue: 11.06.2010

fessional use."

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Excessive exposure may aggravate preexisting asthma and other respiratory disorders (e.g. emphysema, bronchitis, reactive airways dysfunction syndrome).

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Diphenylmethane diisocyanate, isomers and homologues	9016-87-9	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 STOT RE 2; H373 (Respiratory Tract)	>= 20 - < 30
4,4'-Diphenylmethane diisocyanate	101-68-8 202-966-0 615-005-00-9	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 STOT RE 2; H373 (Respiratory Tract) ————————————————————————————————————	>= 10 - < 20

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



2-COMPONENT PUR ADHESIVE - 380 ML / 550 G (comp. B)

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 26.04.2023

 15.1
 28.07.2023
 10611609-00012
 Date of first issue: 11.06.2010

>= 5 % Skin Irrit. 2; H315 >= 5 % Resp. Sens. 1; H334 >= 0,1 %

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

If inhaled : If inhaled, remove to fresh air.

If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

Get medical attention.

In case of skin contact : In case of contact, immediately flush skin with plenty of water

for at least 15 minutes while removing contaminated clothing

and shoes.

Get medical attention.
Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water

for at least 15 minutes.

If easy to do, remove contact lens, if worn.

Get medical attention.

If swallowed, DO NOT induce vomiting.

Get medical attention.

Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

May cause respiratory irritation. Suspected of causing cancer.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



2-COMPONENT PUR ADHESIVE - 380 ML / 550 G (comp. B)

Version Revision Date: SDS Number: Date of last issue: 26.04.2023 15.1 28.07.2023 10611609-00012 Date of first issue: 11.06.2010

May cause damage to organs through prolonged or repeated

exposure.

Respiratory symptoms, including pulmonary edema, may be

delayed.

Excessive exposure may aggravate preexisting asthma and other respiratory disorders (e.g. emphysema, bronchitis, reac-

tive airways dysfunction syndrome).

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Water spray in large fire situations

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Exposure to combustion products may be a hazard to health.

If the temperature rises there is danger of the vessels bursting

due to the high vapor pressure.

Hazardous combustion prod-

ucts

Silicon oxides
Carbon oxides

Metal oxides

Nitrogen oxides (NOx)

Isocyanates

Hydrogen cyanide (hydrocyanic acid)

5.3 Advice for firefighters

Special protective equipment :

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



2-COMPONENT PUR ADHESIVE - 380 ML / 550 G (comp. B)

Version Revision Date: SDS Number: Date of last issue: 26.04.2023 15.1 28.07.2023 10611609-00012 Date of first issue: 11.06.2010

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Follow safe handling advice (see section 7) and personal pro-

tective equipment recommendations (see section 8).

6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g. by containment or oil

barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material.

For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor-

bent.

After approximately one hour, transfer to waste container and

do not seal, due to evolution of carbon dioxide.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to deter-

mine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust

ventilation.

Advice on safe handling : Do not get on skin or clothing.

Do not breathe vapours.

Do not swallow.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



2-COMPONENT PUR ADHESIVE - 380 ML / 550 G (comp. B)

Version Revision Date: SDS Number: Date of last issue: 26.04.2023 15.1 28.07.2023 10611609-00012 Date of first issue: 11.06.2010

Do not get in eyes.

Wash skin thoroughly after handling.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as-

sessment

Keep container tightly closed. Keep away from water.

Protect from moisture.

Already sensitised individuals, and those susceptible to asthma, allergies, chronic or recurrent respiratory disease, should consult their physician regarding working with respiratory irritants or sensitisers.

Take care to prevent spills, waste and minimize release to the

environment.

Hygiene measures If exposure to chemical is likely during typical use, provide eye

flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Contaminated work clothing should not be allowed out of the workplace.

Wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Keep in properly labelled containers. Store locked up. Protect from moisture. Keep in a cool, well-ventilated place. Store in

accordance with the particular national regulations.

Advice on common storage Do not store with the following product types:

Strong oxidizing agents

Gases

Storage class (TRGS 510) 10

Recommended storage tem- : 10 - 50 °C

perature

7.3 Specific end use(s)

Specific use(s) No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Diphenylmethane diisocyanate, iso-	9016-87-9	AGW (Inhalable fraction)	0,05 mg/m3 (MDI)	DE TRGS 900
mers and homo-		,	(= 1)	

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



2-COMPONENT PUR ADHESIVE - 380 ML / 550 G (comp. B)

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 26.04.2023

 15.1
 28.07.2023
 10611609-00012
 Date of first issue: 11.06.2010

logues				
J	Peak-limit: excursion factor (category): 1;=2=(I)			
	Further information: In well-found cases also a momentary value can be established, that never can be exceeded. This substance will be indicated by = in combination with an exceeding value., Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child, Substance sensitizing through the skin and respiratory system			
4,4'- Diphenylmethane diisocyanate	101-68-8	AGW (Vapour and aerosols)	0,05 mg/m3	TRGS 430
	Peak-limit: excursion factor (category): 1;=2=(I)			
	established, th	nat never can be exc ation with an exceed AGW (Vapour and aerosols, inhalable frac-	ed cases also a momentary veeded. This substance will be being value., airway sensitizing 0,05 mg/m3	e indicated by
	tion) Peak-limit: excursion factor (category): 1;=2=(I)			
	Further information: In well-found cases also a momentary value can be established, that never can be exceeded. This substance will be indicated by = in combination with an exceeding value., Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child, Substance sensitizing through the skin and respiratory system			
Dimethyl siloxane reaction with silica	67762-90-7	AGW (Inhalable fraction)	4 mg/m3 (Silica)	DE TRGS 900
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Calcium carbonate	Workers	Inhalation	Long-term systemic effects	6,36 mg/m3
	Consumers	Ingestion	Acute systemic effects	6,1 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	1,06 mg/m3
	Consumers	Ingestion	Long-term systemic effects	6,1 mg/kg bw/day
4,4'-Diphenylmethane diisocyanate	Workers	Inhalation	Long-term local ef- fects	0,05 mg/m3
	Workers	Inhalation	Acute local effects	0,1 mg/m3
	Consumers	Inhalation	Long-term local ef- fects	0,025 mg/m3
	Consumers	Inhalation	Acute local effects	0,05 mg/m3
Benzoic acid, C9-11- branched alkyl esters	Workers	Inhalation	Long-term systemic effects	181 mg/m3

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



2-COMPONENT PUR ADHESIVE - 380 ML / 550 G (comp. B)

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 26.04.2023

 15.1
 28.07.2023
 10611609-00012
 Date of first issue: 11.06.2010

Workers	Skin contact	Long-term systemic effects	206 mg/kg bw/day
Consumers	Inhalation	Long-term systemic effects	53 mg/m3
Consumers	Skin contact	Long-term systemic effects	29 mg/kg bw/day
Consumers	Ingestion	Long-term systemic effects	15,48 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Calcium carbonate	Sewage treatment plant	100 mg/l
4,4'-Diphenylmethane diisocya-	Fresh water	1 mg/l
nate		
	Marine water	0,1 mg/l
	Intermittent use/release	10 mg/l
	Sewage treatment plant	1 mg/l
	Soil	1 mg/kg
Benzoic acid, C9-11-branched	Fresh water sediment	0,065 mg/kg dry
alkyl esters		weight (d.w.)
	Oral (Secondary Poisoning)	6667 mg/kg food

8.2 Exposure controls

Engineering measures

Processing may form hazardous compounds (see section 10).

Minimize workplace exposure concentrations.

If sufficient ventilation is unavailable, use with local exhaust ventilation.

Personal protective equipment

Eye/face protection : Wear the following personal protective equipment:

Safety goggles

Equipment should conform to DIN EN 166

Hand protection

Material : Nitrile rubber
Break through time : >= 480 min
Glove thickness : >= 0,5 mm

Directive : Equipment should conform to DIN EN 374

Wearing time : 240 min

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



2-COMPONENT PUR ADHESIVE - 380 ML / 550 G (comp. B)

Version Revision Date: SDS Number: Date of last issue: 26.04.2023 15.1 28.07.2023 10611609-00012 Date of first issue: 11.06.2010

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

Respiratory protection : If adequate local exhaust ventilation is not available or expo-

sure assessment demonstrates exposures outside the rec-

ommended guidelines, use respiratory protection. Equipment should conform to DIN EN 14387

Filter type : Combined particulates and organic vapour type (A-P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : paste

Colour : coloured

Odour : characteristic

Odour Threshold : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling

range

No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Ignitable (see flash point)

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Flash point : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : Solvent mixture; pH value determination not possible, no

aqueous solution

Viscosity

Viscosity, kinematic : No data available

Solubility(ies)

Water solubility : insoluble

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



2-COMPONENT PUR ADHESIVE - 380 ML / 550 G (comp. B)

Version Revision Date: SDS Number: Date of last issue: 26.04.2023 15.1 28.07.2023 10611609-00012 Date of first issue: 11.06.2010

Partition coefficient: n-

octanol/water

: Not applicable

Vapour pressure : No data available

Density : ca. 1,6 g/cm³

Relative vapour density : No data available

Particle characteristics

Particle size : Not applicable

9.2 Other information

Explosives : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Evaporation rate : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable if used as directed. Follow precautionary advice and avoid incompatible materials and conditions.

Polymerises at high temperatures with evolution of carbon dioxide.

10.3 Possibility of hazardous reactions

Hazardous reactions : Isocyanates react with many materials and the rate of reaction

increases with temperature as well as increased contact; these reactions can become violent. Contact is increased by stirring or if the other material mixes with the isocyanate. Exothermic reaction with acids, amines and alcohols Reacts with water to form carbon dioxide and heat

Isocyanates are not soluble in water and sink to the bottom, but react slowly at the interface. The reaction forms carbon

dioxide gas and a layer of solid polyurea.

Hazardous decomposition products will be formed upon con-

tact with water or humid air.

10.4 Conditions to avoid

Conditions to avoid : Exposure to moisture

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



2-COMPONENT PUR ADHESIVE - 380 ML / 550 G (comp. B)

Version Revision Date: SDS Number: Date of last issue: 26.04.2023 15.1 28.07.2023 10611609-00012 Date of first issue: 11.06.2010

Acids
Bases
Water
Alcohols
Amines
Ammonia
Aluminium
Zinc
Brass
Tin
Copper

Galvanised metals

Humid air

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of : Inhalation

exposure Skin contact Ingestion

Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Components:

Diphenylmethane diisocyanate, isomers and homologues:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 2,24 mg/l

Exposure time: 1 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

4,4'-Diphenylmethane diisocyanate:

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



2-COMPONENT PUR ADHESIVE - 380 ML / 550 G (comp. B)

Version Revision Date: SDS Number: Date of last issue: 26.04.2023 15.1 28.07.2023 10611609-00012 Date of first issue: 11.06.2010

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg

Assessment: The substance or mixture has no acute oral tox-

icity

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 2,24 mg/l

Exposure time: 1 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Remarks: Based on data from similar materials

Skin corrosion/irritation

Causes skin irritation.

Components:

Diphenylmethane diisocyanate, isomers and homologues:

Species : Rabbit Result : Skin irritation

4,4'-Diphenylmethane diisocyanate:

Species : Rabbit

Method : OECD Test Guideline 404

Result : Skin irritation

Remarks : Based on data from similar materials

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

Diphenylmethane diisocyanate, isomers and homologues:

Result : Irritation to eyes, reversing within 7 days

4,4'-Diphenylmethane diisocyanate:

Result : Irritation to eyes, reversing within 7 days Remarks : Based on national or regional regulation.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



2-COMPONENT PUR ADHESIVE - 380 ML / 550 G (comp. B)

Version Revision Date: SDS Number: Date of last issue: 26.04.2023 15.1 28.07.2023 10611609-00012 Date of first issue: 11.06.2010

Components:

Diphenylmethane diisocyanate, isomers and homologues:

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Result : positive

Remarks : Based on data from similar materials

Assessment : Probability or evidence of skin sensitisation in humans

Exposure routes : inhalation (dust/mist/fume)

Species : Rat Result : positive

Assessment : Probability of respiratory sensitisation in humans based on

animal testing

4,4'-Diphenylmethane diisocyanate:

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Result : positive

Assessment : Probability or evidence of skin sensitisation in humans

Exposure routes : Inhalation
Species : Rat
Result : positive

Remarks : Based on data from similar materials

Assessment : Probability of respiratory sensitisation in humans based on

animal testing

Germ cell mutagenicity

Not classified based on available information.

Components:

Diphenylmethane diisocyanate, isomers and homologues:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Rat

Application Route: inhalation (dust/mist/fume)

Method: OECD Test Guideline 474

Result: negative

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



2-COMPONENT PUR ADHESIVE - 380 ML / 550 G (comp. B)

Version Revision Date: SDS Number: Date of last issue: 26.04.2023 15.1 28.07.2023 10611609-00012 Date of first issue: 11.06.2010

4,4'-Diphenylmethane diisocyanate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Rat

Application Route: inhalation (dust/mist/fume)

Method: OECD Test Guideline 474

Result: negative

Carcinogenicity

Suspected of causing cancer.

Components:

Diphenylmethane diisocyanate, isomers and homologues:

Species : Rat

Application Route : inhalation (dust/mist/fume)

Exposure time : 2 Years Result : positive

Carcinogenicity - Assess-

ment

: Limited evidence of carcinogenicity in animal studies

4,4'-Diphenylmethane diisocyanate:

Species : Rat

Application Route : inhalation (dust/mist/fume)

Exposure time : 2 Years Result : positive

Remarks : Based on data from similar materials

Carcinogenicity - Assess-

ment

: Limited evidence of carcinogenicity in animal studies

Reproductive toxicity

Not classified based on available information.

Components:

Diphenylmethane diisocyanate, isomers and homologues:

Effects on foetal develop: Test Type: Embryo-foetal development

ment Species: Rat

Application Route: inhalation (dust/mist/fume)

Result: negative

4,4'-Diphenylmethane diisocyanate:

Effects on foetal develop- : Test Type: Embryo-foetal development

ment Species: Rat

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



2-COMPONENT PUR ADHESIVE - 380 ML / 550 G (comp. B)

Version Revision Date: SDS Number: Date of last issue: 26.04.2023 15.1 28.07.2023 10611609-00012 Date of first issue: 11.06.2010

Application Route: inhalation (dust/mist/fume)

Result: negative

Remarks: Based on data from similar materials

STOT - single exposure

May cause respiratory irritation.

Components:

Diphenylmethane diisocyanate, isomers and homologues:

Assessment : May cause respiratory irritation.

4,4'-Diphenylmethane diisocyanate:

Assessment : May cause respiratory irritation.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Components:

Diphenylmethane diisocyanate, isomers and homologues:

Exposure routes : inhalation (dust/mist/fume)

Target Organs : Respiratory Tract

Assessment : Shown to produce significant health effects in animals at con-

centrations of >0.02 to 0.2 mg/l/6h/d.

4,4'-Diphenylmethane diisocyanate:

Exposure routes : inhalation (dust/mist/fume)

Target Organs : Respiratory Tract

Assessment : Shown to produce significant health effects in animals at con-

centrations of >0.02 to 0.2 mg/l/6h/d.

Repeated dose toxicity

Components:

Diphenylmethane diisocyanate, isomers and homologues:

Species : Rat

NOAEL : 1.4 mg/m3 LOAEL : 4.1 mg/m3

Application Route : inhalation (dust/mist/fume)

Exposure time : 13 Weeks

4,4'-Diphenylmethane diisocyanate:

 Species
 : Rat

 NOAEL
 : 0,2 mg/m3

 LOAEL
 : 1 mg/m3

Application Route : inhalation (dust/mist/fume)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



2-COMPONENT PUR ADHESIVE - 380 ML / 550 G (comp. B)

Version Revision Date: SDS Number: Date of last issue: 26.04.2023 15.1 28.07.2023 10611609-00012 Date of first issue: 11.06.2010

Exposure time : 2 yr

Remarks : Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Diphenylmethane diisocyanate, isomers and homologues:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 1.000 mg/l

Exposure time: 96 h

Toxicity to algae/aquatic

plants

ErC50 (Desmodesmus subspicatus (green algae)): > 1.640

mg/l

Exposure time: 72 h

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

NOEC: > 10 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

4,4'-Diphenylmethane diisocyanate:

Toxicity to fish : LC50 (Oryzias latipes (Orange-red killifish)): > 3.000 mg/l

Exposure time: 96 h

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 129,7 mg/l

Exposure time: 24 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Desmodesmus subspicatus (green algae)): > 1.640

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



2-COMPONENT PUR ADHESIVE - 380 ML / 550 G (comp. B)

Version Revision Date: SDS Number: Date of last issue: 26.04.2023 15.1 28.07.2023 10611609-00012 Date of first issue: 11.06.2010

NOEC (Desmodesmus subspicatus (green algae)): 1.640 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to microorganisms : EC50 : > 100 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

NOEC: 10 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

Remarks: Based on data from similar materials

12.2 Persistence and degradability

Components:

Diphenylmethane diisocyanate, isomers and homologues:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 0 % Exposure time: 28 d

4,4'-Diphenylmethane diisocyanate:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 0 % Exposure time: 28 d

Method: OECD Test Guideline 302

Remarks: Based on data from similar materials

12.3 Bioaccumulative potential

Components:

4,4'-Diphenylmethane diisocyanate:

Bioaccumulation : Species: Cyprinus carpio (Carp)

Bioconcentration factor (BCF): 200

Partition coefficient: n-

octanol/water

log Pow: 4,51

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



2-COMPONENT PUR ADHESIVE - 380 ML / 550 G (comp. B)

Version Revision Date: SDS Number: Date of last issue: 26.04.2023 15.1 28.07.2023 10611609-00012 Date of first issue: 11.06.2010

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.

According to the European Waste Catalogue, Waste Codes

are not product specific, but application specific.

Waste codes should be assigned by the user, preferably in

discussion with the waste disposal authorities.

Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

Waste Code : The following Waste Codes are only suggestions:

used product

08 04 09, waste adhesives and sealants containing organic

solvents or other hazardous substances

08 05 01, waste isocyanates

unused product

08 04 09, waste adhesives and sealants containing organic

solvents or other hazardous substances

08 05 01, waste isocyanates

uncleaned packagings

15 01 10, packaging containing residues of or contaminated

by hazardous substances

Acc. Packaging Act properly emptied packaging: Properly emptied, non-contaminated packaging of nonhazardous products can be supplied to a system for the col-

lection of sales packaging.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



2-COMPONENT PUR ADHESIVE - 380 ML / 550 G (comp. B)

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 26.04.2023

 15.1
 28.07.2023
 10611609-00012
 Date of first issue: 11.06.2010

SECTION 14: Transport information

14.1 UN number or ID number

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good

IATA : UN 3334

14.2 UN proper shipping name

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good

IATA : Aviation regulated liquid, n.o.s.

(Diphenylmethane diisocyanate, isomers and homologues,

4,4'-Diphenylmethane diisocyanate)

14.3 Transport hazard class(es)

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good

Class Subsidiary risks

IATA : 9

14.4 Packing group

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good

IATA (Cargo)

Packing instruction (cargo : 964

aircraft)

Packing instruction (LQ) : Y964
Packing group : III

Labels : Miscellaneous

IATA (Passenger)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



2-COMPONENT PUR ADHESIVE - 380 ML / 550 G (comp. B)

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 26.04.2023

 15.1
 28.07.2023
 10611609-00012
 Date of first issue: 11.06.2010

964

Packing instruction (passen-

ger aircraft)

Packing instruction (LQ) : Y964
Packing group : III

Labels : Miscellaneous

14.5 Environmental hazards

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) Conditions of restriction for the following entries should be considered: Number on list 75, 3

If you intend to use this product as tattoo ink, please contact your vendor

4,4'-Diphenylmethane diisocyanate (Number on list 74, 56)

Diphenylmethane diisocyanate, isomers and homologues (Number on

list 74, 56)

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



2-COMPONENT PUR ADHESIVE - 380 ML / 550 G (comp. B)

Version Revision Date: SDS Number: Date of last issue: 26.04.2023 15.1 28.07.2023 10611609-00012 Date of first issue: 11.06.2010

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Water hazard class (Germa-

ny)

WGK 1 slightly hazardous to water

Classification according to AwSV, Annex 1 (5.2)

Volatile organic compounds Directive 2010/75/EU of 24 November 2010 on industrial

> emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 0,3 %

Other regulations:

TRGS 430 (German regulatory requirements)

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Contains a substance which is subject to the TRGS 905 list of carcinogenic, germ cell mutagenic and reproductive toxic substances.

Diphenylmethane diisocyanate, isomers and homologues

carcinogenic: category 2 according to Annex I of the CLP Directive mutagenic: based on the available data no classification in the categories of Annex I of the CLP Directive

could be made

Harmful for fertility: based on the available data no classification in the categories of Annex I of the CLP

Directive could be made

Harmful for development: based on the available data no classification in the categories of Annex I of the CLP

Directive could be made

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



2-COMPONENT PUR ADHESIVE - 380 ML / 550 G (comp. B)

Version Revision Date: SDS Number: Date of last issue: 26.04.2023 15.1 28.07.2023 10611609-00012 Date of first issue: 11.06.2010

Other information : Items where changes have been made to the previous version

are highlighted in the body of this document by two vertical

lines.

Full text of H-Statements

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.

H319 : Causes serious eye irritation.

H332 : Harmful if inhaled.

H334 : May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

H335 : May cause respiratory irritation. H351 : Suspected of causing cancer.

H373 : May cause damage to organs through prolonged or repeated

exposure if inhaled.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Carc. : Carcinogenicity
Eye Irrit. : Eye irritation

Resp. Sens. : Respiratory sensitisation

Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

STOT RE : Specific target organ toxicity - repeated exposure STOT SE : Specific target organ toxicity - single exposure

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

TRGS 430 : Germany. TRGS 430 - Isocyanates

DE TRGS 900 / AGW : Time Weighted Average TRGS 430 / AGW : Occupational Exposure Limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways: ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



2-COMPONENT PUR ADHESIVE - 380 ML / 550 G (comp. B)

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 26.04.2023

 15.1
 28.07.2023
 10611609-00012
 Date of first issue: 11.06.2010

Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Training advice : Observe requirements and guidance related to training before

using this product at work.

Sources of key data used to compile the Safety Data

Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Classification of the mixture: Classification procedure:

Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Resp. Sens. 1	H334	Calculation method
Skin Sens. 1	H317	Calculation method
Carc. 2	H351	Calculation method
STOT SE 3	H335	Calculation method
STOT RE 2	H373	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN