according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## A/C LEAK STOPP PLUS (aerosol) - 60 ML

Version Revision Date: SDS Number: Date of last issue: 26.09.2023 7.0 30.04.2024 10697946-00012 Date of first issue: 11.06.2010

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : A/C LEAK STOPP PLUS (aerosol) - 60 ML

Product code : 0892764776

Unique Formula Identifier

(UFI)

: CGN9-K08R-J005-3709

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-Crack detection substance stance/Mixture Professional use product

Recommended restrictions

on use

Not applicable

1.3 Details of the supplier of the safety data sheet

Company : Adolf Wuerth GmbH & Co. KG

Reinhold-Würth-Str. 12-17

74653 Künzelsau

Telephone : +49 794015 0

Telefax +49 794015 10 00

E-mail address of person

responsible for the SDS

isi@wuerth.com

1.4 Emergency telephone number

+49 (0)6132 - 84463

#### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

### Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 3 H229: Pressurised container: May burst if heated.

Long-term (chronic) aquatic hazard, Cat-

H411: Toxic to aquatic life with long lasting effects.

egory 2

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## A/C LEAK STOPP PLUS (aerosol) - 60 ML

Version Revision Date: SDS Number: Date of last issue: 26.09.2023 7.0 30.04.2024 10697946-00012 Date of first issue: 11.06.2010

#### 2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

¥2>

Signal word : Warning

Hazard statements : H229 Pressurised container: May burst if heated.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use. P273 Avoid release to the environment.

Response:

P391 Collect spillage.

Storage:

P410 + P412 Protect from sunlight. Do not expose to tem-

peratures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/ container to an approved

waste disposal plant.

#### **Additional Labelling**

EUH208 Contains Methyl methacrylate. May produce an allergic reaction.

0,11 % by mass of the contents are flammable.

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## A/C LEAK STOPP PLUS (aerosol) - 60 ML

Version Revision Date: SDS Number: Date of last issue: 26.09.2023 7.0 30.04.2024 10697946-00012 Date of first issue: 11.06.2010

### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Phenol, isopropylated, phosphate (3:1)	68937-41-7 273-066-3	Repr. 2; H361 STOT RE 2; H373 (Adrenal gland) Aquatic Chronic 1; H410  M-Factor (Chronic aquatic toxicity): 10	>= 1 - < 2,5
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	68411-46-1 270-128-1	Repr. 2; H361f	>= 0,1 - < 1
Methyl methacrylate	80-62-6 201-297-1 607-035-00-6	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Skin Sens. 1; H317 STOT SE 3; H335	>= 0,1 - < 1

For explanation of abbreviations see section 16.

#### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

General advice : In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

If inhaled : If inhaled, remove to fresh air.

Get medical attention.

In case of skin contact : In case of contact, immediately flush skin with soap and plenty

of water.

Remove contaminated clothing and shoes.

Get medical attention.
Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact : Flush eyes with water as a precaution.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## A/C LEAK STOPP PLUS (aerosol) - 60 ML

Version Revision Date: SDS Number: Date of last issue: 26.09.2023 7.0 30.04.2024 10697946-00012 Date of first issue: 11.06.2010

Get medical attention if irritation develops and persists.

If swallowed : If swallowed, DO NOT induce vomiting.

Get medical attention.

Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

Risks : May produce an allergic reaction.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

### **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

None known.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Exposure to combustion products may be a hazard to health. If the temperature rises there is danger of the vessels bursting

due to the high vapor pressure.

Hazardous combustion prod: :

ucts

Carbon oxides

Oxides of phosphorus

#### 5.3 Advice for firefighters

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

#### **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Follow safe handling advice (see section 7) and personal pro-

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## A/C LEAK STOPP PLUS (aerosol) - 60 ML

Version Revision Date: SDS Number: Date of last issue: 26.09.2023 7.0 30.04.2024 10697946-00012 Date of first issue: 11.06.2010

tective equipment recommendations (see section 8).

#### 6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g. by containment or oil

barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material.

For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor-

bent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to deter-

mine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

#### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

### **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Do not get on skin or clothing.

Do not breathe spray. Do not swallow.

Avoid contact with eyes.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as-

sessment

Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

Take care to prevent spills, waste and minimize release to the

environment.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye

flushing systems and safety showers close to the working

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## A/C LEAK STOPP PLUS (aerosol) - 60 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 26.09.2023

 7.0
 30.04.2024
 10697946-00012
 Date of first issue: 11.06.2010

place. When using do not eat, drink or smoke. Contaminated work clothing should not be allowed out of the workplace.

Wash contaminated clothing before re-use.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Do not pierce or burn, even

after use. Keep cool. Protect from sunlight.

Advice on common storage : Do not store with the following product types:

Self-reactive substances and mixtures

Organic peroxides Oxidizing agents Flammable solids Pyrophoric liquids Pyrophoric solids

Self-heating substances and mixtures

Substances and mixtures, which in contact with water, emit

flammable gases

Explosives Gases

Storage class (TRGS 510) : 2B

Recommended storage tem: :

perature

< 50 °C

7.3 Specific end use(s)

Specific use(s) : No data available

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form	Control parameters	Basis
		of exposure)		
Distillates (petrole-	64742-54-7	AGW (Vapour	5 mg/m3	DE TRGS
um), hydrotreated		and aerosols)		900
heavy paraffinic				
	Peak-limit: excursion factor (category): 4;(II)			
	Further information: When there is compliance with the OEL and biological			
	tolerance values, there is no risk of harming the unborn child			
Phenol, isopropy-	68937-41-7	AGW (Inhalable	1 mg/m3	DE TRGS
lated, phosphate		fraction)		900
(3:1)				
	Peak-limit: excursion factor (category): 2;(II)			
		MAK (inhalable	1 mg/m3	DE DFG MAK
		fraction)		

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



# A/C LEAK STOPP PLUS (aerosol) - 60 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 26.09.2023

 7.0
 30.04.2024
 10697946-00012
 Date of first issue: 11.06.2010

II	Peak-limit: excursion factor (category): 2; II			
	Further information: Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed			
Methyl methacry- late	80-62-6	TWA	50 ppm	2009/161/EU
	Further information: Indicative			
		STEL	100 ppm	2009/161/EU
	Further information: Indicative			
		AGW	50 ppm	DE TRGS
			210 mg/m3	900
	Peak-limit: excursion factor (category): 2;(I)			
	Further information: When there is compliance with the OEL and biological			
	tolerance values, there is no risk of harming the unborn child			
		MAK	50 ppm	DE DFG MAK
			210 mg/m3	
	Peak-limit: excursion factor (category): 2; I			
	Further information: Danger of sensitization of the skin, Damage to the em-			
	bryo or foetus is unlikely when the MAK value or the BAT value is observed			

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
1,2- Benzenedicarboxylic acid, di-C9-11- branched alkyl esters, C10-rich	Workers	Inhalation	Long-term systemic effects	5,29 mg/m3
	Workers	Skin contact	Long-term systemic effects	41,67 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	1,3 mg/m3
	Consumers	Skin contact	Long-term systemic effects	20,83 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0,75 mg/kg bw/day
Phenol, isopropylated, phosphate (3:1)	Workers	Inhalation	Long-term systemic effects	0,145 mg/m3
	Workers	Inhalation	Acute systemic effects	700 mg/m3
	Workers	Skin contact	Long-term systemic effects	0,416 mg/kg bw/day
	Workers	Skin contact	Acute systemic effects	2000 mg/kg bw/day
	Workers	Skin contact	Acute local effects	16 mg/cm2
	Consumers	Inhalation	Long-term systemic effects	0,07 mg/m3
	Consumers	Inhalation	Acute systemic effects	350 mg/m3
	Consumers	Skin contact	Long-term systemic effects	0,208 mg/kg bw/day
	Consumers	Skin contact	Acute systemic ef-	100 mg/kg

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



# A/C LEAK STOPP PLUS (aerosol) - 60 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 26.09.2023

 7.0
 30.04.2024
 10697946-00012
 Date of first issue: 11.06.2010

			fects	bw/day
	Consumers	Skin contact	Acute local effects	8 mg/cm2
	Consumers	Ingestion	Long-term systemic	0,04 mg/kg
			effects	bw/day
	Consumers	Ingestion	Acute systemic ef-	50 mg/kg
			fects	bw/day
Methyl methacrylate	Workers	Inhalation	Long-term systemic effects	348,4 mg/m3
	Workers	Inhalation	Long-term local ef- fects	208 mg/m3
	Workers	Inhalation	Acute local effects	416 mg/m3
	Workers	Skin contact	Long-term systemic effects	13,67 mg/kg bw/day
	Workers	Skin contact	Long-term local ef- fects	1,5 mg/cm2
	Workers	Skin contact	Acute local effects	1,5 mg/cm2
	Consumers	Inhalation	Long-term systemic effects	74,3 mg/m3
	Consumers	Inhalation	Long-term local ef- fects	104 mg/m3
	Consumers	Inhalation	Acute local effects	208 mg/m3
	Consumers	Skin contact	Long-term systemic effects	8,2 mg/kg bw/day
	Consumers	Skin contact	Long-term local ef- fects	1,5 mg/cm2
	Consumers	Skin contact	Acute local effects	1,5 mg/cm2
	Consumers	Ingestion	Long-term systemic effects	8,2 mg/kg bw/day
Benzenamine, N- phenyl-, reaction products with 2,4,4- trimethylpentene	Workers	Inhalation	Long-term systemic effects	0,31 mg/m3
	Workers	Skin contact	Long-term systemic effects	0,44 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0,08 mg/m3
	Consumers	Skin contact	Long-term systemic effects	0,22 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0,05 mg/kg bw/day

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

	, , ,	
Substance name	Environmental Compartment	Value
Distillates (petroleum), hy-	Oral (Secondary Poisoning)	9,33 mg/kg food
drotreated heavy paraffinic		
Phenol, isopropylated, phosphate	Fresh water	0,00031 mg/l
(3:1)		
	Marine water	0,000031 mg/l
	Freshwater - intermittent	0,015 mg/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	0,185 mg/kg dry
		weight (d.w.)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## A/C LEAK STOPP PLUS (aerosol) - 60 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 26.09.2023

 7.0
 30.04.2024
 10697946-00012
 Date of first issue: 11.06.2010

	Marine sediment	0,018 mg/kg dry
		weight (d.w.)
	Soil	2,5 mg/kg dry
		weight (d.w.)
	Oral (Secondary Poisoning)	1,85 mg/kg food
Methyl methacrylate	Fresh water	0,94 mg/l
	Freshwater - intermittent	0,69 mg/l
	Marine water	0,094 mg/l
	Sewage treatment plant	10 mg/l
	Fresh water sediment	10,2 mg/kg dry
		weight (d.w.)
	Marine sediment	1,02 mg/kg dry
		weight (d.w.)
	Soil	1,48 mg/kg dry
		weight (d.w.)
Benzenamine, N-phenyl-, reac-	Fresh water	0,034 mg/l
tion products with 2,4,4-		
trimethylpentene		
	Marine water	0,003 mg/l
	Freshwater - intermittent	0,51 mg/l
	Sewage treatment plant	10 mg/l
	Fresh water sediment	0,446 mg/kg dry
		weight (d.w.)
	Marine sediment	0,045 mg/kg dry
		weight (d.w.)
	Soil	17,6 mg/kg dry
		weight (d.w.)
	Oral (Secondary Poisoning)	0,833 mg/kg food

#### 8.2 Exposure controls

### **Engineering measures**

Ensure adequate ventilation, especially in confined areas. Minimize workplace exposure concentrations.

### Personal protective equipment

Eye/face protection : Please follow all applicable local/national requirements when

selecting protective measures for a specific workplace.

Wear the following personal protective equipment:

Safety glasses

Always wear eye protection when the potential for inadvertent

eye contact with the product cannot be excluded. Equipment should conform to DIN EN 166

Hand protection

Material : Nitrile rubber
Break through time : > 240 min
Glove thickness : 0,11 mm

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration and quantity of the hazardous sub-

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## A/C LEAK STOPP PLUS (aerosol) - 60 ML

Version Revision Date: SDS Number: Date of last issue: 26.09.2023 7.0 30.04.2024 10697946-00012 Date of first issue: 11.06.2010

stance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

Respiratory protection : If adequate local exhaust ventilation is not available or expo-

sure assessment demonstrates exposures outside the rec-

ommended guidelines, use respiratory protection. Equipment should conform to DIN EN 14387

Filter type : Combined particulates and organic vapour type (A-P)

### **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and chemical properties

Physical state : aerosol

Colour : green, yellow, opaque

Odour : characteristic

Odour Threshold : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling :

range

Not applicable

Flammability (solid, gas) : Not classified as a flammability hazard

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Flash point : > 200 - < 250 °C

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## A/C LEAK STOPP PLUS (aerosol) - 60 ML

Version Revision Date: SDS Number: Date of last issue: 26.09.2023 7.0 30.04.2024 10697946-00012 Date of first issue: 11.06.2010

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : substance/mixture is non-soluble (in water)

Viscosity

Viscosity, kinematic : Not applicable

Solubility(ies)

Water solubility : No data available

Partition coefficient: n-

octanol/water

Not applicable

Vapour pressure : Not applicable

Density : 0,891 g/cm<sup>3</sup>

Relative vapour density : Not applicable

Particle characteristics

Particle size : Not applicable

9.2 Other information

Explosives : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Evaporation rate : Not applicable

### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

Not classified as a reactivity hazard.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## A/C LEAK STOPP PLUS (aerosol) - 60 ML

Version Revision Date: SDS Number: Date of last issue: 26.09.2023 7.0 30.04.2024 10697946-00012 Date of first issue: 11.06.2010

#### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : If the temperature rises there is danger of the vessels bursting

due to the high vapor pressure.

Can react with strong oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

#### 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

### **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of : Inhalation

exposure Skin contact

Ingestion Eye contact

#### **Acute toxicity**

Not classified based on available information.

#### Components:

### Phenol, isopropylated, phosphate (3:1):

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 200 mg/l

Exposure time: 1 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 10.000 mg/kg

#### Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Methyl methacrylate:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## A/C LEAK STOPP PLUS (aerosol) - 60 ML

Version Revision Date: SDS Number: Date of last issue: 26.09.2023 7.0 30.04.2024 10697946-00012 Date of first issue: 11.06.2010

Acute dermal toxicity : LD50 (Rabbit, male): > 5.000 mg/kg

#### Skin corrosion/irritation

Not classified based on available information.

#### **Components:**

#### Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Species : Rabbit

Method : OECD Test Guideline 404

Result : Mild skin irritation

Methyl methacrylate:

Species : Rabbit Result : Skin irritation

### Serious eye damage/eye irritation

Not classified based on available information.

### **Components:**

### Phenol, isopropylated, phosphate (3:1):

Species : Rabbit

Result : No eye irritation

#### Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Species : Rabbit

Method : OECD Test Guideline 405

Result : No eye irritation

Methyl methacrylate:

Species : Rabbit

Result : No eye irritation

### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.

#### **Components:**

### Phenol, isopropylated, phosphate (3:1):

Test Type : Local lymph node assay (LLNA)

Exposure routes : Skin contact

Species : Mouse

Method : OECD Test Guideline 429

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## A/C LEAK STOPP PLUS (aerosol) - 60 ML

Version Revision Date: SDS Number: Date of last issue: 26.09.2023 7.0 30.04.2024 10697946-00012 Date of first issue: 11.06.2010

Result : equivocal

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Test Type : Maximisation Test Exposure routes : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

Methyl methacrylate:

Test Type : Local lymph node assay (LLNA)

Exposure routes : Skin contact
Species : Mouse
Result : positive

Assessment : Probability or evidence of skin sensitisation in humans

Germ cell mutagenicity

Not classified based on available information.

**Components:** 

Phenol, isopropylated, phosphate (3:1):

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: negative

Test Type: DNA damage and repair, unscheduled DNA syn-

thesis in mammalian cells (in vitro)

Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow

cytogenetic test, chromosomal analysis)

Species: Hamster

Application Route: Ingestion Method: OECD Test Guideline 475

Result: negative

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## A/C LEAK STOPP PLUS (aerosol) - 60 ML

Version Revision Date: SDS Number: Date of last issue: 26.09.2023 7.0 30.04.2024 10697946-00012 Date of first issue: 11.06.2010

Methyl methacrylate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Test Type: in vitro micronucleus test Method: OECD Test Guideline 487

Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)

Species: Mouse

**Application Route: Inhalation** 

Result: negative

#### Carcinogenicity

Not classified based on available information.

#### **Components:**

### Methyl methacrylate:

Species: MouseApplication Route: InhalationExposure time: 102 weeksResult: negative

#### Reproductive toxicity

Not classified based on available information.

#### **Components:**

#### Phenol, isopropylated, phosphate (3:1):

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening

test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 421

Result: positive

Effects on foetal develop-

ment

Test Type: Fertility/early embryonic development

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 414

Result: negative

Reproductive toxicity - As-

sessment

Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

15 / 26

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## A/C LEAK STOPP PLUS (aerosol) - 60 ML

Version Revision Date: SDS Number: Date of last issue: 26.09.2023 7.0 30.04.2024 10697946-00012 Date of first issue: 11.06.2010

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Effects on fertility : Test Type: One-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 443

Result: positive

Effects on foetal develop-

ment

Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

Reproductive toxicity - As-

sessment

Some evidence of adverse effects on sexual function and

fertility, based on animal experiments.

Methyl methacrylate:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 416

Result: negative

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rabbit

Application Route: inhalation (vapour) Method: OECD Test Guideline 414

Result: negative

### STOT - single exposure

Not classified based on available information.

#### Components:

### Methyl methacrylate:

Assessment : May cause respiratory irritation.

### STOT - repeated exposure

Not classified based on available information.

### **Components:**

### Phenol, isopropylated, phosphate (3:1):

Exposure routes : Ingestion
Target Organs : Adrenal gland

Assessment : Shown to produce significant health effects in animals at con-

centrations of >10 to 100 mg/kg bw.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## A/C LEAK STOPP PLUS (aerosol) - 60 ML

Version Revision Date: SDS Number: Date of last issue: 26.09.2023 7.0 30.04.2024 10697946-00012 Date of first issue: 11.06.2010

### Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Assessment : No significant health effects observed in animals at concentra-

tions of 100 mg/kg bw or less.

#### Repeated dose toxicity

#### Components:

#### Phenol, isopropylated, phosphate (3:1):

Species : Rat

NOAEL : < 25 mg/kg Application Route : Ingestion Exposure time : 90 Days

Method : OECD Test Guideline 408

### Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Species : Rat

NOAEL : 25 mg/kg

LOAEL : 75 mg/kg

Application Route : Ingestion

Exposure time : 53 Days

Method : OECD Test Guideline 422

#### Methyl methacrylate:

Species : Rat, male

NOAEL : >= 124,1 mg/kg

Application Route : Ingestion

Exposure time : 104 Weeks

#### **Aspiration toxicity**

Not classified based on available information.

#### 11.2 Information on other hazards

#### **Endocrine disrupting properties**

#### **Product:**

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## A/C LEAK STOPP PLUS (aerosol) - 60 ML

Version Revision Date: SDS Number: Date of last issue: 26.09.2023 7.0 30.04.2024 10697946-00012 Date of first issue: 11.06.2010

### **SECTION 12: Ecological information**

### 12.1 Toxicity

#### **Components:**

Phenol, isopropylated, phosphate (3:1):

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 1,6 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): 1,5 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EL50 (Pseudokirchneriella subcapitata (green algae)): > 2,5

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOELR (Pseudokirchneriella subcapitata (green algae)): 0,31

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 : > 1.000 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Toxicity to fish (Chronic tox-

icity)

NOEC: 0,0031 mg/l Exposure time: 33 d

Species: Pimephales promelas (fathead minnow)

Method: OECD Test Guideline 210

Toxicity to daphnia and other : aquatic invertebrates (Chron-

aquatic invertebratic toxicity)

NOEC: 0,0415 mg/l

Exposure time: 21 d

Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

M-Factor (Chronic aquatic

toxicity)

: 10

### Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 100 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): 51 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

NOELR (Desmodesmus subspicatus (green algae)): > 1 mg/l

Exposure time: 72 h

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## A/C LEAK STOPP PLUS (aerosol) - 60 ML

Version Revision Date: SDS Number: Date of last issue: 26.09.2023 7.0 30.04.2024 10697946-00012 Date of first issue: 11.06.2010

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

EL50 (Desmodesmus subspicatus (green algae)): > 100 mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chron-

ic toxicity)

EL10: 1,69 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 211

Methyl methacrylate:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 159,1 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 69 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

ErC50 (Raphidocelis subcapitata (freshwater green alga)): >

110 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Raphidocelis subcapitata (freshwater green alga)): >=

110 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (activated sludge): 3.162 mg/l

Exposure time: 3 h Method: ISO 8192

Toxicity to fish (Chronic tox-

icity)

EC10: 16,9 mg/l Exposure time: 35 d

Species: Danio rerio (zebra fish) Method: OECD Test Guideline 210

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC: 37 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

#### 12.2 Persistence and degradability

#### **Components:**

### Phenol, isopropylated, phosphate (3:1):

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 17,9 %

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## A/C LEAK STOPP PLUS (aerosol) - 60 ML

Version Revision Date: SDS Number: Date of last issue: 26.09.2023 7.0 30.04.2024 10697946-00012 Date of first issue: 11.06.2010

Exposure time: 28 d

Method: OECD Test Guideline 301D

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 1 % Exposure time: 28 d

Method: OECD Test Guideline 301B

Methyl methacrylate:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 94 % Exposure time: 14 d

Method: OECD Test Guideline 301C

12.3 Bioaccumulative potential

**Components:** 

Phenol, isopropylated, phosphate (3:1):

Bioaccumulation : Species: Lepomis macrochirus (Bluegill sunfish)

Bioconcentration factor (BCF): 776 Method: OECD Test Guideline 305

Partition coefficient: n-

octanol/water

log Pow: > 4

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene:

Partition coefficient: n- : log Pow: > 4

octanol/water Remarks: Calculation

Methyl methacrylate:

Partition coefficient: n-

octanol/water

log Pow: 1,38

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

**Product:** 

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## A/C LEAK STOPP PLUS (aerosol) - 60 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 26.09.2023

 7.0
 30.04.2024
 10697946-00012
 Date of first issue: 11.06.2010

#### 12.6 Endocrine disrupting properties

#### **Product:**

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

#### 12.7 Other adverse effects

No data available

### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.

According to the European Waste Catalogue, Waste Codes

are not product specific, but application specific.

Waste codes should be assigned by the user, preferably in

discussion with the waste disposal authorities.

Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product. Please ensure aerosol cans are sprayed completely empty

(including propellant)

Waste Code : The following Waste Codes are only suggestions:

used product

13 02 08, other engine, gear and lubricating oils

unused product

13 02 08, other engine, gear and lubricating oils

uncleaned packagings

15 01 10, packaging containing residues of or contaminated

by hazardous substances

#### **SECTION 14: Transport information**

#### 14.1 UN number or ID number

ADN : UN 1950
ADR : UN 1950
RID : UN 1950
IMDG : UN 1950

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## A/C LEAK STOPP PLUS (aerosol) - 60 ML

Version Revision Date: SDS Number: Date of last issue: 26.09.2023 7.0 30.04.2024 10697946-00012 Date of first issue: 11.06.2010

IATA : UN 1950

14.2 UN proper shipping name

ADN : AEROSOLS
ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS

(Phenol, isopropylated, phosphate (3:1))

IATA : Aerosols, non-flammable

14.3 Transport hazard class(es)

Class Subsidiary risks

 ADN
 : 2
 2.2

 ADR
 : 2
 2.2

 RID
 : 2
 2.2

IMDG : 2.2 IATA : 2.2

14.4 Packing group

ADN

Packing group : Not assigned by regulation

Classification Code : 5A Labels : 2.2

ADR

Packing group : Not assigned by regulation

Classification Code : 5A Labels : 2.2 Tunnel restriction code : (E)

RID

Packing group : Not assigned by regulation

Classification Code : 5A Hazard Identification Number : 20 Labels : 2.2

**IMDG** 

Packing group : Not assigned by regulation

Labels : 2.2 EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo : 203

aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation
Labels : Non-flammable, non-toxic Gas

IATA (Passenger)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## A/C LEAK STOPP PLUS (aerosol) - 60 ML

Version Revision Date: SDS Number: Date of last issue: 26.09.2023 7.0 30.04.2024 10697946-00012 Date of first issue: 11.06.2010

Packing instruction (passen: 203

ger aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation Labels : Non-flammable, non-toxic Gas

14.5 Environmental hazards

**ADN** 

Environmentally hazardous : yes

**ADR** 

Environmentally hazardous : yes

**RID** 

Environmentally hazardous : yes

**IMDG** 

Marine pollutant : yes

#### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### 14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

### **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mix-

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) Conditions of restriction for the following entries should be considered: Number on list 75

Substance(s) or mixture(s) are listed here according to their appearance in the regulation, irrespective of their use/purpose or the conditions of the restriction. Please refer to the conditions in corresponding Regulation to determine whether an entry is applicable to the placing on the market or not

If you intend to use this product as tattoo ink, please contact your vendor.

1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich (Number on list 52)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## A/C LEAK STOPP PLUS (aerosol) - 60 ML

Version Revision Date: SDS Number: Date of last issue: 26.09.2023 7.0 30.04.2024 10697946-00012 Date of first issue: 11.06.2010

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

Not applicable

Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of

major-accident hazards involving dangerous substances.

Quantity 1 Quantity 2

E2 ENVIRONMENTAL 200 t 500 t

**HAZARDS** 

Water hazard class (Germa-

nv)

WGK 3 highly hazardous to water

Classification according to AwSV, Annex 1 (5.2)

TA Luft List (Germany) : 5.2.1: Total dust:

Not applicable

5.2.2: Inorganic substances in powdered form:

Not applicable

5.2.4: Inorganic substances in gaseous form:

Not applicable

5.2.5: Organic Substances:

Not applicable

5.2.7.1.1: Carcinogenic substance:

Not applicable

5.2.7.1.1: Quartz fine dust PM4:

Not applicable

5.2.7.1.1: Formaldehyde:

Not applicable 5.2.7.1.1: fibres: Not applicable

5.2.7.1.2: Germ cell mutagens:

Not applicable

5.2.7.1.3: Substances toxic to reproduction:

Not applicable

5.2.7.2: Poorly degradable, easily enrichable and highly toxic

organic substances: Not applicable

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## A/C LEAK STOPP PLUS (aerosol) - 60 ML

Version Revision Date: SDS Number: Date of last issue: 26.09.2023 7.0 30.04.2024 10697946-00012 Date of first issue: 11.06.2010

Volatile organic compounds (VOC) content: 0 %

#### 15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

Other information : Items where changes have been made to the previous version

are highlighted in the body of this document by two vertical

lines.

#### **Full text of H-Statements**

H225 : Highly flammable liquid and vapour.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction. H335 : May cause respiratory irritation.

H361 : Suspected of damaging fertility or the unborn child.

H361f : Suspected of damaging fertility.

H373 : May cause damage to organs through prolonged or repeated

exposure.

H410 : Very toxic to aquatic life with long lasting effects.

#### Full text of other abbreviations

Aquatic Chronic : Long-term (chronic) aquatic hazard

Flam. Liq. : Flammable liquids
Repr. : Reproductive toxicity
Skin Irrit. : Skin irritation

Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

STOT RE : Specific target organ toxicity - repeated exposure STOT SE : Specific target organ toxicity - single exposure

2009/161/EU : Europe. COMMISSION DIRECTIVE 2009/161/EU establishing

a third list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending

Commission Directive 2000/39/EC

DE DFG MAK : Germany. MAK BAT Annex IIa

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

2009/161/EU / TWA : Limit Value - eight hours 2009/161/EU / STEL : Short term exposure limit

DE DFG MAK / MAK : MAK value

DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good La-

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## A/C LEAK STOPP PLUS (aerosol) - 60 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 26.09.2023

 7.0
 30.04.2024
 10697946-00012
 Date of first issue: 11.06.2010

boratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association: IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

#### **Further information**

Sources of key data used to compile the Safety Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

#### Classification of the mixture: Classification procedure:

Aerosol 3 H229 Based on product data or assessment

Aquatic Chronic 2 H411 Calculation method

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN