according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



ADHESIVE SEALANT GLASS CLEAR - 290 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.04.2023

 11.0
 29.06.2023
 10605190-00017
 Date of first issue: 11.06.2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ADHESIVE SEALANT GLASS CLEAR - 290 ML

Product code : 08932250

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Adhesives and/or sealants Professional use product

Recommended restrictions

on use

Not applicable

1.3 Details of the supplier of the safety data sheet

Company : Adolf Wuerth GmbH & Co. KG

Reinhold-Würth-Str. 12-17

74653 Künzelsau

Telephone : +49 794015 0

Telefax : +49 794015 10 00

E-mail address of person

responsible for the SDS

: isi@wuerth.com

1.4 Emergency telephone number

+49 (0)6132 - 84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

Additional Labelling

EUH208 Contains Trimethoxyvinylsilane, N-(3-(Trimethoxysilyl)propyl)ethylenediamine,

N-[3-(dimethoxymethylsilyl)propyl]ethylenediamine. May produce an allergic

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



ADHESIVE SEALANT GLASS CLEAR - 290 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.04.2023

 11.0
 29.06.2023
 10605190-00017
 Date of first issue: 11.06.2010

reaction.

EUH210 Safety data sheet available on request.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Trimethoxyvinylsilane	2768-02-7 220-449-8 014-049-00-0 01-2119513215-52	Flam. Liq. 3; H226 Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Sens. 1B; H317 STOT SE 2; H371 (Central nervous system, optic nerve) Acute toxicity estimate Acute oral toxicity: > 300 - 2.000 mg/kg Acute inhalation toxicity (vapour): 16,8 mg/l	>= 1 - < 10
N-(3- (Trimethoxysi- lyl)propyl)ethylenediamine	1760-24-3 217-164-6 01-2119970215-39	Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Dam. 1; H318 Skin Sens. 1B; H317 STOT SE 2; H371 (Central nervous system, optic nerve) STOT RE 2; H373 (Respiratory Tract)	>= 0,25 - < 1

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



ADHESIVE SEALANT GLASS CLEAR - 290 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.04.2023

 11.0
 29.06.2023
 10605190-00017
 Date of first issue: 11.06.2010

		Aquatic Chronic 3; H412	
		Acute toxicity esti- mate	
		Acute oral toxicity: > 300 - 2.000 mg/kg Acute inhalation toxicity (dust/mist): 1,49 mg/l	
N-[3- (dimethoxymethylsi- lyl)propyl]ethylenediamine	3069-29-2 221-336-6 01-2119963926-21	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1A; H317	>= 0,1 - < 1

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

If inhaled : If inhaled, remove to fresh air.

Get medical attention.

In case of skin contact : In case of contact, immediately flush skin with soap and plenty

of water.

Remove contaminated clothing and shoes.

Get medical attention. Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact : Flush eyes with water as a precaution.

Get medical attention if irritation develops and persists.

If swallowed : If swallowed, DO NOT induce vomiting unless directed to do

so by medical personnel. Get medical attention.

Rinse mouth thoroughly with water.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

None known.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



ADHESIVE SEALANT GLASS CLEAR - 290 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.04.2023

 11.0
 29.06.2023
 10605190-00017
 Date of first issue: 11.06.2010

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod: :

ucts

Carbon oxides Silicon oxides

5.3 Advice for firefighters

Special protective equipment :

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Follow safe handling advice (see section 7) and personal pro-

tective equipment recommendations (see section 8).

6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.

Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



ADHESIVE SEALANT GLASS CLEAR - 290 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.04.2023

 11.0
 29.06.2023
 10605190-00017
 Date of first issue: 11.06.2010

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material.

For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor-

bent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to deter-

mine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Do not breathe dust, fume, gas, mist, vapours or spray.

Do not swallow.

Avoid contact with eyes.

Avoid prolonged or repeated contact with skin.

Wash skin thoroughly after handling.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as-

sessment

Keep away from water. Protect from moisture.

Do not eat, drink or smoke when using this product.

Take care to prevent spills, waste and minimize release to the

environment.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye

flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contami-

nated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep in properly labelled containers. Store in accordance with

the particular national regulations.

Advice on common storage : Do not store with the following product types:

Strong oxidizing agents

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



ADHESIVE SEALANT GLASS CLEAR - 290 ML

Revision Date: SDS Number: Date of last issue: 25.04.2023 Version 11.0 29.06.2023 10605190-00017 Date of first issue: 11.06.2010

Storage class (TRGS 510) : 11

Recommended storage tem- : 10 - 35 °C

perature

7.3 Specific end use(s)

Specific use(s) No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Silicon, amorphous	112945-52-	AGW (Inhalable	4 mg/m3	DE TRGS
	5	fraction)	(Silica)	900
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Methanol	67-56-1	TWA	200 ppm	2006/15/EC
			260 mg/m3	
	Further information: Indicative, Identifies the possibility of significant uptake			
	through the skin			
		AGW	100 ppm	DE TRGS
			130 mg/m3	900
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Di-isononyl phthalate	Workers	Inhalation	Long-term systemic effects	51,72 mg/m3
	Workers	Skin contact	Long-term systemic effects	366 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	15,3 mg/m3
	Consumers	Skin contact	Long-term systemic effects	220 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	4,4 mg/kg bw/day
Trimethoxyvinylsilane	Workers	Inhalation	Long-term systemic effects	4,9 mg/m3
	Workers	Skin contact	Long-term systemic	0,69 mg/kg

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



ADHESIVE SEALANT GLASS CLEAR - 290 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.04.2023

 11.0
 29.06.2023
 10605190-00017
 Date of first issue: 11.06.2010

	1	1	effects	bw/day
	Consumers	Inhalation	Long-term systemic effects	1,04 mg/m3
	Consumers	Inhalation	Acute systemic ef- fects	93,4 mg/m3
	Consumers	Skin contact	Long-term systemic effects	0,3 mg/kg bw/day
	Consumers	Skin contact	Acute systemic ef- fects	26,9 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0,3 mg/kg bw/day
N-(3- (Trimethoxysi- lyl)propyl)ethylenedia mine	Workers	Inhalation	Long-term systemic effects	260 mg/m3
	Workers	Inhalation	Acute systemic effects	260 mg/m3
	Workers	Inhalation	Long-term local ef- fects	0,6 mg/m3
	Workers	Inhalation	Acute local effects	5,36 mg/m3
	Consumers	Inhalation	Long-term systemic effects	50 mg/m3
	Consumers	Inhalation	Acute systemic effects	50 mg/m3
	Consumers	Ingestion	Long-term systemic effects	8 mg/kg bw/day
	Consumers	Inhalation	Long-term local ef- fects	0,1 mg/m3
	Consumers	Inhalation	Acute local effects	4 mg/m3
N-[3- (dimethoxymethylsi- lyl)propyl]ethylenedia mine	Workers	Inhalation	Long-term systemic effects	12 mg/m3
	Workers	Inhalation	Acute systemic ef- fects	12 mg/m3
	Workers	Skin contact	Long-term systemic effects	1,7 mg/kg bw/day
	Workers	Skin contact	Acute systemic ef- fects	1,7 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	2,9 mg/m3
	Consumers	Inhalation	Acute systemic effects	2,9 mg/m3
	Consumers	Skin contact	Long-term systemic effects	0,83 mg/kg bw/day
	Consumers	Skin contact	Acute systemic effects	0,83 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0,83 mg/kg bw/day
	Consumers	Ingestion	Acute systemic effects	0,83 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



ADHESIVE SEALANT GLASS CLEAR - 290 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.04.2023

 11.0
 29.06.2023
 10605190-00017
 Date of first issue: 11.06.2010

Substance name	Environmental Compartment	Value
Di-isononyl phthalate	Soil	30 mg/kg
Trimethoxyvinylsilane	Fresh water	0,34 mg/l
	Marine water	0,034 mg/l
	Intermittent use/release	3,4 mg/l
	Sewage treatment plant	110 mg/l
	Fresh water sediment	1,24 mg/kg
	Marine sediment	0,12 mg/kg
	Soil	0,052 mg/kg
N-(3-	Fresh water	0,062 mg/l
(Trimethoxysi-		
lyl)propyl)ethylenediamine		
	Marine water	0,0062 mg/l
	Freshwater - intermittent	0,62 mg/l
	Sewage treatment plant	25 mg/l
	Fresh water sediment	0,22 mg/kg dry
		weight (d.w.)
	Marine sediment	0,022 mg/kg dry
		weight (d.w.)
	Soil	0,0085 mg/kg dry
		weight (d.w.)
N-[3-	Fresh water	0,062 mg/l
(dimethoxymethylsi-		
lyl)propyl]ethylenediamine		
	Marine water	0,0062 mg/l
	Intermittent use/release	0,62 mg/l
	Sewage treatment plant	25 mg/l
	Fresh water sediment	0,24 mg/kg
	Marine sediment	0,024 mg/kg
	Soil	0,01 mg/kg

8.2 Exposure controls

Engineering measures

Processing may form hazardous compounds (see section 10). Ensure adequate ventilation, especially in confined areas.

Minimize workplace exposure concentrations.

Personal protective equipment

Eye/face protection : Please follow all applicable local/national requirements when

selecting protective measures for a specific workplace.

Wear the following personal protective equipment:

Safety glasses

Always wear eye protection when the potential for inadvertent

eye contact with the product cannot be excluded. Equipment should conform to DIN EN 166

Hand protection

Material : Neoprene
Break through time : > 480 min
Glove thickness : > 0,7 mm

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



ADHESIVE SEALANT GLASS CLEAR - 290 ML

Version Revision Date: SDS Number: Date of last issue: 25.04.2023 11.0 29.06.2023 10605190-00017 Date of first issue: 11.06.2010

Directive : Equipment should conform to DIN EN 374

Material : Nitrile rubber
Break through time : > 480 min
Glove thickness : > 0,7 mm

Directive : Equipment should conform to DIN EN 374

Material : butyl-rubber
Break through time : > 480 min
Glove thickness : > 0,7 mm

Directive : Equipment should conform to DIN EN 374

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Skin should be washed after contact.

Respiratory protection : If adequate local exhaust ventilation is not available or expo-

sure assessment demonstrates exposures outside the rec-

ommended guidelines, use respiratory protection.

Equipment should conform to DIN EN 137

Filter type : Self-contained breathing apparatus

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : paste

Colour : translucent

Odour : characteristic

Odour Threshold : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling

range

No data available

Flammability (solid, gas) : Not classified as a flammability hazard

Upper explosion limit / Upper

flammability limit

Not applicable

Lower explosion limit / Lower

flammability limit

Not applicable

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



ADHESIVE SEALANT GLASS CLEAR - 290 ML

Version Revision Date: SDS Number: Date of last issue: 25.04.2023 11.0 29.06.2023 10605190-00017 Date of first issue: 11.06.2010

Flash point : 100 - < 200 °C

Auto-ignition temperature : Not applicable

Decomposition temperature : No data available

pH : substance/mixture reacts with water

Viscosity

Viscosity, kinematic : > 20,5 mm2/s

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

Not applicable

Vapour pressure : Not applicable

Density : 1,06 g/cm³ (20 °C)

Relative vapour density : Not applicable

Particle characteristics

Particle size : No data available

9.2 Other information

Explosives : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Evaporation rate : Not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Can react with strong oxidizing agents.

Hazardous decomposition products will be formed upon con-

tact with water or humid air.

10.4 Conditions to avoid

Conditions to avoid : Exposure to moisture

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



ADHESIVE SEALANT GLASS CLEAR - 290 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.04.2023

 11.0
 29.06.2023
 10605190-00017
 Date of first issue: 11.06.2010

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

Water

10.6 Hazardous decomposition products

Contact with water or humid : Methanol

air

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of : Skin contact

exposure Ingestion

Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Components:

TrimethoxyvinyIsilane:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute toxicity estimate (Humans): > 300 - 2.000 mg/kg

Method: Expert judgement

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): 16,8 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

N-(3-(TrimethoxysilyI)propyI)ethylenediamine:

Acute oral toxicity : LD50 (Rat, female): 1.897 mg/kg

Method: OPPTS 870.1100

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



ADHESIVE SEALANT GLASS CLEAR - 290 ML

Version Revision Date: SDS Number: Date of last issue: 25.04.2023 11.0 29.06.2023 10605190-00017 Date of first issue: 11.06.2010

Acute toxicity estimate (Humans): > 300 - 2.000 mg/kg

Method: Expert judgement

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): 1,49 - 2,44 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: OPPTS 870.1300

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg

Method: OPPTS 870.1200

N-[3-(dimethoxymethylsilyl)propyl]ethylenediamine:

Acute oral toxicity : LD50 (Rat): > 200 - 2.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5,2 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

Trimethoxyvinylsilane:

Species : Rabbit

Result : No skin irritation

N-(3-(TrimethoxysilyI)propyI)ethylenediamine:

Species : Rabbit

Method : OECD Test Guideline 404

Result : Mild skin irritation

 $\label{eq:n-substitution} \textbf{N-[3-(}dimethoxymethylsilyl)propyl] ethylenediamine:$

Species : Rabbit

Method : OECD Test Guideline 404

Result : Skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Trimethoxyvinylsilane:

Species : Rabbit

Method : OECD Test Guideline 405

Result : No eye irritation

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



ADHESIVE SEALANT GLASS CLEAR - 290 ML

Version Revision Date: SDS Number: Date of last issue: 25.04.2023 11.0 29.06.2023 10605190-00017 Date of first issue: 11.06.2010

N-(3-(Trimethoxysilyl)propyl)ethylenediamine:

Species : Rabbit

Method : OECD Test Guideline 405
Result : Irreversible effects on the eye

N-[3-(dimethoxymethylsilyl)propyl]ethylenediamine:

Species : Rabbit

Method : OECD Test Guideline 405
Result : Irreversible effects on the eye

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Product:

Species : Guinea pig

Method : OECD Test Guideline 406
Result : Not a skin sensitizer.

Components:

TrimethoxyvinyIsilane:

Test Type : Buehler Test Exposure routes : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406

Result : positive

Assessment : Probability or evidence of low to moderate skin sensitisation

rate in humans

N-(3-(TrimethoxysilyI)propyI)ethylenediamine:

Test Type : Maximisation Test Exposure routes : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406

Result : positive

Assessment : Probability or evidence of low to moderate skin sensitisation

rate in humans

N-[3-(dimethoxymethylsilyl)propyl]ethylenediamine:

Test Type : Maximisation Test Exposure routes : Skin contact

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



ADHESIVE SEALANT GLASS CLEAR - 290 ML

Version Revision Date: SDS Number: Date of last issue: 25.04.2023 11.0 29.06.2023 10605190-00017 Date of first issue: 11.06.2010

Species : Guinea pig

Method : OECD Test Guideline 406

Result : positive

Assessment : Probability or evidence of high skin sensitisation rate in hu-

mans

Germ cell mutagenicity

Not classified based on available information.

Components:

TrimethoxyvinyIsilane:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection

Result: negative

N-(3-(TrimethoxysilyI)propyI)ethylenediamine:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: negative

Test Type: In vitro sister chromatid exchange assay in mam-

malian cells

Method: OPPTS 870.5900

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection

Result: negative

N-[3-(dimethoxymethylsilyl)propyl]ethylenediamine:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



ADHESIVE SEALANT GLASS CLEAR - 290 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.04.2023

 11.0
 29.06.2023
 10605190-00017
 Date of first issue: 11.06.2010

Method: OECD Test Guideline 474

Result: negative

Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

Components:

Trimethoxyvinylsilane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion

Method: OECD Test Guideline 422

Result: negative

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: inhalation (vapour)

Result: negative

N-(3-(TrimethoxysilyI)propyI)ethylenediamine:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion

Result: negative

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: Ingestion
Method: OECD Test Guideline 414

Result: negative

N-[3-(dimethoxymethylsilyl)propyl]ethylenediamine:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

Effects on foetal develop-

ment

Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion

Result: negative

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



ADHESIVE SEALANT GLASS CLEAR - 290 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.04.2023

 11.0
 29.06.2023
 10605190-00017
 Date of first issue: 11.06.2010

Remarks: Based on data from similar materials

STOT - single exposure

Not classified based on available information.

Components:

Trimethoxyvinylsilane:

Exposure routes : Ingestion

Target Organs : Central nervous system, optic nerve
Assessment : May cause damage to organs.
Remarks : Based on data from similar materials

N-(3-(TrimethoxysilyI)propyl)ethylenediamine:

Exposure routes : Ingestion

Target Organs : Central nervous system, optic nerve
Assessment : May cause damage to organs.
Remarks : Based on data from similar materials

STOT - repeated exposure

Not classified based on available information.

Components:

Trimethoxyvinylsilane:

Exposure routes : Ingestion

Assessment : No significant health effects observed in animals at concentra-

tions of 100 mg/kg bw or less.

N-(3-(TrimethoxysilyI)propyI)ethylenediamine:

Exposure routes : inhalation (dust/mist/fume)

Target Organs : Respiratory Tract

Assessment : Shown to produce significant health effects in animals at con-

centrations of >0.02 to 0.2 mg/l/6h/d.

Repeated dose toxicity

Components:

Trimethoxyvinylsilane:

Species : Rat
LOAEL : 62,5 mg/kg
Application Route : Ingestion
Exposure time : 54 Days

Method : OECD Test Guideline 422

N-(3-(Trimethoxysilyl)propyl)ethylenediamine:

Species : Rat

NOAEL : >= 500 mg/kg Application Route : Ingestion

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



ADHESIVE SEALANT GLASS CLEAR - 290 ML

Version Revision Date: SDS Number: Date of last issue: 25.04.2023 11.0 29.06.2023 10605190-00017 Date of first issue: 11.06.2010

Exposure time : 44 Days

 Species
 : Rat

 NOAEL
 : 0,015 mg/l

 LOAEL
 : 0,045 mg/l

Application Route : inhalation (dust/mist/fume)

Exposure time : 13 Weeks

Method : OECD Test Guideline 413

N-[3-(dimethoxymethylsilyl)propyl]ethylenediamine:

Species : Rat

NOAEL : 500 mg/kg Application Route : Ingestion Exposure time : 29 Days

Remarks : Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Trimethoxyvinylsilane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 191 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 168,7 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

ErC50 (Desmodesmus subspicatus (green algae)): > 957 mg/l

Exposure time: 72 h

NOEC (Desmodesmus subspicatus (green algae)): > 957 mg/l

Exposure time: 72 h

N-(3-(TrimethoxysilyI)propyI)ethylenediamine:

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



ADHESIVE SEALANT GLASS CLEAR - 290 ML

Version Revision Date: SDS Number: Date of last issue: 25.04.2023 29.06.2023 10605190-00017 Date of first issue: 11.06.2010 11.0

LC50 (Danio rerio (zebra fish)): > 100 mg/l Toxicity to fish

Exposure time: 96 h

Method: Directive 67/548/EEC, Annex V, C.1. Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): > 10 - 100 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction Method: Directive 67/548/EEC, Annex V, C.2. Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

ErC50 (Pseudokirchneriella subcapitata (green algae)): > 1 -

10 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): > 1

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to microorganisms EC10 (Pseudomonas putida): > 1 mg/l

Exposure time: 16 h Method: DIN 38 412 Part 8

Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chron-

ic toxicity)

NOEC: >= 1 mg/lExposure time: 21 d

Species: Daphnia magna (Water flea)

Remarks: Based on data from similar materials

N-[3-(dimethoxymethylsilyl)propyl]ethylenediamine:

Toxicity to fish LC50 (Danio rerio (zebra fish)): 597 mg/l

Exposure time: 96 h

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 8,8

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 3,1

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



ADHESIVE SEALANT GLASS CLEAR - 290 ML

Version Revision Date: SDS Number: Date of last issue: 25.04.2023 11.0 29.06.2023 10605190-00017 Date of first issue: 11.06.2010

Toxicity to microorganisms : EC50 (Pseudomonas putida): 67 mg/l

Exposure time: 16 h Method: DIN 38 412 Part 8

Remarks: Based on data from similar materials

12.2 Persistence and degradability

Components:

Trimethoxyvinylsilane:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 51 % Exposure time: 28 d

Method: OECD Test Guideline 301F

N-(3-(Trimethoxysilyl)propyl)ethylenediamine:

Biodegradability : Result: Not readily biodegradable.

Method: Regulation (EC) No. 440/2008, Annex, C.4-A Remarks: Based on data from similar materials

N-[3-(dimethoxymethylsilyl)propyl]ethylenediamine:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 39 % Exposure time: 28 d

Method: Regulation (EC) No. 440/2008, Annex, C.4-A Remarks: Based on data from similar materials

12.3 Bioaccumulative potential

Components:

N-(3-(TrimethoxysilyI)propyl)ethylenediamine:

Partition coefficient: n- : log Pow: -3,3

octanol/water Remarks: Calculation

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



ADHESIVE SEALANT GLASS CLEAR - 290 ML

Version Revision Date: SDS Number: Date of last issue: 25.04.2023 11.0 29.06.2023 10605190-00017 Date of first issue: 11.06.2010

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.

According to the European Waste Catalogue, Waste Codes

are not product specific, but application specific.

Waste codes should be assigned by the user, preferably in

discussion with the waste disposal authorities.

Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

Waste Code : The following Waste Codes are only suggestions:

used product

08 04 10, waste adhesives and sealants other than those

mentioned in 08 04 09

unused product

08 04 10, waste adhesives and sealants other than those

mentioned in 08 04 09

uncleaned packagings 15 01 06, mixed packaging

Acc. Packaging Act properly emptied packaging: Properly emptied, non-contaminated packaging of nonhazardous products can be supplied to a system for the col-

lection of sales packaging.

SECTION 14: Transport information

14.1 UN number or ID number

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



ADHESIVE SEALANT GLASS CLEAR - 290 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.04.2023

 11.0
 29.06.2023
 10605190-00017
 Date of first issue: 11.06.2010

IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.4 Packing group

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA (Cargo) : Not regulated as a dangerous good
IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) Conditions of restriction for the following entries should be considered: Number on list 75
 If you intend to use this product as tattoo ink, please contact your vendor.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



ADHESIVE SEALANT GLASS CLEAR - 290 ML

Version Revision Date: SDS Number: Date of last issue: 25.04.2023 11.0 29.06.2023 10605190-00017 Date of first issue: 11.06.2010

Di-isononyl phthalate (Number on

list 52)

Dioctyltin oxide (Number on list 75,

20)

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Water hazard class (Germa:

ny)

WGK 1 slightly hazardous to water

Classification according to AwSV, Annex 1 (5.2)

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 3,4 %, 36 g/l

Remarks: VOC content excluding water

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Other information : Items where changes have been made to the previous version

are highlighted in the body of this document by two vertical

lines.

Full text of H-Statements

H226 : Flammable liquid and vapour.

H302 : Harmful if swallowed. H315 : Causes skin irritation.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



ADHESIVE SEALANT GLASS CLEAR - 290 ML

Version 11.0	Revision Date: 29.06.2023	SDS Number: 10605190-00017	Date of last issue: 25.04.2023 Date of first issue: 11.06.2010
H317 H318 H332 H371 H373		: Causes serious e: Harmful if inhale: May cause dama	d.
H412		exposure. : Harmful to aquat	ic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam. : Serious eye damage Flam. Liq. : Flammable liquids Skin Irrit. : Skin irritation Skin Sens. : Skin sensitisation

STOT RE : Specific target organ toxicity - repeated exposure
STOT SE : Specific target organ toxicity - single exposure
2006/15/EC : Europe. Indicative occupational exposure limit values
DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

2006/15/EC / TWA : Limit Value - eight hours DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



ADHESIVE SEALANT GLASS CLEAR - 290 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.04.2023

 11.0
 29.06.2023
 10605190-00017
 Date of first issue: 11.06.2010

- Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data

compile the Safety Data
Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN