according to Regulation (EC) No. 1907/2006



REPLAST ME 2C PLASTIC ADHESIVE 30 S - 50 ML (Comp. B)

Version Revision Date: SDS Number: Date of last issue: 22.09.2022 1.6 22.03.2023 7346755-00007 Date of first issue: 06.11.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : REPLAST ME 2C PLASTIC ADHESIVE 30 S - 50 ML (Comp.

B)

Product code : 0893500050

Unique Formula Identifier

(UFI)

: WDV2-209C-2005-FV2E

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Adhesives

stance/Mixture Professional use product

Recommended restrictions

on use

Not applicable

1.3 Details of the supplier of the safety data sheet

Company : Adolf Wuerth GmbH & Co. KG

Reinhold-Würth-Str. 12-17

74653 Künzelsau

Telephone : +49 794015 0

Telefax : +49 794015 10 00

E-mail address of person responsible for the SDS

: isi@wuerth.com

1.4 Emergency telephone number

+49 (0)6132 - 84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Eye irritation, Category 2 H319: Causes serious eye irritation.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006



REPLAST ME 2C PLASTIC ADHESIVE 30 S - 50 ML (Comp. B)

Version Revision Date: SDS Number: Date of last issue: 22.09.2022 1.6 22.03.2023 7346755-00007 Date of first issue: 06.11.2020

Hazard pictograms :

!>

Signal word : Warning

Hazard statements : H319 Causes serious eye irritation.

Precautionary statements : Prevention:

P264 Wash skin thoroughly after handling.P280 Wear eye protection/ face protection.

Response:

P337 + P313 If eye irritation persists: Get medical advice/

attention.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Index-No.		
	Registration number		
1,1',1"',1"'-	102-60-3	Eye Irrit. 2; H319	>= 10 - < 20
ethylenedinitrilotetrapropan-2-ol	203-041-4		
	01-2119552434-41		

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : In the case of accident or if you feel unwell, seek medical ad-

according to Regulation (EC) No. 1907/2006



REPLAST ME 2C PLASTIC ADHESIVE 30 S - 50 ML (Comp. B)

Version Revision Date: SDS Number: Date of last issue: 22.09.2022 1.6 22.03.2023 7346755-00007 Date of first issue: 06.11.2020

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : Wash with water and soap as a precaution.

Get medical attention if symptoms occur.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water

for at least 15 minutes.

If easy to do, remove contact lens, if worn.

Get medical attention.

If swallowed, DO NOT induce vomiting.

Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes serious eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

: Do not use a solid water stream as it may scatter and spread

fire

Flash back possible over considerable distance. Vapours may form explosive mixtures with air.

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod-

ucts

Carbon oxides

Nitrogen oxides (NOx)

according to Regulation (EC) No. 1907/2006



REPLAST ME 2C PLASTIC ADHESIVE 30 S - 50 ML (Comp. B)

Version Revision Date: SDS Number: Date of last issue: 22.09.2022 1.6 22.03.2023 7346755-00007 Date of first issue: 06.11.2020

> Metal oxides Silicon oxides

5.3 Advice for firefighters

Special protective equipment :

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.

Use personal protective equipment.

Follow safe handling advice (see section 7) and personal pro-

tective equipment recommendations (see section 8).

6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g. by containment or oil

barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.

Soak up with inert absorbent material.

Suppress (knock down) gases/vapours/mists with a water

spray jet.

For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor-

bent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to deter-

mine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

according to Regulation (EC) No. 1907/2006



REPLAST ME 2C PLASTIC ADHESIVE 30 S - 50 ML (Comp. B)

Version Revision Date: SDS Number: Date of last issue: 22.09.2022 1.6 22.03.2023 7346755-00007 Date of first issue: 06.11.2020

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust

ventilation.

Advice on safe handling : Avoid breathing vapours.

Do not swallow. Do not get in eyes.

Avoid prolonged or repeated contact with skin.

Wash skin thoroughly after handling.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as-

sessment

Keep container tightly closed.

Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

Take precautionary measures against static discharges.

Take care to prevent spills, waste and minimize release to the

environment.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye

flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contami-

nated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep in properly labelled containers. Keep tightly closed.

Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Keep away from heat and

sources of ignition.

Advice on common storage : Do not store with the following product types:

Strong oxidizing agents

Explosives Gases

Storage class (TRGS 510) : 10

Storage period : 24 Months

Recommended storage tem-

perature

15 - 32 °C

Further information on stor- : Keep in a dry place.

according to Regulation (EC) No. 1907/2006



REPLAST ME 2C PLASTIC ADHESIVE 30 S - 50 ML (Comp. B)

Version Revision Date: SDS Number: Date of last issue: 22.09.2022 1.6 22.03.2023 7346755-00007 Date of first issue: 06.11.2020

age stability

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Talc	14807-96-6	AGW (Inhalable	10 mg/m3	DE TRGS
		fraction)		900
	Peak-limit: excursion factor (category): 2;(II)			
		AGW (Alveolate	1,25 mg/m3	DE TRGS
		fraction)		900
	Peak-limit: excursion factor (category): 2;(II)			
Dimethyl siloxane	67762-90-7	AGW (Inhalable	4 mg/m3	DE TRGS
reaction with silica		fraction)	(Silica)	900
	Further information: When there is compliance with the OEL and biological			
	tolerance values, there is no risk of harming the unborn child			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
2-Oxepanone, polymer with 2-ethyl-2- (hydroxymethyl)-1,3- propanediol	Workers	Inhalation	Long-term systemic effects	3,5 mg/m3
	Workers	Skin contact	Long-term systemic effects	1 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0,9 mg/m3
	Consumers	Inhalation	Acute systemic effects	1,75 mg/m3
	Consumers	Skin contact	Long-term systemic effects	0,5 mg/kg bw/day
	Consumers	Skin contact	Acute systemic effects	1 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0,5 mg/kg bw/day
	Consumers	Ingestion	Acute systemic effects	1 mg/kg bw/day
1,1',1",1"'- ethylenedini- trilotetrapropan-2-ol	Workers	Inhalation	Long-term systemic effects	29,4 mg/m3
	Workers	Skin contact	Long-term systemic effects	4,2 mg/kg bw/day

according to Regulation (EC) No. 1907/2006



REPLAST ME 2C PLASTIC ADHESIVE 30 S - 50 ML (Comp. B)

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 22.09.2022

 1.6
 22.03.2023
 7346755-00007
 Date of first issue: 06.11.2020

Consumers	Inhalation	Long-term systemic effects	8,7 mg/m3
Consumers	Skin contact	Long-term systemic effects	2,5 mg/kg bw/day
Consumers	Ingestion	Long-term systemic effects	2,5 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
2-Oxepanone, polymer with 2-	Fresh water	0,102 mg/l
ethyl-2-(hydroxymethyl)-1,3-		
propanediol		
	Marine water	0,0102 mg/l
	Intermittent use/release	1,02 mg/l
	Sewage treatment plant	670 mg/l
1,1',1",1"'-	Fresh water	0,085 mg/l
ethylenedinitrilotetrapropan-2-ol		_
	Marine water	0,0085 mg/l
	Intermittent use/release	1,51 mg/l
	Sewage treatment plant	70 mg/l
	Fresh water sediment	0,193 mg/kg
	Marine sediment	0,0193 mg/kg
	Soil	0,0183 mg/kg

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation, especially in confined areas.

Minimize workplace exposure concentrations.

Personal protective equipment

Eye/face protection : Wear the following personal protective equipment:

Safety goggles

Equipment should conform to DIN EN 166

Hand protection

Material : Neoprene
Break through time : >= 480 min
Glove thickness : 0,5 mm

Directive : Equipment should conform to DIN EN 374

Material : butyl-rubber
Break through time : >= 480 min
Glove thickness : 0,5 mm

Directive : Equipment should conform to DIN EN 374

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

according to Regulation (EC) No. 1907/2006



REPLAST ME 2C PLASTIC ADHESIVE 30 S - 50 ML (Comp. B)

Version Revision Date: SDS Number: Date of last issue: 22.09.2022 1.6 22.03.2023 7346755-00007 Date of first issue: 06.11.2020

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Wear the following personal protective equipment:

If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic

protective clothing.

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

Respiratory protection : If adequate local exhaust ventilation is not available or expo-

sure assessment demonstrates exposures outside the rec-

ommended guidelines, use respiratory protection. Equipment should conform to DIN EN 14387

Filter type : Combined particulates and organic vapour type (A-P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : paste

Colour : black

Odour : characteristic

Odour Threshold : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling

range

No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Ignitable (see flash point)

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Flash point : 83,8 °C

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : substance/mixture is non-soluble (in water)

according to Regulation (EC) No. 1907/2006



REPLAST ME 2C PLASTIC ADHESIVE 30 S - 50 ML (Comp. B)

Version Revision Date: SDS Number: Date of last issue: 22.09.2022 1.6 22.03.2023 7346755-00007 Date of first issue: 06.11.2020

Viscosity

Viscosity, dynamic : 60 mPa.s

Viscosity, kinematic : No data available

Solubility(ies)

Water solubility : No data available

Partition coefficient: n-

octanol/water

Not applicable

Vapour pressure : No data available

Relative density : 1,29

Relative vapour density : No data available

Particle characteristics

Particle size : Not applicable

9.2 Other information

Explosives : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Metal corrosion rate : Not corrosive to metals

Evaporation rate : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Combustible liquid.

Vapours may form explosive mixture with air. Can react with strong oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

according to Regulation (EC) No. 1907/2006



REPLAST ME 2C PLASTIC ADHESIVE 30 S - 50 ML (Comp. B)

Version Revision Date: SDS Number: Date of last issue: 22.09.2022 1.6 22.03.2023 7346755-00007 Date of first issue: 06.11.2020

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of : Inhalation

exposure Skin contact

Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Components:

1,1',1"',1"'-ethylenedinitrilotetrapropan-2-ol:

Acute oral toxicity : LD50 (Rat): 2.890 mg/kg

Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Skin corrosion/irritation

Not classified based on available information.

Components:

1,1',1"',1"'-ethylenedinitrilotetrapropan-2-ol:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

1,1',1"',1"'-ethylenedinitrilotetrapropan-2-ol:

Species : Rabbit

Method : OECD Test Guideline 405

Result : Irritation to eyes, reversing within 21 days

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

according to Regulation (EC) No. 1907/2006



REPLAST ME 2C PLASTIC ADHESIVE 30 S - 50 ML (Comp. B)

Version Revision Date: SDS Number: Date of last issue: 22.09.2022 1.6 22.03.2023 7346755-00007 Date of first issue: 06.11.2020

Respiratory sensitisation

Not classified based on available information.

Components:

1,1',1"',1"'-ethylenedinitrilotetrapropan-2-ol:

Test Type : Maximisation Test Exposure routes : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

1,1',1"',1"'-ethylenedinitrilotetrapropan-2-ol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

Components:

1,1',1"',1"'-ethylenedinitrilotetrapropan-2-ol:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

Effects on foetal develop-

ment

Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

according to Regulation (EC) No. 1907/2006



REPLAST ME 2C PLASTIC ADHESIVE 30 S - 50 ML (Comp. B)

Version Revision Date: SDS Number: Date of last issue: 22.09.2022 1.6 22.03.2023 7346755-00007 Date of first issue: 06.11.2020

Repeated dose toxicity

Components:

1,1',1"',1"'-ethylenedinitrilotetrapropan-2-ol:

Species : Rat

NOAEL : 300 mg/kg
Application Route : Ingestion
Exposure time : 30 - 49 Days

Method : OECD Test Guideline 422

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

1,1',1"',1"'-ethylenedinitrilotetrapropan-2-ol:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 4.600 mg/l

Exposure time: 96 h

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

LC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

EC50 (Desmodesmus subspicatus (green algae)): 150,67

mg/l

Exposure time: 72 h

Remarks: Based on data from similar materials

NOEC (Desmodesmus subspicatus (green algae)): 4,25 mg/l

Exposure time: 72 h

Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC : 700 mg/l

Exposure time: 3 h

according to Regulation (EC) No. 1907/2006



REPLAST ME 2C PLASTIC ADHESIVE 30 S - 50 ML (Comp. B)

Version Revision Date: SDS Number: Date of last issue: 22.09.2022 1.6 22.03.2023 7346755-00007 Date of first issue: 06.11.2020

Remarks: Based on data from similar materials

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC: 10 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

Remarks: Based on data from similar materials

12.2 Persistence and degradability

Components:

1,1',1"',1"'-ethylenedinitrilotetrapropan-2-ol:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 36 % Exposure time: 28 d

Method: OECD Test Guideline 302B

Remarks: Based on data from similar materials

12.3 Bioaccumulative potential

Components:

1,1',1"',1"'-ethylenedinitrilotetrapropan-2-ol:

Partition coefficient: n-

octanol/water

: log Pow: 0,0

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

No data available

according to Regulation (EC) No. 1907/2006



REPLAST ME 2C PLASTIC ADHESIVE 30 S - 50 ML (Comp. B)

Version Revision Date: SDS Number: Date of last issue: 22.09.2022 1.6 22.03.2023 7346755-00007 Date of first issue: 06.11.2020

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.

According to the European Waste Catalogue, Waste Codes

are not product specific, but application specific.

Waste codes should be assigned by the user, preferably in

discussion with the waste disposal authorities.

Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product.

Waste Code : The following Waste Codes are only suggestions:

used product

08 04 09, waste adhesives and sealants containing organic

solvents or other hazardous substances

unused product

08 04 09, waste adhesives and sealants containing organic

solvents or other hazardous substances

uncleaned packagings

15 01 10, packaging containing residues of or contaminated

by hazardous substances

Acc. Packaging Act properly emptied packaging: Properly emptied, non-contaminated packaging of nonhazardous products can be supplied to a system for the col-

lection of sales packaging.

SECTION 14: Transport information

14.1 UN number or ID number

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

according to Regulation (EC) No. 1907/2006



REPLAST ME 2C PLASTIC ADHESIVE 30 S - 50 ML (Comp. B)

Version Revision Date: SDS Number: Date of last issue: 22.09.2022 1.6 22.03.2023 7346755-00007 Date of first issue: 06.11.2020

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.4 Packing group

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA (Cargo) : Not regulated as a dangerous good
IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)

s,

Conditions of restriction for the following entries should be considered:

Number on list 3

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

: Not applicable

according to Regulation (EC) No. 1907/2006



REPLAST ME 2C PLASTIC ADHESIVE 30 S - 50 ML (Comp. B)

Version Revision Date: SDS Number: Date of last issue: 22.09.2022 1.6 22.03.2023 7346755-00007 Date of first issue: 06.11.2020

Regulation (EU) 2019/1021 on persistent organic pollu- : Not applicable

tants (recast)

Regulation (EC) No 649/2012 of the European Parlia: Not applicable

ment and the Council concerning the export and import

of dangerous chemicals

REACH - List of substances subject to authorisation : Not applicable

(Annex XIV)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

najor-accident nazards involving dangerous substa Not applicable

Water hazard class (Germa-

: WGK 1 slightly hazardous to water

ny)

Classification according to AwSV, Annex 1 (5.2)

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 0,3 %

Contains a substance which is subject to the TRGS 907 : Castor oil

list of sensitizing substances.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Other information : Items where changes have been made to the previous version

are highlighted in the body of this document by two vertical

lines.

Full text of H-Statements

H319 : Causes serious eye irritation.

Full text of other abbreviations

Eye Irrit. : Eye irritation

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration as-

according to Regulation (EC) No. 1907/2006



REPLAST ME 2C PLASTIC ADHESIVE 30 S - 50 ML (Comp. B)

Version Revision Date: SDS Number: Date of last issue: 22.09.2022 1.6 22.03.2023 7346755-00007 Date of first issue: 06.11.2020

sociated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance: PICCS - Philippines Inventory of Chemicals and Chemical Substances: (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet

eChem Portal search results and European Chemicals Agency, http://echa.europa.eu/

Classification of the mixture:

Classification procedure:

Calculation method

Internal technical data, data from raw material SDSs, OECD

Eye Irrit. 2 H319

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN