

Kablove stopice, izolovane

- Izolacijski materijal: PVC.
- Temperaturno područje: -10°C do +75°C.



Cilindrične spojnice

Presjek mm ²	Dužina cca. mm	Art.-Nr.	Pak./kom.
0,5 - 1,0	25	0558 925 1	100/300/500
1,5 - 2,5	25	0558 926 2	
4,0 - 6,0	27	0558 927 4	100/300



Okrugle stopice

Presjek mm ²	Promjer otvora	Art.-Nr.	Pak./kom.
0,5 - 1,0	M 3	0558 900 1	100
	M 4	0558 901 1	100/300
	M 5	0558 902 1	100/500
	M 6	0558 903 1	
	M 8	0558 904 1	100
M 10	0558 904 11		
1,5 - 2,5	M 3,5	0558 907 2	100/300
	M 4	0558 908 2	
	M 5	0558 909 2	100/300/500
	M 6	0558 910 2	
	M 8	0558 911 2	
M 10	0558 912 2	100	
4,0 - 6,0	M 4	0558 914 4	100/300
	M 5	0558 915 4	
	M 6	0558 916 4	
	M 8	0558 917 4	100
	M 10	0558 918 4	
M 12	0558 919 4		



Ženske stopice

Poprečni presjek mm ²	Veličina mm	Art.-Nr.	Pak./kom.
0,5 - 1,0	2,8 x 0,5	0558 960 1	100
	2,8 x 0,8	0558 960	100/300
	4,8 x 0,5	0558 976 1	100/500
	4,8 x 0,8	0558 977 1	100
	6,3 x 0,8	0558 905 1	100/1000
1,5 - 2,5	2,8 x 0,5	0558 959 2	100
	2,8 x 0,8	0558 960 2	
	4,8 x 0,5	0558 976 2	
	4,8 x 0,8	0558 977 2	100/300/1000
	6,3 x 0,8	0558 905 2	
8,2 x 0,8	0558 940 2	100	
4,0 - 6,0	6,3 x 0,8	0558 905 4	100/300
	9,5	0558 941 4	50/300



Ženske stopice, potpuno izolovane

Poprečni presjek mm ²	Veličina mm	Art.-Nr.	Pak./kom.
0,5 - 1,0	6,3 x 0,8	0558 905 11	100/300
1,5 - 2,5		0558 905 22	100/300/500
4,0 - 6,0		0558 905 44	100