

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2-COMPONENT REPAIR-FILLER RSM WOOD (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10785209-00012	Date of first issue: 11.06.2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : 2-COMPONENT REPAIR-FILLER RSM WOOD (comp. A)

Product code : 08903021

Unique Formula Identifier (UFI) : 2D3C-908C-Q00Y-2RS1

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Putty/filler
Professional use product

Recommended restrictions on use : Not applicable

1.3 Details of the supplier of the safety data sheet

Company : Adolf Wuerth GmbH & Co. KG
Reinhold-Würth-Str. 12-17
74653 Künzelsau

Telephone : +49 794015 0

Telefax : +49 794015 10 00

E-mail address of person responsible for the SDS : isi@wuerth.com

1.4 Emergency telephone number

+49 (0)6132 – 84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2-COMPONENT REPAIR-FILLER RSM WOOD (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10785209-00012	Date of first issue: 11.06.2010

Reproductive toxicity, Category 2	H361d: Suspected of damaging the unborn child.
Specific target organ toxicity - repeated exposure, Category 1	H372: Causes damage to organs through prolonged or repeated exposure.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H361d Suspected of damaging the unborn child.
H372 Causes damage to organs through prolonged or repeated exposure.

Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe mist or vapours.
P264 Wash skin thoroughly after handling.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.

Hazardous components which must be listed on the label:

Styrene

Reaction mass of 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]ethanol and 2,2'-[[4-methylphenyl]imino]diethanol

Maleic anhydride

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2-COMPONENT REPAIR-FILLER RSM WOOD (comp. A)

Version 8.0 Revision Date: 06.06.2023 SDS Number: 10785209-00012 Date of last issue: 10.11.2022
Date of first issue: 11.06.2010

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Paint

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Styrene	100-42-5 202-851-5 601-026-00-0 01-2119457861-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Repr. 2; H361d STOT SE 3; H335 STOT RE 1; H372 (Auditory system) Asp. Tox. 1; H304 Aquatic Chronic 3; H412 Acute toxicity estimate Acute inhalation toxicity (vapour): 11,8 mg/l	>= 10 - < 20
N-Ethyl-2-pyrrolidone	2687-91-4 220-250-6 616-208-00-5 01-2119472138-36	Eye Dam. 1; H318 Repr. 1B; H360D	>= 0,1 - < 0,3
Reaction mass of 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]ethanol and 2,2'-[[4-(4-methylphenyl)imino]diethanol	Not Assigned 01-2119979579-10	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Chronic 3; H412 Acute toxicity estimate	>= 0,1 - < 0,25

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2-COMPONENT REPAIR-FILLER RSM WOOD (comp. A)

Version 8.0 Revision Date: 06.06.2023 SDS Number: 10785209-00012 Date of last issue: 10.11.2022
Date of first issue: 11.06.2010

		Acute oral toxicity: 619 mg/kg	
Maleic anhydride	108-31-6 203-571-6 607-096-00-9 01-2119472428-31	Acute Tox. 4; H302 Skin Corr. 1; H314 Eye Dam. 1; H318 Resp. Sens. 1; H334 Skin Sens. 1A; H317 STOT RE 1; H372 (Respiratory Tract) EUH071 specific concentration limit Skin Sens. 1A; H317 >= 0,001 % Acute toxicity esti- mate Acute oral toxicity: 1.090 mg/kg	>= 0,001 - < 0,1

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- If inhaled : If inhaled, remove to fresh air.
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2-COMPONENT REPAIR-FILLER RSM WOOD (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10785209-00012	Date of first issue: 11.06.2010

If easy to do, remove contact lens, if worn.
Get medical attention.

If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention.
Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
Suspected of damaging the unborn child.
Causes damage to organs through prolonged or repeated exposure.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.
Flash back possible over considerable distance.
Vapours may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides
Nitrogen oxides (NO_x)
Oxides of phosphorus
Metal oxides
Sulphur oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

Specific extinguishing meth- : Use extinguishing measures that are appropriate to local cir-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2-COMPONENT REPAIR-FILLER RSM WOOD (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10785209-00012	Date of first issue: 11.06.2010

ods
cumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapours/mists with a water spray jet.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2-COMPONENT REPAIR-FILLER RSM WOOD (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10785209-00012	Date of first issue: 11.06.2010

CONTROLS/PERSONAL PROTECTION section.

- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
Use explosion-proof electrical, ventilating and lighting equipment.
- Advice on safe handling : Do not get on skin or clothing.
Do not breathe mist or vapours.
Do not swallow.
Do not get in eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Non-sparking tools should be used.
Keep container tightly closed.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Do not eat, drink or smoke when using this product.
Take care to prevent spills, waste and minimize release to the environment.
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Contaminated work clothing should not be allowed out of the workplace.
Wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep in properly labelled containers. Store locked up. Keep tightly closed. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Keep away from heat and sources of ignition.

- Advice on common storage : Do not store with the following product types:
Strong oxidizing agents
Self-reactive substances and mixtures
Organic peroxides
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures, which in contact with water, emit flammable gases
Explosives
Gases
Very acutely toxic substances and mixtures

- Storage class (TRGS 510) : 3

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2-COMPONENT REPAIR-FILLER RSM WOOD (comp. A)

Version 8.0 Revision Date: 06.06.2023 SDS Number: 10785209-00012 Date of last issue: 10.11.2022
Date of first issue: 11.06.2010

Recommended storage temperature : 15 - 30 °C

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Talc	14807-96-6	AGW (Inhalable fraction)	10 mg/m ³	DE TRGS 900
		Peak-limit: excursion factor (category): 2;(II)		
		AGW (Alveolate fraction)	1,25 mg/m ³	DE TRGS 900
		Peak-limit: excursion factor (category): 2;(II)		
Styrene	100-42-5	AGW	20 ppm 86 mg/m ³	DE TRGS 900
		Peak-limit: excursion factor (category): 2;(II)		
		Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child		
Titanium dioxide	13463-67-7	AGW (Inhalable fraction)	10 mg/m ³ (Titanium dioxide)	DE TRGS 900
		Peak-limit: excursion factor (category): 2;(II)		
		AGW (Alveolate fraction)	1,25 mg/m ³ (Titanium dioxide)	DE TRGS 900
		Peak-limit: excursion factor (category): 2;(II)		
		BM (Alveolar dust fraction)	0,5 mg/m ³	DE TRGS 527
N-Ethyl-2-pyrrolidone	2687-91-4	AGW (Vapour and aerosols)	5 ppm 23 mg/m ³	DE TRGS 900
		Peak-limit: excursion factor (category): 2;(I)		
		Further information: Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child		
Maleic anhydride	108-31-6	AGW (Vapour and aerosols)	0,02 ppm 0,081 mg/m ³	DE TRGS 900
		Peak-limit: excursion factor (category): 1; =2.5=(I)		
		Further information: In well-founded cases also a momentary value can be established, that never can be exceeded. This substance will be indicated by = in combination with an exceeding value., When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child, Substance sensitizing through the skin and respiratory system		

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2-COMPONENT REPAIR-FILLER RSM WOOD (comp. A)

Version 8.0 Revision Date: 06.06.2023 SDS Number: 10785209-00012 Date of last issue: 10.11.2022
Date of first issue: 11.06.2010

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Styrene	100-42-5	mandelic acid + phenylglyoxylic acid: 600 mg/g Creatinine (Urine)	In case of long-term exposure: after more than one shift, Immediately after exposure or after working hours	TRGS 903

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Styrene	Workers	Inhalation	Long-term systemic effects	85 mg/m ³
	Workers	Inhalation	Acute local effects	289 mg/m ³
	Workers	Inhalation	Acute local effects	306 mg/m ³
	Workers	Skin contact	Long-term systemic effects	406 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	10,2 mg/m ³
	Consumers	Inhalation	Acute systemic effects	174,25 mg/m ³
	Consumers	Inhalation	Acute local effects	182,75 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	343 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	2,1 mg/kg bw/day
	N-Ethyl-2-pyrrolidone	Workers	Inhalation	Long-term systemic effects
Workers		Inhalation	Long-term local effects	13 mg/m ³
Workers		Inhalation	Acute local effects	26 mg/m ³
Workers		Skin contact	Long-term systemic effects	4 mg/kg bw/day
Maleic anhydride		Workers	Inhalation	Long-term systemic effects
	Workers	Inhalation	Acute systemic effects	0,8 mg/m ³
	Workers	Inhalation	Long-term local effects	0,4 mg/m ³
	Workers	Inhalation	Acute local effects	0,8 mg/m ³
	Reaction mass of 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]ethanol and 2,2'-[[4-methylphenyl]imino]diethanol	Workers	Inhalation	Long-term systemic effects
Workers		Skin contact	Long-term systemic	1,4 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2-COMPONENT REPAIR-FILLER RSM WOOD (comp. A)

Version 8.0 Revision Date: 06.06.2023 SDS Number: 10785209-00012 Date of last issue: 10.11.2022
Date of first issue: 11.06.2010

			effects	bw/day
	Consumers	Inhalation	Long-term systemic effects	2,9 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	0,83 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0,83 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Styrene	Soil	0,2 mg/kg
	Marine sediment	0,307 mg/kg
	Fresh water sediment	0,614 mg/kg
	Sewage treatment plant	5 mg/l
	Intermittent use/release	0,04 mg/l
	Marine water	0,014 mg/l
N-Ethyl-2-pyrrolidone	Fresh water	0,028 mg/l
	Fresh water	0,25 mg/l
	Marine water	0,025 mg/l
	Intermittent use/release	1 mg/l
	Sewage treatment plant	10 mg/l
	Fresh water sediment	1,91 mg/kg
Maleic anhydride	Marine sediment	0,191 mg/kg
	Soil	0,235 mg/kg
	Fresh water	0,1 mg/l
	Marine water	0,01 mg/l
	Freshwater - intermittent	0,4281 mg/l
	Sewage treatment plant	44,6 mg/l
Reaction mass of 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]ethanol and 2,2'-[[4-methylphenyl]imino]diethanol	Fresh water sediment	0,334 mg/kg dry weight (d.w.)
	Marine sediment	0,0334 mg/kg dry weight (d.w.)
	Soil	0,0415 mg/kg dry weight (d.w.)
	Fresh water	0,048 mg/l
	Freshwater - intermittent	0,48 mg/l
	Marine water	0,005 mg/l
	Sewage treatment plant	10 mg/l
	Fresh water sediment	1,2 mg/kg dry weight (d.w.)
	Marine sediment	0,12 mg/kg dry weight (d.w.)
	Soil	0,21 mg/kg dry weight (d.w.)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2-COMPONENT REPAIR-FILLER RSM WOOD (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10785209-00012	Date of first issue: 11.06.2010

8.2 Exposure controls

Engineering measures

Minimize workplace exposure concentrations.
If sufficient ventilation is unavailable, use with local exhaust ventilation.
Use explosion-proof electrical, ventilating and lighting equipment.

Personal protective equipment

Eye/face protection : Wear the following personal protective equipment:
Safety goggles
Equipment should conform to DIN EN 166

Hand protection

Material : butyl-rubber
Break through time : > 480 min
Glove thickness : > 0,4 mm
Directive : Equipment should conform to DIN EN 374

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
Equipment should conform to DIN EN 14387

Filter type : Combined particulates and organic vapour type (A-P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid
Colour : brown

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2-COMPONENT REPAIR-FILLER RSM WOOD (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10785209-00012	Date of first issue: 11.06.2010

Odour	:	characteristic
Odour Threshold	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	145 °C
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	Ignitable (see flash point)
Upper explosion limit / Upper flammability limit	:	8,9 %(V)
Lower explosion limit / Lower flammability limit	:	1,2 %(V)
Flash point	:	31 °C
Auto-ignition temperature	:	480 °C Method: DIN 51794
Decomposition temperature	:	No data available
pH	:	Solvent mixture; pH value determination not possible, no aqueous solution
Viscosity		
Viscosity, kinematic	:	> 20,5 mm ² /s (40 °C)
Solubility(ies)		
Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	Not applicable
Vapour pressure	:	6 mbar (20 °C)
Density	:	1,68 g/cm ³ (20 °C)
Relative vapour density	:	No data available
Particle characteristics		
Particle size	:	Not applicable

9.2 Other information

Explosives	:	Not explosive
------------	---	---------------

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2-COMPONENT REPAIR-FILLER RSM WOOD (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10785209-00012	Date of first issue: 11.06.2010

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Evaporation rate : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Flammable liquid and vapour.
Vapours may form explosive mixture with air.
Can react with strong oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Components:

Styrene:

Acute oral toxicity : LD50 (Hamster): > 5.000 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2-COMPONENT REPAIR-FILLER RSM WOOD (comp. A)

Version 8.0 Revision Date: 06.06.2023 SDS Number: 10785209-00012 Date of last issue: 10.11.2022
Date of first issue: 11.06.2010

Acute inhalation toxicity : LC50 (Rat): 11,8 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

N-Ethyl-2-pyrrolidone:

Acute oral toxicity : LD50 (Rat): 3.200 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5,1 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Reaction mass of 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]ethanol and 2,2'-[[4-methylphenyl]imino]diethanol:

Acute oral toxicity : LD50 (Rat, male): 619 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 402

Maleic anhydride:

Acute oral toxicity : LD50 (Rat): 1.090 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 4,35 mg/l
Exposure time: 1 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 2.620 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Components:

Styrene:

Species : Rabbit
Result : Skin irritation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2-COMPONENT REPAIR-FILLER RSM WOOD (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10785209-00012	Date of first issue: 11.06.2010

N-Ethyl-2-pyrrolidone:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Reaction mass of 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]ethanol and 2,2'-[[4-methylphenyl]imino]diethanol:

Species : reconstructed human epidermis (RhE)
Method : OECD Test Guideline 431

Species : reconstructed human epidermis (RhE)
Method : OECD Test Guideline 439

Result : Skin irritation

Maleic anhydride:

Species : Rabbit
Result : Corrosive after 4 hours or less of exposure

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

Styrene:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days

N-Ethyl-2-pyrrolidone:

Species : Rabbit
Method : OECD Test Guideline 405
Result : Irreversible effects on the eye

Reaction mass of 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]ethanol and 2,2'-[[4-methylphenyl]imino]diethanol:

Species : Rabbit
Method : OECD Test Guideline 405
Result : Irreversible effects on the eye

Maleic anhydride:

Species : Rabbit
Result : Irreversible effects on the eye

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2-COMPONENT REPAIR-FILLER RSM WOOD (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10785209-00012	Date of first issue: 11.06.2010

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Components:

N-Ethyl-2-pyrrolidone:

Test Type	: Local lymph node assay (LLNA)
Exposure routes	: Skin contact
Species	: Mouse
Method	: OECD Test Guideline 429
Result	: negative

Reaction mass of 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]ethanol and 2,2'-[[4-methylphenyl]imino]diethanol:

Test Type	: Local lymph node assay (LLNA)
Exposure routes	: Skin contact
Species	: Mouse
Method	: OECD Test Guideline 429
Result	: positive

Assessment : Probability or evidence of skin sensitisation in humans

Maleic anhydride:

Test Type	: Local lymph node assay (LLNA)
Exposure routes	: Skin contact
Species	: Mouse
Result	: positive

Assessment : Probability or evidence of high skin sensitisation rate in humans

Exposure routes	: inhalation (dust/mist/fume)
Species	: Rat
Result	: positive

Assessment : Probability of respiratory sensitisation in humans based on animal testing

Germ cell mutagenicity

Not classified based on available information.

Components:

Styrene:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES)
-----------------------	--

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2-COMPONENT REPAIR-FILLER RSM WOOD (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10785209-00012	Date of first issue: 11.06.2010

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: inhalation (vapour)
Method: OECD Test Guideline 474
Result: negative

N-Ethyl-2-pyrrolidone:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Method: OECD Test Guideline 474
Result: negative

Reaction mass of 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]ethanol and 2,2'-[[4-methylphenyl]imino]diethanol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: positive

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Genotoxicity in vivo : Test Type: In vivo mammalian alkaline comet assay
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 489
Result: negative

Maleic anhydride:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2-COMPONENT REPAIR-FILLER RSM WOOD (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10785209-00012	Date of first issue: 11.06.2010

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)
Species: Rat
Application Route: inhalation (vapour)
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Styrene:

Species : Rat
Application Route : inhalation (vapour)
Exposure time : 104 weeks
Result : positive
Remarks : The mechanism or mode of action may not be relevant in humans.

Maleic anhydride:

Species : Rat
Application Route : Ingestion
Exposure time : 2 Years
Result : negative

Reproductive toxicity

Suspected of damaging the unborn child.

Components:

Styrene:

Effects on fertility : Test Type: Three-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Result: positive

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

N-Ethyl-2-pyrrolidone:

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rabbit
Application Route: Ingestion
Method: OECD Test Guideline 414

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2-COMPONENT REPAIR-FILLER RSM WOOD (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10785209-00012	Date of first issue: 11.06.2010

Result: positive

Reproductive toxicity - Assessment : Clear evidence of adverse effects on development, based on animal experiments.

Reaction mass of 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]ethanol and 2,2'-[[4-methylphenyl]imino]diethanol:

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

Maleic anhydride:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Result: negative

STOT - single exposure

Not classified based on available information.

Components:

Styrene:

Assessment : May cause respiratory irritation.

STOT - repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Components:

Styrene:

Target Organs : Auditory system
Assessment : Causes damage to organs through prolonged or repeated exposure.

Maleic anhydride:

Exposure routes : inhalation (vapour)
Target Organs : Respiratory Tract
Assessment : Shown to produce significant health effects in animals at concentrations of 0.2 mg/l/6h/d or less.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2-COMPONENT REPAIR-FILLER RSM WOOD (comp. A)

Version 8.0 Revision Date: 06.06.2023 SDS Number: 10785209-00012 Date of last issue: 10.11.2022
Date of first issue: 11.06.2010

Repeated dose toxicity

Components:

Styrene:

Species : Rat
NOAEL : 1,28 mg/l
Application Route : inhalation (vapour)
Exposure time : 4 Weeks

Species : Rat
NOAEL : 1.000 - 2.000 mg/kg
Application Route : Ingestion
Exposure time : 78 - 100 Weeks

N-Ethyl-2-pyrrolidone:

Species : Rat
NOAEL : 100 mg/kg
Application Route : Ingestion
Exposure time : 3 Months
Method : OECD Test Guideline 408

Reaction mass of 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]ethanol and 2,2'-[[4-methylphenyl]imino]diethanol:

Species : Rat, female
NOAEL : 100 mg/kg
LOAEL : 300 mg/kg
Application Route : Ingestion
Exposure time : 28 Days
Method : OECD Test Guideline 407

Maleic anhydride:

Species : Rat
LOAEL : 100 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Species : Rat
LOAEL : 0,01 mg/l
Application Route : inhalation (vapour)
Exposure time : 28 Days

Aspiration toxicity

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2-COMPONENT REPAIR-FILLER RSM WOOD (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10785209-00012	Date of first issue: 11.06.2010

Components:

Styrene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Styrene:

Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): 10 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 4,7 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	:	ErC50 (Pseudokirchneriella subcapitata (green algae)): 6,3 mg/l Exposure time: 96 h EC10 (Pseudokirchneriella subcapitata (green algae)): 0,28 mg/l Exposure time: 96 h
Toxicity to microorganisms	:	NOEC (Pseudomonas putida): 72 mg/l Exposure time: 16 h
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC: 1,01 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

N-Ethyl-2-pyrrolidone:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2-COMPONENT REPAIR-FILLER RSM WOOD (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10785209-00012	Date of first issue: 11.06.2010

- Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 464 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 104 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : NOEC (Desmodesmus subspicatus (green algae)): > 101 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 12,5 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Reaction mass of 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]ethanol and 2,2'-[[4-methylphenyl]imino]diethanol:

- Toxicity to fish : LC50 (Cyprinus carpio (Carp)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 48 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- NOEC (Pseudokirchneriella subcapitata (green algae)): 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- Toxicity to microorganisms : EC50 (activated sludge): > 1.000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Maleic anhydride:

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 115 mg/l
Exposure time: 48 h
Test substance: Neutralised product
Method: DIN 38412
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l
Exposure time: 48 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2-COMPONENT REPAIR-FILLER RSM WOOD (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10785209-00012	Date of first issue: 11.06.2010

Test substance: Neutralised product
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (microalgae)): 150 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

ErC50 (Pseudokirchneriella subcapitata (microalgae)): > 150 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC10 (Pseudomonas putida): 44,6 mg/l
Exposure time: 18 h
Test substance: Neutralised product
Method: DIN 38 412 Part 8

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 10 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)

12.2 Persistence and degradability

Components:

Styrene:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 28 d

N-Ethyl-2-pyrrolidone:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 90 - 100 %
Exposure time: 28 d
Method: OECD Test Guideline 301A

Reaction mass of 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]ethanol and 2,2'-[[4-methylphenyl]imino]diethanol:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 1,5 %
Exposure time: 29 d
Method: OECD Test Guideline 301B

Maleic anhydride:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 93,2 %
Exposure time: 11 d

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2-COMPONENT REPAIR-FILLER RSM WOOD (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10785209-00012	Date of first issue: 11.06.2010

Method: OECD Test Guideline 301B

12.3 Bioaccumulative potential

Components:

Styrene:

Partition coefficient: n-
octanol/water : log Pow: 2,96

N-Ethyl-2-pyrrolidone:

Partition coefficient: n-
octanol/water : log Pow: -0,2

Reaction mass of 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]ethanol and 2,2'-[[4-methylphenyl]imino]diethanol:

Partition coefficient: n-
octanol/water : log Pow: 2,17
Method: OECD Test Guideline 117

Maleic anhydride:

Partition coefficient: n-
octanol/water : log Pow: -2,61

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2-COMPONENT REPAIR-FILLER RSM WOOD (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10785209-00012	Date of first issue: 11.06.2010

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- | | | |
|------------------------|---|--|
| Product | : | Dispose of in accordance with local regulations.
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.
Do not dispose of waste into sewer. |
| Contaminated packaging | : | Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product. |
| Waste Code | : | The following Waste Codes are only suggestions:

used product
08 01 11, waste paint and varnish containing organic solvents or other hazardous substances

unused product
08 01 11, waste paint and varnish containing organic solvents or other hazardous substances

uncleaned packagings
15 01 10, packaging containing residues of or contaminated by hazardous substances |

SECTION 14: Transport information

14.1 UN number or ID number

- | | | |
|------|---|---------|
| ADN | : | UN 1263 |
| ADR | : | UN 1263 |
| RID | : | UN 1263 |
| IMDG | : | UN 1263 |
| IATA | : | UN 1263 |

14.2 UN proper shipping name

- | | | |
|-----|---|-------|
| ADN | : | PAINT |
| ADR | : | PAINT |
| RID | : | PAINT |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2-COMPONENT REPAIR-FILLER RSM WOOD (comp. A)

Version 8.0 Revision Date: 06.06.2023 SDS Number: 10785209-00012 Date of last issue: 10.11.2022
Date of first issue: 11.06.2010

IMDG : PAINT

IATA : Paint

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	: 3	
ADR	: 3	
RID	: 3	
IMDG	: 3	
IATA	: 3	

14.4 Packing group

ADN
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

ADR
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

RID
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

IMDG
Packing group : III
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)
Packing instruction (cargo aircraft) : 366
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

IATA (Passenger)
Packing instruction (passenger aircraft) : 355
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2-COMPONENT REPAIR-FILLER RSM WOOD (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10785209-00012	Date of first issue: 11.06.2010

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 75, 3

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : If you intend to use this product as tattoo ink, please contact your vendor.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2-COMPONENT REPAIR-FILLER RSM WOOD (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10785209-00012	Date of first issue: 11.06.2010

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c	FLAMMABLE LIQUIDS	Quantity 1 5.000 t	Quantity 2 50.000 t
-----	-------------------	-----------------------	------------------------

Water hazard class (Germany) : WGK 2 obviously hazardous to water
Classification according to AwSV, Annex 1 (5.2)

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: <= 2 g/l
Remarks: VOC content excluding water

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

The product is subject to the supply restrictions of the Ordinance on the Prohibition of Chemicals.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Other information : Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Full text of H-Statements

H226	: Flammable liquid and vapour.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H334	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	: May cause respiratory irritation.
H360D	: May damage the unborn child.
H361d	: Suspected of damaging the unborn child.
H372	: Causes damage to organs through prolonged or repeated

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2-COMPONENT REPAIR-FILLER RSM WOOD (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10785209-00012	Date of first issue: 11.06.2010

H412 : exposure.
EUH071 : Harmful to aquatic life with long lasting effects.
: Corrosive to the respiratory tract.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Aquatic Chronic : Long-term (chronic) aquatic hazard
Asp. Tox. : Aspiration hazard
Eye Dam. : Serious eye damage
Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Repr. : Reproductive toxicity
Resp. Sens. : Respiratory sensitisation
Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation
STOT RE : Specific target organ toxicity - repeated exposure
STOT SE : Specific target organ toxicity - single exposure
DE TRGS 527 : Germany. TRGS 527 - Activities with nanomaterials
DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.
TRGS 903 : TRGS 903 - Biological limit values
DE TRGS 527 / BM : Assessment scale
DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2-COMPONENT REPAIR-FILLER RSM WOOD (comp. A)

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10785209-00012	Date of first issue: 11.06.2010

Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Classification of the mixture:

Flam. Liq. 3	H226
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Skin Sens. 1	H317
Repr. 2	H361d
STOT RE 1	H372

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN