according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



GLOSS-SEAL - 250 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.07.2023

 10.0
 21.11.2023
 10672177-00013
 Date of first issue: 11.06.2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : GLOSS-SEAL - 250 ML

Product code : 08930126

Unique Formula Identifier

(UFI)

: SY1F-A0QX-J001-V0HV

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Detergent, Polishing Paste Professional use product

Recommended restrictions

on use

Not applicable

1.3 Details of the supplier of the safety data sheet

Company : Adolf Wuerth GmbH & Co. KG

Reinhold-Würth-Str. 12-17

74653 Künzelsau

Telephone : +49 794015 0

Telefax : +49 794015 10 00

E-mail address of person

responsible for the SDS

isi@wuerth.com

1.4 Emergency telephone number

+49 (0)6132 - 84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Long-term (chronic) aquatic hazard, Category 3

H412: Harmful to aquatic life with long lasting ef-

fects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



GLOSS-SEAL - 250 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.07.2023

 10.0
 21.11.2023
 10672177-00013
 Date of first issue: 11.06.2010

Hazard statements : H412 Harmful to aquatic life with long lasting effects.

Supplemental Hazard : EUH066 Repeated exposure may cause skin

Statements dryness or cracking.

Precautionary statements : Prevention:

P273 Avoid release to the environment.

Additional Labelling

The following percentage of the mixture consists of ingredient(s) with unknown hazards to the aquatic environment: 3 %

2.3 Other hazards

This substance/mixture contains components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB).

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No.	Classification	Concentration (% w/w)
	Index-No. Registration number		
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	Not Assigned 01-2119457273-39	Asp. Tox. 1; H304 EUH066	>= 20 - < 30
Propan-2-ol	67-63-0 200-661-7 603-117-00-0 01-2119457558-25	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	>= 1 - < 10
Dimethyl siloxane, HO-term Rxn methyltrimethoxysilane and ami- noethylaminopropyltrimethox- ysilane	69430-37-1	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0,25 - < 1
		M-Factor (Acute aquatic toxicity): 1	

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



GLOSS-SEAL - 250 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.07.2023

 10.0
 21.11.2023
 10672177-00013
 Date of first issue: 11.06.2010

		M-Factor (Chronic aquatic toxicity): 1	
PBT and vPvB substance :			
Decamethylcyclopentasiloxane	541-02-6 208-764-9 01-2119511367-43		>= 0,1 - < 1

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with plenty of water.

Remove contaminated clothing and shoes.

Get medical attention. Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact : Flush eyes with water as a precaution.

Get medical attention if irritation develops and persists.

If swallowed, DO NOT induce vomiting.

Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

Risks : Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray

Alcohol-resistant foam

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



GLOSS-SEAL - 250 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.07.2023

 10.0
 21.11.2023
 10672177-00013
 Date of first issue: 11.06.2010

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Do not use a solid water stream as it may scatter and spread

tire.

Flash back possible over considerable distance. Vapours may form explosive mixtures with air.

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod: :

ucts

Carbon oxides Silicon oxides Metal oxides

Nitrogen oxides (NOx)

5.3 Advice for firefighters

Special protective equipment :

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

so.

Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.

Use personal protective equipment.

Follow safe handling advice (see section 7) and personal pro-

tective equipment recommendations (see section 8).

6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g. by containment or oil

barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



GLOSS-SEAL - 250 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.07.2023

 10.0
 21.11.2023
 10672177-00013
 Date of first issue: 11.06.2010

Soak up with inert absorbent material.

Suppress (knock down) gases/vapours/mists with a water

spray jet.

For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to deter-

mine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust

ventilation.

Advice on safe handling : Do not get on skin or clothing.

Avoid breathing vapours.

Do not swallow.

Avoid contact with eyes.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as-

sessment

Keep container tightly closed.

Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

Take precautionary measures against static discharges.

Take care to prevent spills, waste and minimize release to the

environment.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye

flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contami-

nated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep in properly labelled containers. Keep tightly closed. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Keep away from heat and

sources of ignition.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



GLOSS-SEAL - 250 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.07.2023

 10.0
 21.11.2023
 10672177-00013
 Date of first issue: 11.06.2010

Advice on common storage : Do not store with the following product types:

Strong oxidizing agents

Explosives Gases

Storage class (TRGS 510) : 10

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form	Control parameters	Basis
		of exposure)		
Hydrocarbons,	Not As-	AGW	300 mg/m3	DE TRGS
C10-C13, n-	signed			900
alkanes, isoal-				
kanes, cyclics,				
<2% aromatics				
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: Group exposure limit for hydrocarbon solvent mixtures			
Propan-2-ol	67-63-0	AGW	200 ppm	DE TRGS
			500 mg/m3	900
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: When there is compliance with the OEL and biological			
	tolerance values, there is no risk of harming the unborn child			

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Propan-2-ol	67-63-0	Acetone: 25 mg/l (Blood)	Immediately after exposure or after working hours	TRGS 903
		Acetone: 25 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health ef-	Value
		'	fects	
Propan-2-ol	Workers	Inhalation	Long-term systemic effects	500 mg/m3
	Workers	Skin contact	Long-term systemic effects	888 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	89 mg/m3

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



GLOSS-SEAL - 250 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.07.2023

 10.0
 21.11.2023
 10672177-00013
 Date of first issue: 11.06.2010

	Consumers	Skin contact	Long-term systemic effects	319 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	26 mg/kg bw/day
Kaolin, calcined	Workers	Inhalation	Long-term systemic effects	3 mg/m3
	Workers	Inhalation	Acute systemic ef- fects	3 mg/m3
	Workers	Inhalation	Long-term local ef- fects	3 mg/m3
	Workers	Inhalation	Acute local effects	3 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Propan-2-ol	Fresh water	140,9 mg/l
	Marine water	140,9 mg/l
	Intermittent use/release	140,9 mg/l
	Sewage treatment plant	2251 mg/l
	Fresh water sediment	552 mg/kg dry weight (d.w.)
	Marine sediment	552 mg/kg dry weight (d.w.)
	Soil	28 mg/kg dry weight (d.w.)
	Oral (Secondary Poisoning)	160 mg/kg food
Kaolin, calcined	Fresh water	4,1 mg/l
	Intermittent use/release	25 mg/l
	Marine water	0,41 mg/l
	Sewage treatment plant	1400 mg/l

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation, especially in confined areas. Minimize workplace exposure concentrations.

Personal protective equipment

Eye/face protection : Wear the following personal protective equipment:

Safety glasses

Equipment should conform to DIN EN 166

Hand protection

Material : Nitrile rubber
Break through time : > 240 min
Glove thickness : 0,38 mm

Directive : Equipment should conform to DIN EN 374

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufactur-

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



GLOSS-SEAL - 250 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.07.2023

 10.0
 21.11.2023
 10672177-00013
 Date of first issue: 11.06.2010

er. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Wear the following personal protective equipment:

If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic

protective clothing.

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

Respiratory protection : If adequate local exhaust ventilation is not available or expo-

sure assessment demonstrates exposures outside the rec-

ommended guidelines, use respiratory protection. Equipment should conform to DIN EN 14387

Filter type : Combined particulates and organic vapour type (A-P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : paste

Colour : beige

Odour : characteristic

Odour Threshold : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling :

range

78 °C

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Ignitable (see flash point)

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



GLOSS-SEAL - 250 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.07.2023

 10.0
 21.11.2023
 10672177-00013
 Date of first issue: 11.06.2010

Flash point : 90 °C

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : 8,55

Concentration: 100 %

Viscosity

Viscosity, kinematic : 650 mm2/s (20 °C)

Solubility(ies)

Water solubility : completely miscible

Partition coefficient: n-

octanol/water

Not applicable

Vapour pressure : No data available

Density : 0,96 g/cm³ (20 °C)

Relative vapour density : No data available

Particle characteristics

Particle size : Not applicable

9.2 Other information

Explosives : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Evaporation rate : No data available

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



GLOSS-SEAL - 250 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.07.2023

 10.0
 21.11.2023
 10672177-00013
 Date of first issue: 11.06.2010

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Combustible liquid.

Vapours may form explosive mixture with air. Can react with strong oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of : Inhalation

exposure Skin contact

Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Components:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 4.951 mg/m3

Exposure time: 4 h
Test atmosphere: vapour

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): >= 3.160 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: Based on data from similar materials

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



GLOSS-SEAL - 250 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.07.2023

 10.0
 21.11.2023
 10672177-00013
 Date of first issue: 11.06.2010

Propan-2-ol:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 25 mg/l

Exposure time: 6 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Decamethylcyclopentasiloxane:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 8,67 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Components:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Species : Rabbit

Result : Mild skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

Propan-2-ol:

Species : Rabbit

Result : No skin irritation

Dimethyl siloxane, HO-term Rxn methyltrimethoxysilane and aminoethylaminopropyltri-

methoxysilane:

Result : Skin irritation

Decamethylcyclopentasiloxane:

Species : Rabbit

Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



GLOSS-SEAL - 250 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.07.2023

 10.0
 21.11.2023
 10672177-00013
 Date of first issue: 11.06.2010

Components:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Species : Rabbit

Method : OECD Test Guideline 405

Result : No eye irritation

Remarks : Based on data from similar materials

Propan-2-ol:

Species : Rabbit

Result : Irritation to eyes, reversing within 21 days

Dimethyl siloxane, HO-term Rxn methyltrimethoxysilane and aminoethylaminopropyltri-

methoxysilane:

Result : Irritation to eyes, reversing within 21 days

Decamethylcyclopentasiloxane:

Species : Rabbit

Result : No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative

Remarks : Based on data from similar materials

Propan-2-ol:

Test Type : Buehler Test Exposure routes : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

Decamethylcyclopentasiloxane:

Test Type : Local lymph node assay (LLNA)

Exposure routes : Skin contact
Species : Mouse
Result : negative

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



GLOSS-SEAL - 250 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.07.2023

 10.0
 21.11.2023
 10672177-00013
 Date of first issue: 11.06.2010

Germ cell mutagenicity

Not classified based on available information.

Components:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Result: negative

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Ingestion

Result: negative

Germ cell mutagenicity- As-

sessment

Classified based on benzene content < 0.1% (Regulation (EC)

1272/2008, Annex VI, Part 3, Note P)

Propan-2-ol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection

Result: negative

Decamethylcyclopentasiloxane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Rat

Application Route: inhalation (vapour) Method: OECD Test Guideline 474

Result: negative

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



GLOSS-SEAL - 250 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.07.2023

 10.0
 21.11.2023
 10672177-00013
 Date of first issue: 11.06.2010

Test Type: Unscheduled DNA synthesis (UDS) test with

mammalian liver cells in vivo

Species: Rat

Application Route: Inhalation Method: OECD Test Guideline 486

Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Species : Rat

Application Route : inhalation (vapour)

Exposure time : 105 weeks Result : negative

Remarks : Based on data from similar materials

Carcinogenicity - Assess-

: Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

ment

Propan-2-ol:

Species : Rat

Application Route : inhalation (vapour)

Exposure time : 104 weeks

Method : OECD Test Guideline 451

Result : negative

Reproductive toxicity

Not classified based on available information.

Components:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening

test

Species: Rat

Application Route: inhalation (vapour)

Result: negative

Effects on foetal develop-

Test Type: Embryo-foetal development Species: Rat

ment

Application Route: inhalation (vapour)

Result: negative

Propan-2-ol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



GLOSS-SEAL - 250 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.07.2023

 10.0
 21.11.2023
 10672177-00013
 Date of first issue: 11.06.2010

Result: negative

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: Ingestion

Result: negative

Decamethylcyclopentasiloxane:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: inhalation (vapour)

Method: OPPTS 870.3800

Result: negative

Effects on foetal develop-

ment

Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: inhalation (vapour)

Method: OPPTS 870.3800

Result: negative

STOT - single exposure

Not classified based on available information.

Components:

Propan-2-ol:

Assessment : May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Species : Rat

NOAEL : >= 1.000 mg/kg

Application Route : Ingestion Exposure time : 54 Days

Remarks : Based on data from similar materials

Propan-2-ol:

Species : Rat NOAEL : 12,5 mg/l

Application Route : inhalation (vapour)

Exposure time : 104 Weeks

Decamethylcyclopentasiloxane:

Species : Rat

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



GLOSS-SEAL - 250 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.07.2023

 10.0
 21.11.2023
 10672177-00013
 Date of first issue: 11.06.2010

NOAEL : 1.000 mg/kg
LOAEL : > 1.000 mg/kg
Application Route : Ingestion

Method : OECD Test Guideline 408

Aspiration toxicity

Not classified based on available information.

Components:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 1.000 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): > 1.000 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EL50 (Pseudokirchneriella subcapitata (green algae)): > 1.000

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

NOELR (Pseudokirchneriella subcapitata (green algae)):

1.000 mg/l

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



GLOSS-SEAL - 250 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.07.2023

 10.0
 21.11.2023
 10672177-00013
 Date of first issue: 11.06.2010

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOELR: > 1 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

Remarks: Based on data from similar materials

Propan-2-ol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 9.640 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10.000 mg/l

Exposure time: 24 h

Toxicity to microorganisms : EC50 (Pseudomonas putida): > 1.050 mg/l

Exposure time: 16 h

Dimethyl siloxane, HO-term Rxn methyltrimethoxysilane and aminoethylaminopropyltrimethoxysilane:

Toxicity to daphnia and other : aquatic invertebrates

EC50 (Daphnia sp. (water flea)): > 0,1 - 1 mg/l Exposure time: 48 h

M-Factor (Acute aquatic tox-

icity)

1

M-Factor (Chronic aquatic

toxicity)

: 1

Decamethylcyclopentasiloxane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 16 µg/l

Exposure time: 96 h

Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 2,9 μg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Remarks: No toxicity at the limit of solubility

Toxicity to algae/aquatic

plants

ErC50 (Pseudokirchneriella subcapitata (green algae)): > 12

μg/l

Exposure time: 96 h

Method: OECD Test Guideline 201

Remarks: No toxicity at the limit of solubility

EC10 (Pseudokirchneriella subcapitata (green algae)): > 12

μg/l

Exposure time: 96 h

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



GLOSS-SEAL - 250 ML

Version Revision Date: SDS Number: Date of last issue: 25.07.2023 10.0 21.11.2023 10672177-00013 Date of first issue: 11.06.2010

Method: OECD Test Guideline 201

Remarks: No toxicity at the limit of solubility

Toxicity to microorganisms : EC50 : > 2.000 mg/l

Exposure time: 3 h Method: 88/302/EC

Toxicity to fish (Chronic tox-

icity)

NOEC: 14 μg/l Exposure time: 90 d

Species: Oncorhynchus mykiss (rainbow trout)

Method: OECD Test Guideline 210

Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC: 15 μg/l Exposure time: 21 d

Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

Remarks: No toxicity at the limit of solubility

12.2 Persistence and degradability

Components:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 80 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Remarks: Based on data from similar materials

Propan-2-ol:

Biodegradability : Result: rapidly degradable

BOD/COD : BOD: 1.19 (BOD5)

COD: 2.23 BOD/COD: 53 %

Dimethyl siloxane, HO-term Rxn methyltrimethoxysilane and aminoethylaminopropyltri-

methoxysilane:

Biodegradability : Result: Not readily biodegradable.

Remarks: Based on data from similar materials

Decamethylcyclopentasiloxane:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 0,14 % Exposure time: 28 d

Method: OECD Test Guideline 310

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



GLOSS-SEAL - 250 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.07.2023

 10.0
 21.11.2023
 10672177-00013
 Date of first issue: 11.06.2010

12.3 Bioaccumulative potential

Components:

Propan-2-ol:

Partition coefficient: n-

octanol/water

log Pow: 0,05

Decamethylcyclopentasiloxane:

Bioaccumulation : Species: Pimephales promelas (fathead minnow)

Bioconcentration factor (BCF): 7.060 - 13.300

Method: OECD Test Guideline 305

Partition coefficient: n-

octanol/water

log Pow: 8,023

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains components considered to

be either persistent, bioaccumulative and toxic (PBT), or very

persistent and very bioaccumulative (vPvB).

Components:

Decamethylcyclopentasiloxane:

Assessment : This substance is considered to be persistent, bioaccumulat-

ing and toxic (PBT).

: This substance is considered to be very persistent and very

bioaccumulating (vPvB).

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



GLOSS-SEAL - 250 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.07.2023

 10.0
 21.11.2023
 10672177-00013
 Date of first issue: 11.06.2010

Product : Dispose of in accordance with local regulations.

According to the European Waste Catalogue, Waste Codes

are not product specific, but application specific.

Waste codes should be assigned by the user, preferably in

discussion with the waste disposal authorities.

Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product.

Waste Code : The following Waste Codes are only suggestions:

used product

12 01 09, machining emulsions and solutions free of halogens

unused product

12 01 09, machining emulsions and solutions free of halogens

uncleaned packagings

15 01 10, packaging containing residues of or contaminated

by hazardous substances

Acc. Packaging Act properly emptied packaging: Properly emptied, non-contaminated packaging of nonhazardous products can be supplied to a system for the col-

lection of sales packaging.

SECTION 14: Transport information

14.1 UN number or ID number

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



GLOSS-SEAL - 250 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.07.2023

 10.0
 21.11.2023
 10672177-00013
 Date of first issue: 11.06.2010

IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.4 Packing group

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA (Cargo) : Not regulated as a dangerous good
IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) Conditions of restriction for the following entries should be considered: Number on list 75, 3

If you intend to use this product as tattoo ink, please contact your vendor.

Decamethylcyclopentasiloxane (Number on list 70)

Substance(s) or mixture(s) are listed here according to their appearance in the regulation, irrespective of their use/purpose or the conditions of the restriction. Please refer to the condi-

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



GLOSS-SEAL - 250 ML

Version Revision Date: SDS Number: Date of last issue: 25.07.2023 10.0 21.11.2023 10672177-00013 Date of first issue: 11.06.2010

tions in corresponding Regulation to determine whether an entry is applicable to the placing on the market or

not.

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

Decamethylcyclopentasiloxane

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

: Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Naphthalene

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

Not applicable

Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Water hazard class (Germa: :

חיין

WGK 2 obviously hazardous to water

Classification according to AwSV, Annex 1 (5.2)

TA Luft List (Germany) : 5.2.1: Total dust:

Not applicable

5.2.2: Inorganic substances in powdered form:

Not applicable

5.2.4: Inorganic substances in gaseous form:

Not applicable

5.2.5: Organic Substances:

Class 1: 0,1 % Methanol, Octamethylcyclotetrasiloxane, Di-

phenyl ether

5.2.7.1.1: Carcinogenic substance:

Not applicable

5.2.7.1.1: Quartz fine dust PM4:

Not applicable

5.2.7.1.1: Formaldehyde:

Not applicable 5.2.7.1.1: fibres: Not applicable

5.2.7.1.2: Germ cell mutagens:

Not applicable

5.2.7.1.3: Substances toxic to reproduction:

Not applicable

5.2.7.2: Poorly degradable, easily enrichable and highly toxic

organic substances:

Not applicable

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



GLOSS-SEAL - 250 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.07.2023

 10.0
 21.11.2023
 10672177-00013
 Date of first issue: 11.06.2010

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 23,2 %, 223 g/l

Regulation (EC) No. : 15 % or over but less than 30 %: Aliphatic hydrocarbons

648/2004, as amended less than 5 %: Non-ionic surfactants

Other constituents: Perfumes

Allergens: LIMONENE

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Other information : Items where changes have been made to the previous version

are highlighted in the body of this document by two vertical

lines.

Full text of H-Statements

H225 : Highly flammable liquid and vapour.

H304 : May be fatal if swallowed and enters airways.

H315 : Causes skin irritation.

H319 : Causes serious eye irritation.

H336 : May cause drowsiness or dizziness.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.

EUH066 : Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Aquatic Acute : Short-term (acute) aquatic hazard Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard
Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Skin Irrit. : Skin irritation

STOT SE : Specific target organ toxicity - single exposure

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

TRGS 903 : TRGS 903 - Biological limit values

DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



GLOSS-SEAL - 250 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.07.2023

 10.0
 21.11.2023
 10672177-00013
 Date of first issue: 11.06.2010

of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

Sheet cy, http://echa.europa.eu/

Classification of the mixture:

Classification procedure:

Aquatic Chronic 3 H412 Calculation method

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN