

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



PAINT SEALANT PERFECT GLOSS - 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 26.09.2023
6.0	05.12.2023	10785627-00016	Date of first issue: 21.12.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : PAINT SEALANT PERFECT GLOSS - 1 L

Product code : 0893013001

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Polishing Paste
Automotive, Care product
Professional use product

Recommended restrictions
on use : Not applicable

1.3 Details of the supplier of the safety data sheet

Company : Adolf Wuerth GmbH & Co. KG
Reinhold-Würth-Str. 12-17
74653 Künzelsau

Telephone : +49 794015 0

Telefax : +49 794015 10 00

E-mail address of person
responsible for the SDS : isi@wuerth.com

1.4 Emergency telephone number

+49 (0)6132 – 84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)
Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)
No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

Additional Labelling

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



PAINT SEALANT PERFECT GLOSS - 1 L

Version 6.0 Revision Date: 05.12.2023 SDS Number: 10785627-00016 Date of last issue: 26.09.2023
Date of first issue: 21.12.2018

EUH210 Safety data sheet available on request.

EUH208 Contains Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	Not Assigned 01-2119457273-39	Asp. Tox. 1; H304 EUH066	>= 10 - < 20
White mineral oil (petroleum)	8042-47-5 232-455-8 01-2119487078-27	Asp. Tox. 1; H304	>= 1 - < 10
Ethanol	64-17-5 200-578-6 603-002-00-5 01-2119457610-43	Flam. Liq. 2; H225 Eye Irrit. 2; H319 specific concentration limit Eye Irrit. 2; H319 >= 50 %	>= 1 - < 10
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	55965-84-9 613-167-00-5	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1;	>= 0,0002 - < 0,0015

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



PAINT SEALANT PERFECT GLOSS - 1 L

Version 6.0 Revision Date: 05.12.2023 SDS Number: 10785627-00016 Date of last issue: 26.09.2023
Date of first issue: 21.12.2018

		<p>H410 EUH071</p> <hr/> <p>M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100</p> <hr/> <p>specific concentration limit Skin Corr. 1C; H314 ≥ 0,6 % Skin Irrit. 2; H315 0,06 - < 0,6 % Eye Irrit. 2; H319 0,06 - < 0,6 % Skin Sens. 1A; H317 ≥ 0,0015 % Eye Dam. 1; H318 ≥ 0,6 % EUH071 ≥ 0,6 %</p> <hr/> <p>Acute toxicity estimate Acute oral toxicity: 64 mg/kg Acute inhalation toxicity (dust/mist): 0,171 mg/l Acute dermal toxicity: 87,12 mg/kg</p>
--	--	--

For explanation of abbreviations see section 16.

Alternative CAS Numbers for some regions

Chemical name	Alternative CAS Number(s)
Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	2682-20-4, 26172-55-4

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



PAINT SEALANT PERFECT GLOSS - 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 26.09.2023
6.0	05.12.2023	10785627-00016	Date of first issue: 21.12.2018

advice.

- | | | |
|----------------------------|---|--|
| Protection of first-aiders | : | First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8). |
| If inhaled | : | If inhaled, remove to fresh air.
Get medical attention if symptoms occur. |
| In case of skin contact | : | In case of contact, immediately flush skin with plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse. |
| In case of eye contact | : | Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists. |
| If swallowed | : | If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water. |

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Vapours may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



PAINT SEALANT PERFECT GLOSS - 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 26.09.2023
6.0	05.12.2023	10785627-00016	Date of first issue: 21.12.2018

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



PAINT SEALANT PERFECT GLOSS - 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 26.09.2023
6.0	05.12.2023	10785627-00016	Date of first issue: 21.12.2018

Use explosion-proof electrical, ventilating and lighting equipment.

Advice on safe handling : Do not get on skin or clothing.
Avoid breathing vapours.
Do not swallow.
Avoid contact with eyes.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Non-sparking tools should be used.
Keep container tightly closed.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep in properly labelled containers. Store in accordance with the particular national regulations.

Advice on common storage : No special restrictions on storage with other products.

Storage class (TRGS 510) : 12

Recommended storage temperature : 15 - 25 °C

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	Not Assigned	AGW	300 mg/m ³	DE TRGS 900
Peak-limit: excursion factor (category): 2;(II)				

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



PAINT SEALANT PERFECT GLOSS - 1 L

Version 6.0 Revision Date: 05.12.2023 SDS Number: 10785627-00016 Date of last issue: 26.09.2023
Date of first issue: 21.12.2018

	Further information: Group exposure limit for hydrocarbon solvent mixtures			
White mineral oil (petroleum)	8042-47-5	AGW (Alveolate fraction)	5 mg/m ³	DE TRGS 900
	Peak-limit: excursion factor (category): 4;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
Aluminum oxide	1344-28-1	AGW (Inhalable fraction)	10 mg/m ³	DE TRGS 900
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		AGW (Alveolate fraction)	1,25 mg/m ³	DE TRGS 900
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		BM (Alveolar dust fraction)	0,5 mg/m ³	DE TRGS 527
Ethanol	64-17-5	AGW	200 ppm 380 mg/m ³	DE TRGS 900
	Peak-limit: excursion factor (category): 4;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Ethanol	Workers	Inhalation	Long-term systemic effects	950 mg/m ³
	Workers	Skin contact	Long-term systemic effects	343 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	114 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	206 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	87 mg/kg bw/day
Aluminum oxide	Workers	Inhalation	Long-term systemic effects	15,63 mg/m ³
	Workers	Inhalation	Long-term local effects	15,63 mg/m ³
	Consumers	Ingestion	Long-term systemic effects	6,58 mg/kg bw/day
White mineral oil (petroleum)	Workers	Inhalation	Long-term systemic effects	164,56 mg/m ³
	Workers	Skin contact	Long-term systemic effects	217,05 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	34,78 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	93,02 mg/kg bw/day

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



PAINT SEALANT PERFECT GLOSS - 1 L

Version 6.0 Revision Date: 05.12.2023 SDS Number: 10785627-00016 Date of last issue: 26.09.2023
Date of first issue: 21.12.2018

	Consumers	Ingestion	Long-term systemic effects	25 mg/kg bw/day
--	-----------	-----------	----------------------------	-----------------

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Ethanol	Fresh water	0,96 mg/l
	Freshwater - intermittent	2,75 mg/l
	Marine water	0,79 mg/l
	Sewage treatment plant	580 mg/l
	Fresh water sediment	3,6 mg/kg dry weight (d.w.)
	Marine sediment	2,9 mg/kg dry weight (d.w.)
	Soil	0,63 mg/kg dry weight (d.w.)
	Oral (Secondary Poisoning)	380 mg/kg food
Aluminum oxide	Fresh water	74,9 µg/l
	Sewage treatment plant	20 mg/l

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.
Use explosion-proof electrical, ventilating and lighting equipment.

Personal protective equipment

Eye/face protection : Wear the following personal protective equipment:
Safety glasses
Equipment should conform to DIN EN 166

Hand protection

Material : Nitrile rubber
Break through time : > 10 min
Glove thickness : 0,1 mm
Directive : Equipment should conform to DIN EN 374
Protective index : Class 1

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Skin should be washed after contact.

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
Equipment should conform to DIN EN 14387

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



PAINT SEALANT PERFECT GLOSS - 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 26.09.2023
6.0	05.12.2023	10785627-00016	Date of first issue: 21.12.2018

Filter type : Combined particulates and organic vapour type (A-P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	: paste
Colour	: light brown
Odour	: characteristic
Odour Threshold	: No data available
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: 78 °C
Flammability (solid, gas)	: Not applicable
Flammability (liquids)	: Does not sustain combustion.
Upper explosion limit / Upper flammability limit	: 7 %(V)
Lower explosion limit / Lower flammability limit	: 0,5 %(V)
Flash point	: 36 °C
Auto-ignition temperature	: > 200 °C
Decomposition temperature	: No data available
pH	: 7 (20 °C) Concentration: 100 %
Viscosity Viscosity, kinematic	: 5000 - 8000 mm ² /s (20 °C)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



PAINT SEALANT PERFECT GLOSS - 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 26.09.2023
6.0	05.12.2023	10785627-00016	Date of first issue: 21.12.2018

Solubility(ies)
Water solubility : completely miscible

Partition coefficient: n-
octanol/water : Not applicable

Vapour pressure : 0,6 hPa (20 °C)

Density : 0,967 g/cm³ (20 °C)

Relative vapour density : No data available

Particle characteristics
Particle size : Not applicable

9.2 Other information

Explosives : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Evaporation rate : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : None.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



PAINT SEALANT PERFECT GLOSS - 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 26.09.2023
6.0	05.12.2023	10785627-00016	Date of first issue: 21.12.2018

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Acute oral toxicity	: LD50 (Rat): > 5.000 mg/kg Remarks: Based on data from similar materials
Acute inhalation toxicity	: LC50 (Rat): > 4.951 mg/m ³ Exposure time: 4 h Test atmosphere: vapour Assessment: The substance or mixture has no acute inhalation toxicity Remarks: Based on data from similar materials
Acute dermal toxicity	: LD50 (Rabbit): >= 3.160 mg/kg Assessment: The substance or mixture has no acute dermal toxicity Remarks: Based on data from similar materials

White mineral oil (petroleum):

Acute oral toxicity	: LD50 (Rat): > 5.000 mg/kg
Acute inhalation toxicity	: LC50 (Rat): > 5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: The substance or mixture has no acute inhalation toxicity
Acute dermal toxicity	: LD50 (Rabbit): > 2.000 mg/kg Assessment: The substance or mixture has no acute dermal toxicity

Ethanol:

Acute oral toxicity	: LD50 (Rat): > 5.000 mg/kg Method: OECD Test Guideline 401
Acute inhalation toxicity	: LC50 (Rat): 124,7 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



PAINT SEALANT PERFECT GLOSS - 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 26.09.2023
6.0	05.12.2023	10785627-00016	Date of first issue: 21.12.2018

Exposure time: 4 h
Test atmosphere: vapour

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1):

Acute oral toxicity	: LD50 (Rat): 64 mg/kg
Acute inhalation toxicity	: LC50 (Rat): 0,171 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: Corrosive to the respiratory tract.
Acute dermal toxicity	: LD50 (Rabbit): 87,12 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Species	: Rabbit
Result	: Mild skin irritation
Assessment	: Repeated exposure may cause skin dryness or cracking.

White mineral oil (petroleum):

Species	: Rabbit
Result	: No skin irritation

Ethanol:

Species	: Rabbit
Method	: OECD Test Guideline 404
Result	: No skin irritation

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1):

Species	: Rabbit
Method	: OECD Test Guideline 404
Result	: Corrosive after 1 to 4 hours of exposure

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Species	: Rabbit
Method	: OECD Test Guideline 405
Result	: No eye irritation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



PAINT SEALANT PERFECT GLOSS - 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 26.09.2023
6.0	05.12.2023	10785627-00016	Date of first issue: 21.12.2018

Remarks : Based on data from similar materials

White mineral oil (petroleum):

Species : Rabbit
Result : No eye irritation

Ethanol:

Species : Rabbit
Method : OECD Test Guideline 405
Result : Irritation to eyes, reversing within 21 days

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1):

Result : Irreversible effects on the eye
Remarks : Based on skin corrosivity.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative
Remarks : Based on data from similar materials

White mineral oil (petroleum):

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative

Ethanol:

Test Type : Local lymph node assay (LLNA)
Exposure routes : Skin contact
Species : Mouse
Result : negative

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1):

Test Type : Buehler Test
Exposure routes : Skin contact

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



PAINT SEALANT PERFECT GLOSS - 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 26.09.2023
6.0	05.12.2023	10785627-00016	Date of first issue: 21.12.2018

Species	: Guinea pig
Result	: positive
Assessment	: Probability or evidence of high skin sensitisation rate in humans

Germ cell mutagenicity

Not classified based on available information.

Components:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Genotoxicity in vitro	: Test Type: In vitro mammalian cell gene mutation test Result: negative Remarks: Based on data from similar materials
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Ingestion Result: negative
Germ cell mutagenicity- Assessment	: Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

White mineral oil (petroleum):

Genotoxicity in vitro	: Test Type: In vitro mammalian cell gene mutation test Result: negative
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection Method: OECD Test Guideline 474 Result: negative Remarks: Based on data from similar materials

Ethanol:

Genotoxicity in vitro	: Test Type: In vitro mammalian cell gene mutation test Result: negative Test Type: Bacterial reverse mutation assay (AMES) Result: negative
Genotoxicity in vivo	: Test Type: Rodent dominant lethal test (germ cell) (in vivo) Species: Mouse Application Route: Ingestion Result: equivocal

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



PAINT SEALANT PERFECT GLOSS - 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 26.09.2023
6.0	05.12.2023	10785627-00016	Date of first issue: 21.12.2018

Carcinogenicity

Not classified based on available information.

Components:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Species	:	Rat
Application Route	:	inhalation (vapour)
Exposure time	:	105 weeks
Result	:	negative
Remarks	:	Based on data from similar materials

Carcinogenicity - Assessment	:	Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)
------------------------------	---	--

White mineral oil (petroleum):

Species	:	Rat
Application Route	:	Ingestion
Exposure time	:	24 Months
Result	:	negative

Reproductive toxicity

Not classified based on available information.

Components:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Effects on fertility	:	Test Type: Reproduction/Developmental toxicity screening test Species: Rat Application Route: inhalation (vapour) Result: negative
----------------------	---	---

Effects on foetal development	:	Test Type: Embryo-foetal development Species: Rat Application Route: inhalation (vapour) Result: negative
-------------------------------	---	--

White mineral oil (petroleum):

Effects on fertility	:	Test Type: One-generation reproduction toxicity study Species: Rat Application Route: Skin contact Result: negative
----------------------	---	--

Effects on foetal development	:	Test Type: Embryo-foetal development Species: Rat Application Route: Ingestion Result: negative
-------------------------------	---	--

Ethanol:

Effects on fertility	:	Test Type: Two-generation reproduction toxicity study
----------------------	---	---

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



PAINT SEALANT PERFECT GLOSS - 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 26.09.2023
6.0	05.12.2023	10785627-00016	Date of first issue: 21.12.2018

Species: Mouse
Application Route: Ingestion
Result: negative

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Species	:	Rat
NOAEL	:	≥ 1.000 mg/kg
Application Route	:	Ingestion
Exposure time	:	54 Days
Remarks	:	Based on data from similar materials

White mineral oil (petroleum):

Species	:	Rat
LOAEL	:	> 160 mg/kg
Application Route	:	Ingestion
Exposure time	:	90 Days
Species	:	Rat
LOAEL	:	≥ 1 mg/l
Application Route	:	inhalation (dust/mist/fume)
Exposure time	:	4 Weeks
Method	:	OECD Test Guideline 412

Ethanol:

Species	:	Rat
NOAEL	:	1.280 mg/kg
LOAEL	:	3.156 mg/kg
Application Route	:	Ingestion
Exposure time	:	90 Days

Aspiration toxicity

Not classified based on available information.

Components:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



PAINT SEALANT PERFECT GLOSS - 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 26.09.2023
6.0	05.12.2023	10785627-00016	Date of first issue: 21.12.2018

White mineral oil (petroleum):

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 1.000 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Remarks: Based on data from similar materials

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): > 1.000 mg/l
aquatic invertebrates
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202

Toxicity to algae/aquatic : EL50 (Pseudokirchneriella subcapitata (green algae)): > 1.000
plants
mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

NOELR (Pseudokirchneriella subcapitata (green algae)):
1.000 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to daphnia and other : NOELR: > 1 mg/l
aquatic invertebrates (Chronic toxicity)
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



PAINT SEALANT PERFECT GLOSS - 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 26.09.2023
6.0	05.12.2023	10785627-00016	Date of first issue: 21.12.2018

White mineral oil (petroleum):

- | | | |
|--|---|--|
| Toxicity to fish | : | LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203 |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202 |
| Toxicity to algae/aquatic plants | : | NOEC (Pseudokirchneriella subcapitata (green algae)): 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201 |
| Toxicity to fish (Chronic toxicity) | : | NOEC: 1.000 mg/l
Exposure time: 28 d
Species: Oncorhynchus mykiss (rainbow trout) |
| Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) | : | NOEC: 1.000 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea) |

Ethanol:

- | | | |
|--|---|--|
| Toxicity to fish | : | LC50 (Pimephales promelas (fathead minnow)): > 1.000 mg/l
Exposure time: 96 h |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Ceriodaphnia (water flea)): > 1.000 mg/l
Exposure time: 48 h |
| Toxicity to algae/aquatic plants | : | ErC50 (Chlorella vulgaris (Fresh water algae)): 275 mg/l
Exposure time: 72 h

EC10 (Chlorella vulgaris (Fresh water algae)): 11,5 mg/l
Exposure time: 72 h |
| Toxicity to microorganisms | : | EC50 (Pseudomonas putida): 6.500 mg/l
Exposure time: 16 h |
| Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) | : | NOEC: 9,6 mg/l
Exposure time: 9 d
Species: Daphnia magna (Water flea) |

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1):

- | | | |
|---|---|--|
| Toxicity to fish | : | LC50 (Oncorhynchus mykiss (rainbow trout)): 0,19 mg/l
Exposure time: 96 h |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia magna (Water flea)): 0,16 mg/l
Exposure time: 48 h |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



PAINT SEALANT PERFECT GLOSS - 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 26.09.2023
6.0	05.12.2023	10785627-00016	Date of first issue: 21.12.2018

Toxicity to algae/aquatic plants	:	ErC50 (Skeletonema costatum (marine diatom)): 0,0052 mg/l Exposure time: 48 h NOEC (Skeletonema costatum (marine diatom)): 0,00049 mg/l Exposure time: 48 h
M-Factor (Acute aquatic toxicity)	:	100
Toxicity to fish (Chronic toxicity)	:	NOEC: 0,02 mg/l Exposure time: 36 d Species: Pimephales promelas (fathead minnow)
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC: 0,10 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea)
M-Factor (Chronic aquatic toxicity)	:	100

12.2 Persistence and degradability

Components:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 80 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

White mineral oil (petroleum):

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 31 %
Exposure time: 28 d

Ethanol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 84 %
Exposure time: 20 d

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1):

Biodegradability	:	Result: Not readily biodegradable. Biodegradation: 62 % Exposure time: 28 d Method: OECD Test Guideline 301B
------------------	---	---

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



PAINT SEALANT PERFECT GLOSS - 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 26.09.2023
6.0	05.12.2023	10785627-00016	Date of first issue: 21.12.2018

12.3 Bioaccumulative potential

Components:

Ethanol:

Partition coefficient: n-
octanol/water : log Pow: -0,35

Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1):

Partition coefficient: n-
octanol/water : log Pow: < 1

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	: Dispose of in accordance with local regulations. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities. Do not dispose of waste into sewer.
Contaminated packaging	: Empty containers should be taken to an approved waste handling site for recycling or disposal. If not otherwise specified: Dispose of as unused product.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



PAINT SEALANT PERFECT GLOSS - 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 26.09.2023
6.0	05.12.2023	10785627-00016	Date of first issue: 21.12.2018

Waste Code : The following Waste Codes are only suggestions:

used product
16 03 06, organic wastes other than those mentioned in 16 03 05

unused product
16 03 06, organic wastes other than those mentioned in 16 03 05

uncleaned packagings
15 01 06, mixed packaging

Acc. Packaging Act properly emptied packaging:
Properly emptied, non-contaminated packaging of non-hazardous products can be supplied to a system for the collection of sales packaging.

SECTION 14: Transport information

14.1 UN number or ID number

ADN	: Not regulated as a dangerous good
ADR	: Not regulated as a dangerous good
RID	: Not regulated as a dangerous good
IMDG	: Not regulated as a dangerous good
IATA	: Not regulated as a dangerous good

14.2 UN proper shipping name

ADN	: Not regulated as a dangerous good
ADR	: Not regulated as a dangerous good
RID	: Not regulated as a dangerous good
IMDG	: Not regulated as a dangerous good
IATA	: Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADN	: Not regulated as a dangerous good
ADR	: Not regulated as a dangerous good
RID	: Not regulated as a dangerous good
IMDG	: Not regulated as a dangerous good
IATA	: Not regulated as a dangerous good

14.4 Packing group

ADN	: Not regulated as a dangerous good
-----	-------------------------------------

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



PAINT SEALANT PERFECT GLOSS - 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 26.09.2023
6.0	05.12.2023	10785627-00016	Date of first issue: 21.12.2018

ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA (Cargo)	:	Not regulated as a dangerous good
IATA (Passenger)	:	Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the following entries should be considered: Number on list 75 If you intend to use this product as tattoo ink, please contact your vendor.
--	---	--

Formaldehyde (Number on list 72, 28)

Substance(s) or mixture(s) are listed here according to their appearance in the regulation, irrespective of their use/purpose or the conditions of the restriction. Please refer to the conditions in corresponding Regulation to determine whether an entry is applicable to the placing on the market or not.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	:	Not applicable
---	---	----------------

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
---	---	----------------

Regulation (EU) 2019/1021 on persistent organic pollutants (recast)	:	Not applicable
---	---	----------------

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import	:	Not applicable
---	---	----------------

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



PAINT SEALANT PERFECT GLOSS - 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 26.09.2023
6.0	05.12.2023	10785627-00016	Date of first issue: 21.12.2018

of dangerous chemicals

REACH - List of substances subject to authorisation : Not applicable
(Annex XIV)

The treated article incorporates biocidal products

Active substance : Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
Not applicable

Water hazard class (Germany) : WGK 1 slightly hazardous to water
Classification according to AwSV, Annex 1 (5.2)

TA Luft List (Germany) : 5.2.1: Total dust:
Not applicable
5.2.2: Inorganic substances in powdered form:
Not applicable
5.2.4: Inorganic substances in gaseous form:
Not applicable
5.2.5: Organic Substances:
Not applicable
5.2.7.1.1: Carcinogenic substance:
Class 1: 0,08 % Tetrahydro-1,3,4,6-tetrakis(hydroxymethyl)imidazo[4,5-d]imidazole-2,5(1H,3H)-dione
5.2.7.1.1: Quartz fine dust PM4:
Not applicable
5.2.7.1.1: Formaldehyde:
others: < 0,01 % Formaldehyde
5.2.7.1.1: fibres:
Not applicable
5.2.7.2: Poorly degradable, easily enrichable and highly toxic organic substances:
Not applicable

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 15,05 %, 135,41 g/l
Remarks: VOC content excluding water

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



PAINT SEALANT PERFECT GLOSS - 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 26.09.2023
6.0	05.12.2023	10785627-00016	Date of first issue: 21.12.2018

SECTION 16: Other information

Other information : Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Full text of H-Statements

H225	: Highly flammable liquid and vapour.
H301	: Toxic if swallowed.
H304	: May be fatal if swallowed and enters airways.
H310	: Fatal in contact with skin.
H314	: Causes severe skin burns and eye damage.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H330	: Fatal if inhaled.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
EUH066	: Repeated exposure may cause skin dryness or cracking.
EUH071	: Corrosive to the respiratory tract.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Skin Corr.	: Skin corrosion
Skin Sens.	: Skin sensitisation
DE TRGS 527	: Germany. TRGS 527 - Activities with nanomaterials
DE TRGS 900	: Germany. TRGS 900 - Occupational exposure limit values.
DE TRGS 527 / BM	: Assessment scale
DE TRGS 900 / AGW	: Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization;

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



PAINT SEALANT PERFECT GLOSS - 1 L

Version	Revision Date:	SDS Number:	Date of last issue: 26.09.2023
6.0	05.12.2023	10785627-00016	Date of first issue: 21.12.2018

KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN