

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## RUST CONVERTER - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 12.05.2023
7.1	02.10.2023	10692714-00012	Date of first issue: 06.10.2015

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : RUST CONVERTER - 400 ML

Product code : 0893110400

Unique Formula Identifier (UFI) : RQP2-N0R4-U00H-SAM5

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Paint, Corrosion inhibitor  
Professional use product

Recommended restrictions on use : Not applicable

#### 1.3 Details of the supplier of the safety data sheet

Company : Adolf Wuerth GmbH & Co. KG  
Reinhold-Würth-Str. 12-17  
74653 Künzelsau

Telephone : +49 794015 0

Telefax : +49 794015 10 00

E-mail address of person responsible for the SDS : isi@wuerth.com

#### 1.4 Emergency telephone number

+49 (0)6132 – 84463

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1	H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated.
Acute toxicity, Category 4	H302: Harmful if swallowed.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## RUST CONVERTER - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 12.05.2023
7.1	02.10.2023	10692714-00012	Date of first issue: 06.10.2015

Skin irritation, Category 2	H315: Causes skin irritation.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Specific target organ toxicity - single exposure, Category 3	H336: May cause drowsiness or dizziness.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements :

- H222 Extremely flammable aerosol.
- H229 Pressurised container: May burst if heated.
- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H336 May cause drowsiness or dizziness.
- H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/ eye protection/ face protection.

#### **Response:**

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

#### **Storage:**

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

#### **Hazardous components which must be listed on the label:**

Dimethyl ether  
Butan-1-ol  
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## RUST CONVERTER - 400 ML

Version 7.1      Revision Date: 02.10.2023      SDS Number: 10692714-00012      Date of last issue: 12.05.2023  
Date of first issue: 06.10.2015

weight ≤ 700)  
Pyrogallol

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Dimethyl ether	115-10-6 204-065-8 603-019-00-8	Flam. Gas 1A; H220 Press. Gas Liquefied gas; H280 STOT SE 3; H336	>= 50 - < 70
Acetone	67-64-1 200-662-2 606-001-00-8	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066	>= 10 - < 20
Butan-1-ol	71-36-3 200-751-6 603-004-00-6	Flam. Liq. 3; H226 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H335 STOT SE 3; H336  Acute toxicity estimate  Acute oral toxicity: 790 mg/kg	>= 3 - < 10
Xylene	1330-20-7 215-535-7 601-022-00-9	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335	>= 2,5 - < 10

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## RUST CONVERTER - 400 ML

Version 7.1      Revision Date: 02.10.2023      SDS Number: 10692714-00012      Date of last issue: 12.05.2023  
Date of first issue: 06.10.2015

		STOT RE 2; H373 (Auditory system) Asp. Tox. 1; H304 Aquatic Chronic 3; H412	
		Acute toxicity estimate	
		Acute inhalation toxicity (vapour): 11 mg/l Acute dermal toxicity: 1.100 mg/kg	
n-Butyl acetate	123-86-4 204-658-1 607-025-00-1	Flam. Liq. 3; H226 STOT SE 3; H336 EUH066	$\geq 1 - < 10$
Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq 700$ )	25068-38-6 500-033-5 603-074-00-8	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411	$\geq 2,5 - < 5$
		specific concentration limit Eye Irrit. 2; H319 $\geq 5\%$ Skin Irrit. 2; H315 $\geq 5\%$	
Pyrogallol	87-66-1 201-762-9 604-009-00-6	Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1A; H317 Muta. 2; H341 Aquatic Chronic 3; H412	$\geq 0,25 - < 1$
		Acute toxicity estimate	
		Acute oral toxicity: 800 mg/kg Acute inhalation toxicity (dust/mist): 1,5 mg/l Acute dermal toxicity: 1.100 mg/kg	

For explanation of abbreviations see section 16.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## RUST CONVERTER - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 12.05.2023
7.1	02.10.2023	10692714-00012	Date of first issue: 06.10.2015

---

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- If inhaled : If inhaled, remove to fresh air.  
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
If easy to do, remove contact lens, if worn.  
Get medical attention immediately.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention.  
Rinse mouth thoroughly with water.  
Never give anything by mouth to an unconscious person.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Risks : Harmful if swallowed.  
Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye damage.  
May cause drowsiness or dizziness.

#### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically and supportively.
- 

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## RUST CONVERTER - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 12.05.2023
7.1	02.10.2023	10692714-00012	Date of first issue: 06.10.2015

---

Unsuitable extinguishing media : None known.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Flash back possible over considerable distance.  
Vapours may form explosive mixtures with air.  
Exposure to combustion products may be a hazard to health.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

Hazardous combustion products : Carbon oxides

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.  
Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

### 6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g. by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapours/mists with a water spray jet.  
For large spills, provide dyking or other appropriate contain-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## RUST CONVERTER - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 12.05.2023
7.1	02.10.2023	10692714-00012	Date of first issue: 06.10.2015

---

ment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

- |                         |   |   |
|-------------------------|---|---|
| Technical measures      | : | See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.   |
| Local/Total ventilation | : | If sufficient ventilation is unavailable, use with local exhaust ventilation.<br>If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.   |
| Advice on safe handling | : | Do not get on skin or clothing.<br>Do not breathe spray.<br>Do not swallow.<br>Do not get in eyes.<br>Wash skin thoroughly after handling.<br>Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment<br>Keep container tightly closed.<br>Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.<br>Take precautionary measures against static discharges.<br>Do not eat, drink or smoke when using this product.<br>Take care to prevent spills, waste and minimize release to the environment.<br>Do not spray on an open flame or other ignition source.<br><br>Do not breathe decomposition products. |
| Hygiene measures        | : | If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Contaminated work clothing should not be allowed out of the workplace.<br>Wash contaminated clothing before re-use.  |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## RUST CONVERTER - 400 ML

Version 7.1      Revision Date: 02.10.2023      SDS Number: 10692714-00012      Date of last issue: 12.05.2023  
Date of first issue: 06.10.2015

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store locked up. Keep tightly closed. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Do not pierce or burn, even after use. Keep cool. Protect from sunlight.

Advice on common storage : Do not store with the following product types:  
Self-reactive substances and mixtures  
Organic peroxides  
Oxidizing agents  
Flammable solids  
Pyrophoric liquids  
Pyrophoric solids  
Self-heating substances and mixtures  
Substances and mixtures, which in contact with water, emit flammable gases  
Explosives  
Gases

Storage class (TRGS 510) : 2B

Recommended storage temperature : > 0 °C

### 7.3 Specific end use(s)

Specific use(s) : No data available

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Dimethyl ether	115-10-6	TWA	1.000 ppm 1.920 mg/m <sup>3</sup>	2000/39/EC
		Further information: Indicative		
		AGW	1.000 ppm 1.900 mg/m <sup>3</sup>	DE TRGS 900
		Peak-limit: excursion factor (category): 8;(II)		
Acetone	67-64-1	TWA	500 ppm 1.210 mg/m <sup>3</sup>	2000/39/EC
		Further information: Indicative		
		AGW	500 ppm 1.200 mg/m <sup>3</sup>	DE TRGS 900
		Peak-limit: excursion factor (category): 2;(I)		
		Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child		
Butan-1-ol	71-36-3	AGW	100 ppm 310 mg/m <sup>3</sup>	DE TRGS 900



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## RUST CONVERTER - 400 ML

Version 7.1      Revision Date: 02.10.2023      SDS Number: 10692714-00012      Date of last issue: 12.05.2023  
Date of first issue: 06.10.2015

	Peak-limit: excursion factor (category): 1;(I)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
Xylene	1330-20-7	TWA	50 ppm 221 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 442 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		AGW	50 ppm 220 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: Skin absorption			
n-Butyl acetate	123-86-4	STEL	150 ppm 723 mg/m <sup>3</sup>	2019/1831/E U
	Further information: Indicative			
		TWA	50 ppm 241 mg/m <sup>3</sup>	2019/1831/E U
	Further information: Indicative			
		AGW	62 ppm 300 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit: excursion factor (category): 2;(I)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			

### Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Formaldehyde	50-00-0	TWA	0,3 ppm 0,37 mg/m <sup>3</sup>	2004/37/EC
	Further information: Dermal sensitisation, Carcinogens or mutagens			
		STEL	0,6 ppm 0,74 mg/m <sup>3</sup>	2004/37/EC
	Further information: Dermal sensitisation, Carcinogens or mutagens			
		AGW	0,3 ppm 0,37 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit: excursion factor (category): 2;(I)			
	Further information: Carcinogenic substance Cat. 1A or 1B or carcinogenic activity or procedure according to § 2 (3) No. 4 of the Hazardous Substances Ordinance - in addition, § 10 GefStoffV must be observed, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child, Substance sensitizing through the skin			
Methanol	67-56-1	TWA	200 ppm 260 mg/m <sup>3</sup>	2006/15/EC
	Further information: Indicative, Identifies the possibility of significant uptake through the skin			
		AGW	100 ppm 130 mg/m <sup>3</sup>	DE TRGS 900

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## RUST CONVERTER - 400 ML

Version 7.1      Revision Date: 02.10.2023      SDS Number: 10692714-00012      Date of last issue: 12.05.2023  
Date of first issue: 06.10.2015

	Peak-limit: excursion factor (category): 2;(II)
	Further information: Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child

### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Acetone	67-64-1	Acetone: 80 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903
Butan-1-ol	71-36-3	1-butanol: 2 mg/g creatinine (Urine)	Before next shift	TRGS 903
		1-butanol: 10 mg/g creatinine (Urine)	Immediately after exposure or after working hours	TRGS 903
Xylene	1330-20-7	methylhippuric acid (all isomers): 2.000 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Dimethyl ether	Workers	Inhalation	Long-term systemic effects	1894 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	471 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	2420 mg/m <sup>3</sup>
Acetone	Workers	Inhalation	Long-term systemic effects	1210 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	2420 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	186 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	200 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	62 mg/kg bw/day
Butan-1-ol	Consumers	Ingestion	Long-term systemic effects	62 mg/kg bw/day
	Workers	Inhalation	Long-term local effects	310 mg/m <sup>3</sup>
	Consumers	Ingestion	Long-term systemic effects	3,125 mg/kg bw/day
	Consumers	Inhalation	Long-term local effects	55 mg/m <sup>3</sup>
Xylene	Workers	Inhalation	Long-term systemic effects	221 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	442 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	221 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	442 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic	212 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## RUST CONVERTER - 400 ML

Version  
7.1

Revision Date:  
02.10.2023

SDS Number:  
10692714-00012

Date of last issue: 12.05.2023  
Date of first issue: 06.10.2015

			effects	bw/day
	Consumers	Inhalation	Long-term systemic effects	65,3 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects	260 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	65,3 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	260 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	125 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	12,5 mg/kg bw/day
n-Butyl acetate	Workers	Inhalation	Acute systemic effects	600 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	600 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	300 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	300 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects	300 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	300 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	35,7 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	35,7 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	11 mg/kg bw/day
	Consumers	Skin contact	Acute systemic effects	11 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	6 mg/kg bw/day
	Consumers	Skin contact	Acute systemic effects	6 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	2 mg/kg bw/day
	Consumers	Ingestion	Acute systemic effects	2 mg/kg bw/day
Reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	Workers	Inhalation	Long-term systemic effects	12,25 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	12,25 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	8,33 mg/kg bw/day
	Workers	Skin contact	Acute systemic effects	8,33 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	3,571 mg/kg bw/day

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## RUST CONVERTER - 400 ML

Version 7.1      Revision Date: 02.10.2023      SDS Number: 10692714-00012      Date of last issue: 12.05.2023  
Date of first issue: 06.10.2015

	Consumers	Skin contact	Acute systemic effects	3,571 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0,75 mg/kg bw/day
	Consumers	Ingestion	Acute systemic effects	0,75 mg/kg bw/day
Pyrogallol	Workers	Skin contact	Long-term local effects	0,0062 mg/kg bw/day
	Consumers	Skin contact	Long-term local effects	0,0062 mg/kg bw/day

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Dimethyl ether	Fresh water	0,155 mg/l
	Marine water	0,016 mg/l
	Intermittent use/release	1,549 mg/l
	Sewage treatment plant	160 mg/l
	Fresh water sediment	0,681 mg/kg dry weight (d.w.)
	Marine sediment	0,069 mg/kg dry weight (d.w.)
	Soil	0,045 mg/kg dry weight (d.w.)
Acetone	Fresh water	10,6 mg/l
	Marine water	1,06 mg/l
	Intermittent use/release	21 mg/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	30,4 mg/kg dry weight (d.w.)
	Marine sediment	3,04 mg/kg dry weight (d.w.)
	Soil	29,5 mg/kg dry weight (d.w.)
Butan-1-ol	Fresh water	0,082 mg/l
	Marine water	0,008 mg/l
	Intermittent use/release	2,25 mg/l
	Sewage treatment plant	2476 mg/l
	Fresh water sediment	0,178 mg/kg
	Marine sediment	0,018 mg/kg
	Soil	0,015 mg/kg
Xylene	Fresh water	0,327 mg/l
	Intermittent use/release	0,327 mg/l
	Marine water	0,327 mg/l
	Sewage treatment plant	6,58 mg/l
	Fresh water sediment	12,46 mg/kg dry weight (d.w.)
	Marine sediment	12,46 mg/kg dry weight (d.w.)
	Soil	2,31 mg/kg dry weight (d.w.)
n-Butyl acetate	Fresh water	0,18 mg/l
	Marine water	0,018 mg/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## RUST CONVERTER - 400 ML

Version 7.1      Revision Date: 02.10.2023      SDS Number: 10692714-00012      Date of last issue: 12.05.2023  
Date of first issue: 06.10.2015

	Sewage treatment plant	35,6 mg/l
	Fresh water sediment	0,981 mg/kg dry weight (d.w.)
	Marine sediment	0,098 mg/kg dry weight (d.w.)
	Soil	0,09 mg/kg dry weight (d.w.)
Reaction product: bisphenol-A- (epichlorhydrin); epoxy resin (number average molecular weight $\leq$ 700)	Fresh water	0,006 mg/l
	Freshwater - intermittent	0,018 mg/l
	Marine water	0,001 mg/l
	Marine water - intermittent	0,002 mg/l
	Sewage treatment plant	10 mg/l
	Fresh water sediment	0,996 mg/kg dry weight (d.w.)
	Marine sediment	0,1 mg/kg dry weight (d.w.)
	Soil	0,196 mg/kg dry weight (d.w.)
	Secondary Poisoning	11 mg/kg food
Pyrogallol	Fresh water	0,00433 mg/l
	Marine water	0,000433 mg/l
	Freshwater - intermittent	0,0433 mg/l
	Marine water - intermittent	0,00433 mg/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	0,155 mg/kg dry weight (d.w.)
	Marine sediment	0,0155 mg/kg dry weight (d.w.)
	Soil	0,0285 mg/kg dry weight (d.w.)

### 8.2 Exposure controls

#### Engineering measures

Processing may form hazardous compounds (see section 10).

Minimize workplace exposure concentrations.

If sufficient ventilation is unavailable, use with local exhaust ventilation.

If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

#### Personal protective equipment

Eye/face protection : Wear the following personal protective equipment:  
Chemical resistant goggles must be worn.  
If splashes are likely to occur, wear:  
Face-shield  
Equipment should conform to DIN EN 166

Hand protection

Material : Neoprene  
Break through time : > 480 min

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## RUST CONVERTER - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 12.05.2023
7.1	02.10.2023	10692714-00012	Date of first issue: 06.10.2015

---

Glove thickness : > 0,4 mm

Material : Nitrile rubber  
Break through time : > 480 min  
Glove thickness : > 0,4 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Wear the following personal protective equipment:  
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.  
Equipment should conform to DIN EN 137

Filter type : Self-contained breathing apparatus

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state : Aerosol containing a liquefied gas

Propellant : Dimethyl ether

Colour : clear

Odour : characteristic

Odour Threshold : No data available

Melting point/freezing point : No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## RUST CONVERTER - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 12.05.2023
7.1	02.10.2023	10692714-00012	Date of first issue: 06.10.2015

---

Initial boiling point and boiling range : -24,8 °C

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper flammability limit : 32 %(V)

Lower explosion limit / Lower flammability limit : 2,5 %(V)

Flash point : -18 °C  
Flash point is only valid for liquid portion in the aerosol can.

Auto-ignition temperature : 240 °C

Decomposition temperature : No data available

pH : substance/mixture is non-soluble (in water)

Viscosity  
Viscosity, kinematic : < 7 mm<sup>2</sup>/s (40 °C)

Flow time : < 30 s  
Cross section: 3 mm  
Method: ISO 2431

Solubility(ies)  
Water solubility : insoluble

Partition coefficient: n-octanol/water : Not applicable

Vapour pressure : 5.102 hPa (20 °C)

Density : 0,85 g/cm<sup>3</sup> (20 °C)

Relative vapour density : Not applicable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## RUST CONVERTER - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 12.05.2023
7.1	02.10.2023	10692714-00012	Date of first issue: 06.10.2015

---

Particle characteristics  
Particle size : Not applicable

### 9.2 Other information

Explosives : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Evaporation rate : Not applicable

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Not classified as a reactivity hazard.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Extremely flammable aerosol.  
Vapours may form explosive mixture with air.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.  
Can react with strong oxidizing agents.  
Hazardous decomposition products will be formed at elevated temperatures.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : Oxidizing agents

### 10.6 Hazardous decomposition products

Thermal decomposition : Formaldehyde  
Methanol

---

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Inhalation  
Skin contact  
Ingestion  
Eye contact



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## RUST CONVERTER - 400 ML

Version 7.1      Revision Date: 02.10.2023      SDS Number: 10692714-00012      Date of last issue: 12.05.2023  
Date of first issue: 06.10.2015

---

### Acute toxicity

Harmful if swallowed.

#### Product:

Acute oral toxicity : LD50 Oral: 1.819,5 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

#### Components:

##### **Dimethyl ether:**

Acute inhalation toxicity : LC50 (Rat): 164000 ppm  
Exposure time: 4 h  
Test atmosphere: gas

##### **Acetone:**

Acute oral toxicity : LD50 (Rat): 5.800 mg/kg

Acute inhalation toxicity : LC50 (Rat): 76 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 7.426 mg/kg

##### **Butan-1-ol:**

Acute oral toxicity : LD50 (Rat): 790 mg/kg

Acute inhalation toxicity : LC0 (Rat): > 17,76 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 3.430 mg/kg

##### **Xylene:**

Acute oral toxicity : LD50 (Rat): 3.523 mg/kg  
Method: Directive 67/548/EEC, Annex V, B.1.

Acute inhalation toxicity : Acute toxicity estimate: 11 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Expert judgement  
Remarks: Based on national or regional regulation.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## RUST CONVERTER - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 12.05.2023
7.1	02.10.2023	10692714-00012	Date of first issue: 06.10.2015

---

Acute dermal toxicity : Acute toxicity estimate: 1.100 mg/kg  
Method: Expert judgement  
Remarks: Based on national or regional regulation.

### **n-Butyl acetate:**

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 21,1 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

### **Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq 700$ ):**

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg  
Method: OECD Test Guideline 420  
Assessment: The substance or mixture has no acute oral toxicity  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: Based on data from similar materials

### **Pyrogallol:**

Acute oral toxicity : LD50 (Rat, female): 800 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 1,5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: Expert judgement  
Remarks: Based on national or regional regulation.

Acute dermal toxicity : Acute toxicity estimate: 1.100 mg/kg  
Method: Expert judgement  
Remarks: Based on national or regional regulation.

### **Skin corrosion/irritation**

Causes skin irritation.

### **Components:**

#### **Acetone:**

Assessment : Repeated exposure may cause skin dryness or cracking.

#### **Butan-1-ol:**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## RUST CONVERTER - 400 ML

Version 7.1      Revision Date: 02.10.2023      SDS Number: 10692714-00012      Date of last issue: 12.05.2023  
Date of first issue: 06.10.2015

---

Species : Rabbit  
Result : Skin irritation

### Xylene:

Species : Rabbit  
Result : Skin irritation

### n-Butyl acetate:

Species : Rabbit  
Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

### Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq 700$ ):

Result : Skin irritation  
Remarks : Based on national or regional regulation.

### Pyrogallol:

Species : Mouse  
Result : Skin irritation

### Serious eye damage/eye irritation

Causes serious eye damage.

### Components:

#### Acetone:

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : Irritation to eyes, reversing within 21 days

#### Butan-1-ol:

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : Irreversible effects on the eye

#### Xylene:

Species : Rabbit  
Result : Irritation to eyes, reversing within 21 days

#### n-Butyl acetate:

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : No eye irritation

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## RUST CONVERTER - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 12.05.2023
7.1	02.10.2023	10692714-00012	Date of first issue: 06.10.2015

---

### Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq 700$ ):

Result : Irritation to eyes, reversing within 21 days  
Remarks : Based on national or regional regulation.

### Pyrogallol:

Species : Rabbit  
Result : Irritation to eyes, reversing within 21 days

### Respiratory or skin sensitisation

#### Skin sensitisation

May cause an allergic skin reaction.

#### Respiratory sensitisation

Not classified based on available information.

### Components:

#### Acetone:

Test Type : Maximisation Test  
Exposure routes : Skin contact  
Species : Guinea pig  
Result : negative

#### Butan-1-ol:

Test Type : Maximisation Test  
Exposure routes : Skin contact  
Species : Guinea pig  
Result : negative  
Remarks : Based on data from similar materials

#### Xylene:

Test Type : Local lymph node assay (LLNA)  
Exposure routes : Skin contact  
Species : Mouse  
Result : negative

#### n-Butyl acetate:

Test Type : Maximisation Test  
Exposure routes : Skin contact  
Species : Guinea pig  
Result : negative

### Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq 700$ ):

Test Type : Maximisation Test  
Exposure routes : Skin contact  
Species : Guinea pig

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## RUST CONVERTER - 400 ML

Version 7.1      Revision Date: 02.10.2023      SDS Number: 10692714-00012      Date of last issue: 12.05.2023  
Date of first issue: 06.10.2015

---

Method : OECD Test Guideline 406  
Result : positive  
  
Assessment : Probability or evidence of skin sensitisation in humans

### **Pyrogallol:**

Test Type : Local lymph node assay (LLNA)  
Exposure routes : Skin contact  
Species : Mouse  
Result : positive  
  
Assessment : Probability or evidence of high skin sensitisation rate in humans

### **Germ cell mutagenicity**

Not classified based on available information.

### **Components:**

#### **Dimethyl ether:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative  
  
Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative  
  
Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative  
  
Genotoxicity in vivo : Test Type: Sex-linked recessive lethal test in *Drosophila melanogaster* (in vivo)  
Application Route: inhalation (gas)  
Result: negative

#### **Acetone:**

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test  
Result: negative  
  
Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative  
  
Test Type: Chromosome aberration test in vitro  
Result: negative  
  
Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Ingestion

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## RUST CONVERTER - 400 ML

Version 7.1      Revision Date: 02.10.2023      SDS Number: 10692714-00012      Date of last issue: 12.05.2023  
Date of first issue: 06.10.2015

---

Result: negative

### Butan-1-ol:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo  
cytogenetic assay)  
Species: Mouse  
Application Route: Ingestion  
Method: OECD Test Guideline 474  
Result: negative

### Xylene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Test Type: Chromosome aberration test in vitro  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Test Type: In vitro sister chromatid exchange assay in mam-  
malian cells  
Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)  
Species: Mouse  
Application Route: Skin contact  
Result: negative

### n-Butyl acetate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

### Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq 700$ ):

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: equivocal

Test Type: Chromosome aberration test in vitro  
Result: positive

Test Type: DNA damage and repair, unscheduled DNA syn-  
thesis in mammalian cells (in vitro)  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## RUST CONVERTER - 400 ML

Version 7.1      Revision Date: 02.10.2023      SDS Number: 10692714-00012      Date of last issue: 12.05.2023  
Date of first issue: 06.10.2015

---

cytogenetic assay)  
Species: Mouse  
Application Route: Ingestion  
Result: negative

### Pyrogallol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: positive

Test Type: Chromosome aberration test in vitro  
Result: positive

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo  
cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Result: positive

Germ cell mutagenicity- Assessment : Positive result(s) from in vivo non-mammalian somatic cell  
mutagenicity tests, supported by positive results from in vitro  
mutagenicity assays.

### Carcinogenicity

Not classified based on available information.

### Components:

#### Dimethyl ether:

Species : Rat  
Application Route : inhalation (vapour)  
Exposure time : 2 Years  
Result : negative

#### Acetone:

Species : Mouse  
Application Route : Skin contact  
Exposure time : 424 days  
Result : negative

#### Xylene:

Species : Rat  
Application Route : Ingestion  
Exposure time : 103 weeks  
Result : negative

### Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq 700$ ):

Species : Rat  
Application Route : Ingestion  
Exposure time : 24 Months

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## RUST CONVERTER - 400 ML

Version 7.1      Revision Date: 02.10.2023      SDS Number: 10692714-00012      Date of last issue: 12.05.2023  
Date of first issue: 06.10.2015

---

Method : OECD Test Guideline 453  
Result : negative

Species : Mouse  
Application Route : Skin contact  
Exposure time : 24 Months  
Method : OECD Test Guideline 453  
Result : negative

### Reproductive toxicity

Not classified based on available information.

### Components:

#### Dimethyl ether:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

#### Acetone:

Effects on fertility : Test Type: One-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

#### Butan-1-ol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapour)  
Method: OECD Test Guideline 416  
Result: negative  
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: Ingestion  
Result: negative

#### Xylene:



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## RUST CONVERTER - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 12.05.2023
7.1	02.10.2023	10692714-00012	Date of first issue: 06.10.2015

---

Effects on fertility : Test Type: One-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

### **n-Butyl acetate:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapour)  
Method: OECD Test Guideline 416  
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

### **Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq$ 700):**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 416  
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rabbit  
Application Route: Skin contact  
Result: negative

### **Pyrogallol:**

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: Ingestion  
Result: negative

### **STOT - single exposure**

May cause drowsiness or dizziness.

### **Components:**

#### **Dimethyl ether:**

Assessment : May cause drowsiness or dizziness.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## RUST CONVERTER - 400 ML

Version 7.1      Revision Date: 02.10.2023      SDS Number: 10692714-00012      Date of last issue: 12.05.2023  
Date of first issue: 06.10.2015

---

### Acetone:

Assessment : May cause drowsiness or dizziness.

### Butan-1-ol:

Assessment : May cause respiratory irritation., May cause drowsiness or dizziness.

### Xylene:

Assessment : May cause respiratory irritation.

### n-Butyl acetate:

Assessment : May cause drowsiness or dizziness.

### STOT - repeated exposure

Not classified based on available information.

### Components:

#### Xylene:

Exposure routes : inhalation (vapour)  
Target Organs : Auditory system  
Assessment : Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg/l/6h/d.

### Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq$ 700):

Assessment : No significant health effects observed in animals at concentrations of 200 mg/kg bw or less.

### Pyrogallol:

Assessment : No significant health effects observed in animals at concentrations of 200 mg/kg bw or less.

### Repeated dose toxicity

### Components:

#### Dimethyl ether:

Species : Rat  
NOAEL : 47,11 mg/l  
Application Route : inhalation (vapour)  
Exposure time : 2 yr

#### Acetone:

Species : Rat  
NOAEL : 900 mg/kg  
LOAEL : 1.700 mg/kg  
Application Route : Ingestion

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## RUST CONVERTER - 400 ML

Version 7.1      Revision Date: 02.10.2023      SDS Number: 10692714-00012      Date of last issue: 12.05.2023  
Date of first issue: 06.10.2015

---

Exposure time : 90 Days  
Species : Rat  
NOAEL : 45 mg/l  
Application Route : inhalation (vapour)  
Exposure time : 8 Weeks

### Butan-1-ol:

Species : Rat  
NOAEL : 125 mg/kg  
Application Route : Ingestion  
Exposure time : 13 Weeks

### Xylene:

Species : Rat  
LOAEL : > 0,2 - 1 mg/l  
Application Route : inhalation (vapour)  
Exposure time : 13 Weeks  
Remarks : Based on data from similar materials

Species : Rat  
LOAEL : 150 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days

### n-Butyl acetate:

Species : Rat  
NOAEL : 2,4 mg/l  
Application Route : inhalation (vapour)  
Exposure time : 90 Days

### Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq$ 700):

Species : Rat  
NOAEL : 50 mg/kg  
LOAEL : 250 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days  
Method : OECD Test Guideline 408

Species : Mouse  
NOAEL :  $\geq$  100 mg/kg  
Application Route : Skin contact  
Exposure time : 13 Weeks  
Method : OECD Test Guideline 411

### Pyrogallol:

Species : Rat  
LOAEL : 9,5 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## RUST CONVERTER - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 12.05.2023
7.1	02.10.2023	10692714-00012	Date of first issue: 06.10.2015

---

Application Route : Skin contact  
Exposure time : 3 Months

### Aspiration toxicity

Not classified based on available information.

### Components:

#### Acetone:

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

#### Butan-1-ol:

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

#### Xylene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

## 11.2 Information on other hazards

### Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

##### Dimethyl ether:

Toxicity to fish : LC50 (Poecilia reticulata (guppy)): > 4.100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 4.400 mg/l  
aquatic invertebrates Exposure time: 48 h

Toxicity to microorganisms : EC10 (Pseudomonas putida): > 1.600 mg/l

##### Acetone:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 5.540 mg/l  
Exposure time: 96 h

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## RUST CONVERTER - 400 ML

Version 7.1      Revision Date: 02.10.2023      SDS Number: 10692714-00012      Date of last issue: 12.05.2023  
Date of first issue: 06.10.2015

---

- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia pulex (Water flea)): 8.800 mg/l  
Exposure time: 48 h
- Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): 7.000 mg/l  
Exposure time: 96 h
- Toxicity to microorganisms : EC50 : 61.150 mg/l  
Exposure time: 30 min  
Method: ISO 8192
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: >= 79 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Method: OECD Test Guideline 211

### Butan-1-ol:

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 1.376 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1.328 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 225 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 201
- Toxicity to microorganisms : EC50 (Pseudomonas putida): 4.390 mg/l  
Exposure time: 17 h
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 4,1 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Method: OECD Test Guideline 211

### Xylene:

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 13,5 mg/l  
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1 - 10 mg/l  
Exposure time: 24 h  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials
- Toxicity to algae/aquatic plants : EC50 (Skeletonema costatum (marine diatom)): 10 mg/l  
Exposure time: 72 h
- Toxicity to microorganisms : NOEC : > 100 mg/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## RUST CONVERTER - 400 ML

Version 7.1      Revision Date: 02.10.2023      SDS Number: 10692714-00012      Date of last issue: 12.05.2023  
Date of first issue: 06.10.2015

---

Exposure time: 3 h  
Method: OECD Test Guideline 209  
Remarks: Based on data from similar materials

Toxicity to fish (Chronic toxicity) : NOEC: > 0,1 - < 1 mg/l  
Exposure time: 35 d  
Species: Danio rerio (zebra fish)  
Method: OECD Test Guideline 210  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EL10: > 1 - 10 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Method: OECD Test Guideline 211  
Remarks: Based on data from similar materials

### **n-Butyl acetate:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 18 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia sp. (water flea)): 44 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 397 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): 196 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l  
Exposure time: 40 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 23,2 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Method: OECD Test Guideline 211  
Remarks: Based on data from similar materials

### **Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700):**

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 1 - 10 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 203  
Remarks: Based on data from similar materials

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## RUST CONVERTER - 400 ML

Version 7.1      Revision Date: 02.10.2023      SDS Number: 10692714-00012      Date of last issue: 12.05.2023  
Date of first issue: 06.10.2015

---

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 1 - 10 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EL50 (Scenedesmus capricornutum (fresh water algae)): > 10 - 100 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Remarks: Based on data from similar materials

NOELR (Scenedesmus capricornutum (fresh water algae)): > 1 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Remarks: Based on data from similar materials

Toxicity to microorganisms : IC50 : > 100 mg/l  
Exposure time: 3 h  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: > 0,1 - 1 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Remarks: Based on data from similar materials

### Pyrogallol:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 10 - 35 mg/l  
Exposure time: 24 h  
Method: ISO 7346/1

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 4,33 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 1,53 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

Toxicity to microorganisms : NOEC (activated sludge): > 1.000 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## RUST CONVERTER - 400 ML

Version 7.1      Revision Date: 02.10.2023      SDS Number: 10692714-00012      Date of last issue: 12.05.2023  
Date of first issue: 06.10.2015

---

### 12.2 Persistence and degradability

#### Components:

##### **Dimethyl ether:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 5 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

##### **Acetone:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 91 %  
Exposure time: 28 d

##### **Butan-1-ol:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 92 %  
Exposure time: 20 d

##### **Xylene:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: > 70 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F  
Remarks: Based on data from similar materials

##### **n-Butyl acetate:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 83 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

##### **Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq 700$ ):**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 5 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

##### **Pyrogallol:**

Biodegradability : Result: Not readily biodegradable.

### 12.3 Bioaccumulative potential

#### Components:

##### **Dimethyl ether:**



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## RUST CONVERTER - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 12.05.2023
7.1	02.10.2023	10692714-00012	Date of first issue: 06.10.2015

---

Partition coefficient: n-octanol/water : log Pow: 0,2

### Acetone:

Partition coefficient: n-octanol/water : log Pow: -0,27 - -0,23

### Butan-1-ol:

Partition coefficient: n-octanol/water : log Pow: 1

### Xylene:

Partition coefficient: n-octanol/water : log Pow: 3,16  
Remarks: Calculation

### n-Butyl acetate:

Partition coefficient: n-octanol/water : log Pow: 2,3

### Reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq 700$ ):

Partition coefficient: n-octanol/water : log Pow: 3,5

### Pyrogallol:

Partition coefficient: n-octanol/water : log Pow: -0,47  
Method: Regulation (EC) No. 440/2008, Annex, A.8

## 12.4 Mobility in soil

No data available

## 12.5 Results of PBT and vPvB assessment

### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## 12.6 Endocrine disrupting properties

### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## RUST CONVERTER - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 12.05.2023
7.1	02.10.2023	10692714-00012	Date of first issue: 06.10.2015

---

### 12.7 Other adverse effects

No data available

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

- Product : Dispose of in accordance with local regulations.  
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.  
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.  
Do not dispose of waste into sewer.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Empty containers retain residue and can be dangerous.  
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.  
If not otherwise specified: Dispose of as unused product.  
Please ensure aerosol cans are sprayed completely empty (including propellant)
- Waste Code : The following Waste Codes are only suggestions:
- used product  
16 05 04, gases in pressure containers (including halons)  
containing hazardous substances
  - unused product  
16 05 04, gases in pressure containers (including halons)  
containing hazardous substances
  - uncleaned packagings  
15 01 10, packaging containing residues of or contaminated by hazardous substances
- Acc. Packaging Act properly emptied packaging:  
Properly emptied, non-contaminated packaging of non-hazardous products can be supplied to a system for the collection of sales packaging.
- 

## SECTION 14: Transport information

### 14.1 UN number or ID number

- ADN : UN 1950  
ADR : UN 1950  
RID : UN 1950

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## RUST CONVERTER - 400 ML

Version 7.1      Revision Date: 02.10.2023      SDS Number: 10692714-00012      Date of last issue: 12.05.2023  
Date of first issue: 06.10.2015

---

**IMDG** : UN 1950

**IATA** : UN 1950

### 14.2 UN proper shipping name

**ADN** : AEROSOLS

**ADR** : AEROSOLS

**RID** : AEROSOLS

**IMDG** : AEROSOLS

**IATA** : Aerosols, flammable

### 14.3 Transport hazard class(es)

	Class	Subsidiary risks
<b>ADN</b>	: 2	2.1
<b>ADR</b>	: 2	2.1
<b>RID</b>	: 2	2.1
<b>IMDG</b>	: 2.1	
<b>IATA</b>	: 2.1	

### 14.4 Packing group

**ADN**  
Packing group : Not assigned by regulation  
Classification Code : 5F  
Labels : 2.1

**ADR**  
Packing group : Not assigned by regulation  
Classification Code : 5F  
Labels : 2.1  
Tunnel restriction code : (D)

**RID**  
Packing group : Not assigned by regulation  
Classification Code : 5F  
Hazard Identification Number : 23  
Labels : 2.1

**IMDG**  
Packing group : Not assigned by regulation  
Labels : 2.1  
EmS Code : F-D, S-U

**IATA (Cargo)**  
Packing instruction (cargo aircraft) : 203  
Packing instruction (LQ) : Y203  
Packing group : Not assigned by regulation  
Labels : Flammable Gas

**IATA (Passenger)**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## RUST CONVERTER - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 12.05.2023
7.1	02.10.2023	10692714-00012	Date of first issue: 06.10.2015

---

Packing instruction (passenger aircraft) : 203  
Packing instruction (LQ) : Y203  
Packing group : Not assigned by regulation  
Labels : Flammable Gas

### 14.5 Environmental hazards

#### ADN

Environmentally hazardous : no

#### ADR

Environmentally hazardous : no

#### RID

Environmentally hazardous : no

#### IMDG

Marine pollutant : no

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:  
Number on list 75  
If you intend to use this product as tattoo ink, please contact your vendor.

Substance(s) or mixture(s) are listed here according to their appearance in the regulation, irrespective of their use/purpose or the conditions of the restriction. Please refer to the conditions in corresponding Regulation to determine whether an entry is applicable to the placing on the market or not.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## RUST CONVERTER - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 12.05.2023
7.1	02.10.2023	10692714-00012	Date of first issue: 06.10.2015

---

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point. Acetone (ANNEX II)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

	Quantity 1	Quantity 2
P3a	FLAMMABLE AEROSOLS 150 t	500 t

Water hazard class (Germany) : WGK 2 obviously hazardous to water  
Classification according to AwSV, Annex 1 (5.2)

TA Luft List (Germany) : 5.2.1: Total dust:  
Not applicable  
5.2.2: Inorganic substances in powdered form:  
Not applicable  
5.2.4: Inorganic substances in gaseous form:  
Not applicable  
5.2.5: Organic Substances:  
Not applicable  
5.2.7.1.1: Carcinogenic substance:  
Not applicable  
5.2.7.1.1: Quartz fine dust PM4:  
Not applicable  
5.2.7.1.1: Formaldehyde:  
Not applicable  
5.2.7.1.1: fibres:  
Not applicable  
5.2.7.1.2: Germ cell mutagens:  
Not applicable  
5.2.7.1.3: Substances toxic to reproduction:  
Not applicable  
5.2.7.2: Poorly degradable, easily enrichable and highly toxic organic substances:  
Not applicable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## RUST CONVERTER - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 12.05.2023
7.1	02.10.2023	10692714-00012	Date of first issue: 06.10.2015

---

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 97 %, 754,66 g/l  
Remarks: VOC content excluding water

### Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

### 15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

---

## SECTION 16: Other information

Other information : Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

### Full text of H-Statements

H220 : Extremely flammable gas.  
H225 : Highly flammable liquid and vapour.  
H226 : Flammable liquid and vapour.  
H280 : Contains gas under pressure; may explode if heated.  
H302 : Harmful if swallowed.  
H304 : May be fatal if swallowed and enters airways.  
H312 : Harmful in contact with skin.  
H315 : Causes skin irritation.  
H317 : May cause an allergic skin reaction.  
H318 : Causes serious eye damage.  
H319 : Causes serious eye irritation.  
H332 : Harmful if inhaled.  
H335 : May cause respiratory irritation.  
H336 : May cause drowsiness or dizziness.  
H341 : Suspected of causing genetic defects.  
H373 : May cause damage to organs through prolonged or repeated exposure.  
H411 : Toxic to aquatic life with long lasting effects.  
H412 : Harmful to aquatic life with long lasting effects.  
EUH066 : Repeated exposure may cause skin dryness or cracking.

### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Asp. Tox. : Aspiration hazard  
Eye Dam. : Serious eye damage  
Eye Irrit. : Eye irritation  
Flam. Gas : Flammable gases  
Flam. Liq. : Flammable liquids

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## RUST CONVERTER - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 12.05.2023
7.1	02.10.2023	10692714-00012	Date of first issue: 06.10.2015

Muta.	:	Germ cell mutagenicity
Press. Gas	:	Gases under pressure
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2004/37/EC	:	Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work
2006/15/EC	:	Europe. Indicative occupational exposure limit values
2019/1831/EU	:	Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
DE TRGS 900	:	Germany. TRGS 900 - Occupational exposure limit values.
TRGS 903	:	TRGS 903 - Biological limit values
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
2004/37/EC / STEL	:	Short term exposure limit
2004/37/EC / TWA	:	Long term exposure limit
2006/15/EC / TWA	:	Limit Value - eight hours
2019/1831/EU / TWA	:	Limit Value - eight hours
2019/1831/EU / STEL	:	Short term exposure limit
DE TRGS 900 / AGW	:	Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet;

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## RUST CONVERTER - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 12.05.2023
7.1	02.10.2023	10692714-00012	Date of first issue: 06.10.2015

SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

### Classification of the mixture:

Aerosol 1	H222, H229
Acute Tox. 4	H302
Skin Sens. 1	H317
Skin Irrit. 2	H315
Eye Dam. 1	H318
STOT SE 3	H336
Aquatic Chronic 3	H412

### Classification procedure:

Based on product data or assessment
Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN