

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ALU-SILVER SPRAY HIGHGLOSS PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 18.07.2023
7.2	18.10.2023	10709965-00013	Date of first issue: 11.06.2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name	:	ALU-SILVER SPRAY HIGHGLOSS PERFECT - 400 ML
Product code	:	0893114119
Unique Formula Identifier (UFI)	:	5CH7-U0T2-Q003-RC9M

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- stance/Mixture	:	Solvent-borne coatings Professional use product
Recommended restrictions on use	:	Not applicable

1.3 Details of the supplier of the safety data sheet

Company	:	Adolf Wuerth GmbH & Co. KG Reinhold-Würth-Str. 12-17 74653 Künzelsau
Telephone	:	+49 794015 0
Telefax	:	+49 794015 10 00
E-mail address of person responsible for the SDS	:	isi@wuerth.com

1.4 Emergency telephone number

+49 (0)6132 – 84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1	H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated.
Eye irritation, Category 2	H319: Causes serious eye irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ALU-SILVER SPRAY HIGHGLOSS PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 18.07.2023
7.2	18.10.2023	10709965-00013	Date of first issue: 11.06.2010

Specific target organ toxicity - single exposure, Category 3

H336: May cause drowsiness or dizziness.

Long-term (chronic) aquatic hazard, Category 3

H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Supplemental Hazard Statements : EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P261 Avoid breathing spray.
P273 Avoid release to the environment.

Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

Acetone
n-Butyl acetate
Hydrocarbons, C9, aromatics

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ALU-SILVER SPRAY HIGHGLOSS PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 18.07.2023
7.2	18.10.2023	10709965-00013	Date of first issue: 11.06.2010

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

May displace oxygen and cause rapid suffocation.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Acetone	67-64-1 200-662-2 606-001-00-8 01-2119471330-49	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066	>= 20 - < 30
n-Butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 EUH066	>= 10 - < 20
Hydrocarbons, C9, aromatics	64742-95-6 01-2119455851-35	Flam. Liq. 3; H226 STOT SE 3; H336 STOT SE 3; H335 Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066	>= 10 - < 20

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- | | |
|----------------------------|---|
| General advice | : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice. |
| Protection of first-aiders | : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8). |
| If inhaled | : If inhaled, remove to fresh air.
If not breathing, give artificial respiration.
If breathing is difficult, give oxygen. |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ALU-SILVER SPRAY HIGHGLOSS PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 18.07.2023
7.2	18.10.2023	10709965-00013	Date of first issue: 11.06.2010

Get medical attention immediately.

In case of skin contact : In case of contact, immediately flush skin with plenty of water.
Get medical attention if symptoms occur.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water
for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention.

If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

Risks : Gas reduces oxygen available for breathing.

Causes serious eye irritation.
May cause drowsiness or dizziness.
Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Flash back possible over considerable distance.
Vapours may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
If the temperature rises there is danger of the vessels bursting
due to the high vapor pressure.

Hazardous combustion products : Carbon oxides
Metal oxides

5.3 Advice for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ALU-SILVER SPRAY HIGHGLOSS PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 18.07.2023
7.2	18.10.2023	10709965-00013	Date of first issue: 11.06.2010

for firefighters

Use personal protective equipment.

Specific extinguishing methods

: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.
Remove all sources of ignition.
Ventilate the area.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapours/mists with a water spray jet.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ALU-SILVER SPRAY HIGHGLOSS PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 18.07.2023
7.2	18.10.2023	10709965-00013	Date of first issue: 11.06.2010

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- | | | |
|-------------------------|---|---|
| Technical measures | : | See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section. |
| Local/Total ventilation | : | If sufficient ventilation is unavailable, use with local exhaust ventilation.
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation. |
| Advice on safe handling | : | Do not get on skin or clothing.
Avoid breathing spray.
Do not swallow.
Do not get in eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.
Do not spray on an open flame or other ignition source. |
| Hygiene measures | : | If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use. |

7.2 Conditions for safe storage, including any incompatibilities

- | | | |
|---|---|--|
| Requirements for storage areas and containers | : | Store locked up. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Do not pierce or burn, even after use. Keep cool. Protect from sunlight. |
| Advice on common storage | : | Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Oxidizing agents
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures, which in contact with water, emit flammable gases
Explosives
Gases |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ALU-SILVER SPRAY HIGHGLOSS PERFECT - 400 ML

Version 7.2 Revision Date: 18.10.2023 SDS Number: 10709965-00013 Date of last issue: 18.07.2023
Date of first issue: 11.06.2010

Storage class (TRGS 510) : 2B

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Acetone	67-64-1	TWA	500 ppm 1.210 mg/m ³	2000/39/EC
	Further information: Indicative			
		AGW	500 ppm 1.200 mg/m ³	DE TRGS 900
	Peak-limit: excursion factor (category): 2;(I)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
Propane	74-98-6	AGW	1.000 ppm 1.800 mg/m ³	DE TRGS 900
	Peak-limit: excursion factor (category): 4;(II)			
Butane	106-97-8	AGW	1.000 ppm 2.400 mg/m ³	DE TRGS 900
	Peak-limit: excursion factor (category): 4;(II)			
n-Butyl acetate	123-86-4	STEL	150 ppm 723 mg/m ³	2019/1831/EU
	Further information: Indicative			
		TWA	50 ppm 241 mg/m ³	2019/1831/EU
	Further information: Indicative			
		AGW	62 ppm 300 mg/m ³	DE TRGS 900
	Peak-limit: excursion factor (category): 2;(I)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
Hydrocarbons, C9, aromatics	64742-95-6	AGW	50 mg/m ³	DE TRGS 900
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: Group exposure limit for hydrocarbon solvent mixtures			
Aluminium	7429-90-5	AGW (Inhalable fraction)	10 mg/m ³	DE TRGS 900
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		AGW (Alveolate)	1,25 mg/m ³	DE TRGS

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ALU-SILVER SPRAY HIGHGLOSS PERFECT - 400 ML

Version 7.2 Revision Date: 18.10.2023 SDS Number: 10709965-00013 Date of last issue: 18.07.2023
Date of first issue: 11.06.2010

		fraction)		900
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Acetone	67-64-1	Acetone: 80 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903
Aluminium	7429-90-5	Aluminium: 50 µg/g creatinine (Urine)	In case of long-term exposure: after more than one shift	TRGS 903

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Acetone	Workers	Inhalation	Long-term systemic effects	1210 mg/m ³
	Workers	Inhalation	Acute local effects	2420 mg/m ³
	Workers	Skin contact	Long-term systemic effects	186 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	200 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	62 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	62 mg/kg bw/day
n-Butyl acetate	Workers	Inhalation	Acute systemic effects	600 mg/m ³
	Workers	Inhalation	Acute local effects	600 mg/m ³
	Workers	Inhalation	Long-term systemic effects	300 mg/m ³
	Workers	Inhalation	Long-term local effects	300 mg/m ³
	Consumers	Inhalation	Acute systemic effects	300 mg/m ³
	Consumers	Inhalation	Acute local effects	300 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	35,7 mg/m ³
	Consumers	Inhalation	Long-term local effects	35,7 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	11 mg/kg bw/day
	Consumers	Skin contact	Acute systemic effects	11 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	6 mg/kg bw/day
	Consumers	Skin contact	Acute systemic effects	6 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ALU-SILVER SPRAY HIGHGLOSS PERFECT - 400 ML

Version 7.2 Revision Date: 18.10.2023 SDS Number: 10709965-00013 Date of last issue: 18.07.2023
Date of first issue: 11.06.2010

			fects	bw/day
	Consumers	Ingestion	Long-term systemic effects	2 mg/kg bw/day
	Consumers	Ingestion	Acute systemic effects	2 mg/kg bw/day
Aluminium	Workers	Inhalation	Long-term local effects	3,72 mg/m ³
	Consumers	Ingestion	Long-term systemic effects	3,95 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Acetone	Fresh water	10,6 mg/l
	Marine water	1,06 mg/l
	Intermittent use/release	21 mg/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	30,4 mg/kg dry weight (d.w.)
	Marine sediment	3,04 mg/kg dry weight (d.w.)
	Soil	29,5 mg/kg dry weight (d.w.)
n-Butyl acetate	Fresh water	0,18 mg/l
	Marine water	0,018 mg/l
	Sewage treatment plant	35,6 mg/l
	Fresh water sediment	0,981 mg/kg dry weight (d.w.)
	Marine sediment	0,098 mg/kg dry weight (d.w.)
	Soil	0,09 mg/kg dry weight (d.w.)
Aluminium	Sewage treatment plant	20 mg/l

8.2 Exposure controls

Engineering measures

Minimize workplace exposure concentrations.

If sufficient ventilation is unavailable, use with local exhaust ventilation.

If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Personal protective equipment

Eye/face protection : Wear the following personal protective equipment:
Safety goggles
Equipment should conform to DIN EN 166

Hand protection

Material : butyl-rubber
Break through time : > 480 min
Glove thickness : 0,7 mm

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ALU-SILVER SPRAY HIGHGLOSS PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 18.07.2023
7.2	18.10.2023	10709965-00013	Date of first issue: 11.06.2010

Remarks	: Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.
Skin and body protection	: Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential. Wear the following personal protective equipment: If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing. Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
Respiratory protection	: If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection. Equipment should conform to DIN EN 137
Filter type	: Self-contained breathing apparatus

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	: aerosol
Propellant	: Propane, Butane
Colour	: silver, grey
Odour	: characteristic
Odour Threshold	: No data available
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: Not applicable
Flammability (solid, gas)	: Extremely flammable aerosol.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ALU-SILVER SPRAY HIGHGLOSS PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 18.07.2023
7.2	18.10.2023	10709965-00013	Date of first issue: 11.06.2010

Upper explosion limit / Upper
flammability limit : 13,0 %(V)

Lower explosion limit / Lower
flammability limit : 0,7 %(V)

Flash point : Not applicable

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : Solvent mixture; pH value determination not possible, no
aqueous solution

Viscosity
Viscosity, kinematic : Not applicable

Solubility(ies)
Water solubility : immiscible

Partition coefficient: n-
octanol/water : Not applicable

Vapour pressure : Not applicable

Relative density : No data available

Relative vapour density : Not applicable

Particle characteristics
Particle size : Not applicable

9.2 Other information

Explosives : Not explosive

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ALU-SILVER SPRAY HIGHGLOSS PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 18.07.2023
7.2	18.10.2023	10709965-00013	Date of first issue: 11.06.2010

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Evaporation rate : Not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Extremely flammable aerosol.
Vapours may form explosive mixture with air.
If the temperature rises there is danger of the vessels bursting
due to the high vapor pressure.
Can react with strong oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:

Acetone:

Acute oral toxicity : LD50 (Rat): 5.800 mg/kg

Acute inhalation toxicity : LC50 (Rat): 76 mg/l
Exposure time: 4 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ALU-SILVER SPRAY HIGHGLOSS PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 18.07.2023
7.2	18.10.2023	10709965-00013	Date of first issue: 11.06.2010

Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 7.426 mg/kg

n-Butyl acetate:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 21,1 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Hydrocarbons, C9, aromatics:

Acute oral toxicity : LD50 (Rat, female): 3.492 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 6,193 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 3.160 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Components:

Acetone:

Assessment : Repeated exposure may cause skin dryness or cracking.

n-Butyl acetate:

Species : Rabbit
Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C9, aromatics:

Assessment : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Causes serious eye irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ALU-SILVER SPRAY HIGHGLOSS PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 18.07.2023
7.2	18.10.2023	10709965-00013	Date of first issue: 11.06.2010

Components:

Acetone:

Species	:	Rabbit
Method	:	OECD Test Guideline 405
Result	:	Irritation to eyes, reversing within 21 days

n-Butyl acetate:

Species	:	Rabbit
Method	:	OECD Test Guideline 405
Result	:	No eye irritation

Hydrocarbons, C9, aromatics:

Species	:	Rabbit
Result	:	No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Acetone:

Test Type	:	Maximisation Test
Exposure routes	:	Skin contact
Species	:	Guinea pig
Result	:	negative

n-Butyl acetate:

Test Type	:	Maximisation Test
Exposure routes	:	Skin contact
Species	:	Guinea pig
Result	:	negative

Hydrocarbons, C9, aromatics:

Test Type	:	Maximisation Test
Exposure routes	:	Skin contact
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	negative

Germ cell mutagenicity

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ALU-SILVER SPRAY HIGHGLOSS PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 18.07.2023
7.2	18.10.2023	10709965-00013	Date of first issue: 11.06.2010

Components:

Acetone:

Genotoxicity in vitro	:	Test Type: In vitro mammalian cell gene mutation test Result: negative
		Test Type: Bacterial reverse mutation assay (AMES) Result: negative
		Test Type: Chromosome aberration test in vitro Result: negative
Genotoxicity in vivo	:	Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Ingestion Result: negative

n-Butyl acetate:

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES) Result: negative
-----------------------	---	--

Hydrocarbons, C9, aromatics:

Genotoxicity in vitro	:	Test Type: Chromosome aberration test in vitro Result: negative
Genotoxicity in vivo	:	Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis) Species: Rat Application Route: inhalation (vapour) Result: negative
Germ cell mutagenicity- Assessment	:	Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

Carcinogenicity

Not classified based on available information.

Components:

Acetone:

Species	:	Mouse
Application Route	:	Skin contact
Exposure time	:	424 days
Result	:	negative

Hydrocarbons, C9, aromatics:

Carcinogenicity - Assessment	:	Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)
------------------------------	---	--

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ALU-SILVER SPRAY HIGHGLOSS PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 18.07.2023
7.2	18.10.2023	10709965-00013	Date of first issue: 11.06.2010

Reproductive toxicity

Not classified based on available information.

Components:

Acetone:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Result: negative

n-Butyl acetate:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapour)
Method: OECD Test Guideline 416
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Result: negative

Hydrocarbons, C9, aromatics:

Effects on fertility : Test Type: Three-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapour)
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Mouse
Application Route: inhalation (vapour)
Result: negative

STOT - single exposure

May cause drowsiness or dizziness.

Components:

Acetone:

Assessment : May cause drowsiness or dizziness.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ALU-SILVER SPRAY HIGHGLOSS PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 18.07.2023
7.2	18.10.2023	10709965-00013	Date of first issue: 11.06.2010

n-Butyl acetate:

Assessment : May cause drowsiness or dizziness.

Hydrocarbons, C9, aromatics:

Assessment : May cause drowsiness or dizziness.

Assessment : May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Acetone:

Species : Rat
NOAEL : 900 mg/kg
LOAEL : 1.700 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Species : Rat
NOAEL : 45 mg/l
Application Route : inhalation (vapour)
Exposure time : 8 Weeks

n-Butyl acetate:

Species : Rat
NOAEL : 2,4 mg/l
Application Route : inhalation (vapour)
Exposure time : 90 Days

Hydrocarbons, C9, aromatics:

Species : Rat, female
NOAEL : 900 mg/m³
Application Route : inhalation (vapour)
Exposure time : 12 Months
Remarks : Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

Components:

Acetone:

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ALU-SILVER SPRAY HIGHGLOSS PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 18.07.2023
7.2	18.10.2023	10709965-00013	Date of first issue: 11.06.2010

Hydrocarbons, C9, aromatics:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Acetone:

Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainbow trout)): 5.540 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia pulex (Water flea)): 8.800 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	: NOEC (Pseudokirchneriella subcapitata (green algae)): 7.000 mg/l Exposure time: 96 h
Toxicity to microorganisms	: EC50 : 61.150 mg/l Exposure time: 30 min Method: ISO 8192
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC: >= 79 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

n-Butyl acetate:

Toxicity to fish	: LC50 (Pimephales promelas (fathead minnow)): 18 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia sp. (water flea)): 44 mg/l Exposure time: 48 h
Toxicity to algae/aquatic	: ErC50 (Pseudokirchneriella subcapitata (green algae)): 397

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ALU-SILVER SPRAY HIGHGLOSS PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 18.07.2023
7.2	18.10.2023	10709965-00013	Date of first issue: 11.06.2010

plants	mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: Based on data from similar materials NOEC (Pseudokirchneriella subcapitata (green algae)): 196 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: Based on data from similar materials
Toxicity to microorganisms	: IC50 (Tetrahymena pyriformis): 356 mg/l Exposure time: 40 h
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC: 23,2 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211 Remarks: Based on data from similar materials

Hydrocarbons, C9, aromatics:

Toxicity to fish	: LL50 (Oncorhynchus mykiss (rainbow trout)): 9,2 mg/l Exposure time: 96 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Daphnia magna (Water flea)): 3,2 mg/l Exposure time: 48 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	: EL50 (Pseudokirchneriella subcapitata (green algae)): 7,9 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 201 NOELR (Pseudokirchneriella subcapitata (green algae)): 0,22 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 201
Toxicity to microorganisms	: EC50 : > 99 mg/l Exposure time: 10 min

12.2 Persistence and degradability

Components:

Acetone:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ALU-SILVER SPRAY HIGHGLOSS PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 18.07.2023
7.2	18.10.2023	10709965-00013	Date of first issue: 11.06.2010

Biodegradability : Result: Readily biodegradable.
Biodegradation: 91 %
Exposure time: 28 d

n-Butyl acetate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 83 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Hydrocarbons, C9, aromatics:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 78 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

12.3 Bioaccumulative potential

Components:

Acetone:

Partition coefficient: n- : log Pow: -0,27 - -0,23
octanol/water

n-Butyl acetate:

Partition coefficient: n- : log Pow: 2,3
octanol/water

Hydrocarbons, C9, aromatics:

Partition coefficient: n- : log Pow: 3,7 - 4,5
octanol/water

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ALU-SILVER SPRAY HIGHGLOSS PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 18.07.2023
7.2	18.10.2023	10709965-00013	Date of first issue: 11.06.2010

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- | | | |
|------------------------|---|--|
| Product | : | Dispose of in accordance with local regulations.
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.
Do not dispose of waste into sewer. |
| Contaminated packaging | : | Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.
Please ensure aerosol cans are sprayed completely empty (including propellant) |
| Waste Code | : | The following Waste Codes are only suggestions:

unused product
16 05 04, gases in pressure containers (including halons) containing hazardous substances

used product
16 05 04, gases in pressure containers (including halons) containing hazardous substances

uncleaned packagings
15 01 10, packaging containing residues of or contaminated by hazardous substances

Acc. Packaging Act properly emptied packaging:
Properly emptied, non-contaminated packaging of non-hazardous products can be supplied to a system for the collection of sales packaging. |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ALU-SILVER SPRAY HIGHGLOSS PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 18.07.2023
7.2	18.10.2023	10709965-00013	Date of first issue: 11.06.2010

SECTION 14: Transport information

14.1 UN number or ID number

ADN	:	UN 1950
ADR	:	UN 1950
RID	:	UN 1950
IMDG	:	UN 1950
IATA	:	UN 1950

14.2 UN proper shipping name

ADN	:	AEROSOLS
ADR	:	AEROSOLS
RID	:	AEROSOLS
IMDG	:	AEROSOLS
IATA	:	Aerosols, flammable

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	: 2	2.1
ADR	: 2	2.1
RID	: 2	2.1
IMDG	: 2.1	
IATA	: 2.1	

14.4 Packing group

ADN	
Packing group	: Not assigned by regulation
Classification Code	: 5F
Labels	: 2.1

ADR	
Packing group	: Not assigned by regulation
Classification Code	: 5F
Labels	: 2.1
Tunnel restriction code	: (D)

RID	
Packing group	: Not assigned by regulation
Classification Code	: 5F
Hazard Identification Number	: 23
Labels	: 2.1

IMDG	
Packing group	: Not assigned by regulation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ALU-SILVER SPRAY HIGHGLOSS PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 18.07.2023
7.2	18.10.2023	10709965-00013	Date of first issue: 11.06.2010

Labels : 2.1
EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

IATA (Passenger)

Packing instruction (passenger aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 75
If you intend to use this product as tattoo ink, please contact your vendor.

Substance(s) or mixture(s) are listed here according to their appearance in the regulation, irrespective of their

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ALU-SILVER SPRAY HIGHGLOSS PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 18.07.2023
7.2	18.10.2023	10709965-00013	Date of first issue: 11.06.2010

use/purpose or the conditions of the restriction. Please refer to the conditions in corresponding Regulation to determine whether an entry is applicable to the placing on the market or not.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point. Acetone (ANNEX II)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
P3a	FLAMMABLE AEROSOLS	150 t	500 t
18	Liquefied flammable gases (including LPG) and natural gas	50 t	200 t
34	Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams), (d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the	2.500 t	25.000 t

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ALU-SILVER SPRAY HIGHGLOSS PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 18.07.2023
7.2	18.10.2023	10709965-00013	Date of first issue: 11.06.2010

- products referred to in
points (a) to (d)
- Water hazard class (Germany) : WGK 2 obviously hazardous to water
Classification according to AwSV, Annex 1 (5.2)
- TA Luft List (Germany) : 5.2.1: Total dust:
Not applicable
5.2.2: Inorganic substances in powdered form:
Not applicable
5.2.4: Inorganic substances in gaseous form:
Not applicable
5.2.5: Organic Substances:
Not applicable
5.2.7.1.1: Carcinogenic substance:
Not applicable
5.2.7.1.1: Quartz fine dust PM4:
Not applicable
5.2.7.1.1: Formaldehyde:
Not applicable
5.2.7.1.1: fibres:
Not applicable
5.2.7.1.2: Germ cell mutagens:
Not applicable
5.2.7.1.3: Substances toxic to reproduction:
Not applicable
5.2.7.2: Poorly degradable, easily enrichable and highly toxic
organic substances:
Not applicable
- Volatile organic compounds : Directive 2004/42/EC
VOC content in g/l: 679,4 g/l
Product sub-category: Special finishes
Coatings: All types
VOC limit level 1 (2007): 840 g/l
- Directive 2010/75/EU of 24 November 2010 on industrial
emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 97,2 %, 679,4 g/l
Remarks: VOC content excluding water

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national
regulations, where applicable.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ALU-SILVER SPRAY HIGHGLOSS PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 18.07.2023
7.2	18.10.2023	10709965-00013	Date of first issue: 11.06.2010

SECTION 16: Other information

Other information : Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Full text of H-Statements

H225	: Highly flammable liquid and vapour.
H226	: Flammable liquid and vapour.
H304	: May be fatal if swallowed and enters airways.
H319	: Causes serious eye irritation.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H411	: Toxic to aquatic life with long lasting effects.
EUH066	: Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2019/1831/EU	: Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
DE TRGS 900	: Germany. TRGS 900 - Occupational exposure limit values.
TRGS 903	: TRGS 903 - Biological limit values
2000/39/EC / TWA	: Limit Value - eight hours
2019/1831/EU / TWA	: Limit Value - eight hours
2019/1831/EU / STEL	: Short term exposure limit
DE TRGS 900 / AGW	: Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test popula-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



ALU-SILVER SPRAY HIGHGLOSS PERFECT - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 18.07.2023
7.2	18.10.2023	10709965-00013	Date of first issue: 11.06.2010

tion; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Classification of the mixture:

Aerosol 1	H222, H229
Eye Irrit. 2	H319
STOT SE 3	H336
Aquatic Chronic 3	H412

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN