

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## LACQUER SPRAY SATIN GLOSS PURE WHITE RAL 9010 - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 08.06.2023
14.1	12.09.2023	10639731-00014	Date of first issue: 11.06.2010

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : LACQUER SPRAY SATIN GLOSS PURE WHITE RAL 9010 - 400 ML

Product code : 0893349010

Unique Formula Identifier (UFI) : 4JGD-V0F1-S00W-SFVG

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Paints  
Professional use product

Recommended restrictions on use : Not applicable

#### 1.3 Details of the supplier of the safety data sheet

Company : Adolf Wuerth GmbH & Co. KG  
Reinhold-Würth-Str. 12-17  
74653 Künzelsau

Telephone : +49 794015 0

Telefax : +49 794015 10 00

E-mail address of person responsible for the SDS : isi@wuerth.com

#### 1.4 Emergency telephone number

+49 (0)6132 – 84463

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1	H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated.
Eye irritation, Category 2	H319: Causes serious eye irritation.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## LACQUER SPRAY SATIN GLOSS PURE WHITE RAL 9010 - 400 ML

Version 14.1	Revision Date: 12.09.2023	SDS Number: 10639731-00014	Date of last issue: 08.06.2023 Date of first issue: 11.06.2010
-----------------	------------------------------	-------------------------------	---

Specific target organ toxicity - single exposure, Category 3      H336: May cause drowsiness or dizziness.

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

Supplemental Hazard Statements : EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P261 Avoid breathing spray.  
P271 Use only outdoors or in a well-ventilated area.

#### Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

#### Hazardous components which must be listed on the label:

Acetone  
n-Butyl acetate  
2-Methoxy-1-methylethyl acetate  
Butanone

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## LACQUER SPRAY SATIN GLOSS PURE WHITE RAL 9010 - 400 ML

Version 14.1      Revision Date: 12.09.2023      SDS Number: 10639731-00014      Date of last issue: 08.06.2023  
Date of first issue: 11.06.2010

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

##### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Acetone	67-64-1 200-662-2 606-001-00-8 01-2119471330-49	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066	>= 30 - < 50
n-Butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 EUH066	>= 1 - < 10
2-Methoxy-1-methylethyl acetate	108-65-6 203-603-9 607-195-00-7 01-2119475791-29	Flam. Liq. 3; H226 STOT SE 3; H336	>= 1 - < 10
Xylene	1330-20-7 215-535-7 601-022-00-9 01-2119488216-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 STOT RE 2; H373 (Auditory system) Asp. Tox. 1; H304 Aquatic Chronic 3; H412  Acute toxicity estimate  Acute inhalation toxicity (vapour): 11 mg/l Acute dermal toxicity: 1.100 mg/kg	>= 2,5 - < 10
Ethanol	64-17-5 200-578-6 603-002-00-5 01-2119457610-43	Flam. Liq. 2; H225 Eye Irrit. 2; H319  specific concentration limit Eye Irrit. 2; H319	>= 1 - < 10

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## LACQUER SPRAY SATIN GLOSS PURE WHITE RAL 9010 - 400 ML

Version 14.1      Revision Date: 12.09.2023      SDS Number: 10639731-00014      Date of last issue: 08.06.2023  
Date of first issue: 11.06.2010

		>= 50 %	
Butanone	78-93-3 201-159-0 606-002-00-3 01-2119457290-43	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066	>= 1 - < 10
Butyl glycollate	7397-62-8 230-991-7 01-2119514685-36	Eye Dam. 1; H318 Repr. 2; H361	>= 0,1 - < 1

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- If inhaled : If inhaled, remove to fresh air.  
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.  
Remove contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
If easy to do, remove contact lens, if worn.  
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention.  
Rinse mouth thoroughly with water.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes serious eye irritation.  
May cause drowsiness or dizziness.  
Repeated exposure may cause skin dryness or cracking.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## LACQUER SPRAY SATIN GLOSS PURE WHITE RAL 9010 - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 08.06.2023
14.1	12.09.2023	10639731-00014	Date of first issue: 11.06.2010

---

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Flash back possible over considerable distance.  
Vapours may form explosive mixtures with air.  
Exposure to combustion products may be a hazard to health.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

Hazardous combustion products : Carbon oxides  
Nitrogen oxides (NO<sub>x</sub>)

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.  
Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

### 6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## LACQUER SPRAY SATIN GLOSS PURE WHITE RAL 9010 - 400 ML

Version 14.1	Revision Date: 12.09.2023	SDS Number: 10639731-00014	Date of last issue: 08.06.2023 Date of first issue: 11.06.2010
-----------------	------------------------------	-------------------------------	---

---

Prevent spreading over a wide area (e.g. by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapours/mists with a water spray jet.  
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.  
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Advice on safe handling : Do not get on skin or clothing.  
Do not breathe spray.  
Do not swallow.  
Do not get in eyes.  
Wash skin thoroughly after handling.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Take precautionary measures against static discharges.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## LACQUER SPRAY SATIN GLOSS PURE WHITE RAL 9010 - 400 ML

Version 14.1      Revision Date: 12.09.2023      SDS Number: 10639731-00014      Date of last issue: 08.06.2023  
Date of first issue: 11.06.2010

Take care to prevent spills, waste and minimize release to the environment.  
Do not spray on an open flame or other ignition source.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store locked up. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Do not pierce or burn, even after use. Keep cool. Protect from sunlight.

Advice on common storage : Do not store with the following product types:  
Self-reactive substances and mixtures  
Organic peroxides  
Oxidizing agents  
Flammable solids  
Pyrophoric liquids  
Pyrophoric solids  
Self-heating substances and mixtures  
Substances and mixtures, which in contact with water, emit flammable gases  
Explosives  
Gases

Storage class (TRGS 510) : 2B

Recommended storage temperature : < 40 °C

### 7.3 Specific end use(s)

Specific use(s) : No data available

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Acetone	67-64-1	TWA	500 ppm 1.210 mg/m <sup>3</sup>	2000/39/EC
Further information: Indicative				
		AGW	500 ppm 1.200 mg/m <sup>3</sup>	DE TRGS 900

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## LACQUER SPRAY SATIN GLOSS PURE WHITE RAL 9010 - 400 ML

Version 14.1      Revision Date: 12.09.2023      SDS Number: 10639731-00014      Date of last issue: 08.06.2023  
Date of first issue: 11.06.2010

	Peak-limit: excursion factor (category): 2;(I)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
Propane	74-98-6	AGW	1.000 ppm 1.800 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit: excursion factor (category): 4;(II)			
Butane	106-97-8	AGW	1.000 ppm 2.400 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit: excursion factor (category): 4;(II)			
Isobutane	75-28-5	AGW	1.000 ppm 2.400 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit: excursion factor (category): 4;(II)			
n-Butyl acetate	123-86-4	STEL	150 ppm 723 mg/m <sup>3</sup>	2019/1831/E U
	Further information: Indicative			
		TWA	50 ppm 241 mg/m <sup>3</sup>	2019/1831/E U
	Further information: Indicative			
		AGW	62 ppm 300 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit: excursion factor (category): 2;(I)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
2-Methoxy-1-methylethyl acetate	108-65-6	STEL	100 ppm 550 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	50 ppm 275 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		AGW	50 ppm 270 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit: excursion factor (category): 1;(I)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
Xylene	1330-20-7	TWA	50 ppm 221 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 442 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		AGW	50 ppm 220 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: Skin absorption			
Ethanol	64-17-5	AGW	200 ppm	DE TRGS



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## LACQUER SPRAY SATIN GLOSS PURE WHITE RAL 9010 - 400 ML

Version 14.1      Revision Date: 12.09.2023      SDS Number: 10639731-00014      Date of last issue: 08.06.2023  
Date of first issue: 11.06.2010

			380 mg/m <sup>3</sup>	900
	Peak-limit: excursion factor (category): 4;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
Butanone	78-93-3	STEL	300 ppm 900 mg/m <sup>3</sup>	2000/39/EC
	Further information: Indicative			
		TWA	200 ppm 600 mg/m <sup>3</sup>	2000/39/EC
	Further information: Indicative			
		AGW	200 ppm 600 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit: excursion factor (category): 1;(I)			
	Further information: Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			

### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Acetone	67-64-1	Acetone: 80 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903
Xylene	1330-20-7	methylhippuric acid (all isomers): 2.000 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903
Butanone	78-93-3	2-butanone: 2 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
n-Butyl acetate	Workers	Inhalation	Acute systemic effects	600 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	600 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	300 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	300 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects	300 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	300 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	35,7 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	35,7 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	11 mg/kg bw/day
	Consumers	Skin contact	Acute systemic effects	11 mg/kg bw/day

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## LACQUER SPRAY SATIN GLOSS PURE WHITE RAL 9010 - 400 ML

Version  
14.1

Revision Date:  
12.09.2023

SDS Number:  
10639731-00014

Date of last issue: 08.06.2023  
Date of first issue: 11.06.2010

	Consumers	Skin contact	Long-term systemic effects	6 mg/kg bw/day
	Consumers	Skin contact	Acute systemic effects	6 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	2 mg/kg bw/day
	Consumers	Ingestion	Acute systemic effects	2 mg/kg bw/day
2-Methoxy-1-methylethyl acetate	Workers	Inhalation	Long-term systemic effects	275 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	796 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	33 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	320 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	36 mg/kg bw/day
	Workers	Inhalation	Acute local effects	550 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	33 mg/m <sup>3</sup>
Acetone	Workers	Inhalation	Long-term systemic effects	1210 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	2420 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	186 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	200 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	62 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	62 mg/kg bw/day
Butyl glycollate	Workers	Inhalation	Long-term systemic effects	58,8 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	41,7 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	17,4 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	17,4 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	25 mg/kg bw/day
	Consumers	Skin contact	Long-term local effects	0,11 mg/cm <sup>2</sup>
	Consumers	Ingestion	Long-term systemic effects	4,2 mg/kg bw/day
Butanone	Workers	Inhalation	Long-term systemic effects	600 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	1161 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic	106 mg/m <sup>3</sup>

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## LACQUER SPRAY SATIN GLOSS PURE WHITE RAL 9010 - 400 ML

Version  
14.1

Revision Date:  
12.09.2023

SDS Number:  
10639731-00014

Date of last issue: 08.06.2023  
Date of first issue: 11.06.2010

			effects	
	Workers	Skin contact	Long-term systemic effects	412 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	31 mg/kg bw/day
Ethanol	Workers	Inhalation	Long-term systemic effects	950 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	343 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	114 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	206 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	87 mg/kg bw/day
1,2-Benzenedicarboxylic acid, benzyl C7-9-branched and linear alkyl esters	Workers	Inhalation	Long-term systemic effects	1,32 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	2,8 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0,23 µg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	1 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0,1 mg/kg bw/day
Xylene	Workers	Inhalation	Long-term systemic effects	221 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	442 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	221 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	442 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	212 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	65,3 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects	260 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term local effects	65,3 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute local effects	260 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	125 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	12,5 mg/kg bw/day

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
----------------	---------------------------	-------

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## LACQUER SPRAY SATIN GLOSS PURE WHITE RAL 9010 - 400 ML

Version 14.1      Revision Date: 12.09.2023      SDS Number: 10639731-00014      Date of last issue: 08.06.2023  
Date of first issue: 11.06.2010

n-Butyl acetate	Fresh water	0,18 mg/l
	Marine water	0,018 mg/l
	Sewage treatment plant	35,6 mg/l
	Fresh water sediment	0,981 mg/kg dry weight (d.w.)
	Marine sediment	0,098 mg/kg dry weight (d.w.)
	Soil	0,09 mg/kg dry weight (d.w.)
2-Methoxy-1-methylethyl acetate	Fresh water	0,635 mg/l
	Marine water	0,0635 mg/l
	Intermittent use/release	6,35 mg/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	3,29 mg/kg dry weight (d.w.)
	Marine sediment	0,329 mg/kg dry weight (d.w.)
	Soil	0,29 mg/kg dry weight (d.w.)
	Fresh water	10,6 mg/l
	Marine water	1,06 mg/l
Acetone	Intermittent use/release	21 mg/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	30,4 mg/kg dry weight (d.w.)
	Marine sediment	3,04 mg/kg dry weight (d.w.)
	Soil	29,5 mg/kg dry weight (d.w.)
	Butyl glycollate	Fresh water
Marine water		0,005 mg/l
Intermittent use/release		0,5 mg/l
Sewage treatment plant		232 mg/l
Fresh water sediment		0,203 mg/kg
Marine sediment		0,0203 mg/kg
	Soil	0,0112 mg/kg
	Fresh water	55,8 mg/l
	Freshwater - intermittent	55,8 mg/l
Butanone	Marine water	55,8 mg/l
	Sewage treatment plant	709 mg/l
	Fresh water sediment	284,74 mg/kg dry weight (d.w.)
	Marine sediment	284,7 mg/kg dry weight (d.w.)
	Soil	22,5 mg/kg dry weight (d.w.)
	Oral (Secondary Poisoning)	1000 mg/kg food
Ethanol	Fresh water	0,96 mg/l
	Freshwater - intermittent	2,75 mg/l
	Marine water	0,79 mg/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## LACQUER SPRAY SATIN GLOSS PURE WHITE RAL 9010 - 400 ML

Version 14.1      Revision Date: 12.09.2023      SDS Number: 10639731-00014      Date of last issue: 08.06.2023  
Date of first issue: 11.06.2010

	Sewage treatment plant	580 mg/l
	Fresh water sediment	3,6 mg/kg dry weight (d.w.)
	Marine sediment	2,9 mg/kg dry weight (d.w.)
	Soil	0,63 mg/kg dry weight (d.w.)
	Oral (Secondary Poisoning)	380 mg/kg food
Xylene	Fresh water	0,327 mg/l
	Intermittent use/release	0,327 mg/l
	Marine water	0,327 mg/l
	Sewage treatment plant	6,58 mg/l
	Fresh water sediment	12,46 mg/kg dry weight (d.w.)
	Marine sediment	12,46 mg/kg dry weight (d.w.)
	Soil	2,31 mg/kg dry weight (d.w.)

### 8.2 Exposure controls

#### Engineering measures

Minimize workplace exposure concentrations.

If sufficient ventilation is unavailable, use with local exhaust ventilation.

If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

#### Personal protective equipment

Eye/face protection : Wear the following personal protective equipment:  
Safety goggles  
Equipment should conform to DIN EN 166

#### Hand protection

Material : butyl-rubber  
Break through time : <= 15 min  
Glove thickness : 0,7 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Wear the following personal protective equipment:  
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## LACQUER SPRAY SATIN GLOSS PURE WHITE RAL 9010 - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 08.06.2023
14.1	12.09.2023	10639731-00014	Date of first issue: 11.06.2010

---

Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection. Equipment should conform to DIN EN 137

Filter type : Self-contained breathing apparatus

---

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Physical state : Aerosol containing a liquefied gas

Propellant : Butane, Isobutane, Propane

Colour : white

Odour : solvent-like

Odour Threshold : No data available

Melting point/freezing point : Decomposes before melting.

Initial boiling point and boiling range : Not applicable

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper flammability limit : 13 %(V)

Lower explosion limit / Lower flammability limit : 1,7 %(V)

Flash point : < 0 °C  
Method: DIN 51755 Part 2, closed cup  
Flash point is only valid for liquid portion in the aerosol can.

Auto-ignition temperature : 460 °C

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## LACQUER SPRAY SATIN GLOSS PURE WHITE RAL 9010 - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 08.06.2023
14.1	12.09.2023	10639731-00014	Date of first issue: 11.06.2010

---

Decomposition temperature : The substance or mixture is not classified self-reactive.

pH : substance/mixture is non-polar/aprotic

Viscosity  
Viscosity, kinematic : Not applicable

Solubility(ies)  
Water solubility : insoluble

Partition coefficient: n-  
octanol/water : Not applicable

Vapour pressure : 3.600 hPa (20 °C)

Relative density : 0,833 (23 °C)  
Reference substance: Water

Relative vapour density : Not applicable

Particle characteristics  
Particle size : Not applicable

### 9.2 Other information

Explosives : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Evaporation rate : Not applicable

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Not classified as a reactivity hazard.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## LACQUER SPRAY SATIN GLOSS PURE WHITE RAL 9010 - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 08.06.2023
14.1	12.09.2023	10639731-00014	Date of first issue: 11.06.2010

---

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Extremely flammable aerosol.  
Vapours may form explosive mixture with air.  
If the temperature rises there is danger of the vessels bursting  
due to the high vapor pressure.  
Can react with strong oxidizing agents.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : Oxidizing agents

### 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

---

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Inhalation  
Skin contact  
Ingestion  
Eye contact

#### Acute toxicity

Not classified based on available information.

#### Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

#### Components:

##### Acetone:

Acute oral toxicity : LD50 (Rat): 5.800 mg/kg

Acute inhalation toxicity : LC50 (Rat): 76 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## LACQUER SPRAY SATIN GLOSS PURE WHITE RAL 9010 - 400 ML

Version 14.1	Revision Date: 12.09.2023	SDS Number: 10639731-00014	Date of last issue: 08.06.2023 Date of first issue: 11.06.2010
-----------------	------------------------------	-------------------------------	---

---

Acute dermal toxicity : LD50 (Rabbit): 7.426 mg/kg

### **n-Butyl acetate:**

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 21,1 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

### **2-Methoxy-1-methylethyl acetate:**

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC0 (Rat): 9,48 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rat): > 5.000 mg/kg

### **Xylene:**

Acute oral toxicity : LD50 (Rat): 3.523 mg/kg  
Method: Directive 67/548/EEC, Annex V, B.1.

Acute inhalation toxicity : Acute toxicity estimate: 11 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Expert judgement  
Remarks: Based on national or regional regulation.

Acute dermal toxicity : Acute toxicity estimate: 1.100 mg/kg  
Method: Expert judgement  
Remarks: Based on national or regional regulation.

### **Ethanol:**

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 124,7 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

### **Butanone:**

Acute oral toxicity : LD50 (Rat): > 2.000 - 5.000 mg/kg  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 25,5 mg/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## LACQUER SPRAY SATIN GLOSS PURE WHITE RAL 9010 - 400 ML

Version 14.1      Revision Date: 12.09.2023      SDS Number: 10639731-00014      Date of last issue: 08.06.2023  
Date of first issue: 11.06.2010

---

Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 436  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

### **Butyl glycollate:**

Acute oral toxicity : LD50 (Rat): 4.595 mg/kg

Acute inhalation toxicity : LC0 (Rat):  $\geq$  6,2 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

### **Skin corrosion/irritation**

Repeated exposure may cause skin dryness or cracking.

### **Components:**

#### **Acetone:**

Assessment : Repeated exposure may cause skin dryness or cracking.

#### **n-Butyl acetate:**

Species : Rabbit  
Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

#### **2-Methoxy-1-methylethyl acetate:**

Species : Rabbit  
Result : No skin irritation

#### **Xylene:**

Species : Rabbit  
Result : Skin irritation

#### **Ethanol:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

#### **Butanone:**

Assessment : Repeated exposure may cause skin dryness or cracking.

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## LACQUER SPRAY SATIN GLOSS PURE WHITE RAL 9010 - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 08.06.2023
14.1	12.09.2023	10639731-00014	Date of first issue: 11.06.2010

---

Remarks : Based on data from similar materials

### **Butyl glycollate:**

Species : Rabbit  
Result : No skin irritation

### **Serious eye damage/eye irritation**

Causes serious eye irritation.

### **Components:**

#### **Acetone:**

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : Irritation to eyes, reversing within 21 days

#### **n-Butyl acetate:**

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : No eye irritation

#### **2-Methoxy-1-methylethyl acetate:**

Species : Rabbit  
Result : No eye irritation

#### **Xylene:**

Species : Rabbit  
Result : Irritation to eyes, reversing within 21 days

#### **Ethanol:**

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : Irritation to eyes, reversing within 21 days

#### **Butanone:**

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : Irritation to eyes, reversing within 21 days

#### **Butyl glycollate:**

Species : Rabbit  
Result : Irreversible effects on the eye

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## LACQUER SPRAY SATIN GLOSS PURE WHITE RAL 9010 - 400 ML

Version 14.1      Revision Date: 12.09.2023      SDS Number: 10639731-00014      Date of last issue: 08.06.2023  
Date of first issue: 11.06.2010

---

### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.

#### Components:

##### Acetone:

Test Type : Maximisation Test  
Exposure routes : Skin contact  
Species : Guinea pig  
Result : negative

##### n-Butyl acetate:

Test Type : Maximisation Test  
Exposure routes : Skin contact  
Species : Guinea pig  
Result : negative

##### 2-Methoxy-1-methylethyl acetate:

Test Type : Maximisation Test  
Exposure routes : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

##### Xylene:

Test Type : Local lymph node assay (LLNA)  
Exposure routes : Skin contact  
Species : Mouse  
Result : negative

##### Ethanol:

Test Type : Local lymph node assay (LLNA)  
Exposure routes : Skin contact  
Species : Mouse  
Result : negative

##### Butanone:

Test Type : Buehler Test  
Exposure routes : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## LACQUER SPRAY SATIN GLOSS PURE WHITE RAL 9010 - 400 ML

Version 14.1      Revision Date: 12.09.2023      SDS Number: 10639731-00014      Date of last issue: 08.06.2023  
Date of first issue: 11.06.2010

---

### **Butyl glycollate:**

Test Type : Maximisation Test  
Exposure routes : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

### **Germ cell mutagenicity**

Not classified based on available information.

### **Components:**

#### **Acetone:**

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Test Type: Chromosome aberration test in vitro  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo  
cytogenetic assay)  
Species: Mouse  
Application Route: Ingestion  
Result: negative

#### **n-Butyl acetate:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

#### **2-Methoxy-1-methylethyl acetate:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Test Type: DNA damage and repair, unscheduled DNA syn-  
thesis in mammalian cells (in vitro)  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Result: negative  
Remarks: Based on data from similar materials

#### **Xylene:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Test Type: Chromosome aberration test in vitro

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## LACQUER SPRAY SATIN GLOSS PURE WHITE RAL 9010 - 400 ML

Version 14.1	Revision Date: 12.09.2023	SDS Number: 10639731-00014	Date of last issue: 08.06.2023 Date of first issue: 11.06.2010
-----------------	------------------------------	-------------------------------	---

---

Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Test Type: In vitro sister chromatid exchange assay in mam-  
malian cells  
Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)  
Species: Mouse  
Application Route: Skin contact  
Result: negative

### Ethanol:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)  
Species: Mouse  
Application Route: Ingestion  
Result: equivocal

### Butanone:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Test Type: Chromosome aberration test in vitro  
Result: negative

Test Type: DNA damage and repair, unscheduled DNA syn-  
thesis in mammalian cells (in vitro)  
Result: negative

Test Type: Saccharomyces cerevisiae, gene mutation assay  
(in vitro)  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo  
cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Result: negative

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## LACQUER SPRAY SATIN GLOSS PURE WHITE RAL 9010 - 400 ML

Version 14.1      Revision Date: 12.09.2023      SDS Number: 10639731-00014      Date of last issue: 08.06.2023  
Date of first issue: 11.06.2010

---

### Butyl glycollate:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative

Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Test Type: Mouse Lymphoma  
Method: OECD Test Guideline 476  
Result: negative

### Carcinogenicity

Not classified based on available information.

### Components:

#### Acetone:

Species : Mouse  
Application Route : Skin contact  
Exposure time : 424 days  
Result : negative

#### 2-Methoxy-1-methylethyl acetate:

Species : Rat  
Application Route : inhalation (vapour)  
Exposure time : 2 Years  
Result : negative  
Remarks : Based on data from similar materials

#### Xylene:

Species : Rat  
Application Route : Ingestion  
Exposure time : 103 weeks  
Result : negative

### Reproductive toxicity

Not classified based on available information.

### Components:

#### Acetone:

Effects on fertility : Test Type: One-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Result: negative

Effects on foetal develop- : Test Type: Embryo-foetal development

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## LACQUER SPRAY SATIN GLOSS PURE WHITE RAL 9010 - 400 ML

Version 14.1	Revision Date: 12.09.2023	SDS Number: 10639731-00014	Date of last issue: 08.06.2023 Date of first issue: 11.06.2010
-----------------	------------------------------	-------------------------------	---

---

ment  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

### **n-Butyl acetate:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapour)  
Method: OECD Test Guideline 416  
Result: negative

Effects on foetal develop-  
ment : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

### **2-Methoxy-1-methylethyl acetate:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapour)  
Method: OECD Test Guideline 416  
Result: negative  
Remarks: Based on data from similar materials

Effects on foetal develop-  
ment : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

### **Xylene:**

Effects on fertility : Test Type: One-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

Effects on foetal develop-  
ment : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

### **Ethanol:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Mouse  
Application Route: Ingestion  
Result: negative

### **Butanone:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## LACQUER SPRAY SATIN GLOSS PURE WHITE RAL 9010 - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 08.06.2023
14.1	12.09.2023	10639731-00014	Date of first issue: 11.06.2010

---

Species: Rat  
Application Route: Ingestion  
Result: negative  
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: Inhalation  
Method: OECD Test Guideline 414  
Result: negative

### **Butyl glycollate:**

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 414  
Result: positive

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

### **STOT - single exposure**

May cause drowsiness or dizziness.

### **Components:**

#### **Acetone:**

Assessment : May cause drowsiness or dizziness.

#### **n-Butyl acetate:**

Assessment : May cause drowsiness or dizziness.

#### **2-Methoxy-1-methylethyl acetate:**

Assessment : May cause drowsiness or dizziness.

#### **Xylene:**

Assessment : May cause respiratory irritation.

#### **Butanone:**

Assessment : May cause drowsiness or dizziness.

### **STOT - repeated exposure**

Not classified based on available information.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## LACQUER SPRAY SATIN GLOSS PURE WHITE RAL 9010 - 400 ML

Version 14.1      Revision Date: 12.09.2023      SDS Number: 10639731-00014      Date of last issue: 08.06.2023  
Date of first issue: 11.06.2010

---

### Components:

#### **Xylene:**

Exposure routes : inhalation (vapour)  
Target Organs : Auditory system  
Assessment : Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg/l/6h/d.

### **Repeated dose toxicity**

#### Components:

##### **Acetone:**

Species : Rat  
NOAEL : 900 mg/kg  
LOAEL : 1.700 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days

Species : Rat  
NOAEL : 45 mg/l  
Application Route : inhalation (vapour)  
Exposure time : 8 Weeks

##### **n-Butyl acetate:**

Species : Rat  
NOAEL : 2,4 mg/l  
Application Route : inhalation (vapour)  
Exposure time : 90 Days

##### **2-Methoxy-1-methylethyl acetate:**

Species : Rat  
NOAEL : > 1.000 mg/kg  
Application Route : Ingestion  
Exposure time : 41 - 45 Days  
Method : OECD Test Guideline 422

Species : Mouse  
NOAEL : 1,62 mg/l  
Application Route : inhalation (vapour)  
Exposure time : 2 yr  
Remarks : Based on data from similar materials

Species : Rabbit  
NOAEL : > 1.838 mg/kg  
Application Route : Skin contact  
Exposure time : 90 Days  
Remarks : Based on data from similar materials

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## LACQUER SPRAY SATIN GLOSS PURE WHITE RAL 9010 - 400 ML

Version 14.1      Revision Date: 12.09.2023      SDS Number: 10639731-00014      Date of last issue: 08.06.2023  
Date of first issue: 11.06.2010

---

### **Xylene:**

Species : Rat  
LOAEL : > 0,2 - 1 mg/l  
Application Route : inhalation (vapour)  
Exposure time : 13 Weeks  
Remarks : Based on data from similar materials

Species : Rat  
LOAEL : 150 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days

### **Ethanol:**

Species : Rat  
NOAEL : 1.280 mg/kg  
LOAEL : 3.156 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days

### **Butanone:**

Species : Rat  
NOAEL : 14,84 mg/l  
Application Route : inhalation (vapour)  
Exposure time : 90 Days  
Method : OECD Test Guideline 413

### **Butyl glycollate:**

Species : Rat  
NOAEL : 1.000 mg/kg  
Application Route : Ingestion  
Exposure time : 29 Days  
Method : OECD Test Guideline 407

### **Aspiration toxicity**

Not classified based on available information.

### **Components:**

#### **Acetone:**

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

#### **Xylene:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## LACQUER SPRAY SATIN GLOSS PURE WHITE RAL 9010 - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 08.06.2023
14.1	12.09.2023	10639731-00014	Date of first issue: 11.06.2010

### **Butanone:**

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

## 11.2 Information on other hazards

### **Endocrine disrupting properties**

#### **Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### **Components:**

##### **Acetone:**

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 5.540 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia pulex (Water flea)): 8.800 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	NOEC (Pseudokirchneriella subcapitata (green algae)): 7.000 mg/l Exposure time: 96 h
Toxicity to microorganisms	:	EC50 : 61.150 mg/l Exposure time: 30 min Method: ISO 8192
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC: >= 79 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

##### **n-Butyl acetate:**

Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): 18 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia sp. (water flea)): 44 mg/l Exposure time: 48 h
Toxicity to algae/aquatic	:	ErC50 (Pseudokirchneriella subcapitata (green algae)): 397

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## LACQUER SPRAY SATIN GLOSS PURE WHITE RAL 9010 - 400 ML

Version 14.1      Revision Date: 12.09.2023      SDS Number: 10639731-00014      Date of last issue: 08.06.2023  
Date of first issue: 11.06.2010

---

plants      mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): 196 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

Toxicity to microorganisms      :      IC50 (Tetrahymena pyriformis): 356 mg/l  
Exposure time: 40 h

Toxicity to daphnia and other      :      NOEC: 23,2 mg/l  
aquatic invertebrates (Chronic toxicity)      Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Method: OECD Test Guideline 211  
Remarks: Based on data from similar materials

### **2-Methoxy-1-methylethyl acetate:**

Toxicity to fish      :      LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 - 180 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other      :      EC50 (Daphnia magna (Water flea)): > 500 mg/l  
aquatic invertebrates      Exposure time: 48 h

Toxicity to algae/aquatic      :      ErC50 (Pseudokirchneriella subcapitata (green algae)): > 1.000 mg/l  
plants      Exposure time: 96 h  
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (algae)): > 1.000 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 201

Toxicity to microorganisms      :      EC10 : > 1.000 mg/l  
Exposure time: 0,5 h

Toxicity to daphnia and other      :      NOEC: >= 100 mg/l  
aquatic invertebrates (Chronic toxicity)      Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Method: OECD Test Guideline 211

### **Xylene:**

Toxicity to fish      :      LC50 (Oncorhynchus mykiss (rainbow trout)): 13,5 mg/l  
Exposure time: 96 h

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## LACQUER SPRAY SATIN GLOSS PURE WHITE RAL 9010 - 400 ML

Version 14.1      Revision Date: 12.09.2023      SDS Number: 10639731-00014      Date of last issue: 08.06.2023  
Date of first issue: 11.06.2010

---

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1 - 10 mg/l  
Exposure time: 24 h  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EC50 (Skeletonema costatum (marine diatom)): 10 mg/l  
Exposure time: 72 h

Toxicity to microorganisms : NOEC : > 100 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209  
Remarks: Based on data from similar materials

Toxicity to fish (Chronic toxicity) : NOEC: > 0,1 - < 1 mg/l  
Exposure time: 35 d  
Species: Danio rerio (zebra fish)  
Method: OECD Test Guideline 210  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EL10: > 1 - 10 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Method: OECD Test Guideline 211  
Remarks: Based on data from similar materials

### Ethanol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 1.000 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Ceriodaphnia (water flea)): > 1.000 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (Chlorella vulgaris (Fresh water algae)): 275 mg/l  
Exposure time: 72 h

EC10 (Chlorella vulgaris (Fresh water algae)): 11,5 mg/l  
Exposure time: 72 h

Toxicity to microorganisms : EC50 (Pseudomonas putida): 6.500 mg/l  
Exposure time: 16 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 9,6 mg/l  
Exposure time: 9 d  
Species: Daphnia magna (Water flea)

### Butanone:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2.993 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## LACQUER SPRAY SATIN GLOSS PURE WHITE RAL 9010 - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 08.06.2023
14.1	12.09.2023	10639731-00014	Date of first issue: 11.06.2010

---

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 308 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 2.029 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 1.240 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 201

### Butyl glycollate:

Toxicity to fish : LC0 (Leuciscus idus (Golden orfe)): >= 50 mg/l  
Exposure time: 48 h  
Method: DIN 38412

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 280 mg/l  
Exposure time: 24 h  
Method: DIN 38412

Toxicity to algae/aquatic plants : EC10 (Lemna gibba (gibbous duckweed)): > 87,4 mg/l  
Exposure time: 7 d

Toxicity to microorganisms : EC50 (Pseudomonas putida): 2.320 mg/l  
Exposure time: 18 h

## 12.2 Persistence and degradability

### Components:

#### Acetone:

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 91 %  
Exposure time: 28 d

#### n-Butyl acetate:

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 83 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

#### 2-Methoxy-1-methylethyl acetate:

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 90 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## LACQUER SPRAY SATIN GLOSS PURE WHITE RAL 9010 - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 08.06.2023
14.1	12.09.2023	10639731-00014	Date of first issue: 11.06.2010

---

### **Xylene:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: > 70 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F  
Remarks: Based on data from similar materials

### **Ethanol:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 84 %  
Exposure time: 20 d

### **Butanone:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 98 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

### **Butyl glycollate:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 81 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B

## 12.3 Bioaccumulative potential

### Components:

#### **Acetone:**

Partition coefficient: n-  
octanol/water : log Pow: -0,27 - -0,23

#### **n-Butyl acetate:**

Partition coefficient: n-  
octanol/water : log Pow: 2,3

#### **2-Methoxy-1-methylethyl acetate:**

Partition coefficient: n-  
octanol/water : log Pow: 1,2

#### **Xylene:**

Partition coefficient: n-  
octanol/water : log Pow: 3,16  
Remarks: Calculation



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## LACQUER SPRAY SATIN GLOSS PURE WHITE RAL 9010 - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 08.06.2023
14.1	12.09.2023	10639731-00014	Date of first issue: 11.06.2010

---

### Ethanol:

Partition coefficient: n-octanol/water : log Pow: -0,35

### Butanone:

Partition coefficient: n-octanol/water : log Pow: 0,3

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

No data available

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities. Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal. Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## LACQUER SPRAY SATIN GLOSS PURE WHITE RAL 9010 - 400 ML

Version 14.1	Revision Date: 12.09.2023	SDS Number: 10639731-00014	Date of last issue: 08.06.2023 Date of first issue: 11.06.2010
-----------------	------------------------------	-------------------------------	---

Please ensure aerosol cans are sprayed completely empty  
(including propellant)

Waste Code

: The following Waste Codes are only suggestions:

used product

08 01 11, waste paint and varnish containing organic solvents  
or other hazardous substances

16 05 04, gases in pressure containers (including halons)  
containing hazardous substances

unused product

08 01 11, waste paint and varnish containing organic solvents  
or other hazardous substances

16 05 04, gases in pressure containers (including halons)  
containing hazardous substances

uncleaned packagings

15 01 10, packaging containing residues of or contaminated  
by hazardous substances

Acc. Packaging Act properly emptied packaging:

Properly emptied, non-contaminated packaging of non-  
hazardous products can be supplied to a system for the col-  
lection of sales packaging.

### SECTION 14: Transport information

#### 14.1 UN number or ID number

ADN : UN 1950

ADR : UN 1950

RID : UN 1950

IMDG : UN 1950

IATA : UN 1950

#### 14.2 UN proper shipping name

ADN : AEROSOLS

ADR : AEROSOLS

RID : AEROSOLS

IMDG : AEROSOLS

IATA : Aerosols, flammable

#### 14.3 Transport hazard class(es)

Class

Subsidiary risks

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## LACQUER SPRAY SATIN GLOSS PURE WHITE RAL 9010 - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 08.06.2023
14.1	12.09.2023	10639731-00014	Date of first issue: 11.06.2010

---

<b>ADN</b>	:	2	2.1
<b>ADR</b>	:	2	2.1
<b>RID</b>	:	2	2.1
<b>IMDG</b>	:	2.1	
<b>IATA</b>	:	2.1	

### 14.4 Packing group

**ADN**  
Packing group : Not assigned by regulation  
Classification Code : 5F  
Labels : 2.1

**ADR**  
Packing group : Not assigned by regulation  
Classification Code : 5F  
Labels : 2.1  
Tunnel restriction code : (D)

**RID**  
Packing group : Not assigned by regulation  
Classification Code : 5F  
Hazard Identification Number : 23  
Labels : 2.1

**IMDG**  
Packing group : Not assigned by regulation  
Labels : 2.1  
EmS Code : F-D, S-U

**IATA (Cargo)**  
Packing instruction (cargo aircraft) : 203  
Packing instruction (LQ) : Y203  
Packing group : Not assigned by regulation  
Labels : Flammable Gas

**IATA (Passenger)**  
Packing instruction (passenger aircraft) : 203  
Packing instruction (LQ) : Y203  
Packing group : Not assigned by regulation  
Labels : Flammable Gas

### 14.5 Environmental hazards

**ADN**  
Environmentally hazardous : no

**ADR**  
Environmentally hazardous : no

**RID**  
Environmentally hazardous : no

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## LACQUER SPRAY SATIN GLOSS PURE WHITE RAL 9010 - 400 ML

Version 14.1	Revision Date: 12.09.2023	SDS Number: 10639731-00014	Date of last issue: 08.06.2023 Date of first issue: 11.06.2010
-----------------	------------------------------	-------------------------------	---

### IMDG

Marine pollutant : no

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:  
Number on list 75  
If you intend to use this product as tattoo ink, please contact your vendor.

Formaldehyde (Number on list 72, 28)

Substance(s) or mixture(s) are listed here according to their appearance in the regulation, irrespective of their use/purpose or the conditions of the restriction. Please refer to the conditions in corresponding Regulation to determine whether an entry is applicable to the placing on the market or not.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## LACQUER SPRAY SATIN GLOSS PURE WHITE RAL 9010 - 400 ML

Version 14.1      Revision Date: 12.09.2023      SDS Number: 10639731-00014      Date of last issue: 08.06.2023  
Date of first issue: 11.06.2010

---

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point. Acetone (ANNEX II)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
P3a	FLAMMABLE AEROSOLS	150 t	500 t
18	Liquefied flammable gases (including LPG) and natural gas	50 t	200 t

Water hazard class (Germany) : WGK 1 slightly hazardous to water  
Classification according to AwSV, Annex 1 (5.2)

TA Luft List (Germany) : 5.2.1: Total dust:  
Not applicable  
5.2.2: Inorganic substances in powdered form:  
Not applicable  
5.2.4: Inorganic substances in gaseous form:  
Not applicable  
5.2.5: Organic Substances:  
Class 1: < 0,01 % Methanol, Octamethylcyclotetrasiloxane  
5.2.7.1.1: Carcinogenic substance:  
Not applicable  
5.2.7.1.1: Quartz fine dust PM4:  
Not applicable  
5.2.7.1.1: Formaldehyde:  
others: < 0,01 % Formaldehyde  
5.2.7.1.1: fibres:  
Not applicable  
5.2.7.2: Poorly degradable, easily enrichable and highly toxic organic substances:  
Not applicable

Volatile organic compounds : Directive 2004/42/EC  
VOC content in g/l: 712,88 g/l  
Product sub-category: Special finishes  
Coatings: All types  
VOC limit level 1 (2007): 840 g/l

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 85,58 %, 712,88

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## LACQUER SPRAY SATIN GLOSS PURE WHITE RAL 9010 - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 08.06.2023
14.1	12.09.2023	10639731-00014	Date of first issue: 11.06.2010

g/l

### Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

### 15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

Other information : Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

#### Full text of H-Statements

H225	: Highly flammable liquid and vapour.
H226	: Flammable liquid and vapour.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H361	: Suspected of damaging fertility or the unborn child.
H373	: May cause damage to organs through prolonged or repeated exposure.
H412	: Harmful to aquatic life with long lasting effects.
EUH066	: Repeated exposure may cause skin dryness or cracking.

#### Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Repr.	: Reproductive toxicity
Skin Irrit.	: Skin irritation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2019/1831/EU	: Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## LACQUER SPRAY SATIN GLOSS PURE WHITE RAL 9010 - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 08.06.2023
14.1	12.09.2023	10639731-00014	Date of first issue: 11.06.2010

DE TRGS 900	:	Germany. TRGS 900 - Occupational exposure limit values.
TRGS 903	:	TRGS 903 - Biological limit values
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
2019/1831/EU / TWA	:	Limit Value - eight hours
2019/1831/EU / STEL	:	Short term exposure limit
DE TRGS 900 / AGW	:	Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

### Classification of the mixture:

Aerosol 1	H222, H229
Eye Irrit. 2	H319
STOT SE 3	H336

### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## LACQUER SPRAY SATIN GLOSS PURE WHITE RAL 9010 - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 08.06.2023
14.1	12.09.2023	10639731-00014	Date of first issue: 11.06.2010

---

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN