according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY SPECIAL CLEAR VARNISH HIGH GLOSS - 400 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 24.04.2023

 10.1
 27.07.2023
 10656969-00014
 Date of first issue: 11.06.2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : LACQUER SPRAY SPECIAL CLEAR VARNISH HIGH

GLOSS - 400 ML

Product code : 0893351930

Unique Formula Identifier

(UFI)

8QJD-H0PY-F009-A0F3

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Paints

stance/Mixture Professional use product

Recommended restrictions

on use

: Not applicable

1.3 Details of the supplier of the safety data sheet

Company : Adolf Wuerth GmbH & Co. KG

Reinhold-Würth-Str. 12-17

74653 Künzelsau

Telephone : +49 794015 0

Telefax : +49 794015 10 00

E-mail address of person

responsible for the SDS

: isi@wuerth.com

1.4 Emergency telephone number

+49 (0)6132 - 84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Specific target organ toxicity - single ex- H336: May cause drowsiness or dizziness.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY SPECIAL CLEAR VARNISH HIGH GLOSS - 400 ML

Version Revision Date: SDS Number: Date of last issue: 24.04.2023 10.1 27.07.2023 10656969-00014 Date of first issue: 11.06.2010

posure, Category 3

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Supplemental Hazard

Statements

EUH066

Repeated exposure may cause skin

dryness or cracking.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P280 Wear eye protection/ face protection.

Storage:

P410 + P412 Protect from sunlight. Do not expose to tem-

peratures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

Acetone

n-Butyl acetate

2-Methoxy-1-methylethyl acetate

Butanone

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY SPECIAL CLEAR VARNISH HIGH GLOSS - 400 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 24.04.2023

 10.1
 27.07.2023
 10656969-00014
 Date of first issue: 11.06.2010

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Acetone	67-64-1 200-662-2 606-001-00-8 01-2119471330-49	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066	>= 30 - < 50
n-Butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 EUH066	>= 1 - < 10
2-Methoxy-1-methylethyl acetate	108-65-6 203-603-9 607-195-00-7 01-2119475791-29	Flam. Liq. 3; H226 STOT SE 3; H336	>= 1 - < 10
Xylene	1330-20-7 215-535-7 601-022-00-9 01-2119488216-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 STOT RE 2; H373 (Auditory system) Asp. Tox. 1; H304 Aquatic Chronic 3; H412 Acute toxicity estimate Acute inhalation toxicity (vapour): 11 mg/l Acute dermal toxicity: 1.100 mg/kg	>= 2,5 - < 10
Ethanol	64-17-5 200-578-6 603-002-00-5 01-2119457610-43	Flam. Liq. 2; H225 Eye Irrit. 2; H319 ——— specific concentration limit Eye Irrit. 2; H319 >= 50 %	>= 1 - < 10
Butanone	78-93-3	Flam. Liq. 2; H225	>= 1 - < 10

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY SPECIAL CLEAR VARNISH HIGH GLOSS - 400 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 24.04.2023

 10.1
 27.07.2023
 10656969-00014
 Date of first issue: 11.06.2010

	201-159-0 606-002-00-3 01-2119457290-43	Eye Irrit. 2; H319 STOT SE 3; H336 EUH066	
Butyl glycollate	7397-62-8 230-991-7 01-2119514685-36	Eye Dam. 1; H318 Repr. 2; H361	>= 1 - < 3
Ethylbenzene	100-41-4 202-849-4 601-023-00-4 01-2119489370-35	Flam. Liq. 2; H225 Acute Tox. 4; H332 STOT RE 2; H373 (Auditory system) Asp. Tox. 1; H304 Aquatic Chronic 3; H412 Acute toxicity estimate Acute inhalation toxicity (vapour): 17,8 mg/l	>= 1 - < 2,5

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

If inhaled : If inhaled, remove to fresh air.

Get medical attention.

In case of skin contact : In case of contact, immediately flush skin with plenty of water.

Remove contaminated clothing and shoes.

Get medical attention. Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water

for at least 15 minutes.

If easy to do, remove contact lens, if worn.

Get medical attention.

If swallowed, DO NOT induce vomiting.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY SPECIAL CLEAR VARNISH HIGH GLOSS - 400 ML

Version Revision Date: SDS Number: Date of last issue: 24.04.2023 10.1 27.07.2023 10656969-00014 Date of first issue: 11.06.2010

Get medical attention.

Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes serious eye irritation.

May cause drowsiness or dizziness.

Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Flash back possible over considerable distance.
 Vapours may form explosive mixtures with air.

Exposure to combustion products may be a hazard to health. If the temperature rises there is danger of the vessels bursting

due to the high vapor pressure.

Hazardous combustion prod: :

ucts

Carbon oxides

Nitrogen oxides (NOx)

5.3 Advice for firefighters

Special protective equipment :

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do

SO

Evacuate area.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY SPECIAL CLEAR VARNISH HIGH GLOSS - 400 ML

Version Revision Date: SDS Number: Date of last issue: 24.04.2023 10.1 27.07.2023 10656969-00014 Date of first issue: 11.06.2010

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.

Use personal protective equipment.

Follow safe handling advice (see section 7) and personal pro-

tective equipment recommendations (see section 8).

6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g. by containment or oil

barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.

Soak up with inert absorbent material.

Suppress (knock down) gases/vapours/mists with a water

spray jet.

For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor-

bent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to deter-

mine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust

ventilation.

If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventila-

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY SPECIAL CLEAR VARNISH HIGH GLOSS - 400 ML

Version Revision Date: SDS Number: Date of last issue: 24.04.2023 10.1 27.07.2023 10656969-00014 Date of first issue: 11.06.2010

tion.

Advice on safe handling : Do not get on skin or clothing.

Do not breathe spray. Do not swallow. Do not get in eyes.

Wash skin thoroughly after handling.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as-

sessment

Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

Take precautionary measures against static discharges. Take care to prevent spills, waste and minimize release to the

environment.

Do not spray on an open flame or other ignition source.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye

flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contami-

nated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Store locked up. Keep tightly closed. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Do not pierce or burn, even after use. Keep

cool. Protect from sunlight.

Advice on common storage : Do not store with the following product types:

Self-reactive substances and mixtures

Organic peroxides Oxidizing agents Flammable solids Pyrophoric liquids Pyrophoric solids

Self-heating substances and mixtures

Substances and mixtures, which in contact with water, emit

flammable gases Explosives

Gases

Storage class (TRGS 510) : 2B

Recommended storage tem: :

perature

< 40 °C

7.3 Specific end use(s)

Specific use(s) : No data available

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY SPECIAL CLEAR VARNISH HIGH GLOSS - 400 ML

Version Revision Date: SDS Number: Date of last issue: 24.04.2023 10.1 27.07.2023 10656969-00014 Date of first issue: 11.06.2010

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis		
Acetone	67-64-1	TWA	500 ppm 1.210 mg/m3	2000/39/EC		
	Further inforn	Further information: Indicative				
		AGW	500 ppm 1.200 mg/m3	DE TRGS 900		
	Peak-limit: ex	cursion factor (cated	jory): 2;(l)			
			s compliance with the OEL ar	nd biological		
			of harming the unborn child			
Propane	74-98-6	AGW	1.000 ppm 1.800 mg/m3	DE TRGS 900		
	Peak-limit: ex	cursion factor (cated	jory): 4;(II)			
Butane	106-97-8	AGW	1.000 ppm 2.400 mg/m3	DE TRGS 900		
	Peak-limit: ex	cursion factor (cated	jory): 4;(II)			
n-Butyl acetate	123-86-4	STEL	150 ppm 723 mg/m3	2019/1831/E U		
	Further inforn	nation: Indicative		1		
		TWA	50 ppm 241 mg/m3	2019/1831/E U		
	Further inforn	nation: Indicative	J	-		
		AGW	62 ppm 300 mg/m3	DE TRGS 900		
	Peak-limit: ex	cursion factor (cated		1		
	Further inforn	nation: When there is	s compliance with the OEL are for the compliance with the OEL are for the complex comp	nd biological		
Isobutane	75-28-5	AGW	1.000 ppm 2.400 mg/m3	DE TRGS 900		
	Peak-limit: ex	cursion factor (cated	ory): 4;(II)			
2-Methoxy-1- methylethyl ace- tate	108-65-6	STEL	100 ppm 550 mg/m3	2000/39/EC		
	Further inforn skin, Indicativ	Further information: Identifies the possibility of significant uptake through the skin. Indicative				
		TWA	50 ppm 275 mg/m3	2000/39/EC		
	Further inforn skin, Indicativ	Further information: Identifies the possibility of significant uptake through t				
		AGW	50 ppm 270 mg/m3	DE TRGS 900		
	Peak-limit: ex	cursion factor (cated		•		
	Further inforn	nation: When there is	s compliance with the OEL are for the compliance with the OEL are for the complex comp	nd biological		

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY SPECIAL CLEAR VARNISH HIGH GLOSS - 400 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 24.04.2023

 10.1
 27.07.2023
 10656969-00014
 Date of first issue: 11.06.2010

Xylene	1330-20-7	TWA	50 ppm 221 mg/m3	2000/39/EC			
	Further infor	Further information: Identifies the possibility of significant uptake through the					
	skin, Indicati		r producting or organical open				
	, , , ,	STEL	100 ppm	2000/39/EC			
			442 mg/m3				
	Further infor	mation: Identifies the	e possibility of significant upta	ake through the			
	skin, Indicati		- p	g.v			
		AGW	50 ppm	DE TRGS			
			220 mg/m3	900			
	Peak-limit: e	xcursion factor (cate	egory): 2;(II)	•			
		mation: Skin absorp					
Ethanol	64-17-5	AGW	200 ppm	DE TRGS			
			380 mg/m3	900			
	Peak-limit: e	xcursion factor (cate	<u> </u>	•			
			is compliance with the OEL a	and biological			
			of harming the unborn child				
Butanone	78-93-3	STEL	300 ppm	2000/39/EC			
2010		0.22	900 mg/m3				
	Further infor	mation: Indicative	, coog.				
		TWA	200 ppm	2000/39/EC			
		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	600 mg/m3	2000/00/20			
	Further infor	mation: Indicative	ccc mg/mc				
	T GITTIOI IIIIOI	AGW	200 ppm	DE TRGS			
		7.011	600 mg/m3	900			
	Peak-limit: e	xcursion factor (cate		1000			
	Peak-limit: excursion factor (category): 1;(I) Further information: Skin absorption, When there is compliance with the OEL						
			there is no risk of harming the				
Ethylbenzene	100-41-4	TWA	100 ppm	2000/39/EC			
Laryiberizerie	100 41 4	1 ***	442 mg/m3	2000/03/20			
	Further infor	mation: Identifies th	e possibility of significant upta	ke through the			
	skin, Indicati		e possibility of significant upto	ake unough the			
	JKIII, IIIGIGALI	STEL	200 ppm	2000/39/EC			
		J STEE	884 mg/m3	2000/33/20			
	Further infor	Further information: Identifies the possibility of significant uptake through the					
	skin, Indicati		= possibility of significant upto	ake unough the			
	, , ,	AGW	20 ppm	DE TRGS			
			88 mg/m3	900			
	Peak-limit: e	xcursion factor (cate	<u> </u>	1			
	Peak-limit: excursion factor (category): 2;(II) Further information: Skin absorption, When there is compliance with the OEL						
			there is no risk of harming the				

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Acetone	67-64-1	Acetone: 80 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903
Xylene	1330-20-7	methylhippuric acid (all isomers): 2.000	Immediately after exposure or after	TRGS 903

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY SPECIAL CLEAR VARNISH HIGH GLOSS - 400 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 24.04.2023

 10.1
 27.07.2023
 10656969-00014
 Date of first issue: 11.06.2010

		mg/l (Urine)	working hours	
Butanone	78-93-3	2-butanone: 2 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903
Ethylbenzene	100-41-4	mandelic acid + phenylglyoxylic acid: 250 mg/g Creatinine (Urine)	Immediately after exposure or after working hours	TRGS 903

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
n-Butyl acetate	Workers	Inhalation	Acute systemic effects	600 mg/m3
	Workers	Inhalation	Acute local effects	600 mg/m3
	Workers	Inhalation	Long-term systemic effects	300 mg/m3
	Workers	Inhalation	Long-term local ef- fects	300 mg/m3
	Consumers	Inhalation	Acute systemic effects	300 mg/m3
	Consumers	Inhalation	Acute local effects	300 mg/m3
	Consumers	Inhalation	Long-term systemic effects	35,7 mg/m3
	Consumers	Inhalation	Long-term local ef- fects	35,7 mg/m3
	Consumers	Skin contact	Long-term systemic effects	11 mg/kg bw/day
	Consumers	Skin contact	Acute systemic effects	11 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	6 mg/kg bw/day
	Consumers	Skin contact	Acute systemic effects	6 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	2 mg/kg bw/day
	Consumers	Ingestion	Acute systemic effects	2 mg/kg bw/day
2-Methoxy-1- methylethyl acetate	Workers	Inhalation	Long-term systemic effects	275 mg/m3
	Workers	Skin contact	Long-term systemic effects	796 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	33 mg/m3
	Consumers	Skin contact	Long-term systemic effects	320 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	36 mg/kg bw/day
	Workers	Inhalation	Acute local effects	550 mg/m3

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY SPECIAL CLEAR VARNISH HIGH GLOSS - 400 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 24.04.2023

 10.1
 27.07.2023
 10656969-00014
 Date of first issue: 11.06.2010

	Consumers	Inhalation	Long-term local effects	33 mg/m3
Acetone	Workers	Inhalation	Long-term systemic effects	1210 mg/m3
	Workers	Inhalation	Acute local effects	2420 mg/m3
	Workers	Skin contact	Long-term systemic effects	186 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	200 mg/m3
	Consumers	Skin contact	Long-term systemic effects	62 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	62 mg/kg bw/day
Ethylbenzene	Workers	Inhalation	Long-term systemic effects	77 mg/m3
	Workers	Inhalation	Acute local effects	293 mg/m3
	Workers	Skin contact	Long-term systemic effects	180 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	15 mg/m3
	Consumers	Ingestion	Long-term systemic effects	1,6 mg/kg bw/day
Butanone	Workers	Inhalation	Long-term systemic effects	600 mg/m3
	Workers	Skin contact	Long-term systemic effects	1161 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	106 mg/m3
	Workers	Skin contact	Long-term systemic effects	412 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	31 mg/kg bw/day
Ethanol	Workers	Inhalation	Long-term systemic effects	950 mg/m3
	Workers	Skin contact	Long-term systemic effects	343 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	114 mg/m3
	Consumers	Skin contact	Long-term systemic effects	206 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	87 mg/kg bw/day
1,2- Benzenedicarboxylic acid, benzyl C7-9- branched and linear alkyl esters	Workers	Inhalation	Long-term systemic effects	1,32 mg/m3
	Workers	Skin contact	Long-term systemic effects	2,8 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0,23 μg/m3

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY SPECIAL CLEAR VARNISH HIGH GLOSS - 400 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 24.04.2023

 10.1
 27.07.2023
 10656969-00014
 Date of first issue: 11.06.2010

	Consumers	Skin contact	Long-term systemic effects	1 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0,1 mg/kg bw/day
Butyl glycollate	Workers	Inhalation	Long-term systemic effects	58,8 mg/m3
	Workers	Skin contact	Long-term systemic effects	41,7 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	17,4 mg/m3
	Consumers	Inhalation	Long-term local ef- fects	17,4 mg/m3
	Consumers	Skin contact	Long-term systemic effects	25 mg/kg bw/day
	Consumers	Skin contact	Long-term local ef- fects	0,11 mg/cm2
	Consumers	Ingestion	Long-term systemic effects	4,2 mg/kg bw/day
Xylene	Workers	Inhalation	Long-term systemic effects	221 mg/m3
	Workers	Inhalation	Acute systemic ef- fects	442 mg/m3
	Workers	Inhalation	Long-term local ef- fects	221 mg/m3
	Workers	Inhalation	Acute local effects	442 mg/m3
	Workers	Skin contact	Long-term systemic effects	212 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	65,3 mg/m3
	Consumers	Inhalation	Acute systemic ef- fects	260 mg/m3
	Consumers	Inhalation	Long-term local ef- fects	65,3 mg/m3
	Consumers	Inhalation	Acute local effects	260 mg/m3
	Consumers	Skin contact	Long-term systemic effects	125 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	12,5 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
n-Butyl acetate	Fresh water	0,18 mg/l
	Marine water	0,018 mg/l
	Sewage treatment plant	35,6 mg/l
	Fresh water sediment	0,981 mg/kg dry weight (d.w.)
	Marine sediment	0,098 mg/kg dry weight (d.w.)
	Soil	0,09 mg/kg dry weight (d.w.)
2-Methoxy-1-methylethyl acetate	Fresh water	0,635 mg/l

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY SPECIAL CLEAR VARNISH HIGH GLOSS - 400 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 24.04.2023

 10.1
 27.07.2023
 10656969-00014
 Date of first issue: 11.06.2010

	Marine water	0,0635 mg/l
	Intermittent use/release	6,35 mg/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	3,29 mg/kg dry
	1 Toon water coamient	weight (d.w.)
	Marine sediment	0,329 mg/kg dry
	Manne oddinient	weight (d.w.)
	Soil	0,29 mg/kg dry
		weight (d.w.)
Acetone	Fresh water	10,6 mg/l
	Marine water	1,06 mg/l
	Intermittent use/release	21 mg/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	30,4 mg/kg dry
	Troon water coamen	weight (d.w.)
	Marine sediment	3,04 mg/kg dry
	Wallio Scalliott	weight (d.w.)
	Soil	29,5 mg/kg dry
	0011	weight (d.w.)
Ethylbenzene	Fresh water	0,1 mg/l
Laryisonzene	Freshwater - intermittent	0,1 mg/l
	Marine water	0,01 mg/l
	Sewage treatment plant	9,6 mg/l
	Fresh water sediment	13,7 mg/kg dry
	l lesii water sediirient	weight (d.w.)
	Marine sediment	1,37 mg/kg dry
	Warne odamon	weight (d.w.)
	Soil	2,68 mg/kg dry
	Gon	weight (d.w.)
	Oral (Secondary Poisoning)	20 mg/kg food
Butanone	Fresh water	55,8 mg/l
Batariorio	Freshwater - intermittent	55,8 mg/l
	Marine water	55,8 mg/l
	Sewage treatment plant	709 mg/l
	Fresh water sediment	284,74 mg/kg dry
	l resti water sediment	weight (d.w.)
	Marine sediment	284,7 mg/kg dry
	Wallie Scallicit	weight (d.w.)
	Soil	22,5 mg/kg dry
		weight (d.w.)
	Oral (Secondary Poisoning)	1000 mg/kg food
Ethanol	Fresh water	0,96 mg/l
	Freshwater - intermittent	2,75 mg/l
	Marine water	0,79 mg/l
	Sewage treatment plant	580 mg/l
	Fresh water sediment	1 3 6 ma/ka arv
	Fresh water sediment	3,6 mg/kg dry
		weight (d.w.)
	Fresh water sediment Marine sediment	

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY SPECIAL CLEAR VARNISH HIGH GLOSS - 400 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 24.04.2023

 10.1
 27.07.2023
 10656969-00014
 Date of first issue: 11.06.2010

		weight (d.w.)
	Oral (Secondary Poisoning)	380 mg/kg food
Butyl glycollate	Fresh water	0,05 mg/l
	Marine water	0,005 mg/l
	Intermittent use/release	0,5 mg/l
	Sewage treatment plant	232 mg/l
	Fresh water sediment	0,203 mg/kg
	Marine sediment	0,0203 mg/kg
	Soil	0,0112 mg/kg
Xylene	Fresh water	0,327 mg/l
	Intermittent use/release	0,327 mg/l
	Marine water	0,327 mg/l
	Sewage treatment plant	6,58 mg/l
	Fresh water sediment	12,46 mg/kg dry weight (d.w.)
	Marine sediment	12,46 mg/kg dry weight (d.w.)
	Soil	2,31 mg/kg dry weight (d.w.)

8.2 Exposure controls

Engineering measures

Minimize workplace exposure concentrations.

If sufficient ventilation is unavailable, use with local exhaust ventilation.

If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Personal protective equipment

Eye/face protection : Wear the following personal protective equipment:

Safety goggles

Equipment should conform to DIN EN 166

Hand protection

Material : butyl-rubber
Break through time : < 15 min
Glove thickness : 0,7 mm

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Wear the following personal protective equipment:

If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY SPECIAL CLEAR VARNISH HIGH GLOSS - 400 ML

Version Revision Date: SDS Number: Date of last issue: 24.04.2023 10.1 27.07.2023 10656969-00014 Date of first issue: 11.06.2010

protective clothing.

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

Respiratory protection : If adequate local exhaust ventilation is not available or expo-

sure assessment demonstrates exposures outside the rec-

ommended guidelines, use respiratory protection.

Equipment should conform to DIN EN 137

Filter type : Self-contained breathing apparatus

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : aerosol

Propellant : Butane, Isobutane, Propane

Colour : colourless

Odour : solvent-like

Odour Threshold : No data available

Melting point/freezing point : Decomposes before melting.

Initial boiling point and boiling

range

Not applicable

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper

flammability limit

13,0 %(V)

Lower explosion limit / Lower

flammability limit

1,7 %(V)

Flash point : < 0 °C

Method: DIN 51755 Part 2, closed cup

Flash point is only valid for liquid portion in the aerosol can.

Auto-ignition temperature : 365 °C

Decomposition temperature : The substance or mixture is not classified self-reactive.

pH : substance/mixture is non-polar/aprotic

Viscosity

Viscosity, kinematic : Not applicable

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY SPECIAL CLEAR VARNISH HIGH GLOSS - 400 ML

Version Revision Date: SDS Number: Date of last issue: 24.04.2023 10.1 27.07.2023 10656969-00014 Date of first issue: 11.06.2010

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

Not applicable

Vapour pressure : 3.600 hPa (20 °C)

Relative density : 0,8 (23 °C)

Reference substance: Water

Relative vapour density : Not applicable

Particle characteristics

Particle size : Not applicable

9.2 Other information

Explosives : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Evaporation rate : Not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Extremely flammable aerosol.

Vapours may form explosive mixture with air.

If the temperature rises there is danger of the vessels bursting

due to the high vapor pressure.

Can react with strong oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY SPECIAL CLEAR VARNISH HIGH GLOSS - 400 ML

Version Revision Date: SDS Number: Date of last issue: 24.04.2023 10.1 27.07.2023 10656969-00014 Date of first issue: 11.06.2010

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of:

exposure

Inhalation Skin contact Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg

Method: Calculation method

Components:

Acetone:

Acute oral toxicity : LD50 (Rat): 5.800 mg/kg

Acute inhalation toxicity : LC50 (Rat): 76 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 7.426 mg/kg

n-Butyl acetate:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 21,1 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

2-Methoxy-1-methylethyl acetate:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC0 (Rat): 9,48 mg/l

Exposure time: 4 h
Test atmosphere: vapour

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY SPECIAL CLEAR VARNISH HIGH GLOSS - 400 ML

Version **Revision Date:** SDS Number: Date of last issue: 24.04.2023 10.1 27.07.2023 10656969-00014 Date of first issue: 11.06.2010

Acute dermal toxicity LD50 (Rat): > 5.000 mg/kg

Xylene:

Acute oral toxicity LD50 (Rat): 3.523 mg/kg

Method: Directive 67/548/EEC, Annex V, B.1.

Acute toxicity estimate: 11 mg/l Acute inhalation toxicity

> Exposure time: 4 h Test atmosphere: vapour Method: Expert judgement

Remarks: Based on national or regional regulation.

Acute dermal toxicity Acute toxicity estimate: 1.100 mg/kg

Method: Expert judgement

Remarks: Based on national or regional regulation.

Ethanol:

Acute oral toxicity LD50 (Rat): > 5.000 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity LC50 (Rat): 124,7 mg/l

Exposure time: 4 h

Test atmosphere: vapour

Butanone:

LD50 (Rat): > 2.000 - 5.000 mg/kgAcute oral toxicity

Remarks: Based on data from similar materials

Acute inhalation toxicity LC50 (Rat): > 25,5 mg/l

> Exposure time: 4 h Test atmosphere: vapour

Method: OECD Test Guideline 436

Remarks: Based on data from similar materials

Acute dermal toxicity LD50 (Rabbit): > 5.000 mg/kg

Butyl glycollate:

Acute oral toxicity : LD50 (Rat): 4.595 mg/kg

Acute inhalation toxicity LC0 (Rat): >= 6.2 mg/l

Exposure time: 4 h Test atmosphere: vapour

Ethylbenzene:

LD50 (Rat): 3.500 mg/kg Acute oral toxicity

Acute inhalation toxicity LC50 (Rat): 17,8 mg/l

Exposure time: 4 h

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY SPECIAL CLEAR VARNISH HIGH GLOSS - 400 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 24.04.2023

 10.1
 27.07.2023
 10656969-00014
 Date of first issue: 11.06.2010

Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Components:

Acetone:

Assessment : Repeated exposure may cause skin dryness or cracking.

n-Butyl acetate:

Species : Rabbit

Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

2-Methoxy-1-methylethyl acetate:

Species : Rabbit

Result : No skin irritation

Xylene:

Species : Rabbit Result : Skin irritation

Ethanol:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Butanone:

Assessment : Repeated exposure may cause skin dryness or cracking.

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Remarks : Based on data from similar materials

Butyl glycollate:

Species : Rabbit

Result : No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY SPECIAL CLEAR VARNISH HIGH GLOSS - 400 ML

Version Revision Date: SDS Number: Date of last issue: 24.04.2023 10.1 27.07.2023 10656969-00014 Date of first issue: 11.06.2010

Components:

Acetone:

Species : Rabbit

Method : OECD Test Guideline 405

Result : Irritation to eyes, reversing within 21 days

n-Butyl acetate:

Species : Rabbit

Method : OECD Test Guideline 405

Result : No eye irritation

2-Methoxy-1-methylethyl acetate:

Species : Rabbit

Result : No eye irritation

Xylene:

Species : Rabbit

Result : Irritation to eyes, reversing within 21 days

Ethanol:

Species : Rabbit

Method : OECD Test Guideline 405

Result : Irritation to eyes, reversing within 21 days

Butanone:

Species : Rabbit

Method : OECD Test Guideline 405

Result : Irritation to eyes, reversing within 21 days

Butyl glycollate:

Species : Rabbit

Result : Irreversible effects on the eye

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Acetone:

Test Type : Maximisation Test Exposure routes : Skin contact

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY SPECIAL CLEAR VARNISH HIGH GLOSS - 400 ML

Version Revision Date: SDS Number: Date of last issue: 24.04.2023 10.1 27.07.2023 10656969-00014 Date of first issue: 11.06.2010

Species : Guinea pig Result : negative

n-Butyl acetate:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative

2-Methoxy-1-methylethyl acetate:

Test Type : Maximisation Test Exposure routes : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

Xylene:

Test Type : Local lymph node assay (LLNA)

Exposure routes : Skin contact
Species : Mouse
Result : negative

Ethanol:

Test Type : Local lymph node assay (LLNA)

Exposure routes : Skin contact
Species : Mouse
Result : negative

Butanone:

Test Type : Buehler Test Exposure routes : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

Butyl glycollate:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

Germ cell mutagenicity

Not classified based on available information.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY SPECIAL CLEAR VARNISH HIGH GLOSS - 400 ML

Version Revision Date: SDS Number: Date of last issue: 24.04.2023 10.1 27.07.2023 10656969-00014 Date of first issue: 11.06.2010

Components:

Acetone:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Result: negative

Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: Chromosome aberration test in vitro

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Ingestion

Result: negative

n-Butyl acetate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

2-Methoxy-1-methylethyl acetate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: DNA damage and repair, unscheduled DNA syn-

thesis in mammalian cells (in vitro)

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: negative

Remarks: Based on data from similar materials

Xylene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: Chromosome aberration test in vitro

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: negative

Test Type: In vitro sister chromatid exchange assay in mam-

malian cells Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY SPECIAL CLEAR VARNISH HIGH GLOSS - 400 ML

Version Revision Date: SDS Number: Date of last issue: 24.04.2023 10.1 27.07.2023 10656969-00014 Date of first issue: 11.06.2010

Species: Mouse

Application Route: Skin contact

Result: negative

Ethanol:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Result: negative

Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)

Species: Mouse

Application Route: Ingestion

Result: equivocal

Butanone:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: negative

Test Type: Chromosome aberration test in vitro

Result: negative

Test Type: DNA damage and repair, unscheduled DNA syn-

thesis in mammalian cells (in vitro)

Result: negative

Test Type: Saccharomyces cerevisiae, gene mutation assay

(in vitro)

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection

Result: negative

Butyl glycollate:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY SPECIAL CLEAR VARNISH HIGH GLOSS - 400 ML

Version Revision Date: SDS Number: Date of last issue: 24.04.2023 10.1 27.07.2023 10656969-00014 Date of first issue: 11.06.2010

> Test Type: Mouse Lymphoma Method: OECD Test Guideline 476

Result: negative

Ethylbenzene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Test Type: Chromosome aberration test in vitro

Result: negative

Genotoxicity in vivo : Test Type: Unscheduled DNA synthesis (UDS) test with

mammalian liver cells in vivo

Species: Mouse

Application Route: Inhalation Method: OECD Test Guideline 486

Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Acetone:

Species : Mouse
Application Route : Skin contact
Exposure time : 424 days
Result : negative

2-Methoxy-1-methylethyl acetate:

Species : Rat

Application Route : inhalation (vapour)

Exposure time : 2 Years
Result : negative

Remarks : Based on data from similar materials

Xylene:

Species : Rat
Application Route : Ingestion
Exposure time : 103 weeks
Result : negative

Ethylbenzene:

Species : Rat

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY SPECIAL CLEAR VARNISH HIGH GLOSS - 400 ML

Version Revision Date: SDS Number: Date of last issue: 24.04.2023 10.1 27.07.2023 10656969-00014 Date of first issue: 11.06.2010

Application Route : inhalation (vapour)

Exposure time : 104 weeks Result : positive

Remarks : The mechanism or mode of action may not be relevant in hu-

mans.

Reproductive toxicity

Not classified based on available information.

Components:

Acetone:

Effects on fertility : Test Type: One-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion

Result: negative

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: inhalation (vapour)

Result: negative

n-Butyl acetate:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: inhalation (vapour) Method: OECD Test Guideline 416

Result: negative

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: inhalation (vapour)

Result: negative

2-Methoxy-1-methylethyl acetate:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: inhalation (vapour) Method: OECD Test Guideline 416

Result: negative

Remarks: Based on data from similar materials

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: inhalation (vapour)

Result: negative

Xylene:

Effects on fertility : Test Type: One-generation reproduction toxicity study

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY SPECIAL CLEAR VARNISH HIGH GLOSS - 400 ML

Version Revision Date: SDS Number: Date of last issue: 24.04.2023 10.1 27.07.2023 10656969-00014 Date of first issue: 11.06.2010

Species: Rat

Application Route: inhalation (vapour)

Result: negative

Effects on foetal develop-

ment

: Test Type: Embryo-foetal development

Species: Rat

Application Route: inhalation (vapour)

Result: negative

Ethanol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Mouse

Application Route: Ingestion

Result: negative

Butanone:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: Inhalation Method: OECD Test Guideline 414

Result: negative

Butyl glycollate:

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 414

Result: positive

Reproductive toxicity - As-

sessment

Some evidence of adverse effects on sexual function and

fertility, and/or on development, based on animal experiments.

Ethylbenzene:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: inhalation (vapour) Method: OECD Test Guideline 416

Result: negative

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: Inhalation Method: OECD Test Guideline 414

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY SPECIAL CLEAR VARNISH HIGH GLOSS - 400 ML

Version Revision Date: SDS Number: Date of last issue: 24.04.2023 10.1 27.07.2023 10656969-00014 Date of first issue: 11.06.2010

Result: negative

STOT - single exposure

May cause drowsiness or dizziness.

Components:

Acetone:

Assessment : May cause drowsiness or dizziness.

n-Butyl acetate:

Assessment : May cause drowsiness or dizziness.

2-Methoxy-1-methylethyl acetate:

Assessment : May cause drowsiness or dizziness.

Xylene:

Assessment : May cause respiratory irritation.

Butanone:

Assessment : May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Components:

Xylene:

Exposure routes : inhalation (vapour)
Target Organs : Auditory system

Assessment : Shown to produce significant health effects in animals at con-

centrations of >0.2 to 1 mg/l/6h/d.

Ethylbenzene:

Exposure routes : inhalation (vapour)
Target Organs : Auditory system

Assessment : Shown to produce significant health effects in animals at con-

centrations of >0.2 to 1 mg/l/6h/d.

Repeated dose toxicity

Components:

Acetone:

 Species
 : Rat

 NOAEL
 : 900 mg/kg

 LOAEL
 : 1.700 mg/kg

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY SPECIAL CLEAR VARNISH HIGH GLOSS - 400 ML

Version Revision Date: SDS Number: Date of last issue: 24.04.2023 10.1 27.07.2023 10656969-00014 Date of first issue: 11.06.2010

Application Route : Ingestion Exposure time : 90 Days

Species : Rat NOAEL : 45 mg/l

Application Route : inhalation (vapour)

Exposure time : 8 Weeks

n-Butyl acetate:

Species : Rat NOAEL : 2,4 mg/l

Application Route : inhalation (vapour)

Exposure time : 90 Days

2-Methoxy-1-methylethyl acetate:

Species : Rat

NOAEL : > 1.000 mg/kg
Application Route : Ingestion
Exposure time : 41 - 45 Days

Method : OECD Test Guideline 422

Species : Mouse NOAEL : 1,62 mg/l

Application Route : inhalation (vapour)

Exposure time : 2 yr

Remarks : Based on data from similar materials

Species : Rabbit

NOAEL : > 1.838 mg/kg
Application Route : Skin contact
Exposure time : 90 Days

Remarks : Based on data from similar materials

Xylene:

Species : Rat

LOAEL : > 0,2 - 1 mg/l
Application Route : inhalation (vapour)

Exposure time : 13 Weeks

Remarks : Based on data from similar materials

Species : Rat

LOAEL : 150 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Ethanol:

Species : Rat

NOAEL : 1.280 mg/kg LOAEL : 3.156 mg/kg

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY SPECIAL CLEAR VARNISH HIGH GLOSS - 400 ML

Version Revision Date: SDS Number: Date of last issue: 24.04.2023 10.1 27.07.2023 10656969-00014 Date of first issue: 11.06.2010

Application Route : Ingestion Exposure time : 90 Days

Butanone:

Species : Rat NOAEL : 14,84 mg/l

Application Route : inhalation (vapour)

Exposure time : 90 Days

Method : OECD Test Guideline 413

Butyl glycollate:

Species : Rat

NOAEL : 1.000 mg/kg
Application Route : Ingestion
Exposure time : 29 Days

Method : OECD Test Guideline 407

Ethylbenzene:

Species : Rat LOAEL : 0,868 mg/l

Application Route : inhalation (vapour)

Exposure time : 13 Weeks

Species : Rat

NOAEL : 75 mg/kg

LOAEL : 250 mg/kg

Application Route : Ingestion

Method : OECD Test Guideline 408

Aspiration toxicity

Not classified based on available information.

Components:

Acetone:

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

Xylene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Butanone:

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY SPECIAL CLEAR VARNISH HIGH GLOSS - 400 ML

Version Revision Date: SDS Number: Date of last issue: 24.04.2023 10.1 27.07.2023 10656969-00014 Date of first issue: 11.06.2010

Ethylbenzene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Acetone:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 5.540 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia pulex (Water flea)): 8.800 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

NOEC (Pseudokirchneriella subcapitata (green algae)): 7.000

mg/l

Exposure time: 96 h

Toxicity to microorganisms : EC50 : 61.150 mg/l

Exposure time: 30 min Method: ISO 8192

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

NOEC: >= 79 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

n-Butyl acetate:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 18 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia sp. (water flea)): 44 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic : ErC50 (Pseudokirchneriella subcapitata (green algae)): 397

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY SPECIAL CLEAR VARNISH HIGH GLOSS - 400 ML

Version Revision Date: SDS Number: Date of last issue: 24.04.2023 10.1 27.07.2023 10656969-00014 Date of first issue: 11.06.2010

plants mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): 196

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l

Exposure time: 40 h

Toxicity to daphnia and other : aquatic invertebrates (Chron-

aquatic invertebrates (Chronic toxicity)

NOEC: 23,2 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

Remarks: Based on data from similar materials

2-Methoxy-1-methylethyl acetate:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 - 180

mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 500 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

ErC50 (Pseudokirchneriella subcapitata (green algae)): >

1.000 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (algae)): > 1.000 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 201

Toxicity to microorganisms : EC10 : > 1.000 mg/l

Exposure time: 0,5 h

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC: >= 100 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Method: OECD Test Guideline 211

Xylene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 13,5 mg/l

Exposure time: 96 h

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY SPECIAL CLEAR VARNISH HIGH GLOSS - 400 ML

Version Revision Date: SDS Number: Date of last issue: 24.04.2023 10.1 27.07.2023 10656969-00014 Date of first issue: 11.06.2010

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 1 - 10 mg/l

Exposure time: 24 h

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

EC50 (Skeletonema costatum (marine diatom)): 10 mg/l

Exposure time: 72 h

Toxicity to microorganisms : NOEC : > 100 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Remarks: Based on data from similar materials

Toxicity to fish (Chronic tox-

icity)

NOEC: > 0,1 - < 1 mg/l Exposure time: 35 d

Species: Danio rerio (zebra fish) Method: OECD Test Guideline 210

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

EL10: > 1 - 10 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

Remarks: Based on data from similar materials

Ethanol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 1.000 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Ceriodaphnia (water flea)): > 1.000 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

ErC50 (Chlorella vulgaris (Fresh water algae)): 275 mg/l

Exposure time: 72 h

EC10 (Chlorella vulgaris (Fresh water algae)): 11,5 mg/l

Exposure time: 72 h

Toxicity to microorganisms : EC50 (Pseudomonas putida): 6.500 mg/l

Exposure time: 16 h

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC: 9,6 mg/l Exposure time: 9 d

Species: Daphnia magna (Water flea)

Butanone:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2.993 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY SPECIAL CLEAR VARNISH HIGH GLOSS - 400 ML

Version Revision Date: SDS Number: Date of last issue: 24.04.2023 10.1 27.07.2023 10656969-00014 Date of first issue: 11.06.2010

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 308 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

ErC50 (Pseudokirchneriella subcapitata (green algae)): 2.029

mg/l

Exposure time: 96 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 1.240

mg/l

Exposure time: 96 h

Method: OECD Test Guideline 201

Butyl glycollate:

Toxicity to fish : LC0 (Leuciscus idus (Golden orfe)): >= 50 mg/l

Exposure time: 48 h Method: DIN 38412

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 280 mg/l

Exposure time: 24 h Method: DIN 38412

Toxicity to algae/aquatic

plants

EC10 (Lemna gibba (gibbous duckweed)): > 87,4 mg/l

Exposure time: 7 d

Toxicity to microorganisms : EC50 (Pseudomonas putida): 2.320 mg/l

Exposure time: 18 h

Ethylbenzene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 4,2 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 1,8 - 2,4 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 3,6

mg/l

Exposure time: 96 h

NOEC (Pseudokirchneriella subcapitata (green algae)): 3,4

mg/l

Exposure time: 96 h

Toxicity to microorganisms : EC50 (Nitrosomonas sp.): 96 mg/l

Exposure time: 24 h

Toxicity to daphnia and other : aquatic invertebrates (Chron-

NOEC: 0,96 mg/l Exposure time: 7 d

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY SPECIAL CLEAR VARNISH HIGH GLOSS - 400 ML

Version Revision Date: SDS Number: Date of last issue: 24.04.2023 10.1 27.07.2023 10656969-00014 Date of first issue: 11.06.2010

ic toxicity) Species: Ceriodaphnia dubia (water flea)

12.2 Persistence and degradability

Components:

Acetone:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 91 % Exposure time: 28 d

n-Butyl acetate:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 83 % Exposure time: 28 d

Method: OECD Test Guideline 301D

2-Methoxy-1-methylethyl acetate:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 90 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Xylene:

Biodegradability : Result: Readily biodegradable.

Biodegradation: > 70 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Remarks: Based on data from similar materials

Ethanol:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 84 % Exposure time: 20 d

Butanone:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 98 % Exposure time: 28 d

Method: OECD Test Guideline 301D

Butyl glycollate:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 81 % Exposure time: 28 d

Method: OECD Test Guideline 301B

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY SPECIAL CLEAR VARNISH HIGH GLOSS - 400 ML

Version Revision Date: SDS Number: Date of last issue: 24.04.2023 10.1 27.07.2023 10656969-00014 Date of first issue: 11.06.2010

Ethylbenzene:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 70 - 80 %

Exposure time: 28 d

12.3 Bioaccumulative potential

Components:

Acetone:

Partition coefficient: n-

octanol/water

log Pow: -0,27 - -0,23

n-Butyl acetate:

Partition coefficient: n-

octanol/water

log Pow: 2,3

2-Methoxy-1-methylethyl acetate:

Partition coefficient: n-

octanol/water

: log Pow: 1,2

Xylene:

Partition coefficient: n-

octanol/water

log Pow: 3,16

Remarks: Calculation

Ethanol:

Partition coefficient: n-

octanol/water

log Pow: -0,35

Butanone:

Partition coefficient: n-

log Pow: 0,3

octanol/water

Ethylbenzene:

Partition coefficient: n-

octanol/water

log Pow: 3,6

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY SPECIAL CLEAR VARNISH HIGH GLOSS - 400 ML

Version Revision Date: SDS Number: Date of last issue: 24.04.2023 10.1 27.07.2023 10656969-00014 Date of first issue: 11.06.2010

0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.

According to the European Waste Catalogue, Waste Codes

are not product specific, but application specific.

Waste codes should be assigned by the user, preferably in

discussion with the waste disposal authorities.

Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product. Please ensure aerosol cans are sprayed completely empty

(including propellant)

Waste Code : The following Waste Codes are only suggestions:

used product

16 05 04, gases in pressure containers (including halons)

containing hazardous substances

08 01 11, waste paint and varnish containing organic solvents

or other hazardous substances

unused product

16 05 04, gases in pressure containers (including halons)

containing hazardous substances

08 01 11, waste paint and varnish containing organic solvents

or other hazardous substances

uncleaned packagings

15 01 10, packaging containing residues of or contaminated

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY SPECIAL CLEAR VARNISH HIGH GLOSS - 400 ML

Version Revision Date: SDS Number: Date of last issue: 24.04.2023 10.1 27.07.2023 10656969-00014 Date of first issue: 11.06.2010

by hazardous substances

Acc. Packaging Act properly emptied packaging: Properly emptied, non-contaminated packaging of nonhazardous products can be supplied to a system for the col-

Subsidiary risks

lection of sales packaging.

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 1950
ADR : UN 1950
RID : UN 1950
IMDG : UN 1950
IATA : UN 1950

14.2 UN proper shipping name

ADN : AEROSOLS
ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS

IATA : Aerosols, flammable

14.3 Transport hazard class(es)

ADN : 2 2.1
ADR : 2 2.1
RID : 2 2.1
IMDG : 2.1

Class

IATA : 2.1

14.4 Packing group

ADN

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1

ADR

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1 Tunnel restriction code : (D)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY SPECIAL CLEAR VARNISH HIGH GLOSS - 400 ML

Version Revision Date: SDS Number: Date of last issue: 24.04.2023 10.1 27.07.2023 10656969-00014 Date of first issue: 11.06.2010

RID

Packing group : Not assigned by regulation

Classification Code : 5F Hazard Identification Number : 23 Labels : 2.1

IMDG

Packing group : Not assigned by regulation

Labels : 2.1 EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo : 203

aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

IATA (Passenger)

Packing instruction (passen: 203

ger aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on : Conditions of restriction for the fol-

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY SPECIAL CLEAR VARNISH HIGH GLOSS - 400 ML

Version Revision Date: SDS Number: Date of last issue: 24.04.2023 10.1 27.07.2023 10656969-00014 Date of first issue: 11.06.2010

the market and use of certain dangerous substances,

mixtures and articles (Annex XVII)

lowing entries should be considered:

Number on list 75

If you intend to use this product as tattoo ink, please contact your ven-

dor.

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

Not applicable

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors

This product is regulated by Regulation (EU) 2019/1148: all suspi- Acetone (ANNEX II) cious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Quantity 1 Quantity 2
P3a FLAMMABLE AEROSOLS 150 t 500 t

18 Liquefied flammable gases 50 t 200 t

(including LPG) and natural

gas

Water hazard class (Germa-

ny)

WGK 1 slightly hazardous to water

Classification according to AwSV, Annex 1 (5.2)

Volatile organic compounds : Directive 2004/42/EC

VOC content in g/l: 699,84 g/l

Product sub-category: Special finishes

Coatings: All types

VOC limit level 1 (2007): 840 g/l

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 87,48 %, 699,84

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY SPECIAL CLEAR VARNISH HIGH GLOSS - 400 ML

Version Revision Date: SDS Number: Date of last issue: 24.04.2023 10.1 27.07.2023 10656969-00014 Date of first issue: 11.06.2010

g/l

Remarks: VOC content excluding water

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Other information : Items where changes have been made to the previous version

are highlighted in the body of this document by two vertical

lines.

Full text of H-Statements

H225 : Highly flammable liquid and vapour.
H226 : Flammable liquid and vapour.

H304 : May be fatal if swallowed and enters airways.

H312 : Harmful in contact with skin. H315 : Causes skin irritation.

H318 : Causes serious eye damage. H319 : Causes serious eye irritation.

H332 : Harmful if inhaled.

H335 : May cause respiratory irritation. H336 : May cause drowsiness or dizziness.

H361 : Suspected of damaging fertility or the unborn child.

H373 : May cause damage to organs through prolonged or repeated

exposure.

H412 : Harmful to aquatic life with long lasting effects.

EUH066 : Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard Eye Dam. : Serious eye damage

Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Repr. : Reproductive toxicity

Skin Irrit. : Skin irritation

STOT RE : Specific target organ toxicity - repeated exposure STOT SE : Specific target organ toxicity - single exposure

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values

2019/1831/EU : Europe. Commission Directive 2019/1831/EU establishing a

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY SPECIAL CLEAR VARNISH HIGH GLOSS - 400 ML

Version Revision Date: SDS Number: Date of last issue: 24.04.2023 10.1 27.07.2023 10656969-00014 Date of first issue: 11.06.2010

fifth list of indicative occupational exposure limit values

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

TRGS 903 : TRGS 903 - Biological limit values

2000/39/EC / TWA : Limit Value - eight hours 2000/39/EC / STEL : Short term exposure limit 2019/1831/EU / TWA : Limit Value - eight hours 2019/1831/EU / STEL : Short term exposure limit DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada): ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to : compile the Safety Data

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

Sheet cy, http://echa.europa.eu/

Classification of the mixture: Classification procedure:

Aerosol 1 H222, H229 Based on product data or assessment

Eye Irrit. 2 H319 Calculation method

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY SPECIAL CLEAR VARNISH HIGH GLOSS - 400 ML

Version Revision Date: SDS Number: Date of last issue: 24.04.2023 10.1 27.07.2023 10656969-00014 Date of first issue: 11.06.2010

STOT SE 3 H336 Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN