

Version	Revision Date:	SDS Number:	Date of last issue: 28.07.2023
5.1	07.09.2023	10648248-00017	Date of first issue: 26.07.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name	:	LACQUER SPRAY QUATTRO RAL 6002 LEAF GREEN - 400 ML
Product code	:	0893396002
Unique Formula Identifier (UFI)	:	RFD1-900Y-600E-J79W

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- stance/Mixture	:	Paint Professional use product
Recommended restrictions on use	:	Not applicable

1.3 Details of the supplier of the safety data sheet

Company	:	Adolf Wuerth GmbH & Co. KG Reinhold-Würth-Str. 12-17 74653 Künzelsau
Telephone	:	+49 794015 0
Telefax	:	+49 794015 10 00
E-mail address of person responsible for the SDS	:	isi@wuerth.com

1.4 Emergency telephone number

+49 (0)6132 - 84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)					
Aerosols, Category 1	H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated.				
Specific target organ toxicity - single ex-	H336: May cause drowsiness or dizziness.				



Version 5.1	Revision Date: 07.09.2023		DS Num 0648248		Date of last issue: 28.07.2023 Date of first issue: 26.07.2018
posure	, Category 3				
2.2 Label e	lements				
	ing (REGULATION (E	: :	No 1272	2/2008)	
Signal	word	:	Dange	r	
Hazaro	statements	:	H222 H229 H336	Pressurise	flammable aerosol. d container: May burst if heated. e drowsiness or dizziness.
Precautionary statements :		:	 Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source P251 Do not pierce or burn, even after use. P261 Avoid breathing spray. P271 Use only outdoors or in a well-ventilated area. Storage: P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. 		

Hazardous components which must be listed on the label:

Dimethyl ether n-Butyl acetate

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



Version	Revision Date:	SDS Number:	Date of last issue: 28.07.2023
5.1	07.09.2023	10648248-00017	Date of first issue: 26.07.2018

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Components			
Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Dimethyl ether	115-10-6 204-065-8 603-019-00-8 01-2119472128-37	Flam. Gas 1A; H220 Press. Gas Liquefied gas; H280 STOT SE 3; H336	>= 30 - < 50
n-Butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 EUH066	>= 20 - < 30
Xylene	1330-20-7 215-535-7 601-022-00-9 01-2119488216-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 STOT RE 2; H373 (Auditory system) Asp. Tox. 1; H304 Aquatic Chronic 3; H412 Acute toxicity esti- mate Acute inhalation tox- icity (vapour): 11 mg/l Acute dermal toxicity: 1 100 mg/kg	>= 2,5 - < 10
Ethylbenzene	100-41-4 202-849-4 601-023-00-4	1.100 mg/kgFlam. Liq. 2; H225Acute Tox. 4; H332STOT RE 2; H373(Auditory system)Asp. Tox. 1; H304Aquatic Chronic 3;H412Acute toxicity estimateAcute inhalation toxicity (vapour): 17,8	>= 1 - < 2,5

For explanation of abbreviations see section 16.



Version	Revision Date:	SDS Number:	Date of last issue: 28.07.2023
5.1	07.09.2023	10648248-00017	Date of first issue: 26.07.2018

SECTION 4: First aid measures

4.1 Description of first aid measures				
General advice	:	In the case of accident or if you feel unwell, seek medical ad- vice immediately. When symptoms persist or in all cases of doubt seek medical advice.		
Protection of first-aiders	:	First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).		
If inhaled	:	If inhaled, remove to fresh air. Get medical attention.		
In case of skin contact	:	In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.		
In case of eye contact	:	Flush eyes with water as a precaution. Get medical attention if irritation develops and persists.		
If swallowed	:	If swallowed, DO NOT induce vomiting. Get medical attention if symptoms occur. Rinse mouth thoroughly with water.		
4.2 Most important symptoms and effects, both acute and delayed				
Risks	:	May cause drowsiness or dizziness.		

4.3 Indication of any immediate medical attention and special treatment needed Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media		
Suitable extinguishing media	:	Water spray Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	:	None known.



Versi 5.1	ion	Revision Date: 07.09.2023		OS Number: 648248-00017	Date of last issue: 28.07.2023 Date of first issue: 26.07.2018	
5.2 S	special	hazards arising from	the	substance or mi	kture	
Specific hazards during fire- fighting		:	Flash back possible over considerable distance. Vapours may form explosive mixtures with air. Exposure to combustion products may be a hazard to health. If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.			
	Hazard ucts	ous combustion prod-	:	Carbon oxides Nitrogen oxides (I Metal oxides Chlorine compour		
5.3 A	dvice	for firefighters				
	Specia for firef	l protective equipment ighters	:		e, wear self-contained breathing apparatus. ective equipment.	
	Specifi ods	c extinguishing meth-	:	cumstances and t Use water spray t	measures that are appropriate to local cir- he surrounding environment. o cool unopened containers. ged containers from fire area if it is safe to do	

SECTION 6: Accidental release measures

6.1 Personal precautions, prote	ctive equipment and emergency procedures
Personal precautions	 Remove all sources of ignition. Use personal protective equipment. Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
6.2 Environmental precautions	
Environmental precautions	 Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g. by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.
6.3 Methods and material for co	ntainment and cleaning up
Methods for cleaning up	: Non-sparking tools should be used. Soak up with inert absorbent material.

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 6002 LEAF GREEN - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 28.07.2023
5.1	07.09.2023	10648248-00017	Date of first issue: 26.07.2018
		Clean up remain bent. Local or nationa posal of this ma employed in the mine which regu Sections 13 and	re recovered material in appropriate container. hing materials from spill with suitable absor- al regulations may apply to releases and dis- terial, as well as those materials and items cleanup of releases. You will need to deter- ulations are applicable. I 15 of this SDS provide information regarding hational requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures :	See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
Local/Total ventilation :	If sufficient ventilation is unavailable, use with local exhaust ventilation. If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventila- tion.
Advice on safe handling :	Do not get on skin or clothing. Do not breathe spray. Do not swallow. Avoid contact with eyes. Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as- sessment Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharges. Take care to prevent spills, waste and minimize release to the environment. Do not spray on an open flame or other ignition source. Do not breathe decomposition products.
Hygiene measures :	If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contami- nated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage	:	Store locked up. Keep in a cool, well-ventilated place. Store in
areas and containers		accordance with the particular national regulations. Do not



Vers 5.1	sion	Revision Date: 07.09.2023)S Number: 648248-00017	Date of last issue: 28.07.2023 Date of first issue: 26.07.2018
				pierce or burn, ev light.	ven after use. Keep cool. Protect from sun-
	Advice	on common storage	:	Self-reactive sub- Organic peroxide Oxidizing agents Flammable solids Pyrophoric liquids Pyrophoric solids Self-heating subs	s s stances and mixtures mixtures, which in contact with water, emit
	Storage	e class (TRGS 510)	:	2B	
7.3	-	c end use(s)		N. Isters - Malle	
	Specifi	c use(s)	:	No data available	

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis		
Dimethyl ether	115-10-6	TWA	1.000 ppm 1.920 mg/m3	2000/39/EC		
	Further inform	nation: Indicative				
		AGW	1.000 ppm 1.900 mg/m3	DE TRGS 900		
	Peak-limit: ex	cursion factor (categ	ory): 8;(II)			
n-Butyl acetate	123-86-4	STEL	150 ppm 723 mg/m3	2019/1831/E U		
	Further inform	Further information: Indicative				
		TWA	50 ppm 241 mg/m3	2019/1831/E U		
	Further inform	nation: Indicative	· · · · · · ·	•		
		AGW	62 ppm 300 mg/m3	DE TRGS 900		
	Peak-limit: ex	cursion factor (categ	ory): 2;(l)			
			compliance with the OEL ar	nd biological		
Titanium dioxide	13463-67-7	AGW (Inhalable fraction)	10 mg/m3 (Titanium dioxide)	DE TRGS 900		
	Peak-limit: ex	cursion factor (categ	ory): 2;(II)			

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by



Commission Regulation (EU) 2020/878

LACQUER SPRAY QUATTRO RAL 6002 LEAF **GREEN - 400 ML**

ersion 1	Revision Da 07.09.2023		S Number: 48248-00017	Date of last issue: 28.07.20 Date of first issue: 26.07.20				
-	0.10012020							
				ere is compliance with the OE				
		tolerance va		risk of harming the unborn ch				
			AGW (Alveola		DE TRGS			
			fraction)	(Titanium dioxide)	900			
		Peak-limit: e	xcursion factor (category): 2;(II)				
		Further infor	mation: When th	ere is compliance with the OE	L and biological			
		tolerance va	lues, there is no	risk of harming the unborn ch	ild			
Xylene	Э	1330-20-7	TWA	50 ppm	2000/39/EC			
				221 mg/m3				
		Further infor	mation: Identifie	s the possibility of significant u	ptake through the			
		skin, Indicative						
		,	STEL	100 ppm	2000/39/EC			
			•••==	442 mg/m3				
	Further information: Identifies the possibility of significant uptake through the							
		skin, Indicative						
			AGW	50 ppm	DE TRGS			
				220 mg/m3	900			
		Peak-limit: excursion factor (category): 2;(II)						
			mation: Skin abs					
Ethylb	enzene	100-41-4	TWA	100 ppm	2000/39/EC			
,				442 mg/m3				
		Further information: Identifies the possibility of significant uptake through the skin, Indicative						
			STEL	200 ppm	2000/39/EC			
				884 mg/m3				
		Further information: Identifies the possibility of significant uptake through the						
		skin, Indicati	ve					
			AGW	20 ppm	DE TRGS			
				88 mg/m3	900			
		Peak-limit: e	xcursion factor (
				sorption, When there is compli	ance with the OEL			
		and biological tolerance values, there is no risk of harming the unborn child						

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis		
Formaldehyde	50-00-0	TWA	0,3 ppm 0,37 mg/m3	2004/37/EC		
	Further inform	nation: Dermal sensit	isation, Carcinogens or muta	agens		
		STEL	0,6 ppm	2004/37/EC		
			0,74 mg/m3			
	Further inform	Further information: Dermal sensitisation, Carcinogens or mutagens				
		AGW	0,3 ppm	DE TRGS		
			0,37 mg/m3	900		
	Peak-limit: ex	cursion factor (categ	ory): 2;(I)			
	activity or pro	cedure according to	substance Cat. 1A or 1B or 0 § 2 (3) No. 4 of the Hazardou	us Substances		
			toffV must be observed, Wh ogical tolerance values, there			

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by



Commission Regulation (EU) 2020/878

LACQUER SPRAY QUATTRO RAL 6002 LEAF GREEN - 400 ML

Version 5.1	Revision Date 07.09.2023		5 Number: 48248-00017	Date of last issue: Date of first issue:		
L		harming the	unborn child, Sub	stance sensitizing t	hrough the sk	in
Metha	anol	67-56-1	TWA	200 ppm 260 mg/m3		2006/15/EC
		Further infor through the s		, Identifies the poss	ibility of signif	icant uptake
			AGW	100 ppm 130 mg/m3		DE TRGS 900
		Peak-limit: e	xcursion factor (ca	ategory): 2;(II)		
				rption, When there s, there is no risk of		

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Xylene	1330-20-7	methylhippuric acid (all isomers): 2.000 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903
Ethylbenzene	100-41-4	mandelic acid + phenylglyoxylic acid: 250 mg/g creatinine (Urine)	Immediately after exposure or after working hours	TRGS 903

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health ef-	Value
	Lind USC	Exposure routes	fects	Value
Xylene	Workers	Inhalation	Long-term systemic effects	221 mg/m3
	Workers	Inhalation	Acute systemic ef-	442 mg/m3
	WOIKEIS	Innalation	fects	442 mg/m3
	Workers	Inhalation	Long-term local ef- fects	221 mg/m3
	Workers	Inhalation	Acute local effects	442 mg/m3
	Workers	Skin contact	Long-term systemic effects	212 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	65,3 mg/m3
	Consumers	Inhalation	Acute systemic ef- fects	260 mg/m3
	Consumers	Inhalation	Long-term local ef- fects	65,3 mg/m3
	Consumers	Inhalation	Acute local effects	260 mg/m3
	Consumers	Skin contact	Long-term systemic effects	125 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	12,5 mg/kg bw/day
Ethylbenzene	Workers	Inhalation	Long-term systemic effects	77 mg/m3
	Workers	Inhalation	Acute local effects	293 mg/m3
	Workers	Skin contact	Long-term systemic	180 mg/kg
			effects	bw/day

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



sion	Revision Date: 07.09.2023			of last issue: 28.07.2023 of first issue: 26.07.2018	
		Consumers	Inhalation	Long-term systemic effects	15 mg/m3
		Consumers	Ingestion	Long-term systemic effects	1,6 mg/kg bw/day
n-Buty	l acetate	Workers	Inhalation	Acute systemic ef- fects	600 mg/m3
		Workers	Inhalation	Acute local effects	600 mg/m3
		Workers	Inhalation	Long-term systemic effects	300 mg/m3
		Workers	Inhalation	Long-term local ef- fects	300 mg/m3
		Consumers	Inhalation	Acute systemic ef- fects	300 mg/m3
		Consumers	Inhalation	Acute local effects	300 mg/m3
		Consumers	Inhalation	Long-term systemic effects	35,7 mg/m
		Consumers	Inhalation	Long-term local ef- fects	35,7 mg/m
		Consumers	Skin contact	Long-term systemic effects	11 mg/kg bw/day
		Consumers	Skin contact	Acute systemic ef- fects	11 mg/kg bw/day
		Consumers	Skin contact	Long-term systemic effects	6 mg/kg bw/day
		Consumers	Skin contact	Acute systemic ef- fects	6 mg/kg bw/day
		Consumers	Ingestion	Long-term systemic effects	2 mg/kg bw/day
		Consumers	Ingestion	Acute systemic ef- fects	2 mg/kg bw/day
Dimeth	nyl ether	Workers	Inhalation	Long-term systemic effects	1894 mg/m
		Consumers	Inhalation	Long-term systemic effects	471 mg/m3
nitroph metho	nethoxy-4- nenyl)azo]-N-(2- xyphenyl)-3- tyramide	Workers	Inhalation	Long-term systemic effects	49 mg/m3
		Workers	Inhalation	Long-term local ef- fects	3 mg/m3
		Workers	Skin contact	Long-term systemic effects	42 mg/kg bw/day
		Consumers	Skin contact	Long-term systemic effects	25 mg/kg bw/day
		Consumers	Ingestion	Long-term systemic effects	25 mg/kg bw/day
Diiron	trioxide	Workers	Inhalation	Long-term local ef- fects	10 mg/m3
		Workers	Inhalation	Long-term systemic effects	10 mg/m3
1-[(2,4	-	Consumers	Ingestion	Long-term systemic	2,8 mg/kg

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 6002 LEAF GREEN - 400 ML

sion	Revision Date: 07.09.2023			of last issue: 28.07.2023 of first issue: 26.07.2018	
Dinitre napht	ophenyl)azo]-2- :hol			effects	bw/day
	on black	Workers	Inhalation	Long-term local ef- fects	0,5 mg/m3
Pigme	ent Blue 15	Workers	Inhalation	Long-term systemic effects	4 mg/m3
		Workers	Skin contact	Long-term systemic effects	450 mg/kg bw/day
		Consumers	Skin contact	Long-term systemic effects	225 mg/kg bw/day
		Consumers	Ingestion	Long-term systemic effects	45 mg/kg bw/day
4-[(2, trichlo phe- nyl)az		Workers	Inhalation	Long-term systemic effects	49 mg/m3
		Workers	Inhalation	Long-term local ef- fects	3 mg/m3
		Workers	Skin contact	Long-term systemic effects	42 mg/kg bw/day
		Consumers	Skin contact	Long-term systemic effects	25 mg/kg bw/day
		Consumers	Ingestion	Long-term systemic effects	25 mg/kg bw/day
C.I. P	igment violet 19	Workers	Inhalation	Long-term systemic effects	147 mg/m3
		Workers	Inhalation	Long-term local ef- fects	3 mg/m3
		Workers	Skin contact	Long-term systemic effects	42 mg/kg bw/day
		Consumers	Skin contact	Long-term systemic effects	25 mg/kg bw/day
		Consumers	Ingestion	Long-term systemic effects	25 mg/kg bw/day
C.I. P	igment Green 7	Workers	Inhalation	Long-term systemic effects	4 mg/m3
		Workers	Skin contact	Long-term systemic effects	450 mg/kg bw/day
		Consumers	Skin contact	Long-term systemic effects	225 mg/kg bw/day
		Consumers	Ingestion	Long-term systemic effects	45 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Xylene	Fresh water	0,327 mg/l
	Intermittent use/release	0,327 mg/l
	Marine water	0,327 mg/l
	Sewage treatment plant	6,58 mg/l

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by



Commission Regulation (EU) 2020/878

LACQUER SPRAY QUATTRO RAL 6002 LEAF GREEN - 400 ML

sion	Revision Date: 07.09.2023	SDS Number: Date of last issue 10648248-00017 Date of first issue	
		Fresh water sediment	12,46 mg/kg d weight (d.w.)
		Marine sediment	12,46 mg/kg d weight (d.w.)
		Soil	2,31 mg/kg dry weight (d.w.)
Ethylb	penzene	Fresh water	0,1 mg/l
		Freshwater - intermittent	0,1 mg/l
		Marine water	0,01 mg/l
		Sewage treatment plant	9,6 mg/l
		Fresh water sediment	13,7 mg/kg dry weight (d.w.)
		Marine sediment	1,37 mg/kg dry weight (d.w.)
		Soil	2,68 mg/kg dry weight (d.w.)
		Oral (Secondary Poisoning)	20 mg/kg food
n-Buty	yl acetate	Fresh water	0,18 mg/l
		Marine water	0,018 mg/l
		Sewage treatment plant	35,6 mg/l
		Fresh water sediment	0,981 mg/kg d weight (d.w.)
		Marine sediment	0,098 mg/kg d weight (d.w.)
		Soil	0,09 mg/kg dry weight (d.w.)
Dimet	thyl ether	Fresh water	0,155 mg/l
Diriot		Marine water	0,016 mg/l
		Intermittent use/release	1,549 mg/l
		Sewage treatment plant	160 mg/l
		Fresh water sediment	0,681 mg/kg d weight (d.w.)
		Marine sediment	0,069 mg/kg d weight (d.w.)
		Soil	0,045 mg/kg d weight (d.w.)
Carbo	on black	Fresh water	1 mg/l
		Freshwater - intermittent	10 mg/l
		Marine water	0,1 mg/l
		Marine water - intermittent	1 mg/l
Piame	ent Blue 15	Fresh water sediment	10 mg/kg
		Marine sediment	1 mg/kg
		Soil	1 mg/kg
CIP	igment Green 7	Fresh water sediment	10 mg/kg
0		Marine sediment	1 mg/kg
		Soil	1 mg/kg

8.2 Exposure controls

Engineering measures

Processing may form hazardous compounds (see section 10).



Version 5.1	Revision Date: 07.09.2023		DS Number: 648248-00017	Date of last issue: 28.07.2023 Date of first issue: 26.07.2018				
lf sui If ad	Minimize workplace exposure concentrations. If sufficient ventilation is unavailable, use with local exhaust ventilation. If advised by assessment of the local exposure potential, use only in an area equipped with plosion-proof exhaust ventilation.							
Pers	Personal protective equipment							
Eye/	face protection	:	Wear the following personal protective equipment: Safety glasses Equipment should conform to DIN EN 166					
Hand	d protection							
B G	laterial reak through time Glove thickness Directive	:	Nitrile rubber > 30 min 0,4 mm Equipment should	d conform to DIN EN 374				
R	emarks	:	on the concentrat stance and specif we recommend c aforementioned p	protect hands against chemicals depending ion and quantity of the hazardous sub- fic to place of work. For special applications, larifying the resistance to chemicals of the protective gloves with the glove manufactur- before breaks and at the end of workday.				
Skin	and body protection	:	 Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential. Wear the following personal protective equipment: If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing. Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc). 					
Resp	piratory protection	:	sure assessment ommended guide	exhaust ventilation is not available or expo- demonstrates exposures outside the rec- lines, use respiratory protection. d conform to DIN EN 137				
F	ilter type	:	Self-contained bro	eathing apparatus				

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	: aerosol
Propellant	: Dimethyl ether



Vers 5.1	sion	Revision Date: 07.09.2023		S Number: 648248-00017	Date of last issue: 28.07.2023 Date of first issue: 26.07.2018
	Colour		:	coloured	
	Odour		:	aromatic	
	Odour ⁻	Threshold	:	No data available	
	Melting	point/freezing point	:	No data available	
	Initial be range	oiling point and boiling	:	-24 °C	
	Flamma	ability (solid, gas)	:	Extremely flamma	able aerosol.
		explosion limit / Upper bility limit	:	18,6 %(V)	
		explosion limit / Lower bility limit	:	1,1 %(V)	
	Flash p	oint	:	Not applicable	
	Auto-ig	nition temperature	:	235 °C	
	Decom	position temperature	:	No data available	
	рН		:	Solvent mixture; aqueous solution	oH value determination not possible, no
	Viscosi Visc	ty osity, kinematic	:	Not applicable	
	Flow tin	ne	:	20 s at 20 °C Cross section: 4 Method: DIN 532	
	Solubili Wat	ty(ies) er solubility	:	immiscible, partly	miscible
	Partitio	n coefficient: n-	:	Not applicable	

Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 6002 LEAF GREEN - 400 ML

Version 5.1	Revision Date: 07.09.2023		S Number: 648248-00017	Date of last issue: 28.07.2023 Date of first issue: 26.07.2018			
octanol/water							
Vapour pressure		: 5.200 hPa (20 °C)					
Density		: 0,8 g/cm³ (20 °C)					
Relative vapour density		: Not applicable					
Particle characteristics Particle size		: Not applicable					
9.2 Other information Explosives		:	Not explosive				
Oxidizi	Oxidizing properties : The substance or mixture is not classified as oxid		r mixture is not classified as oxidizing.				
Evapor	ation rate : Not applicable						

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	Extremely flammable aerosol. Vapours may form explosive mixture with air. If the temperature rises there is danger of the vessels bursting due to the high vapor pressure. Can react with strong oxidizing agents. Hazardous decomposition products will be formed at elevated temperatures.
10.4 Conditions to avoid		
Conditions to avoid	:	Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents



Version 5.1	Revision Date: 07.09.2023		OS Number: 648248-00017	Date of last issue: 28.07.2023 Date of first issue: 26.07.2018			
10.6 Ha	zardous decomposition p	oroo	ducts				
	ermal decomposition	:					
SECTIO	ON 11: Toxicological in	for	mation				
11.1 Inf	ormation on hazard class	ses	as defined in Reg	gulation (EC) No 1272/2008			
	ormation on likely routes of osure	:	Inhalation Skin contact Ingestion Eye contact				
	ute toxicity classified based on availa	ble	information.				
Pro	duct:						
Αςι	Acute inhalation toxicity		Acute toxicity estimate: > 20 mg/l Exposure time: 4 h Test atmosphere: vapour Method: Calculation method				
Αςι	Acute dermal toxicity		Acute toxicity estimate: > 2.000 mg/kg Method: Calculation method				
Co	mponents:						
Din	nethyl ether:						
Acı	ite inhalation toxicity	:	LC50 (Rat): 1640 Exposure time: 4 Test atmosphere	h			
n-E	utyl acetate:						
Acı	ite oral toxicity	:	LD50 (Rat): > 5.0	000 mg/kg			
Аси	Acute inhalation toxicity		LC50 (Rat): > 21,1 mg/l Exposure time: 4 h Test atmosphere: vapour Method: OECD Test Guideline 403				
Аси	ite dermal toxicity	:	: LD50 (Rabbit): > 5.000 mg/kg				
Xyl	ene:						
-	ite oral toxicity	:	LD50 (Rat): 3.52 Method: Directive	3 mg/kg e 67/548/EEC, Annex V, B.1.			
Acu	ite inhalation toxicity	:	Acute toxicity est Exposure time: 4				

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



/ersion 5.1	Revision Date: 07.09.2023		OS Number: 648248-00017	Date of last issue: 28.07.2023 Date of first issue: 26.07.2018	
			Test atmosphere Method: Expert j Remarks: Based		
Acute	Acute dermal toxicity		Acute toxicity estimate: 1.100 mg/kg Method: Expert judgement Remarks: Based on national or regional regulation.		
Ethyl	benzene:				
-	Acute oral toxicity		LD50 (Rat): 3.50	0 mg/kg	
Acute	Acute inhalation toxicity		LC50 (Rat): 17,8 mg/l Exposure time: 4 h Test atmosphere: vapour		
Acute	e dermal toxicity	:	LD50 (Rabbit): >	5.000 mg/kg	
-	corrosion/irritation lassified based on avai	ilable	information.		
Prod	<u>uct:</u>				
Resu	Result		Repeated expos	ure does not cause skin dryness or cracking.	
Com	ponents:				
n-Bu	tyl acetate:				
Spec Resu		:	Rabbit No skin irritation		
Asse	ssment	:	Repeated expos	ure may cause skin dryness or cracking.	
Xyler	ne:				
Spec Resu		:	Rabbit Skin irritation		
Serio	ous eye damage/eye i	rritati	on		
Not c	lassified based on avai	ilable	information.		
Com	ponents:				
n-Bu	tyl acetate:				
Spec		:	Rabbit		
Meth Resu		:	OECD Test Guideline 405No eye irritation		
Xyler	ne:				
Spec	ies	:	: Rabbit		
Resu	Result		: Irritation to eyes, reversing within 21 days		
			17 / 33		



Version	Revisio
5.1	07.09.2

vision Date: 09.2023 SDS Number: 10648248-00017

Date of last issue: 28.07.2023 Date of first issue: 26.07.2018

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

n-Butyl acetate:

Test Type	:	Maximisation Test
Exposure routes	:	Skin contact
Species	:	Guinea pig
Result	:	negative

Xylene:

Test Type	:	Local lymph node assay (LLNA)
Exposure routes	:	Skin contact
Species	:	Mouse
Result	:	negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Dimethyl ether:

Billiouryrourion	
Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative
	Test Type: Chromosome aberration test in vitro Method: OECD Test Guideline 473 Result: negative
	Test Type: In vitro mammalian cell gene mutation test Method: OECD Test Guideline 476 Result: negative
Genotoxicity in vivo	: Test Type: Sex-linked recessive lethal test in Drosophila mel- anogaster (in vivo) Application Route: inhalation (gas) Result: negative
n-Butyl acetate:	
Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative



ersion 1	Revision Date: 07.09.2023	SDS Number: 10648248-00017	Date of last issue: 28.07.2023 Date of first issue: 26.07.2018
Xylen	le:		
Genotoxicity in vitro		: Test Type: B Result: nega	acterial reverse mutation assay (AMES) tive
		Test Type: C Result: nega	hromosome aberration test in vitro tive
		Test Type: In Result: nega	vitro mammalian cell gene mutation test
		Test Type: In malian cells Result: nega	vitro sister chromatid exchange assay in mam-
Geno	toxicity in vivo	Species: Mor	coute: Skin contact
Ethyl	benzene:		
Geno	toxicity in vitro	: Test Type: B Result: nega	acterial reverse mutation assay (AMES) tive
			vitro mammalian cell gene mutation test CD Test Guideline 476 tive
		Test Type: C Result: nega	hromosome aberration test in vitro tive
Geno	toxicity in vivo	mammalian I Species: Mor Application R	coute: Inhalation DD Test Guideline 486
Carci	nogenicity		
Not cl	assified based on ava	ailable information.	
<u>Comp</u>	oonents:		
	thyl ether:		
Speci Applic	es cation Route	: Rat : inhalation (va	apour)
	sure time	: 2 Years : negative	
Xylen	ie:		
Speci	95	: Rat	



Version 5.1	Revision Date: 07.09.2023		Number: 8248-00017	Date of last issue: 28.07.2023 Date of first issue: 26.07.2018	
	cation Route sure time t	: 1	gestion)3 weeks egative		
Speci Applic	ation Route sure time t	: in : 1 : p : T	at halation (vapo 04 weeks ositive he mechanism ans.	ur) a or mode of action may not be relevant in hu-	
•	oductive toxicity assified based on avai	lable inf	ormation.		
Comp	oonents:				
Dimet	thyl ether:				
Effect	s on fertility	re S A	production/depecies: Rat	bined repeated dose toxicity study with the velopmental toxicity screening test te: inhalation (vapour)	
Effect ment	s on foetal develop-	S A	: Test Type: Embryo-foetal development Species: Rat Application Route: inhalation (vapour) Result: negative		
n-But	yl acetate:				
	s on fertility	S A N	: Test Type: Two-generation reproduction toxicity study Species: Rat Application Route: inhalation (vapour) Method: OECD Test Guideline 416 Result: negative		
Effect ment	s on foetal develop-	S A	Test Type: Embryo-foetal development Species: Rat Application Route: inhalation (vapour) Result: negative		
Xylen	e:				
-	s on fertility	S A	pecies: Rat	-generation reproduction toxicity study te: inhalation (vapour)	
Effect ment	s on foetal develop-		est Type: Emb pecies: Rat	ryo-foetal development	



rsion	Revision Date: 07.09.2023	SDS Number: 10648248-0001	Date of last issue: 28.07.2023 7 Date of first issue: 26.07.2018		
		Application Result: nega	Route: inhalation (vapour) ative		
Ethvl	benzene:				
-	s on fertility	Species: Ra Application	Route: inhalation (vapour) CD Test Guideline 416		
Effect ment	s on foetal develop-	: Test Type: Embryo-foetal development Species: Rat Application Route: Inhalation Method: OECD Test Guideline 414 Result: negative			
	- single exposure				
-	ause drowsiness or di	zziness.			
Comp	oonents:				
	thyl ether: ssment	: May cause of	drowsiness or dizziness.		
n-But	yl acetate:				
Asses	ssment	: May cause of	drowsiness or dizziness.		
Xylen	e:				
Asses	ssment	: May cause i	espiratory irritation.		
	- repeated exposure assified based on ava				
Com	oonents:				
Xylen	ie:				
Expos Targe	sure routes et Organs ssment				
Ethyl	benzene:				
	sure routes et Organs	: inhalation (v : Auditory sys			
	ssment	: Shown to pr	oduce significant health effects in animals at cor of >0.2 to 1 mg/l/6h/d.		

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 6002 LEAF GREEN - 400 ML

Vers 5.1	sion	Revision Date: 07.09.2023		DS Number: 648248-00017	Date of last issue: 28.07.2023 Date of first issue: 26.07.2018
	Repeat	ed dose toxicity			
	<u>Compo</u>	onents:			
	Dimeth	yl ether:			
			:	Rat 47,11 mg/l inhalation (vapour 2 yr)
	n-Buty	l acetate:			
	Species NOAEL Applica	S	:	Rat 2,4 mg/l inhalation (vapour 90 Days)
	Xylene	:			
	Species LOAEL Applica	s tion Route ire time		Rat > 0,2 - 1 mg/l inhalation (vapour 13 Weeks Based on data fro) m similar materials
	Species LOAEL Applica Exposu	tion Route	:	Rat 150 mg/kg Ingestion 90 Days	
	Ethylbe	enzene:			
			:	Rat 0,868 mg/l inhalation (vapour 13 Weeks)
	Species NOAEL LOAEL Applica Method	tion Route		Rat 75 mg/kg 250 mg/kg Ingestion OECD Test Guide	line 408
	A	tion toviaitu			

Aspiration toxicity

Not classified based on available information.

Components:

Xylene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.



Version	Revision Date:	SDS Number:	Date of last issue: 28.07.2023
5.1	07.09.2023	10648248-00017	Date of first issue: 26.07.2018

Ethylbenzene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Dimethyl ether:

Toxicity to fish	:	LC50 (Poecilia reticulata (guppy)): > 4.100 mg/l Exposure time: 96 h	
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 4.400 mg/l Exposure time: 48 h	
Toxicity to microorganisms	:	EC10 (Pseudomonas putida): > 1.600 mg/l	
n-Butyl acetate:			
Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): 18 mg/l Exposure time: 96 h	
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia sp. (water flea)): 44 mg/l Exposure time: 48 h	
Toxicity to algae/aquatic plants	:	ErC50 (Pseudokirchneriella subcapitata (green algae)): 397 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: Based on data from similar materials	
		NOEC (Pseudokirchneriella subcapitata (green algae)): 196 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: Based on data from similar materials	



Vers 5.1	sion	Revision Date: 07.09.2023		S Number: 648248-00017	Date of last issue: 28.07.2023 Date of first issue: 26.07.2018
	Toxicity	to microorganisms	:	IC50 (Tetrahymer Exposure time: 40	na pyriformis): 356 mg/l) h
		to daphnia and other invertebrates (Chron- ty)	:	NOEC: 23,2 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211 Remarks: Based on data from similar materials	
	Xylene	:			
	Toxicity		:	LC50 (Oncorhync Exposure time: 96	hus mykiss (rainbow trout)): 13,5 mg/l 3 h
		to daphnia and other invertebrates	:	Exposure time: 24 Method: OECD Te	agna (Water flea)): > 1 - 10 mg/l l h est Guideline 202 on data from similar materials
	Toxicity plants	to algae/aquatic	:	EC50 (Skeletoner Exposure time: 72	na costatum (marine diatom)): 10 mg/l ? h
	Toxicity	to microorganisms	:	NOEC : > 100 mg Exposure time: 3 Method: OECD Te Remarks: Based of	h
	Toxicity icity)	to fish (Chronic tox-	:	NOEC: > 0,1 - < 1 Exposure time: 35 Species: Danio re Method: OECD Te Remarks: Based of	i d rio (zebra fish)
		to daphnia and other invertebrates (Chron- ty)	:	Method: OECD Te	d magna (Water flea)
	Ethvlbe	enzene:			
	Toxicity		:	LC50 (Oncorhync Exposure time: 96 Method: OECD Te	
		to daphnia and other invertebrates	:	EC50 (Daphnia m Exposure time: 48	agna (Water flea)): 1,8 - 2,4 mg/l 3 h
	Toxicity plants	to algae/aquatic	:	EC50 (Pseudokiro mg/l Exposure time: 96	chneriella subcapitata (green algae)): 3,6 Sh

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878




Versior 5.1	n Revision Date: 07.09.2023		DS Number: 648248-00017	Date of last issue: 28.07.2023 Date of first issue: 26.07.2018
			NOEC (Pseudoki mg/l Exposure time: 9	rchneriella subcapitata (green algae)): 3,4 6 h
Тс	xicity to microorganisms	:	EC50 (Nitrosomo Exposure time: 2	
aq	Toxicity to daphnia and other aquatic invertebrates (Chron-ic toxicity)		NOEC: 0,96 mg/l Exposure time: 7 Species: Cerioda	
12.2 Pe	ersistence and degradabi	lity		
<u>Cc</u>	omponents:			
Di	methyl ether:			
Bi	odegradability	:	Result: Not readi Biodegradation: Exposure time: 2 Method: OECD T	5 %
n-	Butyl acetate:			
Bi	odegradability	:	Result: Readily b Biodegradation: Exposure time: 2 Method: OECD T	83 %
Xy	vlene:			
-	odegradability	:		> 70 %
Et	hylbenzene:			
	odegradability	:	Result: Readily b Biodegradation: Exposure time: 2	70 - 80 %
12.3 Bi	oaccumulative potential			
<u>Cc</u>	omponents:			
Pa	methyl ether: artition coefficient: n- tanol/water	:	log Pow: 0,2	
n-	Butyl acetate:			



Version 5.1	Revision Date: 07.09.2023	SDS Number: 10648248-00017	Date of last issue: 28.07.2023 Date of first issue: 26.07.2018
	tion coefficient: n- nol/water	: log Pow: 2,3	
Xyle	ne:		
	tion coefficient: n- nol/water	: log Pow: 3,16 Remarks: Ca	
Ethy	lbenzene:		
	tion coefficient: n- nol/water	: log Pow: 3,6	
12.4 Mob	ility in soil		
No d	ata available		
12.5 Resu	ults of PBT and vPvB	assessment	
Prod	uct:		
Asse	ssment	to be either p	ce/mixture contains no components considered ersistent, bioaccumulative and toxic (PBT), or nt and very bioaccumulative (vPvB) at levels of er.
12.6 Ende	ocrine disrupting pro	perties	
Prod	uct:		
Asse	ssment	ered to have REACH Artic	ce/mixture does not contain components consid- endocrine disrupting properties according to le 57(f) or Commission Delegated regulation 00 or Commission Regulation (EU) 2018/605 at 6 or higher.
	er adverse effects ata available		
SECTIO	N 13: Disposal cons	siderations	
13 1 Was	te treatment methods		
Prod		: Dispose of in According to are not produ Waste codes discussion w	accordance with local regulations. the European Waste Catalogue, Waste Codes act specific, but application specific. should be assigned by the user, preferably in ith the waste disposal authorities. se of waste into sewer.
Cont	aminated packaging	: Empty contai	ners should be taken to an approved waste han-

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by





LACQUER SPRAY QUATTRO RAL 6002 LEAF GREEN - 400 ML

Version 5.1	Revision Date: 07.09.2023	SDS Number: 10648248-00017	Date of last issue: 28.07.2023 Date of first issue: 26.07.2018
		of ignition. Th If not otherwis	ntainers to heat, flame, sparks, or other sources ey may explode and cause injury and/or death. se specified: Dispose of as unused product. e aerosol cans are sprayed completely empty pellant)
Wast	e Code	: The following	Waste Codes are only suggestions:
		containing has 08 01 11, was	es in pressure containers (including halons) zardous substances ste paint and varnish containing organic solvents rdous substances
		containing has 08 01 11, was	ct es in pressure containers (including halons) zardous substances ste paint and varnish containing organic solvents rdous substances
		uncleaned pa 15 01 10, pac by hazardous	kaging containing residues of or contaminated
		Properly emp	ng Act properly emptied packaging: tied, non-contaminated packaging of non- oducts can be supplied to a system for the col- s packaging.

SECTION 14: Transport information

14.1 UN number or ID number

ADN	:	UN 1950
ADR	:	UN 1950
RID	:	UN 1950
IMDG	:	UN 1950
ΙΑΤΑ	:	UN 1950
14.2 UN proper shipping name		
ADN	:	AEROSOLS
ADR	:	AEROSOLS
RID	:	AEROSOLS
IMDG	:	AEROSOLS
ΙΑΤΑ	:	Aerosols, flammable

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



Version 5.1	Revision Date: 07.09.2023		DS Number: 648248-00017	Date of last issue: 28.07.2023 Date of first issue: 26.07.2018
14.3 Trans	port hazard class(es)			
			Class	Subsidiary risks
ADN		:	2	2.1
ADR		:	2	2.1
RID		:	2	2.1
IMDG		:	2.1	
ΙΑΤΑ		:	2.1	
14.4 Packi	ng group			
	ng group fication Code	:	Not assigned by r 5F 2.1	egulation
Classi Labels	ng group fication Code s I restriction code	:	Not assigned by r 5F 2.1 (D)	egulation
Classi	ng group fication Code d Identification Number	:	Not assigned by r 5F 23 2.1	egulation
IMDG Packir Labels EmS (:	Not assigned by r 2.1 F-D, S-U	egulation
Packir aircraf Packir	ng instruction (LQ)	:	203 Y203	
Packir Labels	ng group	:	Not assigned by r Flammable Gas	egulation
IATA (Packir ger air Packir	(Passenger) ng instruction (passen- craft) ng instruction (LQ) ng group	:		egulation
	onmental hazards			
ADN Enviro	nmentally hazardous	;	no	
ADR	nmentally hazardous	:	no	



Version	Revision Date:	SDS Number:	Date of last issue: 28.07.2023
5.1	07.09.2023	10648248-00017	Date of first issue: 26.07.2018

RID

Environmentally hazardous	:	no
IMDG		
Marine pollutant	:	no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Remarks

: Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	 Conditions of restriction for the f lowing entries should be conside Number on list 75 If you intend to use this product tattoo ink, please contact your v dor. 	ered: as
	3-Hydroxy-N-(o-tolyl)-4-[(2,4,5- trichlorophenyl)azo]naphthalene carboxamide (Number on list 75 2-[(2-methoxy-4-nitrophenyl)azo (2-methoxyphenyl)-3-oxobutyra (Number on list 75)	5) 5]-N-
	Substance(s) or mixture(s) are I here according to their appearant in the regulation, irrespective of use/purpose or the conditions of restriction. Please refer to the conditions in corresponding Regulation determine whether an entry is a cable to the placing on the mark not.	nce their f the ondi- on to ppli-
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	: Not applicable	
Regulation (EC) No 1005/2009 on substances that de- plete the ozone layer	: Not applicable	
Regulation (EU) 2019/1021 on persistent organic pollu- tants (recast)	: Not applicable	



Version 5.1	Revision Date: 07.09.2023		DS Number: 648248-00017		st issue: 28.07.20 rst issue: 26.07.20	
mer	ulation (EC) No 649/2012 It and the Council concerr angerous chemicals				lot applicable	
	ACH - List of substances s nex XIV)	ubje	ect to authorisatior	i : N	lot applicable	
	eso III: Directive 2012/18/ or-accident hazards involv					
P3a			FLAMMABLE AE	ROSOLS	Quantity 1 150 t	Quantity 2 500 t
Wat ny)	er hazard class (Germa-	:	WGK 1 slightly had Classification acc		water wSV, Annex 1 (5.	2)
TAI	Luft List (Germany)	:	Not applicable 5.2.4: Inorganic s Not applicable 5.2.5: Organic Su Class 1: 0,08 % I 5.2.7.1.1: Carcino Not applicable 5.2.7.1.1: Quartz Not applicable 5.2.7.1.1: Formal Not applicable 5.2.7.1.2: Germ o Not applicable 5.2.7.1.3: Substa Not applicable	substances Ibstances: Phthalic and ogenic subs fine dust P dehyde: cell mutage nces toxic t egradable, o	nydride stance: M4: ns:	
Vola	atile organic compounds	:	emissions (integr	/l: 669 g/l gory: Species (2007): 840 5/EU of 24 l ated pollution ompounds) g/l November 2010 of on prevention and (VOC) content: 85	control)



Version	Revision Date:	SDS Number:	Date of last issue: 28.07.2023
5.1	07.09.2023	10648248-00017	Date of first issue: 26.07.2018

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

CTION 16: Other infor	mation
Other information	: Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.
Full text of H-Statemen	ıts
H220	: Extremely flammable gas.
H225	: Highly flammable liquid and vapour.
H226	: Flammable liquid and vapour.
H280	: Contains gas under pressure; may explode if heated.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H373	: May cause damage to organs through prolonged or repeated
H412	exposure. Harmful to aquatic life with long lasting effects.
EUH066	: Repeated exposure may cause skin dryness or cracking.
Full text of other abbre	
Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Aqualle Chronic Asp. Tox.	: Aspiration hazard
Eye Irrit.	: Eye irritation
Flam. Gas	: Flammable gases
Flam. Liq.	: Flammable liquids
Press. Gas	: Gases under pressure
Skin Irrit.	: Skin irritation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	Europe. Commission Directive 2000/39/EC establishing a first
	list of indicative occupational exposure limit values
2004/37/EC	: Europe. Directive 2004/37/EC on the protection of workers
	from the risks related to exposure to carcinogens or mutager
	at work

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 6002 LEAF GREEN - 400 ML

Version	Revision Date: 07.09.2023	SDS Number:	Date of last issue: 28.07.2023
5.1		10648248-00017	Date of first issue: 26.07.2018
DE TR TRGS 2000/3 2000/3 2004/3 2006/1 2019/1 2019/1	1831/EU RGS 900	: Europe. Comm fifth list of indic : Germany. TRC	oosure limit oosure limit oosure limit oosure limit ooght hours oosure limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIOC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet

:

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, http://echa.europa.eu/



assessment

LACQUER SPRAY QUATTRO RAL 6002 LEAF GREEN - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 28.07.2023	
5.1	07.09.2023	10648248-00017	Date of first issue: 26.07.2018	

Classification of th	e mixture:	Classification procedure:
Aerosol 1	H222, H229	Based on product data or ass
STOT SE 3	H336	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN