according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 7021 BLACKGREY - 400 ML

Version Revision Date: SDS Number: Date of last issue: 23.11.2022 13.0 06.06.2023 10623182-00010 Date of first issue: 11.06.2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : LACQUER SPRAY QUATTRO RAL 7021 BLACKGREY - 400

ML

Product code : 0893397021

Unique Formula Identifier

(UFI)

S848-60NE-200Y-9FGT

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Paint

stance/Mixture Professional use product

Recommended restrictions : Not applicable

on use

1.3 Details of the supplier of the safety data sheet

Company : Adolf Wuerth GmbH & Co. KG

Reinhold-Würth-Str. 12-17

74653 Künzelsau

Telephone : +49 794015 0

Telefax : +49 794015 10 00

E-mail address of person

responsible for the SDS

: isi@wuerth.com

1.4 Emergency telephone number

+49 (0)6132 - 84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Specific target organ toxicity - single ex-

posure, Category 3

H336: May cause drowsiness or dizziness.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 7021 BLACKGREY - 400 ML

Version Revision Date: SDS Number: Date of last issue: 23.11.2022 13.0 06.06.2023 10623182-00010 Date of first issue: 11.06.2010

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms





Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H336 May cause drowsiness or dizziness.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P271 Use only outdoors or in a well-ventilated area.

Storage:

P410 + P412 Protect from sunlight. Do not expose to tem-

peratures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

Dimethyl ether n-Butyl acetate

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

	0.4.0.1.1	01 '6' ''	
Chemical name	CAS-No.	Classification	Concentration

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 7021 BLACKGREY - 400 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 23.11.2022

 13.0
 06.06.2023
 10623182-00010
 Date of first issue: 11.06.2010

	EC-No. Index-No. Registration number		(% w/w)
Dimethyl ether	115-10-6 204-065-8 603-019-00-8 01-2119472128-37	Flam. Gas 1A; H220 Press. Gas Liquefied gas; H280 STOT SE 3; H336	>= 30 - < 50
n-Butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 EUH066	>= 20 - < 30
Xylene	1330-20-7 215-535-7 601-022-00-9 01-2119488216-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 STOT RE 2; H373 (Auditory system) Asp. Tox. 1; H304 Aquatic Chronic 3; H412 Acute toxicity estimate Acute inhalation toxicity (vapour): 11 mg/l Acute dermal toxicity: 1.100 mg/kg	>= 2,5 - < 10
Ethylbenzene	100-41-4 202-849-4 601-023-00-4	Flam. Liq. 2; H225 Acute Tox. 4; H332 STOT RE 2; H373 (Auditory system) Asp. Tox. 1; H304 Aquatic Chronic 3; H412 Acute toxicity estimate Acute inhalation toxicity (vapour): 17,8 mg/l	>= 1 - < 2,5
Substances with a workplace expo			
Barium sulfate	7727-43-7 231-784-4		>= 1 - < 10

For explanation of abbreviations see section 16.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 7021 BLACKGREY - 400 ML

Version Revision Date: SDS Number: Date of last issue: 23.11.2022 13.0 06.06.2023 10623182-00010 Date of first issue: 11.06.2010

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with plenty of water.

Remove contaminated clothing and shoes.

Get medical attention. Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact : Flush eyes with water as a precaution.

Get medical attention if irritation develops and persists.

If swallowed : If swallowed, DO NOT induce vomiting.

Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

Risks : May cause drowsiness or dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

None known.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 7021 BLACKGREY - 400 ML

Version Revision Date: SDS Number: Date of last issue: 23.11.2022 13.0 06.06.2023 10623182-00010 Date of first issue: 11.06.2010

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Flash back possible over considerable distance. Vapours may form explosive mixtures with air.

Exposure to combustion products may be a hazard to health. If the temperature rises there is danger of the vessels bursting

due to the high vapor pressure.

Hazardous combustion prod: :

ucts

Carbon oxides

Nitrogen oxides (NOx)

Metal oxides Sulphur oxides

5.3 Advice for firefighters

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.

Use personal protective equipment.

Follow safe handling advice (see section 7) and personal pro-

tective equipment recommendations (see section 8).

6.2 Environmental precautions

Environmental precautions

Avoid release to the environment.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g. by containment or oil

barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.

Soak up with inert absorbent material.

Suppress (knock down) gases/vapours/mists with a water

spray jet.

For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 7021 BLACKGREY - 400 ML

Version Revision Date: SDS Number: Date of last issue: 23.11.2022 06.06.2023 10623182-00010 Date of first issue: 11.06.2010 13.0

> be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation If sufficient ventilation is unavailable, use with local exhaust

ventilation.

If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventila-

tion.

Do not get on skin or clothing. Advice on safe handling

> Do not breathe spray. Do not swallow.

Avoid contact with eyes.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as-

sessment

Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

Take precautionary measures against static discharges. Take care to prevent spills, waste and minimize release to the

environment.

Do not spray on an open flame or other ignition source.

Do not breathe decomposition products.

Hygiene measures If exposure to chemical is likely during typical use, provide eye

flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contami-

nated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Store locked up. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Do not

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 7021 BLACKGREY - 400 ML

Version Revision Date: SDS Number: Date of last issue: 23.11.2022 13.0 06.06.2023 10623182-00010 Date of first issue: 11.06.2010

pierce or burn, even after use. Keep cool. Protect from sun-

light.

Advice on common storage : Do not store with the following product types:

Self-reactive substances and mixtures

Organic peroxides Oxidizing agents Flammable solids Pyrophoric liquids Pyrophoric solids

Self-heating substances and mixtures

Substances and mixtures, which in contact with water, emit

flammable gases

Explosives Gases

Storage class (TRGS 510) : 2B

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis		
Dimethyl ether	115-10-6	TWA	1.000 ppm 1.920 mg/m3	2000/39/EC		
	Further inform	nation: Indicative				
		AGW	1.000 ppm 1.900 mg/m3	DE TRGS 900		
	Peak-limit: ex	cursion factor (categ	ory): 8;(II)			
n-Butyl acetate	123-86-4	STEL	150 ppm 723 mg/m3	2019/1831/E U		
	Further inform	nation: Indicative				
		TWA	50 ppm 241 mg/m3	2019/1831/E U		
	Further inform	nation: Indicative				
		AGW	62 ppm 300 mg/m3	DE TRGS 900		
	Peak-limit: ex	Peak-limit: excursion factor (category): 2;(I)				
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child					
Barium sulfate	7727-43-7	AGW (Inhalable fraction)	10 mg/m3	DE TRGS 900		
	Peak-limit: ex	Peak-limit: excursion factor (category): 2;(II)				

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 7021 BLACKGREY - 400 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 23.11.2022

 13.0
 06.06.2023
 10623182-00010
 Date of first issue: 11.06.2010

	1	A C \	1.05	L DE TDOC		
		AGW (Alveolate fraction)	1,25 mg/m3	DE TRGS 900		
	Peak-limit: ex	cursion factor (cated	jory): 2;(II)			
		TWA	0,5 mg/m3	2006/15/EC		
			(Barium)			
	Further inforr	nation: Indicative				
Xylene	1330-20-7	TWA	50 ppm 221 mg/m3	2000/39/EC		
	Further inforr skin, Indicativ		possibility of significant uptal	ke through the		
		STEL	100 ppm 442 mg/m3	2000/39/EC		
		Further information: Identifies the possibility of significant uptake through the skin, Indicative				
		AGW	50 ppm	DE TRGS		
			220 mg/m3	900		
	Peak-limit: excursion factor (category): 2;(II)					
	Further inforr	nation: Skin absorpti	on			
Ethylbenzene	100-41-4	TWA	100 ppm 442 mg/m3	2000/39/EC		
	Further inforr skin, Indicativ		possibility of significant uptal	ke through the		
		STEL	200 ppm 884 mg/m3	2000/39/EC		
	Further inforr skin, Indicativ		possibility of significant uptal	ke through the		
		AGW	20 ppm 88 mg/m3	DE TRGS 900		
	Peak-limit: ex	cursion factor (cated	•	•		
		Further information: Skin absorption, When there is compliance with the OEL				
and biological tolerance values, the			ere is no risk of harming the	unborn child		

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis		
Formaldehyde	50-00-0	TWA	0,3 ppm 0,37 mg/m3	2004/37/EC		
	Further inform	ı nation: Dermal sensit	isation, Carcinogens or muta	l agens		
		STEL	0,6 ppm	2004/37/EC		
			0,74 mg/m3			
	Further information: Dermal sensitisation, Carcinogens or mutagens					
		AGW	0,3 ppm	DE TRGS		
			0,37 mg/m3	900		
	Peak-limit: ex	cursion factor (categ	ory): 2;(I)			
			substance Cat. 1A or 1B or of			
	activity or procedure according to § 2 (3) No. 4 of the Hazardous Substances					
	Ordinance - in addition, § 10 GefStoffV must be observed, When there is					
		compliance with the OEL and biological tolerance values, there is no risk of				
	harming the u	nborn child, Substar	nce sensitizing through the sk	<u>kin</u>		

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 7021 BLACKGREY - 400 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 23.11.2022

 13.0
 06.06.2023
 10623182-00010
 Date of first issue: 11.06.2010

Methanol	67-56-1	TWA	200 ppm 260 mg/m3	2006/15/EC	
	Further inform through the sk		entifies the possibility of signif	icant uptake	
		AGW	100 ppm 130 mg/m3	DE TRGS 900	
	Peak-limit: excursion factor (category): 2;(II)				
	Further information: Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child				

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Xylene	1330-20-7	methylhippuric acid (all isomers): 2.000 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903
Ethylbenzene	100-41-4	mandelic acid + phenylglyoxylic acid: 250 mg/g Creatinine (Urine)	Immediately after exposure or after working hours	TRGS 903

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Xylene	Workers	Inhalation	Long-term systemic effects	221 mg/m3
	Workers	Inhalation	Acute systemic effects	442 mg/m3
	Workers	Inhalation	Long-term local ef- fects	221 mg/m3
	Workers	Inhalation	Acute local effects	442 mg/m3
	Workers	Skin contact	Long-term systemic effects	212 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	65,3 mg/m3
	Consumers	Inhalation	Acute systemic effects	260 mg/m3
	Consumers	Inhalation	Long-term local ef- fects	65,3 mg/m3
	Consumers	Inhalation	Acute local effects	260 mg/m3
	Consumers	Skin contact	Long-term systemic effects	125 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	12,5 mg/kg bw/day
Ethylbenzene	Workers	Inhalation	Long-term systemic effects	77 mg/m3
	Workers	Inhalation	Acute local effects	293 mg/m3
	Workers	Skin contact	Long-term systemic effects	180 mg/kg bw/day
_	Consumers	Inhalation	Long-term systemic	15 mg/m3

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 7021 BLACKGREY - 400 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 23.11.2022

 13.0
 06.06.2023
 10623182-00010
 Date of first issue: 11.06.2010

	I	Ī	effects	1
	Consumers	Ingestion	Long-term systemic effects	1,6 mg/kg bw/day
n-Butyl acetate	Workers	Inhalation	Acute systemic effects	600 mg/m3
	Workers	Inhalation	Acute local effects	600 mg/m3
	Workers	Inhalation	Long-term systemic effects	300 mg/m3
	Workers	Inhalation	Long-term local ef- fects	300 mg/m3
	Consumers	Inhalation	Acute systemic ef- fects	300 mg/m3
	Consumers	Inhalation	Acute local effects	300 mg/m3
	Consumers	Inhalation	Long-term systemic effects	35,7 mg/m3
	Consumers	Inhalation	Long-term local ef- fects	35,7 mg/m3
	Consumers	Skin contact	Long-term systemic effects	11 mg/kg bw/day
	Consumers	Skin contact	Acute systemic effects	11 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	6 mg/kg bw/day
	Consumers	Skin contact	Acute systemic effects	6 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	2 mg/kg bw/day
	Consumers	Ingestion	Acute systemic effects	2 mg/kg bw/day
Dimethyl ether	Workers	Inhalation	Long-term systemic effects	1894 mg/m3
	Consumers	Inhalation	Long-term systemic effects	471 mg/m3
2-[(2-methoxy-4- nitrophenyl)azo]-N-(2- methoxyphenyl)-3- oxobutyramide	Workers	Inhalation	Long-term systemic effects	49 mg/m3
	Workers	Inhalation	Long-term local ef- fects	3 mg/m3
	Workers	Skin contact	Long-term systemic effects	42 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	25 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	25 mg/kg bw/day
1-[(2,4- Dinitrophenyl)azo]-2- naphthol	Consumers	Ingestion	Long-term systemic effects	2,8 mg/kg bw/day
Barium sulfate	Workers	Inhalation	Long-term local ef- fects	10 mg/m3
	Workers	Inhalation	Long-term systemic	10 mg/m3

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 7021 BLACKGREY - 400 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 23.11.2022

 13.0
 06.06.2023
 10623182-00010
 Date of first issue: 11.06.2010

		effects	
Consumers	Inhalation	Long-term systemic effects	10 mg/m3
Consumers	Ingestion	Long-term systemic effects	13000 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Xylene	Fresh water	0,327 mg/l
	Intermittent use/release	0,327 mg/l
	Marine water	0,327 mg/l
	Sewage treatment plant	6,58 mg/l
	Fresh water sediment	12,46 mg/kg dry
		weight (d.w.)
	Marine sediment	12,46 mg/kg dry
		weight (d.w.)
	Soil	2,31 mg/kg dry
		weight (d.w.)
Ethylbenzene	Fresh water	0,1 mg/l
	Freshwater - intermittent	0,1 mg/l
	Marine water	0,01 mg/l
	Sewage treatment plant	9,6 mg/l
	Fresh water sediment	13,7 mg/kg dry
		weight (d.w.)
	Marine sediment	1,37 mg/kg dry
		weight (d.w.)
	Soil	2,68 mg/kg dry
		weight (d.w.)
	Oral (Secondary Poisoning)	20 mg/kg food
n-Butyl acetate	Fresh water	0,18 mg/l
	Marine water	0,018 mg/l
	Sewage treatment plant	35,6 mg/l
	Fresh water sediment	0,981 mg/kg dry
		weight (d.w.)
	Marine sediment	0,098 mg/kg dry
		weight (d.w.)
	Soil	0,09 mg/kg dry
		weight (d.w.)
Dimethyl ether	Fresh water	0,155 mg/l
	Marine water	0,016 mg/l
	Intermittent use/release	1,549 mg/l
	Sewage treatment plant	160 mg/l
	Fresh water sediment	0,681 mg/kg dry
		weight (d.w.)
	Marine sediment	0,069 mg/kg dry
		weight (d.w.)
	Soil	0,045 mg/kg dry
		weight (d.w.)
Barium sulfate	Fresh water	0,115 mg/l
	Sewage treatment plant	62,2 mg/l

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 7021 BLACKGREY - 400 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 23.11.2022

 13.0
 06.06.2023
 10623182-00010
 Date of first issue: 11.06.2010

Fresh water sediment	600,4 mg/kg dry weight (d.w.)
Soil	207,7 mg/kg dry
	weight (d.w.)

8.2 Exposure controls

Engineering measures

Processing may form hazardous compounds (see section 10).

Minimize workplace exposure concentrations.

If sufficient ventilation is unavailable, use with local exhaust ventilation.

If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Personal protective equipment

Eye/face protection : Wear the following personal protective equipment:

Safety glasses

Equipment should conform to DIN EN 166

Hand protection

Material : Nitrile rubber
Break through time : > 30 min
Glove thickness : 0,4 mm

Directive : Equipment should conform to DIN EN 374

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Wear the following personal protective equipment:

If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic

protective clothing.

Respiratory protection : If adequate local exhaust ventilation is not available or expo-

sure assessment demonstrates exposures outside the rec-

ommended guidelines, use respiratory protection.

Equipment should conform to DIN EN 137

Filter type : Self-contained breathing apparatus

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : aerosol

Propellant : Dimethyl ether

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 7021 BLACKGREY - 400 ML

Version Revision Date: SDS Number: Date of last issue: 23.11.2022 13.0 06.06.2023 10623182-00010 Date of first issue: 11.06.2010

Colour : grey

Odour : aromatic

Odour Threshold : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling

range

-24 °C

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper

flammability limit

18,6 %(V)

Lower explosion limit / Lower

flammability limit

1,1 %(V)

Flash point : Not applicable

Auto-ignition temperature : 235 °C

Decomposition temperature : No data available

pH : Solvent mixture; pH value determination not possible, no

aqueous solution

Viscosity

Viscosity, kinematic : Not applicable

Flow time : 20 s at 20 °C

Method: DIN 53211 (CF4)

Solubility(ies)

Water solubility : immiscible, partly miscible

Partition coefficient: n-

octanol/water

Not applicable

Vapour pressure : 5.200 hPa (20 °C)

Density : 0,8 g/cm³ (20 °C)

Relative vapour density : Not applicable

Particle characteristics

Particle size : Not applicable

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 7021 BLACKGREY - 400 ML

Version Revision Date: SDS Number: Date of last issue: 23.11.2022 13.0 06.06.2023 10623182-00010 Date of first issue: 11.06.2010

9.2 Other information

Explosives : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Evaporation rate : Not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Extremely flammable aerosol.

Vapours may form explosive mixture with air.

If the temperature rises there is danger of the vessels bursting

due to the high vapor pressure.

Can react with strong oxidizing agents.

Hazardous decomposition products will be formed at elevated

temperatures.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

Thermal decomposition : Formaldehyde

Methanol

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of : Inhalation

exposure Skin contact

Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 7021 BLACKGREY - 400 ML

Version Revision Date: SDS Number: Date of last issue: 23.11.2022 13.0 06.06.2023 10623182-00010 Date of first issue: 11.06.2010

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg

Method: Calculation method

Components:

Dimethyl ether:

Acute inhalation toxicity : LC50 (Rat): 164000 ppm

Exposure time: 4 h Test atmosphere: gas

n-Butyl acetate:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 21,1 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Xylene:

Acute oral toxicity : LD50 (Rat): 3.523 mg/kg

Method: Directive 67/548/EEC, Annex V, B.1.

Acute inhalation toxicity : Acute toxicity estimate: 11 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Expert judgement

Remarks: Based on national or regional regulation.

Acute dermal toxicity : Acute toxicity estimate: 1.100 mg/kg

Method: Expert judgement

Remarks: Based on national or regional regulation.

Ethylbenzene:

Acute oral toxicity : LD50 (Rat): 3.500 mg/kg

Acute inhalation toxicity : LC50 (Rat): 17,8 mg/l

Exposure time: 4 h
Test atmosphere: vapour

' '

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Barium sulfate:

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 7021 BLACKGREY - 400 ML

Version Revision Date: SDS Number: Date of last issue: 23.11.2022 13.0 06.06.2023 10623182-00010 Date of first issue: 11.06.2010

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Product:

Result : Repeated exposure does not cause skin dryness or cracking.

Components:

n-Butyl acetate:

Species : Rabbit

Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

Xylene:

Species : Rabbit Result : Skin irritation

Barium sulfate:

Species : reconstructed human epidermis (RhE)

Method : OECD Test Guideline 439

Remarks : Based on data from similar materials

Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

n-Butyl acetate:

Species : Rabbit

Method : OECD Test Guideline 405

Result : No eye irritation

Xylene:

Species : Rabbit

Result : Irritation to eyes, reversing within 21 days

Barium sulfate:

Species : Rabbit

Method : OECD Test Guideline 405

Result : No eye irritation

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 7021 BLACKGREY - 400 ML

Version Revision Date: SDS Number: Date of last issue: 23.11.2022 13.0 06.06.2023 10623182-00010 Date of first issue: 11.06.2010

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

n-Butyl acetate:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative

Xylene:

Test Type : Local lymph node assay (LLNA)

Exposure routes : Skin contact
Species : Mouse
Result : negative

Barium sulfate:

Test Type : Local lymph node assay (LLNA)

Exposure routes : Skin contact Species : Mouse

Method : OECD Test Guideline 429

Result : negative

Remarks : Based on data from similar materials

Germ cell mutagenicity

Not classified based on available information.

Components:

Dimethyl ether:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Genotoxicity in vivo : Test Type: Sex-linked recessive lethal test in Drosophila mel-

anogaster (in vivo)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 7021 BLACKGREY - 400 ML

Version Revision Date: SDS Number: Date of last issue: 23.11.2022 13.0 06.06.2023 10623182-00010 Date of first issue: 11.06.2010

Application Route: inhalation (gas)

Result: negative

n-Butyl acetate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Xylene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: Chromosome aberration test in vitro

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: negative

Test Type: In vitro sister chromatid exchange assay in mam-

malian cells Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)

Species: Mouse

Application Route: Skin contact

Result: negative

Ethylbenzene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Test Type: Chromosome aberration test in vitro

Result: negative

Genotoxicity in vivo : Test Type: Unscheduled DNA synthesis (UDS) test with

mammalian liver cells in vivo

Species: Mouse

Application Route: Inhalation Method: OECD Test Guideline 486

Result: negative

Barium sulfate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Remarks: Based on data from similar materials

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 7021 BLACKGREY - 400 ML

Version Revision Date: SDS Number: Date of last issue: 23.11.2022 13.0 06.06.2023 10623182-00010 Date of first issue: 11.06.2010

Test Type: Chromosome aberration test in vitro

Result: negative

Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Components:

Dimethyl ether:

Species : Rat

Application Route : inhalation (vapour)

Exposure time : 2 Years
Result : negative

Xylene:

Species : Rat
Application Route : Ingestion
Exposure time : 103 weeks
Result : negative

Ethylbenzene:

Species : Rat

Application Route : inhalation (vapour)

Exposure time : 104 weeks
Result : positive

Remarks : The mechanism or mode of action may not be relevant in hu-

mans.

Barium sulfate:

Species : Rat
Application Route : Ingestion
Exposure time : 2 Years
Result : negative

Remarks : Based on data from similar materials

Reproductive toxicity

Not classified based on available information.

Components:

Dimethyl ether:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 7021 BLACKGREY - 400 ML

Version Revision Date: SDS Number: Date of last issue: 23.11.2022 13.0 06.06.2023 10623182-00010 Date of first issue: 11.06.2010

Species: Rat

Application Route: inhalation (vapour)

Result: negative

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: inhalation (vapour)

Result: negative

n-Butyl acetate:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: inhalation (vapour) Method: OECD Test Guideline 416

Result: negative

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: inhalation (vapour)

Result: negative

Xylene:

Effects on fertility : Test Type: One-generation reproduction toxicity study

Species: Rat

Application Route: inhalation (vapour)

Result: negative

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: inhalation (vapour)

Result: negative

Ethylbenzene:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: inhalation (vapour) Method: OECD Test Guideline 416

Result: negative

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: Inhalation Method: OECD Test Guideline 414

Result: negative

Barium sulfate:

Effects on fertility : Test Type: Fertility/early embryonic development

Species: Rat

Application Route: Ingestion

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 7021 BLACKGREY - 400 ML

Version Revision Date: SDS Number: Date of last issue: 23.11.2022 13.0 06.06.2023 10623182-00010 Date of first issue: 11.06.2010

Result: negative

Remarks: Based on data from similar materials

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 414

Result: negative

Remarks: Based on data from similar materials

STOT - single exposure

May cause drowsiness or dizziness.

Components:

Dimethyl ether:

Assessment : May cause drowsiness or dizziness.

n-Butyl acetate:

Assessment : May cause drowsiness or dizziness.

Xylene:

Assessment : May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Components:

Xylene:

Exposure routes : inhalation (vapour)
Target Organs : Auditory system

Assessment : Shown to produce significant health effects in animals at con-

centrations of >0.2 to 1 mg/l/6h/d.

Ethylbenzene:

Exposure routes : inhalation (vapour)
Target Organs : Auditory system

Assessment : Shown to produce significant health effects in animals at con-

centrations of >0.2 to 1 mg/l/6h/d.

Barium sulfate:

Assessment : No significant health effects observed in animals at concentra-

tions of 100 mg/kg bw or less.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 7021 BLACKGREY - 400 ML

Version Revision Date: SDS Number: Date of last issue: 23.11.2022 13.0 06.06.2023 10623182-00010 Date of first issue: 11.06.2010

Repeated dose toxicity

Components:

Dimethyl ether:

Species : Rat NOAEL : 47,11 mg/l

Application Route : inhalation (vapour)

Exposure time : 2 yr

n-Butyl acetate:

Species : Rat NOAEL : 2,4 mg/l

Application Route : inhalation (vapour)

Exposure time : 90 Days

Xylene:

Species : Rat

LOAEL : > 0,2 - 1 mg/l
Application Route : inhalation (vapour)

Exposure time : 13 Weeks

Remarks : Based on data from similar materials

Species : Rat

LOAEL : 150 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Ethylbenzene:

Species : Rat LOAEL : 0,868 mg/l

Application Route : inhalation (vapour)

Exposure time : 13 Weeks

Species : Rat
NOAEL : 75 mg/kg
LOAEL : 250 mg/kg
Application Route : Ingestion

Method : OECD Test Guideline 408

Barium sulfate:

Species : Rat

NOAEL : 61,1 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Remarks : Based on data from similar materials

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 7021 BLACKGREY - 400 ML

Version Revision Date: SDS Number: Date of last issue: 23.11.2022 13.0 06.06.2023 10623182-00010 Date of first issue: 11.06.2010

Aspiration toxicity

Not classified based on available information.

Components:

Xylene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Ethylbenzene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Dimethyl ether:

Toxicity to fish : LC50 (Poecilia reticulata (guppy)): > 4.100 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 4.400 mg/l

Exposure time: 48 h

Toxicity to microorganisms : EC10 (Pseudomonas putida): > 1.600 mg/l

n-Butyl acetate:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 18 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia sp. (water flea)): 44 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

ErC50 (Pseudokirchneriella subcapitata (green algae)): 397

mg/l

Exposure time: 72 h

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 7021 BLACKGREY - 400 ML

Version Revision Date: SDS Number: Date of last issue: 23.11.2022 13.0 06.06.2023 10623182-00010 Date of first issue: 11.06.2010

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): 196

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l

Exposure time: 40 h

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

NOEC: 23,2 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

Remarks: Based on data from similar materials

Xylene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 13,5 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 1 - 10 mg/l

Exposure time: 24 h

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

EC50 (Skeletonema costatum (marine diatom)): 10 mg/l

Exposure time: 72 h

Toxicity to microorganisms : NOEC

NOEC: > 100 mg/l Exposure time: 3 h

Method: OECD Test Guideline 209

Remarks: Based on data from similar materials

Toxicity to fish (Chronic tox-

icity)

NOEC: > 0,1 - < 1 mg/l Exposure time: 35 d

Species: Danio rerio (zebra fish) Method: OECD Test Guideline 210

Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chron-

ic toxicity)

EL10: > 1 - 10 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

Remarks: Based on data from similar materials

Ethylbenzene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 4,2 mg/l

Exposure time: 96 h

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 7021 BLACKGREY - 400 ML

Version Revision Date: SDS Number: Date of last issue: 23.11.2022 13.0 06.06.2023 10623182-00010 Date of first issue: 11.06.2010

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 1,8 - 2,4 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 3,6

mg/l

Exposure time: 96 h

NOEC (Pseudokirchneriella subcapitata (green algae)): 3,4

mg/l

Exposure time: 96 h

Toxicity to microorganisms : EC50 (Nitrosomonas sp.): 96 mg/l

Exposure time: 24 h

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

NOEC: 0,96 mg/l Exposure time: 7 d

Species: Ceriodaphnia dubia (water flea)

Barium sulfate:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l

Exposure time: 48 h

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

NOEC (Pseudokirchneriella subcapitata (green algae)): > 1

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to microorganisms : EC50 : > 600 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Remarks: Based on data from similar materials

NOEC: > 600 mg/l Exposure time: 3 h

Method: OECD Test Guideline 209

Remarks: Based on data from similar materials

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 7021 BLACKGREY - 400 ML

Version Revision Date: SDS Number: Date of last issue: 23.11.2022 13.0 06.06.2023 10623182-00010 Date of first issue: 11.06.2010

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

NOEC: > 1 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Remarks: Based on data from similar materials

12.2 Persistence and degradability

Components:

Dimethyl ether:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 5 % Exposure time: 28 d

Method: OECD Test Guideline 301D

n-Butyl acetate:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 83 % Exposure time: 28 d

Method: OECD Test Guideline 301D

Xylene:

Biodegradability : Result: Readily biodegradable.

Biodegradation: > 70 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Remarks: Based on data from similar materials

Ethylbenzene:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 70 - 80 %

Exposure time: 28 d

12.3 Bioaccumulative potential

Components:

octanol/water

Dimethyl ether:

Partition coefficient: n-

. .

log Pow: 0,2

n-Butyl acetate:

Partition coefficient: n-

octanol/water

: log Pow: 2,3

Xylene:

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 7021 BLACKGREY - 400 ML

Version Revision Date: SDS Number: Date of last issue: 23.11.2022 13.0 06.06.2023 10623182-00010 Date of first issue: 11.06.2010

Partition coefficient: n-

octanol/water

: log Pow: 3,16

Remarks: Calculation

Ethylbenzene:

Partition coefficient: n-

octanol/water

log Pow: 3,6

Barium sulfate:

Bioaccumulation : Species: Lepomis macrochirus (Bluegill sunfish)

Bioconcentration factor (BCF): < 500

Partition coefficient: n-

octanol/water

log Pow: -1,03

Remarks: Calculation

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.

According to the European Waste Catalogue, Waste Codes

are not product specific, but application specific.

Waste codes should be assigned by the user, preferably in

discussion with the waste disposal authorities.

Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste han-

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 7021 BLACKGREY - 400 ML

Version Revision Date: SDS Number: Date of last issue: 23.11.2022 13.0 06.06.2023 10623182-00010 Date of first issue: 11.06.2010

dling site for recycling or disposal.

Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product. Please ensure aerosol cans are sprayed completely empty (including propellant)

Waste Code : The following Waste Codes are only suggestions:

unused product

16 05 04, gases in pressure containers (including halons)

containing hazardous substances

08 01 11, waste paint and varnish containing organic solvents

or other hazardous substances

used product

16 05 04, gases in pressure containers (including halons)

containing hazardous substances

08 01 11, waste paint and varnish containing organic solvents

or other hazardous substances

uncleaned packagings

15 01 10, packaging containing residues of or contaminated

by hazardous substances

Acc. Packaging Act properly emptied packaging: Properly emptied, non-contaminated packaging of nonhazardous products can be supplied to a system for the col-

lection of sales packaging.

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 1950
ADR : UN 1950
RID : UN 1950
IMDG : UN 1950
IATA : UN 1950

14.2 UN proper shipping name

ADN : AEROSOLS
ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 7021 BLACKGREY - 400 ML

Version Revision Date: SDS Number: Date of last issue: 23.11.2022 13.0 06.06.2023 10623182-00010 Date of first issue: 11.06.2010

IATA : Aerosols, flammable

14.3 Transport hazard class(es)

Class Subsidiary risks

ADN : 2 2.1
ADR : 2 2.1
RID : 2 2.1

IMDG : 2.1
IATA : 2.1

14.4 Packing group

ADN

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1

ADR

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1 Tunnel restriction code : (D)

RID

Packing group : Not assigned by regulation

Classification Code : 5F Hazard Identification Number : 23 Labels : 2.1

IMDG

Packing group : Not assigned by regulation

Labels : 2.1 EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo : 203

aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

IATA (Passenger)

Packing instruction (passen- : 203

ger aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

14.5 Environmental hazards

ADN

Environmentally hazardous : no

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 7021 BLACKGREY - 400 ML

Version Revision Date: SDS Number: Date of last issue: 23.11.2022 13.0 06.06.2023 10623182-00010 Date of first issue: 11.06.2010

ADR

Environmentally hazardous : no

rid

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 75

If you intend to use this product as tattoo ink, please contact your ven-

dor.

2-[(2-methoxy-4-nitrophenyl)azo]-N-(2-methoxyphenyl)-3-oxobutyramide

(Number on list 75)

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

: Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 7021 BLACKGREY - 400 ML

Version Revision Date: SDS Number: Date of last issue: 23.11.2022 13.0 06.06.2023 10623182-00010 Date of first issue: 11.06.2010

Quantity 1 Quantity 2

P3a FLAMMABLE AEROSOLS 150 t 500 t

Water hazard class (Germa- : W

ny)

WGK 1 slightly hazardous to water

Classification according to AwSV, Annex 1 (5.2)

Volatile organic compounds : Directive 2004/42/EC

VOC content in g/l: 669 g/l

Product sub-category: Special finishes

Coatings: All types

VOC limit level 1 (2007): 840 g/l

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 85 %, 669 g/l

Remarks: VOC content excluding water

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Other information : Items where changes have been made to the previous version

are highlighted in the body of this document by two vertical

lines.

Full text of H-Statements

H220 : Extremely flammable gas.

H225 : Highly flammable liquid and vapour.
H226 : Flammable liquid and vapour.

H280 : Contains gas under pressure; may explode if heated.

H304 : May be fatal if swallowed and enters airways.

H312 : Harmful in contact with skin.

H315 : Causes skin irritation. H319 : Causes serious eye irritation.

H332 : Harmful if inhaled.

H335 : May cause respiratory irritation. H336 : May cause drowsiness or dizziness.

H373 : May cause damage to organs through prolonged or repeated

exposure.

H412 : Harmful to aquatic life with long lasting effects.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 7021 BLACKGREY - 400 ML

Version Revision Date: SDS Number: Date of last issue: 23.11.2022 13.0 06.06.2023 10623182-00010 Date of first issue: 11.06.2010

EUH066 : Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard
Eye Irrit. : Eye irritation
Flam. Gas : Flammable gases
Flam. Liq. : Flammable liquids
Press. Gas : Gases under pressure

Skin Irrit. : Skin irritation

STOT RE : Specific target organ toxicity - repeated exposure STOT SE : Specific target organ toxicity - single exposure

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values

2004/37/EC : Europe. Directive 2004/37/EC on the protection of workers

from the risks related to exposure to carcinogens or mutagens

at work

2006/15/EC : Europe. Indicative occupational exposure limit values 2019/1831/EU : Europe. Commission Directive 2019/1831/EU establishing a

fifth list of indicative occupational exposure limit values

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

TRGS 903 : TRGS 903 - Biological limit values

2000/39/EC / TWA Limit Value - eight hours 2000/39/EC / STEL Short term exposure limit 2004/37/EC / STEL Short term exposure limit 2004/37/EC / TWA Long term exposure limit Limit Value - eight hours 2006/15/EC / TWA Limit Value - eight hours 2019/1831/EU / TWA 2019/1831/EU / STEL Short term exposure limit DE TRGS 900 / AGW Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified;

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 7021 BLACKGREY - 400 ML

Version Revision Date: SDS Number: Date of last issue: 23.11.2022 13.0 06.06.2023 10623182-00010 Date of first issue: 11.06.2010

NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data

Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Classification of the mixture: Classification procedure:

Aerosol 1 H222, H229 Based on product data or assessment

STOT SE 3 H336 Calculation method

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN