

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 9002 GREYWHITE - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 15.05.2023
12.1	07.09.2023	10625317-00011	Date of first issue: 11.06.2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : LACQUER SPRAY QUATTRO RAL 9002 GREYWHITE - 400 ML

Product code : 0893399002

Unique Formula Identifier (UFI) : R503-A0NT-H00X-JVQ8

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Paint
Professional use product

Recommended restrictions on use : Not applicable

1.3 Details of the supplier of the safety data sheet

Company : Adolf Wuerth GmbH & Co. KG
Reinhold-Würth-Str. 12-17
74653 Künzelsau

Telephone : +49 794015 0

Telefax : +49 794015 10 00

E-mail address of person responsible for the SDS : isi@wuerth.com

1.4 Emergency telephone number

+49 (0)6132 – 84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.
H229: Pressurised container: May burst if heated.

Specific target organ toxicity - single ex- H336: May cause drowsiness or dizziness.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 9002 GREYWHITE - 400 ML

Version 12.1 Revision Date: 07.09.2023 SDS Number: 10625317-00011 Date of last issue: 15.05.2023
Date of first issue: 11.06.2010

posure, Category 3

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H336 May cause drowsiness or dizziness.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P261 Avoid breathing spray.
P271 Use only outdoors or in a well-ventilated area.

Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

Dimethyl ether
n-Butyl acetate

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 9002 GREYWHITE - 400 ML

Version 12.1 Revision Date: 07.09.2023 SDS Number: 10625317-00011 Date of last issue: 15.05.2023
Date of first issue: 11.06.2010

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Dimethyl ether	115-10-6 204-065-8 603-019-00-8 01-2119472128-37	Flam. Gas 1A; H220 Press. Gas Liquefied gas; H280 STOT SE 3; H336	>= 30 - < 50
n-Butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 EUH066	>= 20 - < 30
Xylene	1330-20-7 215-535-7 601-022-00-9 01-2119488216-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 STOT RE 2; H373 (Auditory system) Asp. Tox. 1; H304 Aquatic Chronic 3; H412 Acute toxicity estimate Acute inhalation toxicity (vapour): 11 mg/l Acute dermal toxicity: 1.100 mg/kg	>= 2,5 - < 10
Ethylbenzene	100-41-4 202-849-4 601-023-00-4	Flam. Liq. 2; H225 Acute Tox. 4; H332 STOT RE 2; H373 (Auditory system) Asp. Tox. 1; H304 Aquatic Chronic 3; H412 Acute toxicity estimate Acute inhalation toxicity (vapour): 17,8 mg/l	>= 1 - < 2,5

For explanation of abbreviations see section 16.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 9002 GREYWHITE - 400 ML

Version 12.1	Revision Date: 07.09.2023	SDS Number: 10625317-00011	Date of last issue: 15.05.2023 Date of first issue: 11.06.2010
-----------------	------------------------------	-------------------------------	---

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- If inhaled : If inhaled, remove to fresh air.
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : May cause drowsiness or dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically and supportively.
-

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : None known.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 9002 GREYWHITE - 400 ML

Version 12.1	Revision Date: 07.09.2023	SDS Number: 10625317-00011	Date of last issue: 15.05.2023 Date of first issue: 11.06.2010
-----------------	------------------------------	-------------------------------	---

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Flash back possible over considerable distance.
Vapours may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

Hazardous combustion products : Carbon oxides
Nitrogen oxides (NOx)

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapours/mists with a water spray jet.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absor-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 9002 GREYWHITE - 400 ML

Version 12.1	Revision Date: 07.09.2023	SDS Number: 10625317-00011	Date of last issue: 15.05.2023 Date of first issue: 11.06.2010
-----------------	------------------------------	-------------------------------	---

bent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- | | | |
|-------------------------|---|---|
| Technical measures | : | See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section. |
| Local/Total ventilation | : | If sufficient ventilation is unavailable, use with local exhaust ventilation.
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation. |
| Advice on safe handling | : | Do not get on skin or clothing.
Do not breathe spray.
Do not swallow.
Avoid contact with eyes.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.
Do not spray on an open flame or other ignition source.

Do not breathe decomposition products. |
| Hygiene measures | : | If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use. |

7.2 Conditions for safe storage, including any incompatibilities

- | | | |
|---|---|--|
| Requirements for storage areas and containers | : | Store locked up. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Do not pierce or burn, even after use. Keep cool. Protect from sunlight. |
|---|---|--|

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 9002 GREYWHITE - 400 ML

Version 12.1 Revision Date: 07.09.2023 SDS Number: 10625317-00011 Date of last issue: 15.05.2023
Date of first issue: 11.06.2010

Advice on common storage : Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Oxidizing agents
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures, which in contact with water, emit flammable gases
Explosives
Gases

Storage class (TRGS 510) : 2B

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Dimethyl ether	115-10-6	TWA	1.000 ppm 1.920 mg/m ³	2000/39/EC
		Further information: Indicative		
		AGW	1.000 ppm 1.900 mg/m ³	DE TRGS 900
		Peak-limit: excursion factor (category): 8;(II)		
n-Butyl acetate	123-86-4	STEL	150 ppm 723 mg/m ³	2019/1831/EU
		Further information: Indicative		
		TWA	50 ppm 241 mg/m ³	2019/1831/EU
		Further information: Indicative		
		AGW	62 ppm 300 mg/m ³	DE TRGS 900
		Peak-limit: excursion factor (category): 2;(I)		
		Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child		
Titanium dioxide	13463-67-7	AGW (Inhalable fraction)	10 mg/m ³ (Titanium dioxide)	DE TRGS 900
		Peak-limit: excursion factor (category): 2;(II)		
		Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child		

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 9002 GREYWHITE - 400 ML

Version 12.1 Revision Date: 07.09.2023 SDS Number: 10625317-00011 Date of last issue: 15.05.2023
Date of first issue: 11.06.2010

		AGW (Alveolate fraction)	1,25 mg/m ³ (Titanium dioxide)	DE TRGS 900
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
Xylene	1330-20-7	TWA	50 ppm 221 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 442 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		AGW	50 ppm 220 mg/m ³	DE TRGS 900
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: Skin absorption			
Ethylbenzene	100-41-4	TWA	100 ppm 442 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	200 ppm 884 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		AGW	20 ppm 88 mg/m ³	DE TRGS 900
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Formaldehyde	50-00-0	TWA	0,3 ppm 0,37 mg/m ³	2004/37/EC
	Further information: Dermal sensitisation, Carcinogens or mutagens			
		STEL	0,6 ppm 0,74 mg/m ³	2004/37/EC
	Further information: Dermal sensitisation, Carcinogens or mutagens			
		AGW	0,3 ppm 0,37 mg/m ³	DE TRGS 900
	Peak-limit: excursion factor (category): 2;(I)			
	Further information: Carcinogenic substance Cat. 1A or 1B or carcinogenic activity or procedure according to § 2 (3) No. 4 of the Hazardous Substances Ordinance - in addition, § 10 GefStoffV must be observed, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child, Substance sensitizing through the skin			
Methanol	67-56-1	TWA	200 ppm	2006/15/EC

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 9002 GREYWHITE - 400 ML

Version 12.1 Revision Date: 07.09.2023 SDS Number: 10625317-00011 Date of last issue: 15.05.2023
Date of first issue: 11.06.2010

			260 mg/m ³	
	Further information: Indicative, Identifies the possibility of significant uptake through the skin			
		AGW	100 ppm 130 mg/m ³	DE TRGS 900
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Xylene	1330-20-7	methylhippuric acid (all isomers): 2.000 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903
Ethylbenzene	100-41-4	mandelic acid + phenylglyoxylic acid: 250 mg/g creatinine (Urine)	Immediately after exposure or after working hours	TRGS 903

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Xylene	Workers	Inhalation	Long-term systemic effects	221 mg/m ³
			Acute systemic effects	442 mg/m ³
	Workers	Inhalation	Long-term local effects	221 mg/m ³
			Acute local effects	442 mg/m ³
	Workers	Skin contact	Long-term systemic effects	212 mg/kg bw/day
			Consumers	Inhalation
	Consumers	Inhalation	Acute systemic effects	260 mg/m ³
			Long-term local effects	65,3 mg/m ³
	Consumers	Inhalation	Acute local effects	260 mg/m ³
			Consumers	Skin contact
Ethylbenzene	Workers	Inhalation	Long-term systemic effects	12,5 mg/kg bw/day
			Long-term systemic effects	77 mg/m ³
	Workers	Inhalation	Acute local effects	293 mg/m ³
			Workers	Skin contact
	Consumers	Inhalation	Long-term systemic effects	15 mg/m ³

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 9002 GREYWHITE - 400 ML

Version
12.1

Revision Date:
07.09.2023

SDS Number:
10625317-00011

Date of last issue: 15.05.2023
Date of first issue: 11.06.2010

	Consumers	Ingestion	Long-term systemic effects	1,6 mg/kg bw/day
n-Butyl acetate	Workers	Inhalation	Acute systemic effects	600 mg/m3
	Workers	Inhalation	Acute local effects	600 mg/m3
	Workers	Inhalation	Long-term systemic effects	300 mg/m3
	Workers	Inhalation	Long-term local effects	300 mg/m3
	Consumers	Inhalation	Acute systemic effects	300 mg/m3
	Consumers	Inhalation	Acute local effects	300 mg/m3
	Consumers	Inhalation	Long-term systemic effects	35,7 mg/m3
	Consumers	Inhalation	Long-term local effects	35,7 mg/m3
	Consumers	Skin contact	Long-term systemic effects	11 mg/kg bw/day
	Consumers	Skin contact	Acute systemic effects	11 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	6 mg/kg bw/day
	Consumers	Skin contact	Acute systemic effects	6 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	2 mg/kg bw/day
	Consumers	Ingestion	Acute systemic effects	2 mg/kg bw/day
Dimethyl ether	Workers	Inhalation	Long-term systemic effects	1894 mg/m3
	Consumers	Inhalation	Long-term systemic effects	471 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Xylene	Fresh water	0,327 mg/l
	Intermittent use/release	0,327 mg/l
	Marine water	0,327 mg/l
	Sewage treatment plant	6,58 mg/l
	Fresh water sediment	12,46 mg/kg dry weight (d.w.)
	Marine sediment	12,46 mg/kg dry weight (d.w.)
	Soil	2,31 mg/kg dry weight (d.w.)
Ethylbenzene	Fresh water	0,1 mg/l
	Freshwater - intermittent	0,1 mg/l
	Marine water	0,01 mg/l
	Sewage treatment plant	9,6 mg/l
	Fresh water sediment	13,7 mg/kg dry weight (d.w.)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 9002 GREYWHITE - 400 ML

Version 12.1 Revision Date: 07.09.2023 SDS Number: 10625317-00011 Date of last issue: 15.05.2023
Date of first issue: 11.06.2010

	Marine sediment	1,37 mg/kg dry weight (d.w.)
	Soil	2,68 mg/kg dry weight (d.w.)
	Oral (Secondary Poisoning)	20 mg/kg food
n-Butyl acetate	Fresh water	0,18 mg/l
	Marine water	0,018 mg/l
	Sewage treatment plant	35,6 mg/l
	Fresh water sediment	0,981 mg/kg dry weight (d.w.)
	Marine sediment	0,098 mg/kg dry weight (d.w.)
	Soil	0,09 mg/kg dry weight (d.w.)
Dimethyl ether	Fresh water	0,155 mg/l
	Marine water	0,016 mg/l
	Intermittent use/release	1,549 mg/l
	Sewage treatment plant	160 mg/l
	Fresh water sediment	0,681 mg/kg dry weight (d.w.)
	Marine sediment	0,069 mg/kg dry weight (d.w.)
	Soil	0,045 mg/kg dry weight (d.w.)

8.2 Exposure controls

Engineering measures

Processing may form hazardous compounds (see section 10).

Minimize workplace exposure concentrations.

If sufficient ventilation is unavailable, use with local exhaust ventilation.

If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Personal protective equipment

Eye/face protection : Wear the following personal protective equipment:
Safety glasses
Equipment should conform to DIN EN 166

Hand protection

Material : Nitrile rubber
Break through time : > 30 min
Glove thickness : 0,4 mm
Directive : Equipment should conform to DIN EN 374

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 9002 GREYWHITE - 400 ML

Version 12.1	Revision Date: 07.09.2023	SDS Number: 10625317-00011	Date of last issue: 15.05.2023 Date of first issue: 11.06.2010
-----------------	------------------------------	-------------------------------	---

- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
- Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
Equipment should conform to DIN EN 137
- Filter type : Self-contained breathing apparatus

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Physical state : aerosol
- Propellant : Dimethyl ether
- Colour : grey, white
- Odour : aromatic
- Odour Threshold : No data available
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : -24 °C
- Flammability (solid, gas) : Extremely flammable aerosol.
- Upper explosion limit / Upper flammability limit : 18,6 %(V)
- Lower explosion limit / Lower : 1,1 %(V)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 9002 GREYWHITE - 400 ML

Version 12.1	Revision Date: 07.09.2023	SDS Number: 10625317-00011	Date of last issue: 15.05.2023 Date of first issue: 11.06.2010
-----------------	------------------------------	-------------------------------	---

flammability limit

Flash point : Not applicable

Auto-ignition temperature : 235 °C

Decomposition temperature : No data available

pH : Solvent mixture; pH value determination not possible, no aqueous solution

Viscosity
Viscosity, kinematic : Not applicable

Flow time : 20 s at 20 °C
Method: DIN 53211 (CF4)

Solubility(ies)
Water solubility : immiscible, partly miscible

Partition coefficient: n-
octanol/water : Not applicable

Vapour pressure : 5.200 hPa (20 °C)

Density : 0,8 g/cm³ (20 °C)

Relative vapour density : Not applicable

Particle characteristics
Particle size : Not applicable

9.2 Other information

Explosives : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 9002 GREYWHITE - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 15.05.2023
12.1	07.09.2023	10625317-00011	Date of first issue: 11.06.2010

Evaporation rate : Not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Extremely flammable aerosol.
Vapours may form explosive mixture with air.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
Can react with strong oxidizing agents.
Hazardous decomposition products will be formed at elevated temperatures.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

Thermal decomposition : Formaldehyde
Methanol

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 9002 GREYWHITE - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 15.05.2023
12.1	07.09.2023	10625317-00011	Date of first issue: 11.06.2010

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Components:

Dimethyl ether:

Acute inhalation toxicity : LC50 (Rat): 164000 ppm
Exposure time: 4 h
Test atmosphere: gas

n-Butyl acetate:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg
Acute inhalation toxicity : LC50 (Rat): > 21,1 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Xylene:

Acute oral toxicity : LD50 (Rat): 3.523 mg/kg
Method: Directive 67/548/EEC, Annex V, B.1.
Acute inhalation toxicity : Acute toxicity estimate: 11 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Expert judgement
Remarks: Based on national or regional regulation.
Acute dermal toxicity : Acute toxicity estimate: 1.100 mg/kg
Method: Expert judgement
Remarks: Based on national or regional regulation.

Ethylbenzene:

Acute oral toxicity : LD50 (Rat): 3.500 mg/kg
Acute inhalation toxicity : LC50 (Rat): 17,8 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Product:

Result : Repeated exposure does not cause skin dryness or cracking.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 9002 GREYWHITE - 400 ML

Version 12.1 Revision Date: 07.09.2023 SDS Number: 10625317-00011 Date of last issue: 15.05.2023
Date of first issue: 11.06.2010

Components:

n-Butyl acetate:

Species : Rabbit
Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

Xylene:

Species : Rabbit
Result : Skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

n-Butyl acetate:

Species : Rabbit
Method : OECD Test Guideline 405
Result : No eye irritation

Xylene:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

n-Butyl acetate:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative

Xylene:

Test Type : Local lymph node assay (LLNA)
Exposure routes : Skin contact
Species : Mouse
Result : negative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 9002 GREYWHITE - 400 ML

Version 12.1	Revision Date: 07.09.2023	SDS Number: 10625317-00011	Date of last issue: 15.05.2023 Date of first issue: 11.06.2010
-----------------	------------------------------	-------------------------------	---

Germ cell mutagenicity

Not classified based on available information.

Components:

Dimethyl ether:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Genotoxicity in vivo : Test Type: Sex-linked recessive lethal test in *Drosophila melanogaster* (in vivo)
Application Route: inhalation (gas)
Result: negative

n-Butyl acetate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Xylene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: In vitro sister chromatid exchange assay in mammalian cells
Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)
Species: Mouse
Application Route: Skin contact
Result: negative

Ethylbenzene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 9002 GREYWHITE - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 15.05.2023
12.1	07.09.2023	10625317-00011	Date of first issue: 11.06.2010

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Genotoxicity in vivo : Test Type: Unscheduled DNA synthesis (UDS) test with
mammalian liver cells in vivo
Species: Mouse
Application Route: Inhalation
Method: OECD Test Guideline 486
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Dimethyl ether:

Species : Rat
Application Route : inhalation (vapour)
Exposure time : 2 Years
Result : negative

Xylene:

Species : Rat
Application Route : Ingestion
Exposure time : 103 weeks
Result : negative

Ethylbenzene:

Species : Rat
Application Route : inhalation (vapour)
Exposure time : 104 weeks
Result : positive
Remarks : The mechanism or mode of action may not be relevant in humans.

Reproductive toxicity

Not classified based on available information.

Components:

Dimethyl ether:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the
reproduction/developmental toxicity screening test
Species: Rat
Application Route: inhalation (vapour)
Result: negative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 9002 GREYWHITE - 400 ML

Version 12.1	Revision Date: 07.09.2023	SDS Number: 10625317-00011	Date of last issue: 15.05.2023 Date of first issue: 11.06.2010
-----------------	------------------------------	-------------------------------	---

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Result: negative

n-Butyl acetate:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapour)
Method: OECD Test Guideline 416
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Result: negative

Xylene:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapour)
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Result: negative

Ethylbenzene:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapour)
Method: OECD Test Guideline 416
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Inhalation
Method: OECD Test Guideline 414
Result: negative

STOT - single exposure

May cause drowsiness or dizziness.

Components:

Dimethyl ether:

Assessment : May cause drowsiness or dizziness.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 9002 GREYWHITE - 400 ML

Version 12.1 Revision Date: 07.09.2023 SDS Number: 10625317-00011 Date of last issue: 15.05.2023
Date of first issue: 11.06.2010

n-Butyl acetate:

Assessment : May cause drowsiness or dizziness.

Xylene:

Assessment : May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Components:

Xylene:

Exposure routes : inhalation (vapour)
Target Organs : Auditory system
Assessment : Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg/l/6h/d.

Ethylbenzene:

Exposure routes : inhalation (vapour)
Target Organs : Auditory system
Assessment : Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg/l/6h/d.

Repeated dose toxicity

Components:

Dimethyl ether:

Species : Rat
NOAEL : 47,11 mg/l
Application Route : inhalation (vapour)
Exposure time : 2 yr

n-Butyl acetate:

Species : Rat
NOAEL : 2,4 mg/l
Application Route : inhalation (vapour)
Exposure time : 90 Days

Xylene:

Species : Rat
LOAEL : > 0,2 - 1 mg/l
Application Route : inhalation (vapour)
Exposure time : 13 Weeks
Remarks : Based on data from similar materials

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 9002 GREYWHITE - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 15.05.2023
12.1	07.09.2023	10625317-00011	Date of first issue: 11.06.2010

Species : Rat
LOAEL : 150 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Ethylbenzene:

Species : Rat
LOAEL : 0,868 mg/l
Application Route : inhalation (vapour)
Exposure time : 13 Weeks

Species : Rat
NOAEL : 75 mg/kg
LOAEL : 250 mg/kg
Application Route : Ingestion
Method : OECD Test Guideline 408

Aspiration toxicity

Not classified based on available information.

Components:

Xylene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Ethylbenzene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Dimethyl ether:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 9002 GREYWHITE - 400 ML

Version 12.1 Revision Date: 07.09.2023 SDS Number: 10625317-00011 Date of last issue: 15.05.2023
Date of first issue: 11.06.2010

Toxicity to fish : LC50 (Poecilia reticulata (guppy)): > 4.100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 4.400 mg/l
aquatic invertebrates Exposure time: 48 h

Toxicity to microorganisms : EC10 (Pseudomonas putida): > 1.600 mg/l

n-Butyl acetate:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 18 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia sp. (water flea)): 44 mg/l
aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic : ErC50 (Pseudokirchneriella subcapitata (green algae)): 397
plants mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): 196
mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l
Exposure time: 40 h

Toxicity to daphnia and other : NOEC: 23,2 mg/l
aquatic invertebrates (Chron- Exposure time: 21 d
ic toxicity) Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Xylene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 13,5 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 1 - 10 mg/l
aquatic invertebrates Exposure time: 24 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic : EC50 (Skeletonema costatum (marine diatom)): 10 mg/l
plants Exposure time: 72 h

Toxicity to microorganisms : NOEC : > 100 mg/l
Exposure time: 3 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 9002 GREYWHITE - 400 ML

Version 12.1	Revision Date: 07.09.2023	SDS Number: 10625317-00011	Date of last issue: 15.05.2023 Date of first issue: 11.06.2010
-----------------	------------------------------	-------------------------------	---

Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Toxicity to fish (Chronic toxicity) : NOEC: > 0,1 - < 1 mg/l
Exposure time: 35 d
Species: Danio rerio (zebra fish)
Method: OECD Test Guideline 210
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EL10: > 1 - 10 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Ethylbenzene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 4,2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1,8 - 2,4 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 3,6 mg/l
Exposure time: 96 h

NOEC (Pseudokirchneriella subcapitata (green algae)): 3,4 mg/l
Exposure time: 96 h

Toxicity to microorganisms : EC50 (Nitrosomonas sp.): 96 mg/l
Exposure time: 24 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0,96 mg/l
Exposure time: 7 d
Species: Ceriodaphnia dubia (water flea)

12.2 Persistence and degradability

Components:

Dimethyl ether:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 5 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

n-Butyl acetate:

Biodegradability : Result: Readily biodegradable.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 9002 GREYWHITE - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 15.05.2023
12.1	07.09.2023	10625317-00011	Date of first issue: 11.06.2010

Biodegradation: 83 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Xylene:

Biodegradability : Result: Readily biodegradable.
Biodegradation: > 70 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

Ethylbenzene:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 70 - 80 %
Exposure time: 28 d

12.3 Bioaccumulative potential

Components:

Dimethyl ether:

Partition coefficient: n-
octanol/water : log Pow: 0,2

n-Butyl acetate:

Partition coefficient: n-
octanol/water : log Pow: 2,3

Xylene:

Partition coefficient: n-
octanol/water : log Pow: 3,16
Remarks: Calculation

Ethylbenzene:

Partition coefficient: n-
octanol/water : log Pow: 3,6

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 9002 GREYWHITE - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 15.05.2023
12.1	07.09.2023	10625317-00011	Date of first issue: 11.06.2010

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.
Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.
Please ensure aerosol cans are sprayed completely empty (including propellant)

Waste Code : The following Waste Codes are only suggestions:

unused product
16 05 04, gases in pressure containers (including halons) containing hazardous substances
08 01 11, waste paint and varnish containing organic solvents or other hazardous substances

used product
16 05 04, gases in pressure containers (including halons) containing hazardous substances
08 01 11, waste paint and varnish containing organic solvents or other hazardous substances

uncleaned packagings
15 01 10, packaging containing residues of or contaminated by hazardous substances

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 9002 GREYWHITE - 400 ML

Version 12.1 Revision Date: 07.09.2023 SDS Number: 10625317-00011 Date of last issue: 15.05.2023
Date of first issue: 11.06.2010

Acc. Packaging Act properly emptied packaging:
Properly emptied, non-contaminated packaging of non-
hazardous products can be supplied to a system for the col-
lection of sales packaging.

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 1950
ADR : UN 1950
RID : UN 1950
IMDG : UN 1950
IATA : UN 1950

14.2 UN proper shipping name

ADN : AEROSOLS
ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS
IATA : Aerosols, flammable

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	: 2	2.1
ADR	: 2	2.1
RID	: 2	2.1
IMDG	: 2.1	
IATA	: 2.1	

14.4 Packing group

ADN
Packing group : Not assigned by regulation
Classification Code : 5F
Labels : 2.1

ADR
Packing group : Not assigned by regulation
Classification Code : 5F
Labels : 2.1
Tunnel restriction code : (D)

RID
Packing group : Not assigned by regulation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 9002 GREYWHITE - 400 ML

Version 12.1	Revision Date: 07.09.2023	SDS Number: 10625317-00011	Date of last issue: 15.05.2023 Date of first issue: 11.06.2010
-----------------	------------------------------	-------------------------------	---

Classification Code : 5F
Hazard Identification Number : 23
Labels : 2.1

IMDG

Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

IATA (Passenger)

Packing instruction (passenger aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 75
If you intend to use this product as

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 9002 GREYWHITE - 400 ML

Version 12.1	Revision Date: 07.09.2023	SDS Number: 10625317-00011	Date of last issue: 15.05.2023 Date of first issue: 11.06.2010
-----------------	------------------------------	-------------------------------	---

tattoo ink, please contact your vendor.

Substance(s) or mixture(s) are listed here according to their appearance in the regulation, irrespective of their use/purpose or the conditions of the restriction. Please refer to the conditions in corresponding Regulation to determine whether an entry is applicable to the placing on the market or not.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
P3a	FLAMMABLE AEROSOLS	150 t	500 t

Water hazard class (Germany) : WGK 1 slightly hazardous to water
Classification according to AwSV, Annex 1 (5.2)

TA Luft List (Germany) : 5.2.1: Total dust:
Not applicable
5.2.2: Inorganic substances in powdered form:
Not applicable
5.2.4: Inorganic substances in gaseous form:
Not applicable
5.2.5: Organic Substances:
Class 1: 0,08 % Phthalic anhydride
5.2.7.1.1: Carcinogenic substance:
Not applicable
5.2.7.1.1: Quartz fine dust PM4:
Not applicable
5.2.7.1.1: Formaldehyde:
Not applicable
5.2.7.1.1: fibres:
Not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 9002 GREYWHITE - 400 ML

Version 12.1	Revision Date: 07.09.2023	SDS Number: 10625317-00011	Date of last issue: 15.05.2023 Date of first issue: 11.06.2010
-----------------	------------------------------	-------------------------------	---

5.2.7.1.2: Germ cell mutagens:

Not applicable

5.2.7.1.3: Substances toxic to reproduction:

Not applicable

5.2.7.2: Poorly degradable, easily enrichable and highly toxic organic substances:

Not applicable

Volatile organic compounds : Directive 2004/42/EC
VOC content in g/l: 669 g/l
Product sub-category: Special finishes
Coatings: All types
VOC limit level 1 (2007): 840 g/l

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 85 %, 669 g/l
Remarks: VOC content excluding water

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Other information : Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Full text of H-Statements

H220 : Extremely flammable gas.
H225 : Highly flammable liquid and vapour.
H226 : Flammable liquid and vapour.
H280 : Contains gas under pressure; may explode if heated.
H304 : May be fatal if swallowed and enters airways.
H312 : Harmful in contact with skin.
H315 : Causes skin irritation.
H319 : Causes serious eye irritation.
H332 : Harmful if inhaled.
H335 : May cause respiratory irritation.
H336 : May cause drowsiness or dizziness.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 9002 GREYWHITE - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 15.05.2023
12.1	07.09.2023	10625317-00011	Date of first issue: 11.06.2010

H373 : May cause damage to organs through prolonged or repeated exposure.
H412 : Harmful to aquatic life with long lasting effects.
EUH066 : Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Aquatic Chronic : Long-term (chronic) aquatic hazard
Asp. Tox. : Aspiration hazard
Eye Irrit. : Eye irritation
Flam. Gas : Flammable gases
Flam. Liq. : Flammable liquids
Press. Gas : Gases under pressure
Skin Irrit. : Skin irritation
STOT RE : Specific target organ toxicity - repeated exposure
STOT SE : Specific target organ toxicity - single exposure
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2004/37/EC : Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work
2006/15/EC : Europe. Indicative occupational exposure limit values
2019/1831/EU : Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.
TRGS 903 : TRGS 903 - Biological limit values
2000/39/EC / TWA : Limit Value - eight hours
2000/39/EC / STEL : Short term exposure limit
2004/37/EC / STEL : Short term exposure limit
2004/37/EC / TWA : Long term exposure limit
2006/15/EC / TWA : Limit Value - eight hours
2019/1831/EU / TWA : Limit Value - eight hours
2019/1831/EU / STEL : Short term exposure limit
DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization;

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



LACQUER SPRAY QUATTRO RAL 9002 GREYWHITE - 400 ML

Version 12.1	Revision Date: 07.09.2023	SDS Number: 10625317-00011	Date of last issue: 15.05.2023 Date of first issue: 11.06.2010
-----------------	------------------------------	-------------------------------	---

KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Classification of the mixture:

Aerosol 1 H222, H229
STOT SE 3 H336

Classification procedure:

Based on product data or assessment
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN