according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## PIPE AND THREAD SEALANT MEDIUM STRENGTH - 48 ML / 50 G

Version Revision Date: SDS Number: Date of last issue: 02.03.2024 11.1 28.03.2024 10630277-00018 Date of first issue: 11.06.2010

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : PIPE AND THREAD SEALANT MEDIUM STRENGTH - 48

ML / 50 G

Product code : 0893577050

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Adhesives and/or sealants Professional use product

Recommended restrictions

on use

Not applicable

1.3 Details of the supplier of the safety data sheet

Company : Adolf Wuerth GmbH & Co. KG

Reinhold-Würth-Str. 12-17

74653 Künzelsau

Telephone : +49 794015 0

Telefax : +49 794015 10 00

E-mail address of person responsible for the SDS

: isi@wuerth.com

#### 1.4 Emergency telephone number

+49 (0)6132 - 84463

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Long-term (chronic) aquatic hazard, Cat-

H412: Harmful to aquatic life with long lasting ef-

egory 3

fects.

#### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard statements : H412 Harmful to aquatic life with long lasting effects.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## PIPE AND THREAD SEALANT MEDIUM STRENGTH - 48 ML / 50 G

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02.03.2024

 11.1
 28.03.2024
 10630277-00018
 Date of first issue: 11.06.2010

Precautionary statements : Prevention:

P273 Avoid release to the environment.

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Components

Chemical name  2-(2-Methylprop-2-enoyloxy)ethyl	CAS-No. EC-No. Index-No. Registration number 25852-47-5	Classification  Aquatic Chronic 3;	Concentration (% w/w) >= 50 - < 70
2-methylprop-2-enoate α,α-dimethylbenzyl hydroperoxide	80-15-9 201-254-7 617-002-00-8 01-2119475796-19	Org. Perox. E; H242 Acute Tox. 4; H302 Acute Tox. 3; H331 Acute Tox. 2; H310 Skin Corr. 1; H314 Eye Dam. 1; H318 STOT SE 3; H335 STOT RE 2; H373 (Lungs) Aquatic Chronic 2; H411 ——————————————————————————————————	>= 0,25 - < 1

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



# PIPE AND THREAD SEALANT MEDIUM STRENGTH - 48 ML / 50 G

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02.03.2024

 11.1
 28.03.2024
 10630277-00018
 Date of first issue: 11.06.2010

		Eye Irrit. 2; H319 1 - < 3 % STOT SE 3; H335 >= 1 %	
		Acute toxicity esti- mate	
		Acute oral toxicity: 382 mg/kg Acute inhalation toxicity (vapour): 3 mg/l Acute dermal toxicity: 133,6 mg/kg	
2'-Phenylacetohydrazide	114-83-0 204-055-3	Acute Tox. 3; H301 Acute Tox. 3; H311 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Aquatic Acute 1; H400	>= 0,25 - < 1
		M-Factor (Acute aquatic toxicity): 1	
		Acute toxicity esti- mate	
		Acute oral toxicity: 270 mg/kg Acute dermal toxicity: 300,03 mg/kg	
p-Benzoquinone	106-51-4 203-405-2 606-013-00-3	Flam. Sol. 1; H228 Acute Tox. 3; H301 Acute Tox. 3; H331 Skin Corr. 1; H314 Eye Dam. 1; H318 Skin Sens. 1B; H317 Muta. 2; H341 STOT SE 3; H336 STOT SE 3; H335 Aquatic Acute 1; H400 Aquatic Chronic 1; H410  M-Factor (Acute aquatic toxicity): 10	>= 0,0025 - < 0,025
		M-Factor (Chronic aquatic toxicity): 10	

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## PIPE AND THREAD SEALANT MEDIUM STRENGTH - 48 ML / 50 G

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02.03.2024

 11.1
 28.03.2024
 10630277-00018
 Date of first issue: 11.06.2010

Acute toxicity estimate

Acute oral toxicity:
130 mg/kg
Acute inhalation toxicity (dust/mist):
0,5001 mg/l

For explanation of abbreviations see section 16.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

Protection of first-aiders : No special precautions are necessary for first aid responders.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : Wash with water and soap as a precaution.

Get medical attention if symptoms occur.

In case of eye contact : Flush eyes with water as a precaution.

Get medical attention if irritation develops and persists.

If swallowed, DO NOT induce vomiting.

Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

## 4.2 Most important symptoms and effects, both acute and delayed

None known.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

#### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

None known.

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire- : Exposure to combustion products may be a hazard to health.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## PIPE AND THREAD SEALANT MEDIUM STRENGTH - 48 ML / 50 G

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02.03.2024

 11.1
 28.03.2024
 10630277-00018
 Date of first issue: 11.06.2010

fighting

Hazardous combustion prod: :

ucts

Silicon oxides Carbon oxides

Nitrogen oxides (NOx) Sulphur oxides Fluorine compounds

5.3 Advice for firefighters

Special protective equipment :

for firefighters

Wear self-contained breathing apparatus for firefighting if nec-

essary. Use personal protective equipment.

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Follow safe handling advice (see section 7) and personal pro-

tective equipment recommendations (see section 8).

6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g. by containment or oil

barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material.

For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor-

bent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to deter-

mine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## PIPE AND THREAD SEALANT MEDIUM STRENGTH - 48 ML / 50 G

Version Revision Date: SDS Number: Date of last issue: 02.03.2024 11.1 28.03.2024 10630277-00018 Date of first issue: 11.06.2010

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

**SECTION 7: Handling and storage** 

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Handle in accordance with good industrial hygiene and safety

practice, based on the results of the workplace exposure as-

sessment

Take care to prevent spills, waste and minimize release to the

environment.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye

flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contami-

nated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

s tot storage . Reep in prop

Keep in properly labelled containers. Store in accordance with

the particular national regulations.

Advice on common storage : Do not store with the following product types:

Strong oxidizing agents

Gases

Storage class (TRGS 510) : 10

Storage period : 12 Months

Recommended storage tem: :

perature

20 °C

7.3 Specific end use(s)

Specific use(s) : No data available

## **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

#### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form	Control parameters	Basis
		of exposure)		

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## PIPE AND THREAD SEALANT MEDIUM STRENGTH - 48 ML / 50 G

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02.03.2024

 11.1
 28.03.2024
 10630277-00018
 Date of first issue: 11.06.2010

Polytetrafluoroeth- ylene	9002-84-0	MAK (measured as the alveolate fraction)	0,3 mg/m3	DE DFG MAK
	Peak-limit: excursion factor (category): 8; II			
	Further information: Substances that cause cancer in humans or animals or that are considered to be carcinogenic for humans and for which a MAK value can be derived., Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed			
		MAK (inhalable fraction)	4 mg/m3	DE DFG MAK
	Peak-limit: excursion factor (category): 8; II			
	Further information: Substances that cause cancer in humans or animals or that are considered to be carcinogenic for humans and for which a MAK value can be derived., Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed			

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
1,2-Benzisothiazol- 3(2H)-one 1,1-dioxide	Workers	Inhalation	Long-term systemic effects	4,19 mg/m3
	Workers	Skin contact	Long-term systemic effects	2,381 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	1,035 mg/m3
	Consumers	Skin contact	Long-term systemic effects	1,190 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	0,595 mg/kg bw/day
α,α-dimethylbenzyl hydroperoxide	Workers	Inhalation	Long-term systemic effects	6 mg/m3

## Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
1,2-Benzisothiazol-3(2H)-one	Fresh water	0,104 mg/l
1,1-dioxide		_
	Marine water	0,0104 mg/l
	Intermittent use/release	1,044 mg/l
	Fresh water sediment	104,403 mg/kg
	Marine sediment	104,403 mg/kg
	Soil	29,024 mg/kg
	Sewage treatment plant	12,304 mg/l
α,α-dimethylbenzyl hydroperox- ide	Fresh water	0,0031 mg/l
	Marine water	0,00031 mg/l
	Freshwater - intermittent	0,031 mg/l
	Sewage treatment plant	0,35 mg/l
	Fresh water sediment	0,023 mg/kg dry
		weight (d.w.)
	Marine sediment	0,0023 mg/kg dry

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## PIPE AND THREAD SEALANT MEDIUM STRENGTH - 48 ML / 50 G

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02.03.2024

 11.1
 28.03.2024
 10630277-00018
 Date of first issue: 11.06.2010

	weight (d.w.)
Soil	0,0029 mg/kg dry
	weight (d.w.)

### 8.2 Exposure controls

#### **Engineering measures**

Ensure adequate ventilation, especially in confined areas.

Minimize workplace exposure concentrations.

### Personal protective equipment

Eye/face protection : Please follow all applicable local/national requirements when

selecting protective measures for a specific workplace.

Wear the following personal protective equipment:

Safety glasses

Always wear eye protection when the potential for inadvertent

eye contact with the product cannot be excluded. Equipment should conform to DIN EN 166

Hand protection

Material : Nitrile rubber
Break through time : 480 min
Glove thickness : > 0,4 mm

Directive : Equipment should conform to DIN EN 374

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Skin should be washed after contact.

Respiratory protection : If adequate local exhaust ventilation is not available or expo-

sure assessment demonstrates exposures outside the rec-

ommended guidelines, use respiratory protection.

Equipment should conform to DIN EN 143

Filter type : Particulates type (P)

## **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

Physical state : liquid

Colour : yellow

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## PIPE AND THREAD SEALANT MEDIUM STRENGTH - 48 ML / 50 G

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02.03.2024

 11.1
 28.03.2024
 10630277-00018
 Date of first issue: 11.06.2010

Odour : characteristic

Odour Threshold : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling :

range

ca. 324 °C

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Ignitable (see flash point)

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Flash point : > 100 °C

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : substance/mixture is non-soluble (in water)

Viscosity

Viscosity, dynamic : 18.000 - 30.000 mPa.s (20 °C)

Viscosity, kinematic : No data available

Solubility(ies)

Water solubility : practically insoluble

Partition coefficient: n-

octanol/water

Not applicable

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## PIPE AND THREAD SEALANT MEDIUM STRENGTH - 48 ML / 50 G

Version Revision Date: SDS Number: Date of last issue: 02.03.2024 11.1 28.03.2024 10630277-00018 Date of first issue: 11.06.2010

Vapour pressure : No data available

Density : 1,05 g/cm³ (20 °C)

Relative vapour density : No data available

Particle characteristics

Particle size : Not applicable

9.2 Other information

Explosives : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Evaporation rate : No data available

### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

Not classified as a reactivity hazard.

#### 10.2 Chemical stability

Stable under normal conditions.

## 10.3 Possibility of hazardous reactions

Hazardous reactions : Can react with strong oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

#### 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## PIPE AND THREAD SEALANT MEDIUM STRENGTH - 48 ML / 50 G

Version Revision Date: SDS Number: Date of last issue: 02.03.2024 11.1 28.03.2024 10630277-00018 Date of first issue: 11.06.2010

### **SECTION 11: Toxicological information**

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of:

exposure

Inhalation Skin contact

Ingestion Eye contact

#### **Acute toxicity**

Not classified based on available information.

**Product:** 

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg

Method: Calculation method

#### **Components:**

#### 2-(2-Methylprop-2-enoyloxy)ethyl 2-methylprop-2-enoate:

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg

Acute dermal toxicity : LD50 (Mouse): > 2.000 mg/kg

#### α,α-dimethylbenzyl hydroperoxide:

Acute oral toxicity : LD50 (Rat, male): 382 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 3 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Expert judgement

Remarks: Based on national or regional regulation.

Acute dermal toxicity : LD50 (Rabbit, male): 133,6 mg/kg

2'-Phenylacetohydrazide:

Acute oral toxicity : LD50 (Mouse): 270 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 300 - 2.000 mg/kg

Remarks: Based on data from similar materials

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## PIPE AND THREAD SEALANT MEDIUM STRENGTH - 48 ML / 50 G

Version Revision Date: SDS Number: Date of last issue: 02.03.2024 11.1 28.03.2024 10630277-00018 Date of first issue: 11.06.2010

p-Benzoquinone:

Acute oral toxicity : LD50 (Rat): 130 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 0,5001 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Expert judgement

Remarks: Based on national or regional regulation.

#### Skin corrosion/irritation

Not classified based on available information.

#### **Components:**

## 2-(2-Methylprop-2-enoyloxy)ethyl 2-methylprop-2-enoate:

Species : Rabbit

Result : No skin irritation

Remarks : Based on data from similar materials

## $\alpha,\alpha$ -dimethylbenzyl hydroperoxide:

Species : Rabbit

Result : Corrosive after 4 hours or less of exposure

2'-Phenylacetohydrazide:

Species : Rabbit Result : Skin irritation

Remarks : Based on data from similar materials

p-Benzoquinone:

Species : reconstructed human epidermis (RhE)

Method : OECD Test Guideline 431

Result : Corrosive after 4 hours or less of exposure

#### Serious eye damage/eye irritation

Not classified based on available information.

#### **Components:**

#### 2-(2-Methylprop-2-enoyloxy)ethyl 2-methylprop-2-enoate:

Species : Rabbit

Method : OECD Test Guideline 405

Result : No eye irritation

Remarks : Based on data from similar materials

#### α,α-dimethylbenzyl hydroperoxide:

Species : Rabbit

Result : Irreversible effects on the eye

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## PIPE AND THREAD SEALANT MEDIUM STRENGTH - 48 ML / 50 G

Version Revision Date: SDS Number: Date of last issue: 02.03.2024 11.1 28.03.2024 10630277-00018 Date of first issue: 11.06.2010

2'-Phenylacetohydrazide:

Species : Rabbit

Result : Irritation to eyes, reversing within 21 days Remarks : Based on data from similar materials

p-Benzoquinone:

Result : Irreversible effects on the eye Remarks : Based on skin corrosivity.

## Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.

### **Components:**

#### p-Benzoquinone:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Result : positive

Remarks : Based on data from similar materials

Assessment : Probability or evidence of low to moderate skin sensitisation

rate in humans

#### Germ cell mutagenicity

Not classified based on available information.

## **Components:**

### 2-(2-Methylprop-2-enoyloxy)ethyl 2-methylprop-2-enoate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Remarks: Based on data from similar materials

### $\alpha,\alpha$ -dimethylbenzyl hydroperoxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: positive

Test Type: DNA damage and repair, unscheduled DNA syn-

thesis in mammalian cells (in vitro)

Result: positive

Test Type: Chromosome aberration test in vitro

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## PIPE AND THREAD SEALANT MEDIUM STRENGTH - 48 ML / 50 G

Version Revision Date: SDS Number: Date of last issue: 02.03.2024 11.1 28.03.2024 10630277-00018 Date of first issue: 11.06.2010

Result: positive

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Skin contact

Result: negative

Germ cell mutagenicity- As-

sessment

Weight of evidence does not support classification as a germ

cell mutagen.

2'-Phenylacetohydrazide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: positive

p-Benzoquinone:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Result: positive

Test Type: in vitro micronucleus test

Result: positive

Test Type: DNA damage and repair, unscheduled DNA syn-

thesis in mammalian cells (in vitro)

Result: positive

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Ingestion

Result: positive

Germ cell mutagenicity- As-

sessment

Positive result(s) from in vivo non-mammalian somatic cell

mutagenicity tests, supported by positive results from in vitro

mutagenicity assays.

#### Carcinogenicity

Not classified based on available information.

#### Reproductive toxicity

Not classified based on available information.

### **Components:**

#### 2-(2-Methylprop-2-enoyloxy)ethyl 2-methylprop-2-enoate:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## PIPE AND THREAD SEALANT MEDIUM STRENGTH - 48 ML / 50 G

Version Revision Date: SDS Number: Date of last issue: 02.03.2024 11.1 28.03.2024 10630277-00018 Date of first issue: 11.06.2010

Result: negative

Remarks: Based on data from similar materials

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 414

Result: negative

Remarks: Based on data from similar materials

### $\alpha, \alpha$ -dimethylbenzyl hydroperoxide:

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 414

Result: negative

#### STOT - single exposure

Not classified based on available information.

### **Components:**

### $\alpha,\alpha$ -dimethylbenzyl hydroperoxide:

Assessment : May cause respiratory irritation.

p-Benzoquinone:

Assessment : May cause respiratory irritation.

Remarks : Based on national or regional regulation.

Assessment : May cause drowsiness or dizziness.

### STOT - repeated exposure

Not classified based on available information.

## **Components:**

### $\alpha,\alpha$ -dimethylbenzyl hydroperoxide:

Exposure routes : Inhalation Target Organs : Lungs

Assessment : Shown to produce significant health effects in animals at con-

centrations of >0.2 to 1 mg/l/6h/d.

#### Repeated dose toxicity

#### **Components:**

#### 2-(2-Methylprop-2-enoyloxy)ethyl 2-methylprop-2-enoate:

Species : Rat

NOAEL : 1.000 mg/kg

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## PIPE AND THREAD SEALANT MEDIUM STRENGTH - 48 ML / 50 G

Version Revision Date: SDS Number: Date of last issue: 02.03.2024 11.1 28.03.2024 10630277-00018 Date of first issue: 11.06.2010

**Application Route** Ingestion Exposure time 56 Days

Method OECD Test Guideline 422

Remarks Based on data from similar materials

**Species** Rat LOAEL > 1 mg/l

Application Route : inhalation (vapour)

Exposure time : 90 Davs

Method : OECD Test Guideline 413

Remarks Based on data from similar materials

#### **Aspiration toxicity**

Not classified based on available information.

#### 11.2 Information on other hazards

#### **Endocrine disrupting properties**

#### **Product:**

Assessment The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

#### **SECTION 12: Ecological information**

#### 12.1 Toxicity

#### **Components:**

#### 2-(2-Methylprop-2-enoyloxy)ethyl 2-methylprop-2-enoate:

Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): 19,02 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

### α,α-dimethylbenzyl hydroperoxide:

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): 3,9 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 18,84 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic ErC50 (Desmodesmus subspicatus (green algae)): 3,1 mg/l

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## PIPE AND THREAD SEALANT MEDIUM STRENGTH - 48 ML / 50 G

Version Revision Date: SDS Number: Date of last issue: 02.03.2024 11.1 28.03.2024 10630277-00018 Date of first issue: 11.06.2010

plants Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Desmodesmus subspicatus (green algae)): 1 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

2'-Phenylacetohydrazide:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 0,1 - 1 mg/l

Exposure time: 96 h

Remarks: Based on data from similar materials

M-Factor (Acute aquatic tox-

icity)

: 1

p-Benzoquinone:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 0,045 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 0,059 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

ErC50 (Desmodesmus subspicatus (green algae)): 1,5 mg/l

Exposure time: 72 h

M-Factor (Acute aquatic tox-

icity)

10

Toxicity to microorganisms : EC50 (activated sludge): 12 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

M-Factor (Chronic aquatic

toxicity)

10

#### 12.2 Persistence and degradability

#### **Components:**

## 2-(2-Methylprop-2-enoyloxy)ethyl 2-methylprop-2-enoate:

Biodegradability : Result: Readily biodegradable.

Remarks: Based on data from similar materials

#### α,α-dimethylbenzyl hydroperoxide:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 3 % Exposure time: 28 d

Method: OECD Test Guideline 301B

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## PIPE AND THREAD SEALANT MEDIUM STRENGTH - 48 ML / 50 G

Version Revision Date: SDS Number: Date of last issue: 02.03.2024 11.1 28.03.2024 10630277-00018 Date of first issue: 11.06.2010

2'-Phenylacetohydrazide:

Biodegradability : Result: Readily biodegradable.

Remarks: Based on data from similar materials

p-Benzoquinone:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 56 % Exposure time: 28 d

Method: OECD Test Guideline 301A

#### 12.3 Bioaccumulative potential

#### Components:

#### 2-(2-Methylprop-2-enoyloxy)ethyl 2-methylprop-2-enoate:

Partition coefficient: n- : log Pow: < 4

octanol/water Method: OECD Test Guideline 117

### $\alpha,\alpha$ -dimethylbenzyl hydroperoxide:

Partition coefficient: n- : log Pow: 1,6

octanol/water Method: OECD Test Guideline 117

p-Benzoquinone:

Partition coefficient: n- : log Pow: 0,2

octanol/water Method: OECD Test Guideline 107

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

#### **Product:**

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

### 12.6 Endocrine disrupting properties

#### **Product:**

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## PIPE AND THREAD SEALANT MEDIUM STRENGTH - 48 ML / 50 G

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 02.03.2024

 11.1
 28.03.2024
 10630277-00018
 Date of first issue: 11.06.2010

#### 12.7 Other adverse effects

No data available

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.

According to the European Waste Catalogue, Waste Codes

are not product specific, but application specific.

Waste codes should be assigned by the user, preferably in

discussion with the waste disposal authorities.

Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

Waste Code : The following Waste Codes are only suggestions:

used product

08 04 09, waste adhesives and sealants containing organic

solvents or other hazardous substances

unused product

08 04 09, waste adhesives and sealants containing organic

solvents or other hazardous substances

uncleaned packagings

15 01 10, packaging containing residues of or contaminated

by hazardous substances

Acc. Packaging Act properly emptied packaging:
Properly emptied, non-contaminated packaging of non-hazardous products can be supplied to a system for the col-

lection of sales packaging.

#### **SECTION 14: Transport information**

## 14.1 UN number or ID number

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

#### 14.2 UN proper shipping name

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## PIPE AND THREAD SEALANT MEDIUM STRENGTH - 48 ML / 50 G

Version Revision Date: SDS Number: Date of last issue: 02.03.2024 11.1 28.03.2024 10630277-00018 Date of first issue: 11.06.2010

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.4 Packing group

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA (Cargo) : Not regulated as a dangerous good
IATA (Passenger) : Not regulated as a dangerous good

#### 14.5 Environmental hazards

Not regulated as a dangerous good

#### 14.6 Special precautions for user

Not applicable

### 14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

#### **SECTION 15: Regulatory information**

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) Conditions of restriction for the following entries should be considered: Number on list 75, 3

Substance(s) or mixture(s) are listed here according to their appearance in the regulation, irrespective of their use/purpose or the conditions of the restriction. Please refer to the condi-

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## PIPE AND THREAD SEALANT MEDIUM STRENGTH - 48 ML / 50 G

Version Revision Date: SDS Number: Date of last issue: 02.03.2024 11.1 28.03.2024 10630277-00018 Date of first issue: 11.06.2010

> tions in corresponding Regulation to determine whether an entry is applicable to the placing on the market or

not.

If you intend to use this product as tattoo ink, please contact your ven-

dor.

N,N-diethyl-p-(phenylazo)aniline

(Number on list 43)

Cumene (Number on list 28)

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

: Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Water hazard class (Germa-

WGK 2 obviously hazardous to water

ny)

Classification according to AwSV, Annex 1 (5.2)

TA Luft List (Germany) : 5.2.1: Total dust:

Not applicable

5.2.2: Inorganic substances in powdered form:

Not applicable

5.2.4: Inorganic substances in gaseous form:

Not applicable

5.2.5: Organic Substances: Class 1: 0,01 % p-Benzoquinone 5.2.7.1.1: Carcinogenic substance:

Class 1: 0,1 % Cumene

5.2.7.1.1: Quartz fine dust PM4:

Not applicable

5.2.7.1.1: Formaldehyde:

Not applicable 5.2.7.1.1: fibres: Not applicable

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## PIPE AND THREAD SEALANT MEDIUM STRENGTH - 48 ML / 50 G

Version Revision Date: SDS Number: Date of last issue: 02.03.2024 11.1 28.03.2024 10630277-00018 Date of first issue: 11.06.2010

5.2.7.2: Poorly degradable, easily enrichable and highly toxic

organic substances: Not applicable

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 0,74 %, 7,81 g/l

Remarks: VOC content excluding water

#### Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

#### 15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

Other information : Items where changes have been made to the previous version

are highlighted in the body of this document by two vertical

lines.

### **Full text of H-Statements**

H228 : Flammable solid.

H242 : Heating may cause a fire.

H301 : Toxic if swallowed.
H302 : Harmful if swallowed.
H310 : Fatal in contact with skin.
H311 : Toxic in contact with skin.

H314 : Causes severe skin burns and eye damage.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.

H331 : Toxic if inhaled.

H335
H336
H341
May cause respiratory irritation.
May cause drowsiness or dizziness.
Suspected of causing genetic defects.

H373 : May cause damage to organs through prolonged or repeated

exposure.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.
 H411 : Toxic to aquatic life with long lasting effects.
 H412 : Harmful to aquatic life with long lasting effects.

#### Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## PIPE AND THREAD SEALANT MEDIUM STRENGTH - 48 ML / 50 G

Version Revision Date: SDS Number: Date of last issue: 02.03.2024 11.1 28.03.2024 10630277-00018 Date of first issue: 11.06.2010

Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam.: Serious eye damageEye Irrit.: Eye irritationFlam. Sol.: Flammable solidsMuta.: Germ cell mutagenicityOrg. Perox.: Organic peroxides

Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

STOT RE : Specific target organ toxicity - repeated exposure STOT SE : Specific target organ toxicity - single exposure

DE DFG MAK : Germany. MAK BAT Annex IIa

DE DFG MAK / MAK : MAK value

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

#### **Further information**

Sources of key data used to compile the Safety Data

Sheet

: Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



## PIPE AND THREAD SEALANT MEDIUM STRENGTH - 48 ML / 50 G

Version Revision Date: SDS Number: Date of last issue: 02.03.2024 11.1 28.03.2024 10630277-00018 Date of first issue: 11.06.2010

Classification of the mixture: Classification procedure:

Aquatic Chronic 3 H412 Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN