according to Regulation (EC) No. 1907/2006



BATTERY LI-ION 18 V / 5,0 AH M-CUBE BASIC

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.09.2019

 2.0
 10.01.2020
 4832428-00002
 Date of first issue: 06.09.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : BATTERY LI-ION 18 V / 5,0 AH M-CUBE BASIC

Product code : 5703450000

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Battery, Article

stance/Mixture Professional use product

1.3 Details of the supplier of the safety data sheet

Company : Adolf Wuerth GmbH & Co. KG

Reinhold-Würth-Str. 12-17

74653 Künzelsau

Telephone : +49 794015 0

Telefax : +49 794015 10 00

E-mail address of person

responsible for the SDS

: prodsafe@wuerth.com

1.4 Emergency telephone number

+49 (0)6132 - 84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

Additional Labelling

Restricted to professional users.

EUH210 Safety data sheet available on request.

EUH208 Contains Nickel, Cobalt lithium dioxide, 4-Fluoro-1,3-dioxolan-2-one, Lithium

nickel oxide. May produce an allergic reaction.

2.3 Other hazards

None known.

according to Regulation (EC) No. 1907/2006



BATTERY LI-ION 18 V / 5,0 AH M-CUBE BASIC

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.09.2019

 2.0
 10.01.2020
 4832428-00002
 Date of first issue: 06.09.2019

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Lithium nickel oxide	12325-84-7	Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Muta. 2; H341 Carc. 1A; H350i Repr. 2; H361d STOT RE 1; H372 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 10	
Cobalt lithium dioxide	12190-79-3 235-362-0	Resp. Sens. 1B; H334 Muta. 2; H341 Carc. 1B; H350 Repr. 1B; H360F STOT RE 1; H372 Aquatic Chronic 2; H411	>= 2,5 - < 10
methyl propionate	554-12-1 209-060-4 607-027-00-2	Flam. Liq. 2; H225 Acute Tox. 4; H332 Eye Dam. 1; H318	>= 3 - < 10
Lithium hexafluorophosphate	21324-40-3 244-334-7	Acute Tox. 3; H301 Skin Corr. 1A; H314 Eye Dam. 1; H318 STOT RE 1; H372	>=1-<3
4-Fluoro-1,3-dioxolan-2-one	114435-02-8 483-360-5	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 STOT RE 1; H372	>= 1 - < 10
REACH - Candidate List of Substantia	nces of Very High Conce	ern for Authorisation (Art	icle 59). :
N-Methyl-2-pyrrolidone	872-50-4 212-828-1 606-021-00-7	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Repr. 1B; H360D STOT SE 3; H335	>= 0,3 - < 1

For explanation of abbreviations see section 16.

according to Regulation (EC) No. 1907/2006



BATTERY LI-ION 18 V / 5,0 AH M-CUBE BASIC

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.09.2019

 2.0
 10.01.2020
 4832428-00002
 Date of first issue: 06.09.2019

SECTION 4: First aid measures

4.1 Description of first aid measures

Protection of first-aiders : No special precautions are necessary for first aid responders.

If inhaled : Not applicable

In case of skin contact : Not applicable

In case of eye contact : Not applicable

If swallowed : Not applicable

4.2 Most important symptoms and effects, both acute and delayed

Risks : May produce an allergic reaction.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

None known.

Metal oxides

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod: :

ucts

Nickel compounds
Carbon oxides
Cobalt compounds
Fluorine compounds

Oxides of phosphorus

5.3 Advice for firefighters

Special protective equipment :

for firefighters

Wear self-contained breathing apparatus for firefighting if nec-

essary. Use personal protective equipment.

Specific extinguishing meth-

ods

: Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

according to Regulation (EC) No. 1907/2006



BATTERY LI-ION 18 V / 5,0 AH M-CUBE BASIC

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.09.2019

 2.0
 10.01.2020
 4832428-00002
 Date of first issue: 06.09.2019

Remove undamaged containers from fire area if it is safe to do

SO

Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Follow safe handling advice and personal protective equip-

ment recommendations.

6.2 Environmental precautions

Environmental precautions : Discharge into the environment must be avoided.

Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Sweep up or vacuum up spillage and collect in suitable con-

tainer for disposal.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to deter-

mine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Avoid prolonged or repeated contact with skin.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as-

sessment

Keep away from water. Protect from moisture.

Take care to prevent spills, waste and minimize release to the

environment.

Hygiene measures : When using do not eat, drink or smoke.

according to Regulation (EC) No. 1907/2006



BATTERY LI-ION 18 V / 5,0 AH M-CUBE BASIC

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.09.2019

 2.0
 10.01.2020
 4832428-00002
 Date of first issue: 06.09.2019

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep in properly labelled containers. Store in accordance with

the particular national regulations.

Advice on common storage

Do not store with the following product types:

Strong oxidizing agents

Storage class (TRGS 510)

: 11, Combustible Solids

Recommended storage tem: :

perature

< 125 °C

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Lithium nickel ox- ide	12325-84-7	AGW (Inhalable fraction)	0,03 mg/m3	DE TRGS 900
Peak-limit: excursion factor (category)	8;(II)			
Further information	For nickel compounds classified as Carc 1A or 1B, see TRGS 910 and TRGS 561. An assessment based on the AGW for nickel metal can be carried out if nickel metal only is present. If nickel-containing dusts are formed during activities in which only surface oxidation is to be controlled, they must be treated as nickel-metal-containing mixtures. When using thermal processes in the presence of oxygen, a formation of oxidic nickel compounds must always be assumed. This is the case, for example, in welding (electrodes or wire) and thermal cutting with or from alloys, in the metal injection of alloys, in the melting and casting of alloys, and in the grinding and separation of alloys with 'spark formation'. Further recommendations as well as examples of working methods, for which the AGW or the ERB can be used for assessment, are contained in the IFA workbook (code 0537)., The occupational medicaltoxicological derivation of this value is based on a plausibility analysis. The values for respirable dust for nickel metal in TRGS 900 and for nickel compounds in TRGS 910 are to be considered., Commission for dangerous substances, The threshold value is based on the element content of the corresponding metal., When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child, Substance sensitizing through the skin			
Graphite	7782-42-5	AGW (Inhalable fraction)	10 mg/m3	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)			

according to Regulation (EC) No. 1907/2006



BATTERY LI-ION 18 V / 5,0 AH M-CUBE BASIC

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.09.2019

 2.0
 10.01.2020
 4832428-00002
 Date of first issue: 06.09.2019

Further information	General dust value. For this substance no specific occupational exposure limit value is established, since the AGS does not yet have information regarding unspecific action on the respiratory organs in excess of the normal values., Commission for dangerous substances, Senate commission for the review of			
			gerous for the health (MAK-	
	Compounded	AGW (Alveolate fraction)	1,25 mg/m3	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)	,		
Aluminium	7429-90-5	AGW (Inhalable fraction)	10 mg/m3	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)			
Further information	value is estab unspecific act Commission to	olished, since the AG tion on the respirator for dangerous substa t the work place dan	ance no specific occupation S does not yet have informately organs in excess of the notances, Senate commission for the health (MAK-	ation regarding ormal values., or the review of commission).
		AGW (Alveolate fraction)	1,25 mg/m3	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)			
Cobalt lithium dioxide	12190-79-3	AGW (Inhalable fraction)	0,2 mg/m3 (Lithium)	DE TRGS 900
Peak-limit: excursion factor (category)	1;(I)			
Further information	for the health ment content	(MAK-commission). of the corresponding	of compounds at the work p The threshold value is base metal., When there is comp es, there is no risk of harmin	ed on the ele- pliance with the
		Acceptable concentration (Alveolate part)	0,5 microgram per cubic meter (Cobalt)	DE TRGS 910
Further information			ted with the risk 4:10000, Th	ne concentra-
	.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	Tolerable con- centration (Alveo- late part)	5 microgram per cubic meter (Cobalt)	DE TRGS 910
Peak-limit: excursion factor (category)	8 - Excursion	factor according to N	Number 3.2.5	
Further information	The concentra	ations apply to the el	ement of the metal	
Polyethylene	9002-88-4	AGW (Inhalable fraction)	10 mg/m3	DE TRGS 900
Peak-limit: excursion factor (catego-	2;(II)			

according to Regulation (EC) No. 1907/2006



BATTERY LI-ION 18 V / 5,0 AH M-CUBE BASIC

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.09.2019

 2.0
 10.01.2020
 4832428-00002
 Date of first issue: 06.09.2019

1	1			
ry) Further information	General dust value. For this substance no specific occupational exposure limit value is established, since the AGS does not yet have information regarding unspecific action on the respiratory organs in excess of the normal values., Commission for dangerous substances, Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
	, , , , , , , , , , , , , , , , , , , ,	AGW (Alveolate fraction)	1,25 mg/m3	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)			
Lithium hexafluor- ophosphate	21324-40-3	AGW (Inhalable fraction)	1 mg/m3 (Fluorine)	DE TRGS 900
Peak-limit: excursion factor (category)	4;(II)			
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission)., Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		TWA	2,5 mg/m3 (Fluorine)	2000/39/EC
Further information	Indicative			
N-Methyl-2- pyrrolidone	872-50-4	TWA	10 ppm 40 mg/m3	2009/161/EU
Further information	Identifies the	possibility of signific	ant uptake through the skin,	
		STEL	20 ppm 80 mg/m3	2009/161/EU
		AGW (Vapour)	20 ppm 82 mg/m3	DE TRGS 900
Peak-limit: excursion factor (category)	2;(I)			
Further information	Senate commission for the review of compounds at the work place dangerous for the health has also established a BEI-value for the same OEL value in the 'MAK- and BAT-value list', Commission for dangerous substances, Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission)., European Union (The EU has established a limit value: deviations in value and peak limit are possible), Sum of vapor and aerosols., Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Phosphoric acid	7664-38-2	TWA	1 mg/m3	2000/39/EC
Further information	Indicative			
		STEL	2 mg/m3	2000/39/EC

according to Regulation (EC) No. 1907/2006



BATTERY LI-ION 18 V / 5,0 AH M-CUBE BASIC

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.09.2019

 2.0
 10.01.2020
 4832428-00002
 Date of first issue: 06.09.2019

		AGW (Inhalable fraction)	2 mg/m3	DE TRGS 900		
Peak-limit: excursion factor (category)	2;(I)					
Further information	compounds a European Uni and peak limit	Commission for dangerous substances, Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission)., European Union (The EU has established a limit value: deviations in value and peak limit are possible), When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child				
Hydrofluoric acid	7664-39-3	TWA	1,8 ppm 1,5 mg/m3	2000/39/EC		
Further information	Indicative					
		STEL	3 ppm 2,5 mg/m3	2000/39/EC		
		AGW	1 ppm 0,83 mg/m3	DE TRGS 900		
Peak-limit: excursion factor (category)	2;(I)					
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission)., European Union (The EU has established a limit value: deviations in value and peak limit are possible), Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child					
Lithium fluoride	7789-24-4	AGW (Inhalable fraction)	1 mg/m3 (Fluorine)	DE TRGS 900		
Peak-limit: excursion factor (category)	4;(II)					
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission)., Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child					
		AGW (Inhalable fraction)	0,2 mg/m3 (Lithium)	DE TRGS 900		
Peak-limit: excursion factor (category)	1;(I)	,				
Further information	for the health ment content	(MAK-commission). of the corresponding	of compounds at the work p , The threshold value is base g metal., When there is comp es, there is no risk of harmin	d on the ele- liance with the		
		TWA	2,5 mg/m3 (Fluorine)	2000/39/EC		
Further information	Indicative					

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Lithium hexafluorophos-	21324-40-3	fluoride (Fluorine):	Immediately after	TRGS 903
phate		7 mg/g Creatinine	exposure or after	

according to Regulation (EC) No. 1907/2006



BATTERY LI-ION 18 V / 5,0 AH M-CUBE BASIC

Version Revision Date: SDS Number: Date of last issue: 06.09.2019 2.0 10.01.2020 4832428-00002 Date of first issue: 06.09.2019

		(Urine)	working hours	
		fluoride (Fluorine): 4 mg/g Creatinine (Urine)	Before next shift	TRGS 903
N-Methyl-2-pyrrolidone	872-50-4	5-Hydroxy-N- methyl-2- pyrrolidone: 150 mg/I (Urine)	Immediately after exposure or after working hours	TRGS 903

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Aluminium	Workers	Inhalation	Long-term local ef- fects	3,72 mg/m3
	Consumers	Ingestion	Long-term systemic effects	3,95 mg/kg bw/day
Iron	Workers	Inhalation	Long-term local ef- fects	3 mg/m3
	Consumers	Inhalation	Long-term local ef- fects	1,5 mg/m3
	Consumers	Ingestion	Long-term systemic effects	0,71 mg/kg bw/day
Copper	Consumers	Inhalation	Acute systemic effects	20 mg/m3
	Consumers	Skin contact	Acute systemic effects	273 mg/kg bw/day
	Workers	Skin contact	Long-term systemic effects	137 mg/kg bw/day
	Workers	Inhalation	Acute systemic effects	20 mg/m3
	Workers	Skin contact	Acute systemic effects	273 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	137 mg/kg bw/day
N-Methyl-2- pyrrolidone	Workers	Inhalation	Long-term systemic effects	14,4 mg/m3
	Workers	Inhalation	Long-term local ef- fects	40 mg/m3
	Workers	Skin contact	Long-term systemic effects	4,8 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	3,6 mg/m3
	Consumers	Inhalation	Long-term local ef- fects	4,5 mg/m3
	Consumers	Skin contact	Long-term systemic effects	2,4 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0,85 mg/kg bw/day
Graphite	Consumers	Inhalation	Long-term local ef- fects	0,3 mg/m3
	Consumers	Ingestion	Long-term systemic effects	813 mg/kg bw/day

according to Regulation (EC) No. 1907/2006



BATTERY LI-ION 18 V / 5,0 AH M-CUBE BASIC

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.09.2019

 2.0
 10.01.2020
 4832428-00002
 Date of first issue: 06.09.2019

	Workers	Inhalation	Long-term local effects	1,2 mg/m3
Lithium hexafluoro- phosphate	Workers	Inhalation	Long-term systemic effects	0,931 mg/m3
	Workers	Skin contact	Long-term systemic effects	0,133 mg/kg bw/day
Cobalt lithium dioxide	Workers	Inhalation	Long-term local effects	0,0664 mg/m3
	Consumers	Inhalation	Long-term local effects	0,0105 mg/m3
	Consumers	Ingestion	Long-term systemic effects	0,0495 mg/kg bw/day
Dimethyl carbonate	Workers	Inhalation	Long-term systemic effects	17,2 mg/m3
	Workers	Inhalation	Acute systemic ef- fects	57 mg/m3
	Workers	Skin contact	Long-term systemic effects	5 mg/kg bw/day
	Workers	Inhalation	Acute local effects	57 mg/m3
	Workers	Skin contact	Acute systemic effects	66,7 mg/kg bw/day
	Workers	Skin contact	Acute local effects	17,7 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	4,4 mg/m3
	Consumers	Inhalation	Acute systemic effects	42,5 mg/m3
	Consumers	Inhalation	Acute local effects	42,5 mg/m3
	Consumers	Skin contact	Long-term systemic effects	2,5 mg/kg bw/day
	Consumers	Skin contact	Acute systemic ef- fects	33,3 mg/kg bw/day
	Consumers	Skin contact	Acute local effects	8,9 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	2,5 mg/kg bw/day
	Consumers	Ingestion	Acute systemic ef- fects	50 mg/kg bw/day
4-Fluoro-1,3-dioxolan- 2-one	Workers	Inhalation	Long-term systemic effects	0,164 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Aluminium	Sewage treatment plant	20 mg/l
Copper	Fresh water	7,8 µg/l
	Marine water	5,2 μg/l
	Sewage treatment plant	230 μg/l
	Fresh water sediment	87 mg/kg
	Marine sediment	676 mg/kg
	Soil	65 mg/kg
N-Methyl-2-pyrrolidone	Fresh water	0,25 mg/l
	Freshwater - intermittent	5 mg/l
	Marine water	0,025 mg/l

according to Regulation (EC) No. 1907/2006



BATTERY LI-ION 18 V / 5,0 AH M-CUBE BASIC

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.09.2019

 2.0
 10.01.2020
 4832428-00002
 Date of first issue: 06.09.2019

	Sewage treatment plant	10 mg/l
	Fresh water sediment	1,09 mg/kg dry
		weight (d.w.)
	Marine sediment	1,09 mg/kg dry
		weight (d.w.)
	Soil	0,07 mg/kg dry
		weight (d.w.)
Lithium hexafluorophosphate	Fresh water	0,31 mg/l
	Marine water	0,031 mg/l
	Intermittent use/release	0,68 mg/l
	Sewage treatment plant	48 mg/l
	Fresh water sediment	7,73 mg/kg dry
		weight (d.w.)
	Marine sediment	1,55 mg/kg dry
		weight (d.w.)
	Soil	13,5 mg/kg dry
		weight (d.w.)
Cobalt lithium dioxide	Fresh water	0,0006 mg/l
	Marine water	0,00236 mg/l
	Sewage treatment plant	0,37 mg/l
	Fresh water sediment	9,5 mg/kg dry
		weight (d.w.)
	Marine sediment	9,5 mg/kg dry
		weight (d.w.)
	Soil	10,9 mg/kg dry
		weight (d.w.)
Dimethyl carbonate	Fresh water	0,5 mg/l
	Marine water	0,05 mg/l
	Intermittent use/release	1 mg/l
	Sewage treatment plant	188 mg/l
4-Fluoro-1,3-dioxolan-2-one	Fresh water	0,008 mg/l
	Freshwater - intermittent	0,084 mg/l
	Marine water	0,001 mg/l
	Marine water - intermittent	0,008 mg/l
	Sewage treatment plant	8 mg/l
	Fresh water sediment	0,035 mg/kg dry
		weight (d.w.)
	Marine sediment	0,004 mg/kg dry
		weight (d.w.)
	Soil	0,002 mg/kg dry
		weight (d.w.)

8.2 Exposure controls

Engineering measures

Not applicable

Personal protective equipment

Eye protection : Not applicable

Hand protection

Remarks : not required

according to Regulation (EC) No. 1907/2006



BATTERY LI-ION 18 V / 5,0 AH M-CUBE BASIC

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.09.2019

 2.0
 10.01.2020
 4832428-00002
 Date of first issue: 06.09.2019

Skin and body protection : Not applicable

Respiratory protection : If adequate local exhaust ventilation is not available or expo-

sure assessment demonstrates exposures outside the rec-

ommended guidelines, use respiratory protection.

Equipment should conform to DIN EN 133

Filter type : Combined particulates, acidic gas/vapour and organic vapour

type (AE-P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : solid

Colour : No data available

Odour : odourless

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling

range

No data available

Flash point : Not applicable

Evaporation rate : Not applicable

Flammability (solid, gas) : Not classified as a flammability hazard

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : Not applicable

Relative vapour density : Not applicable

Density : No data available

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: Not applicable

according to Regulation (EC) No. 1907/2006



BATTERY LI-ION 18 V / 5,0 AH M-CUBE BASIC

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.09.2019

 2.0
 10.01.2020
 4832428-00002
 Date of first issue: 06.09.2019

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

Particle size : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Can react with strong oxidizing agents.

Hazardous decomposition products will be formed upon con-

tact with water or humid air.

10.4 Conditions to avoid

Conditions to avoid : Exposure to moisture

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

Water

10.6 Hazardous decomposition products

Contact with water or humid

air

Phosphoric acid Hydrofluoric acid

Lithium fluoride

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of:

exposure

Skin contact Ingestion

Eye contact

Acute toxicity

Not classified based on available information.

according to Regulation (EC) No. 1907/2006



BATTERY LI-ION 18 V / 5,0 AH M-CUBE BASIC

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.09.2019

 2.0
 10.01.2020
 4832428-00002
 Date of first issue: 06.09.2019

Product:

Acute oral toxicity : Assessment: The substance or mixture has no acute oral tox-

icity

Remarks: Based on bioavailability assessment according to

1.3.2.4.5 UN GHS/CLP article 12

Acute inhalation toxicity : Assessment: The substance or mixture has no acute inhala-

tion toxicity, Not corrosive to the respiratory tract

Remarks: Based on bioavailability assessment according to

1.3.2.4.5 UN GHS/CLP article 12

Components:

Lithium nickel oxide:

Acute oral toxicity : LD50 (Rat): > 300 mg/kg

Remarks: Based on data from similar materials

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

Remarks: Based on data from similar materials

Cobalt lithium dioxide:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Method: OECD Test Guideline 425

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

Method: OECD Test Guideline 402

Remarks: Based on data from similar materials

methyl propionate:

Acute oral toxicity : LD50 (Rabbit): 2.002 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 11 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Expert judgement

Remarks: Based on harmonised classification in EU regulation

1272/2008, Annex VI

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Lithium hexafluorophosphate:

Acute oral toxicity : LD50 (Rat): > 50 - 300 mg/kg

Method: OECD Test Guideline 423

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

4-Fluoro-1,3-dioxolan-2-one:

Acute oral toxicity : LD50 (Rat, female): 500 mg/kg

according to Regulation (EC) No. 1907/2006



BATTERY LI-ION 18 V / 5,0 AH M-CUBE BASIC

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.09.2019

 2.0
 10.01.2020
 4832428-00002
 Date of first issue: 06.09.2019

Method: OECD Test Guideline 423

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

Method: OECD Test Guideline 402

N-Methyl-2-pyrrolidone:

Acute oral toxicity : LD50 (Rat): 4.150 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5,1 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rat): > 5.000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Product:

Result : No skin irritation

Remarks : Based on bioavailability assessment according to 1.3.2.4.5

UN GHS/CLP article 12

Components:

Lithium nickel oxide:

Species : Rabbit

Method : OECD Test Guideline 404

Result : Corrosive after 3 minutes to 1 hour of exposure

Remarks : Based on data from similar materials

Cobalt lithium dioxide:

Species : reconstructed human epidermis (RhE)

Method : OECD Test Guideline 439

Result : No skin irritation

methyl propionate:

Species : reconstructed human epidermis (RhE)

Method : OECD Test Guideline 439

Result : No skin irritation

Lithium hexafluorophosphate:

Species : reconstructed human epidermis (RhE)

Method : OECD Test Guideline 431

Result : Corrosive after 3 minutes or less of exposure

4-Fluoro-1,3-dioxolan-2-one:

according to Regulation (EC) No. 1907/2006



BATTERY LI-ION 18 V / 5,0 AH M-CUBE BASIC

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.09.2019

 2.0
 10.01.2020
 4832428-00002
 Date of first issue: 06.09.2019

Species : reconstructed human epidermis (RhE)

Species : reconstructed human epidermis (RhE)

Method : OECD Test Guideline 439

Result : Skin irritation

N-Methyl-2-pyrrolidone:

Result : Skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Result : No eye irritation

Remarks : Based on bioavailability assessment according to 1.3.2.4.5

UN GHS/CLP article 12

Components:

Lithium nickel oxide:

Result : Irreversible effects on the eye Remarks : Based on skin corrosivity.

Cobalt lithium dioxide:

Species : Rabbit

Method : OECD Test Guideline 405

Result : No eye irritation

methyl propionate:

Species : Chicken eye

Method : OECD Test Guideline 438

Result : Irreversible effects on the eye

Lithium hexafluorophosphate:

Result : Irreversible effects on the eye Remarks : Based on skin corrosivity.

4-Fluoro-1,3-dioxolan-2-one:

Species : Rabbit

Method : OECD Test Guideline 405

Result : Irritation to eyes, reversing within 21 days Remarks : Based on data from similar materials

N-Methyl-2-pyrrolidone:

Species : Rabbit

Result : Irritation to eyes, reversing within 21 days

according to Regulation (EC) No. 1907/2006



BATTERY LI-ION 18 V / 5,0 AH M-CUBE BASIC

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.09.2019

 2.0
 10.01.2020
 4832428-00002
 Date of first issue: 06.09.2019

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Product:

Assessment : Does not cause respiratory sensitisation.

Remarks : Based on bioavailability assessment according to 1.3.2.4.5

UN GHS/CLP article 12

Assessment : Does not cause skin sensitisation.

Remarks : Based on bioavailability assessment according to 1.3.2.4.5

UN GHS/CLP article 12

Components:

Lithium nickel oxide:

Exposure routes : Skin contact Species : Humans Result : positive

Remarks : Based on data from similar materials

Assessment : Probability or evidence of skin sensitisation in humans

Cobalt lithium dioxide:

Test Type : Local lymph node assay (LLNA)

Exposure routes : Skin contact Species : Mouse

Method : OECD Test Guideline 429

Result : negative

Exposure routes : inhalation (dust/mist/fume)

Species : Humans Result : positive

Remarks : Based on data from similar materials

Assessment : Probability or evidence of low to moderate respiratory sensiti-

sation rate in humans

methyl propionate:

Test Type : Direct Peptide Reactivity Assay (DPRA)

Method : OECD Test Guideline 442C

Test Type : KeratinoSens assay

Method : OECD Test Guideline 442D

Result : negative

according to Regulation (EC) No. 1907/2006



BATTERY LI-ION 18 V / 5,0 AH M-CUBE BASIC

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.09.2019

 2.0
 10.01.2020
 4832428-00002
 Date of first issue: 06.09.2019

Lithium hexafluorophosphate:

Test Type : Local lymph node assay (LLNA)

Exposure routes : Skin contact Species : Mouse

Method : OECD Test Guideline 429

Result : negative

4-Fluoro-1,3-dioxolan-2-one:

Test Type : Local lymph node assay (LLNA)

Exposure routes : Skin contact Species : Mouse

Method : OECD Test Guideline 429

Result : positive

Assessment : Probability or evidence of skin sensitisation in humans

N-Methyl-2-pyrrolidone:

Test Type : Local lymph node assay (LLNA)

Exposure routes : Skin contact Species : Mouse

Method : OECD Test Guideline 429

Result : negative

Remarks : Based on data from similar materials

Germ cell mutagenicity

Not classified based on available information.

Components:

Lithium nickel oxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test

Result: positive

Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro

Result: positive

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow

cytogenetic test, chromosomal analysis)

Species: Mouse

Application Route: Intraperitoneal injection

Result: positive

Remarks: Based on data from similar materials

Germ cell mutagenicity- As-

sessment

Positive result(s) from in vivo mammalian somatic cell muta-

genicity tests.

according to Regulation (EC) No. 1907/2006



BATTERY LI-ION 18 V / 5,0 AH M-CUBE BASIC

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.09.2019

 2.0
 10.01.2020
 4832428-00002
 Date of first issue: 06.09.2019

Cobalt lithium dioxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: positive

Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: positive

Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: positive

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Micronucleus test

Species: Mouse

Application Route: Intraperitoneal injection

Result: positive

Remarks: Based on data from similar materials

Test Type: Mutagenicity (in vivo mammalian bone-marrow

cytogenetic test, chromosomal analysis)

Species: Mouse

Application Route: Ingestion

Result: positive

Remarks: Based on data from similar materials

Test Type: Rodent dominant lethal test (germ cell) (in vivo)

Species: Mouse

Application Route: Ingestion

Result: positive

Remarks: Based on data from similar materials

Germ cell mutagenicity- As-

sessment

Positive result(s) from in vivo mammalian somatic cell muta-

genicity tests.

methyl propionate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Lithium hexafluorophosphate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: positive

Remarks: Based on data from similar materials

according to Regulation (EC) No. 1907/2006



BATTERY LI-ION 18 V / 5,0 AH M-CUBE BASIC

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.09.2019

 2.0
 10.01.2020
 4832428-00002
 Date of first issue: 06.09.2019

Test Type: Chromosome aberration test in vitro

Result: positive

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

Germ cell mutagenicity- As-

sessment

Weight of evidence does not support classification as a germ

cell mutagen.

4-Fluoro-1,3-dioxolan-2-one:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: positive

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: positive

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection

Method: OECD Test Guideline 474

Result: negative

N-Methyl-2-pyrrolidone:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Test Type: DNA damage and repair, unscheduled DNA syn-

thesis in mammalian cells (in vitro)

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Ingestion

Method: OECD Test Guideline 474

Result: negative

Test Type: Mutagenicity (in vivo mammalian bone-marrow

cytogenetic test, chromosomal analysis)

Species: Hamster

according to Regulation (EC) No. 1907/2006



BATTERY LI-ION 18 V / 5,0 AH M-CUBE BASIC

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.09.2019

 2.0
 10.01.2020
 4832428-00002
 Date of first issue: 06.09.2019

Application Route: Ingestion Method: OECD Test Guideline 475

Result: negative

Carcinogenicity

Not classified based on available information.

Product:

Result : negative

Remarks : Based on bioavailability assessment according to 1.3.2.4.5

UN GHS/CLP article 12

Components:

Lithium nickel oxide:

Species : Humans

Application Route : inhalation (dust/mist/fume)

Result : positive

Remarks : Based on data from similar materials

Carcinogenicity - Assess-

Positive evidence from human epidemiological studies (inhala-

ment

tion)

Cobalt lithium dioxide:

Species : Rat

Application Route : inhalation (dust/mist/fume)

Exposure time : 105 weeks Result : positive

Remarks : Based on data from similar materials

Species : Mouse

Application Route : inhalation (dust/mist/fume)

Exposure time : 105 weeks
Result : positive

Remarks : Based on data from similar materials

Carcinogenicity - Assess-

ment

Sufficient evidence of carcinogenicity in animal experiments

N-Methyl-2-pyrrolidone:

Species : Rat
Application Route : Ingestion
Exposure time : 2 Years
Result : negative

Species : Rat

Application Route : inhalation (vapour)

Exposure time : 2 Years Result : negative

according to Regulation (EC) No. 1907/2006



BATTERY LI-ION 18 V / 5,0 AH M-CUBE BASIC

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.09.2019

 2.0
 10.01.2020
 4832428-00002
 Date of first issue: 06.09.2019

Reproductive toxicity

Not classified based on available information.

Product:

Effects on fertility : Result: negative

Remarks: Based on bioavailability assessment according to

1.3.2.4.5 UN GHS/CLP article 12

Effects on foetal develop-

ment

: Result: negative

Remarks: Based on bioavailability assessment according to

1.3.2.4.5 UN GHS/CLP article 12

Components:

Lithium nickel oxide:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 416

Result: negative

Remarks: Based on data from similar materials

Reproductive toxicity - As-

sessment

Some evidence of adverse effects on development, based on

animal experiments.

Cobalt lithium dioxide:

Effects on fertility : Test Type: Fertility/early embryonic development

Species: Rat

Application Route: Ingestion

Result: positive

Remarks: Based on data from similar materials

Test Type: Fertility/early embryonic development

Species: Mouse

Application Route: Ingestion

Result: positive

Remarks: Based on data from similar materials

Test Type: Fertility/early embryonic development

Species: Mouse

Application Route: inhalation (dust/mist/fume)

Result: positive

Remarks: Based on data from similar materials

Test Type: Fertility/early embryonic development

Species: Rat

Application Route: inhalation (dust/mist/fume)

Result: positive

Remarks: Based on data from similar materials

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: Ingestion

according to Regulation (EC) No. 1907/2006



BATTERY LI-ION 18 V / 5,0 AH M-CUBE BASIC

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.09.2019

 2.0
 10.01.2020
 4832428-00002
 Date of first issue: 06.09.2019

Method: OECD Test Guideline 414

Result: negative

Remarks: Based on data from similar materials

Reproductive toxicity - As-

sessment

Clear evidence of adverse effects on sexual function and fertil-

ity, based on animal experiments.

Lithium hexafluorophosphate:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

4-Fluoro-1,3-dioxolan-2-one:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening

test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 421

Result: negative

Effects on foetal develop-

ment

Test Type: Reproduction/Developmental toxicity screening

test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 421

Result: negative

N-Methyl-2-pyrrolidone:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion

Method: OECD Test Guideline 416

Result: negative

Effects on foetal develop-

ment

: Test Type: Embryo-foetal development

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 414

Result: positive

Test Type: Fertility/early embryonic development

Species: Rat

Application Route: inhalation (vapour)

Result: positive

according to Regulation (EC) No. 1907/2006



BATTERY LI-ION 18 V / 5,0 AH M-CUBE BASIC

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.09.2019

 2.0
 10.01.2020
 4832428-00002
 Date of first issue: 06.09.2019

Test Type: Embryo-foetal development

Species: Rabbit

Application Route: Ingestion

Result: positive

Reproductive toxicity - As-

sessment

Clear evidence of adverse effects on development, based on

animal experiments.

STOT - single exposure

Not classified based on available information.

Components:

N-Methyl-2-pyrrolidone:

Assessment : May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Product:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, repeated exposure.

Remarks : Based on bioavailability assessment according to 1.3.2.4.5

UN GHS/CLP article 12

Components:

Lithium nickel oxide:

Target Organs : Lungs

Assessment : Shown to produce significant health effects in animals at con-

centrations of 0.02 mg/l/6h/d or less.

Exposure routes : inhalation (dust/mist/fume)

Target Organs : Lungs

Assessment : Shown to produce significant health effects in animals at con-

centrations of 0.02 mg/l/6h/d or less.

Cobalt lithium dioxide:

Exposure routes : Ingestion

Target Organs : Thyroid, Heart, Blood

Assessment : Shown to produce significant health effects in animals at con-

centrations of 10 mg/kg bw or less.

Exposure routes : inhalation (dust/mist/fume)

Target Organs : Respiratory Tract

Assessment : Shown to produce significant health effects in animals at con-

centrations of 0.02 mg/l/6h/d or less.

Lithium hexafluorophosphate:

Exposure routes : Ingestion

according to Regulation (EC) No. 1907/2006



BATTERY LI-ION 18 V / 5,0 AH M-CUBE BASIC

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.09.2019

 2.0
 10.01.2020
 4832428-00002
 Date of first issue: 06.09.2019

Target Organs : Bone, Teeth

Assessment : Shown to produce significant health effects in animals at con-

centrations of 10 mg/kg bw or less.

Exposure routes : inhalation (gas)
Target Organs : Bone, Teeth

Assessment : Shown to produce significant health effects in animals at con-

centrations of 50 ppmV/6h/d or less.

4-Fluoro-1,3-dioxolan-2-one:

Exposure routes : Ingestion Target Organs : Teeth

Assessment : Shown to produce significant health effects in animals at con-

centrations of 10 mg/kg bw or less.

Repeated dose toxicity

Components:

Lithium nickel oxide:

Species : Rat

LOAEL : > 0.0 - 0.02 mg/l

Application Route : inhalation (dust/mist/fume)

Exposure time : 2 yr

Remarks : Based on data from similar materials

Cobalt lithium dioxide:

Species : Rat

LOAEL : 1,26 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Method : OECD Test Guideline 408

Remarks : Based on data from similar materials

Species : Mouse LOAEL : < 0,01 mg/l

Application Route : inhalation (dust/mist/fume)

Exposure time : 13 Weeks

Method : OECD Test Guideline 413

Remarks : Based on data from similar materials

Species : Rat

LOAEL : < 0,01 mg/l

Application Route : inhalation (dust/mist/fume)

Exposure time : 13 Weeks

Method : OECD Test Guideline 413

Remarks : Based on data from similar materials

Lithium hexafluorophosphate:

Species : Rat LOAEL : < 50 ppm

according to Regulation (EC) No. 1907/2006



BATTERY LI-ION 18 V / 5,0 AH M-CUBE BASIC

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.09.2019

 2.0
 10.01.2020
 4832428-00002
 Date of first issue: 06.09.2019

Application Route : inhalation (gas) Exposure time : 1 Months

Remarks : Based on data from similar materials

4-Fluoro-1,3-dioxolan-2-one:

Species : Rat
NOAEL : 5 mg/kg
Application Route : Ingestion
Exposure time : 35 - 48 Days

Method : OECD Test Guideline 421

N-Methyl-2-pyrrolidone:

Species : Rat, male
NOAEL : 169 mg/kg
LOAEL : 433 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Method : OECD Test Guideline 408

 Species
 : Rat

 NOAEL
 : 0,5 mg/l

 LOAEL
 : 1 mg/l

Application Route : inhalation (dust/mist/fume)

Exposure time : 96 Days

Method : OECD Test Guideline 413

Species : Rabbit

NOAEL : 826 mg/kg

LOAEL : 1.653 mg/kg

Application Route : Skin contact

Exposure time : 20 Days

Aspiration toxicity

Not classified based on available information.

Experience with human exposure

Components:

Cobalt lithium dioxide:

Inhalation : Target Organs: Respiratory system

Ingestion : Target Organs: Blood

Target Organs: Heart

Target Organs: Thyroid

N-Methyl-2-pyrrolidone:

Skin contact : Symptoms: Skin irritation

according to Regulation (EC) No. 1907/2006



BATTERY LI-ION 18 V / 5,0 AH M-CUBE BASIC

Version Revision Date: Date of last issue: 06.09.2019 SDS Number: 4832428-00002 Date of first issue: 06.09.2019 2.0 10.01.2020

SECTION 12: Ecological information

12.1 Toxicity

Product:

Ecotoxicology Assessment

Components:

Lithium nickel oxide:

Toxicity to fish LC50 (Pimephales promelas (fathead minnow)): > 0,1 - 1 mg/l

Exposure time: 96 h

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

LC50 (Ceriodaphnia dubia (water flea)): > 0,1 - 1 mg/l

Exposure time: 48 h

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): > 0,1 -

1 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

M-Factor (Acute aquatic tox- : 1

icity)

Toxicity to microorganisms EC50 : > 10 - 100 mg/l

Exposure time: 3 h Method: ISO 8192

Remarks: Based on data from similar materials

Toxicity to fish (Chronic tox-

icity)

NOEC: > 0.01 - 0.1 mg/l

Exposure time: 8 d

Species: Danio rerio (zebra fish)

Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chron-

ic toxicity)

EC10: > 0.001 - 0.01 mg/l

Exposure time: 7 d

Species: Ceriodaphnia dubia (water flea) Remarks: Based on data from similar materials

M-Factor (Chronic aquatic

toxicity)

10

Cobalt lithium dioxide:

Toxicity to fish LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l

Exposure time: 96 h

Remarks: Based on transformation/dissolution testing and

data from soluble metal compounds

Toxicity to daphnia and other : EL50 (Ceriodaphnia dubia (water flea)): > 100 mg/l

according to Regulation (EC) No. 1907/2006



BATTERY LI-ION 18 V / 5,0 AH M-CUBE BASIC

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.09.2019

 2.0
 10.01.2020
 4832428-00002
 Date of first issue: 06.09.2019

aguatic invertebrates Exposure time: 48 h

Remarks: Based on transformation/dissolution testing and

data from soluble metal compounds

Toxicity to algae/aquatic

plants

EL50 (Champia parvula (marine algae)): > 1 - 10 mg/l

Exposure time: 7 d

Remarks: Based on transformation/dissolution testing and

data from soluble metal compounds

EL10 (Champia parvula (marine algae)): > 0,1 - 1 mg/l

Exposure time: 7 d

Remarks: Based on transformation/dissolution testing and

data from soluble metal compounds

Toxicity to fish (Chronic tox-

icity)

EL10: > 1 mg/l

Exposure time: 34 d

Species: Danio rerio (zebra fish)

Remarks: Based on transformation/dissolution testing and

data from soluble metal compounds

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

EL10: > 1 mg/l Exposure time: 28 d

Method: OECD Test Guideline 211

Remarks: Based on transformation/dissolution testing and

data from soluble metal compounds

methyl propionate:

Toxicity to algae/aquatic

plants

EC10 (Desmodesmus subspicatus (green algae)): > 500 mg/l

Exposure time: 72 h

ErC50 (Desmodesmus subspicatus (green algae)): > 500 mg/l

Exposure time: 72 h

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC: 3,2 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Lithium hexafluorophosphate:

Toxicity to fish : LC50 :> 10 - 100 mg/l

Exposure time: 96 h

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l

Exposure time: 48 h

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

EC50 : > 10 - 100 mg/l Exposure time: 96 h

Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC : > 100 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

according to Regulation (EC) No. 1907/2006



BATTERY LI-ION 18 V / 5,0 AH M-CUBE BASIC

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.09.2019

 2.0
 10.01.2020
 4832428-00002
 Date of first issue: 06.09.2019

Remarks: Based on data from similar materials

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC: > 1 - 10 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Remarks: Based on data from similar materials

4-Fluoro-1,3-dioxolan-2-one:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 6 - 60 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 8,4 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

ErC50 (Pseudokirchneriella subcapitata (green algae)): 32

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 2,2

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to microorganisms : NOEC : 80 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

N-Methyl-2-pyrrolidone:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 500 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 1.000 mg/l

Exposure time: 24 h Method: DIN 38412

Toxicity to algae/aquatic

plants

ErC50 (Desmodesmus subspicatus (green algae)): 600,5 mg/l

Exposure time: 72 h

EC10 (Desmodesmus subspicatus (green algae)): 92,6 mg/l

Exposure time: 72 h

Toxicity to microorganisms : EC50 : > 600 mg/l

Exposure time: 30 min Method: ISO 8192

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC: 12,5 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Method: OECD Test Guideline 211

according to Regulation (EC) No. 1907/2006



BATTERY LI-ION 18 V / 5,0 AH M-CUBE BASIC

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.09.2019

 2.0
 10.01.2020
 4832428-00002
 Date of first issue: 06.09.2019

12.2 Persistence and degradability

Components:

methyl propionate:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 77 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Lithium hexafluorophosphate:

Biodegradability : Result: rapidly degradable

4-Fluoro-1,3-dioxolan-2-one:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 65 % Exposure time: 28 d

Method: OECD Test Guideline 301D

N-Methyl-2-pyrrolidone:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 73 % Exposure time: 28 d

Method: OECD Test Guideline 301C

12.3 Bioaccumulative potential

Components:

methyl propionate:

Partition coefficient: n- : log Pow: 0,8

octanol/water Method: OECD Test Guideline 117

4-Fluoro-1,3-dioxolan-2-one:

Partition coefficient: n- : log Pow: -0,435

octanol/water Method: OECD Test Guideline 107

N-Methyl-2-pyrrolidone:

Partition coefficient: n- : log Pow: -0,46

octanol/water Method: OECD Test Guideline 107

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Not relevant

12.6 Other adverse effects

No data available

according to Regulation (EC) No. 1907/2006



BATTERY LI-ION 18 V / 5,0 AH M-CUBE BASIC

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.09.2019

 2.0
 10.01.2020
 4832428-00002
 Date of first issue: 06.09.2019

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.

According to the European Waste Catalogue, Waste Codes

are not product specific, but application specific.

Waste codes should be assigned by the user, preferably in

discussion with the waste disposal authorities.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

Waste Code : The following Waste Codes are only suggestions:

used product

16 06 05, other batteries and accumulators

unused product

16 06 05, other batteries and accumulators

uncleaned packagings

15 01 10, packaging containing residues of or contaminated

by hazardous substances

SECTION 14: Transport information

14.1 UN number

ADN : UN 3480
ADR : UN 3480
RID : UN 3480
IMDG : UN 3480
IATA (Cargo) : UN 3480
IATA (Passenger) : UN 3480

Not permitted for transport

14.2 UN proper shipping name

ADN : LITHIUM ION BATTERIES
ADR : LITHIUM ION BATTERIES
RID : LITHIUM ION BATTERIES
IMDG : LITHIUM ION BATTERIES

IATA (Cargo) : Lithium ion batteries

IATA (Passenger) : LITHIUM ION BATTERIES

Not permitted for transport

14.3 Transport hazard class(es)

according to Regulation (EC) No. 1907/2006



BATTERY LI-ION 18 V / 5,0 AH M-CUBE BASIC

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.09.2019

 2.0
 10.01.2020
 4832428-00002
 Date of first issue: 06.09.2019

ADN : 9
ADR : 9
RID : 9
IMDG : 9
IATA (Cargo) : 9

IATA (Passenger) : Not permitted for transport

14.4 Packing group

ADN

Packing group : Not assigned by regulation

Classification Code : M4 Labels : 9A

ADR

Packing group : Not assigned by regulation

Classification Code : M4 Labels : 9A Tunnel restriction code : (E)

RID

Packing group : Not assigned by regulation

Classification Code : M4 Hazard Identification Number : 90 Labels : 9A

IMDG

Packing group : Not assigned by regulation

Labels : 9A EmS Code : F-A, S-I

IATA (Cargo)

Packing instruction (cargo

aircraft)

Packing group : Not assigned by regulation

965

Labels

IATA (Passenger) : Not permitted for transport

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data

according to Regulation (EC) No. 1907/2006



BATTERY LI-ION 18 V / 5,0 AH M-CUBE BASIC

Version Revision Date: SDS Number: Date of last issue: 06.09.2019 4832428-00002 Date of first issue: 06.09.2019 2.0 10.01.2020

Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: N-Methyl-2-pyrrolidone

REACH - List of substances subject to authorisation

(Annex XIV)

Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

Regulation (EC) No 850/2004 on persistent organic pol-

lutants

Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

Conditions of restriction for the following entries should be considered:

Nickel (Number on list 27)

N-Methyl-2-pyrrolidone (Number on

list 72, 71, 30)

Lithium nickel oxide (Number on list

27)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Water contaminating class

(Germany)

WGK 3 highly hazardous to water

Classification according to AwSV, Annex 1 (5.2)

Directive 2010/75/EU of 24 November 2010 on industrial Volatile organic compounds

emissions (integrated pollution prevention and control)

Remarks: Not applicable

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Contains a substance which is subject to the TRGS 905

list of carcinogenic, germ cell mutagenic and reproduc-

tive toxic substances.

: Cobalt lithium dioxide

according to Regulation (EC) No. 1907/2006



BATTERY LI-ION 18 V / 5,0 AH M-CUBE BASIC

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.09.2019

 2.0
 10.01.2020
 4832428-00002
 Date of first issue: 06.09.2019

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Other information : Items where changes have been made to the previous version

are highlighted in the body of this document by two vertical

lines.

Full text of H-Statements

H225 : Highly flammable liquid and vapour.

H301 : Toxic if swallowed. H302 : Harmful if swallowed.

H314 : Causes severe skin burns and eye damage.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.

H332 : Harmful if inhaled.

H334 : May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

H335 : May cause respiratory irritation. H341 : Suspected of causing genetic defects.

H350 : May cause cancer.

H350i : May cause cancer by inhalation. H360D : May damage the unborn child.

H360F : May damage fertility.

H361d : Suspected of damaging the unborn child.

H372 : Causes damage to organs through prolonged or repeated

exposure.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.H411 : Toxic to aquatic life with long lasting effects.

Carcinogenicity

Full text of other abbreviations

Carc.

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam. : Serious eye damage
Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Muta. : Germ cell mutagenicity
Repr. : Reproductive toxicity
Resp. Sens. : Respiratory sensitisation

Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

STOT RE : Specific target organ toxicity - repeated exposure STOT SE : Specific target organ toxicity - single exposure

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values

2009/161/EU : Europe. COMMISSION DIRECTIVE 2009/161/EU establishing

according to Regulation (EC) No. 1907/2006



BATTERY LI-ION 18 V / 5,0 AH M-CUBE BASIC

Version Revision Date: SDS Number: Date of last issue: 06.09.2019 2.0 10.01.2020 4832428-00002 Date of first issue: 06.09.2019

a third list of indicative occupational exposure limit values in

implementation of Council Directive 98/24/EC and amending

Commission Directive 2000/39/EC

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.
DE TRGS 910 : Germany. TRGS 910 - Substance-specific acceptable and

tolerable concentrations and equivalence values for carcino-

genic hazardous substances.

TRGS 903 : TRGS 903 - Biological limit values

2000/39/EC / TWA : Limit Value - eight hours 2000/39/EC / STEL : Short term exposure limit 2009/161/EU / TWA : Limit Value - eight hours 2009/161/EU / STEL : Short term exposure limit DE TRGS 900 / AGW : Time Weighted Average DE TRGS 910 / Acceptable : Acceptable concentration

concentration

DE TRGS 910 / Tolerable

concentration

Tolerable concentration

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

according to Regulation (EC) No. 1907/2006



BATTERY LI-ION 18 V / 5,0 AH M-CUBE BASIC

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.09.2019

 2.0
 10.01.2020
 4832428-00002
 Date of first issue: 06.09.2019

Sheet cy, http://echa.europa.eu/

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN