

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2C UNIVERSALPRIMER LIGHT GREY - 10 KG

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10713575-00010	Date of first issue: 11.06.2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name	:	2C UNIVERSALPRIMER LIGHT GREY - 10 KG
Product code	:	5866103110
Unique Formula Identifier (UFI)	:	VMCC-V0HG-400G-JHQ7

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture	:	Primers Professional use product
Recommended restrictions on use	:	Not applicable

1.3 Details of the supplier of the safety data sheet

Company	:	Adolf Wuerth GmbH & Co. KG Reinhold-Würth-Str. 12-17 74653 Künzelsau
Telephone	:	+49 794015 0
Telefax	:	+49 794015 10 00
E-mail address of person responsible for the SDS	:	isi@wuerth.com

1.4 Emergency telephone number

+49 (0)6132 – 84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Specific target organ toxicity - single exposure, Category 3	H336: May cause drowsiness or dizziness.
Long-term (chronic) aquatic hazard, Category 2	H411: Toxic to aquatic life with long lasting effects.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2C UNIVERSALPRIMER LIGHT GREY - 10 KG

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10713575-00010	Date of first issue: 11.06.2010

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Supplemental Hazard Statements : EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing mist or vapours.
P273 Avoid release to the environment.
Response:
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.
P391 Collect spillage.

Hazardous components which must be listed on the label:

n-Butyl acetate
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
2-Methoxy-1-methylethyl acetate

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Vapours may form explosive mixture with air.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2C UNIVERSALPRIMER LIGHT GREY - 10 KG

Version 8.0 Revision Date: 06.06.2023 SDS Number: 10713575-00010 Date of last issue: 10.11.2022
Date of first issue: 11.06.2010

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Paint

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
n-Butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 EUH066	$\geq 10 - < 20$
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-48-9 01-2119463258-33	Flam. Liq. 3; H226 STOT SE 3; H336 Asp. Tox. 1; H304 EUH066	$\geq 1 - < 10$
Trizinc bis(orthophosphate)	7779-90-0 231-944-3 030-011-00-6 01-2119485044-40	Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	$\geq 2,5 - < 10$
2-Butoxyethyl acetate	112-07-2 203-933-3 607-038-00-2 01-2119475112-47	Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 4; H312 Acute toxicity estimate Acute oral toxicity: 1.880 mg/kg Acute inhalation toxicity (vapour): 20 mg/l Acute dermal toxicity: 1.500 mg/kg	$\geq 1 - < 10$
2-Methoxy-1-methylethyl acetate	108-65-6 203-603-9 607-195-00-7 01-2119475791-29	Flam. Liq. 3; H226 STOT SE 3; H336	$\geq 1 - < 10$
Xylene	1330-20-7 215-535-7 601-022-00-9 01-2119488216-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335	$\geq 1 - < 2,5$

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2C UNIVERSALPRIMER LIGHT GREY - 10 KG

Version 8.0 Revision Date: 06.06.2023 SDS Number: 10713575-00010 Date of last issue: 10.11.2022
Date of first issue: 11.06.2010

		STOT RE 2; H373 (Auditory system) Asp. Tox. 1; H304 Aquatic Chronic 3; H412	
		Acute toxicity estimate	
		Acute inhalation toxicity (vapour): 11 mg/l Acute dermal toxicity: 1.100 mg/kg	
Zinc oxide	1314-13-2 215-222-5 030-013-00-7 01-2119463881-32	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	$\geq 0,1 - < 0,25$
		M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2C UNIVERSALPRIMER LIGHT GREY - 10 KG

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10713575-00010	Date of first issue: 11.06.2010

Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

Risks : May cause drowsiness or dizziness.
Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Dry powder
Carbon dioxide (CO₂)
Dry sand

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.
Flash back possible over considerable distance.
Vapours may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides
Metal oxides
Oxides of phosphorus
Sulphur oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.
Use personal protective equipment.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2C UNIVERSALPRIMER LIGHT GREY - 10 KG

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10713575-00010	Date of first issue: 11.06.2010

Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapours/mists with a water spray jet.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
Use explosion-proof electrical, ventilating and lighting equipment.

Advice on safe handling : Do not get on skin or clothing.
Do not breathe mist or vapours.
Do not swallow.
Avoid contact with eyes.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2C UNIVERSALPRIMER LIGHT GREY - 10 KG

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10713575-00010	Date of first issue: 11.06.2010

Non-sparking tools should be used.
Keep container tightly closed.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep in properly labelled containers. Store locked up. Keep tightly closed. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Keep away from heat and sources of ignition.

Advice on common storage : Do not store with the following product types:
Strong oxidizing agents
Self-reactive substances and mixtures
Organic peroxides
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures, which in contact with water, emit flammable gases
Explosives
Gases
Very acutely toxic substances and mixtures

Storage class (TRGS 510) : 3

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Titanium dioxide	13463-67-7	AGW (Inhalable fraction)	10 mg/m ³ (Titanium dioxide)	DE TRGS 900
Peak-limit: excursion factor (category): 2;(II)				
Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child				

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2C UNIVERSALPRIMER LIGHT GREY - 10 KG

Version 8.0 Revision Date: 06.06.2023 SDS Number: 10713575-00010 Date of last issue: 10.11.2022
Date of first issue: 11.06.2010

		AGW (Alveolate fraction)	1,25 mg/m3 (Titanium dioxide)	DE TRGS 900
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
n-Butyl acetate	123-86-4	STEL	150 ppm 723 mg/m3	2019/1831/EU
	Further information: Indicative			
		TWA	50 ppm 241 mg/m3	2019/1831/EU
	Further information: Indicative			
		AGW	62 ppm 300 mg/m3	DE TRGS 900
	Peak-limit: excursion factor (category): 2;(I)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
Talc	14807-96-6	AGW (Inhalable fraction)	10 mg/m3	DE TRGS 900
	Peak-limit: excursion factor (category): 2;(II)			
		AGW (Alveolate fraction)	1,25 mg/m3	DE TRGS 900
	Peak-limit: excursion factor (category): 2;(II)			
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-48-9	AGW	300 mg/m3	DE TRGS 900
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: Group exposure limit for hydrocarbon solvent mixtures			
2-Methoxy-1-methylethyl acetate	108-65-6	STEL	100 ppm 550 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	50 ppm 275 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		AGW	50 ppm 270 mg/m3	DE TRGS 900
	Peak-limit: excursion factor (category): 1;(I)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
2-Butoxyethyl acetate	112-07-2	STEL	50 ppm 333 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	20 ppm 133 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		AGW (Vapour)	10 ppm	DE TRGS

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2C UNIVERSALPRIMER LIGHT GREY - 10 KG

Version 8.0 Revision Date: 06.06.2023 SDS Number: 10713575-00010 Date of last issue: 10.11.2022
Date of first issue: 11.06.2010

		and aerosols)	65 mg/m3	900
	Peak-limit: excursion factor (category): 2;(I)			
	Further information: Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
Xylene	1330-20-7	TWA	50 ppm 221 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 442 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		AGW	50 ppm 220 mg/m3	DE TRGS 900
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: Skin absorption			

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
2-Butoxyethyl acetate	112-07-2	butoxy acetic acid: 150 mg/g Creati- nine (Urine)	In case of long- term exposure: after more than one shift, Immedi- ately after expo- sure or after work- ing hours	TRGS 903
Xylene	1330-20-7	methylhippuric acid (all isomers): 2.000 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health ef- fects	Value
n-Butyl acetate	Workers	Inhalation	Acute systemic ef- fects	600 mg/m3
	Workers	Inhalation	Acute local effects	600 mg/m3
	Workers	Inhalation	Long-term systemic effects	300 mg/m3
	Workers	Inhalation	Long-term local ef- fects	300 mg/m3
	Consumers	Inhalation	Acute systemic ef- fects	300 mg/m3
	Consumers	Inhalation	Acute local effects	300 mg/m3
	Consumers	Inhalation	Long-term systemic effects	35,7 mg/m3
	Consumers	Inhalation	Long-term local ef- fects	35,7 mg/m3
	Consumers	Skin contact	Long-term systemic effects	11 mg/kg bw/day
	Consumers	Skin contact	Acute systemic ef-	11 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2C UNIVERSALPRIMER LIGHT GREY - 10 KG

Version 8.0 Revision Date: 06.06.2023 SDS Number: 10713575-00010 Date of last issue: 10.11.2022
Date of first issue: 11.06.2010

			fects	bw/day
	Consumers	Skin contact	Long-term systemic effects	6 mg/kg bw/day
	Consumers	Skin contact	Acute systemic effects	6 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	2 mg/kg bw/day
	Consumers	Ingestion	Acute systemic effects	2 mg/kg bw/day
Xylene	Workers	Inhalation	Long-term systemic effects	221 mg/m3
	Workers	Inhalation	Acute systemic effects	442 mg/m3
	Workers	Inhalation	Long-term local effects	221 mg/m3
	Workers	Inhalation	Acute local effects	442 mg/m3
	Workers	Skin contact	Long-term systemic effects	212 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	65,3 mg/m3
	Consumers	Inhalation	Acute systemic effects	260 mg/m3
	Consumers	Inhalation	Long-term local effects	65,3 mg/m3
	Consumers	Inhalation	Acute local effects	260 mg/m3
	Consumers	Skin contact	Long-term systemic effects	125 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	12,5 mg/kg bw/day
2-Methoxy-1-methylethyl acetate	Workers	Inhalation	Long-term systemic effects	275 mg/m3
	Workers	Skin contact	Long-term systemic effects	796 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	33 mg/m3
	Consumers	Skin contact	Long-term systemic effects	320 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	36 mg/kg bw/day
	Workers	Inhalation	Acute local effects	550 mg/m3
	Consumers	Inhalation	Long-term local effects	33 mg/m3
2-Butoxyethyl acetate	Workers	Inhalation	Long-term systemic effects	133 mg/m3
	Workers	Inhalation	Acute systemic effects	775 mg/m3
	Workers	Inhalation	Acute local effects	333 mg/m3
	Workers	Skin contact	Long-term systemic effects	102 mg/kg bw/day
	Workers	Skin contact	Acute systemic effects	102 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic	67 mg/m3

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2C UNIVERSALPRIMER LIGHT GREY - 10 KG

Version 8.0 Revision Date: 06.06.2023 SDS Number: 10713575-00010 Date of last issue: 10.11.2022
Date of first issue: 11.06.2010

			effects	
	Consumers	Inhalation	Acute systemic effects	499 mg/m3
	Consumers	Inhalation	Acute local effects	166 mg/m3
	Consumers	Skin contact	Long-term systemic effects	36 mg/kg bw/day
	Consumers	Skin contact	Acute systemic effects	27 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	4,3 mg/kg bw/day
	Consumers	Ingestion	Acute systemic effects	18 mg/kg bw/day
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	Workers	Inhalation	Long-term systemic effects	871 mg/m3
	Workers	Skin contact	Long-term systemic effects	77 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	185 mg/m3
	Consumers	Skin contact	Long-term systemic effects	46 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	46 mg/kg bw/day
Barite (Ba(SO4))	Workers	Inhalation	Long-term systemic effects	10 mg/m3
	Workers	Inhalation	Long-term local effects	10 mg/m3
	Consumers	Inhalation	Long-term systemic effects	10 mg/m3
	Consumers	Ingestion	Long-term systemic effects	13000 mg/kg bw/day
Zinc oxide	Workers	Inhalation	Long-term systemic effects	5 mg/m3
	Workers	Inhalation	Long-term local effects	0,5 mg/m3
	Workers	Skin contact	Long-term systemic effects	83 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	2,5 mg/m3
	Consumers	Skin contact	Long-term systemic effects	83 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0,83 mg/kg bw/day
Trizinc bis(orthophosphate)	Workers	Inhalation	Long-term systemic effects	5 mg/m3
	Workers	Skin contact	Long-term systemic effects	83 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	2,5 mg/m3
	Consumers	Skin contact	Long-term systemic effects	83 mg/kg bw/day

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2C UNIVERSALPRIMER LIGHT GREY - 10 KG

Version 8.0 Revision Date: 06.06.2023 SDS Number: 10713575-00010 Date of last issue: 10.11.2022
Date of first issue: 11.06.2010

	Consumers	Ingestion	Long-term systemic effects	0,83 mg/kg bw/day
Aluminium ortho-phosphate	Workers	Inhalation	Long-term systemic effects	8,14 mg/m3
	Consumers	Inhalation	Long-term systemic effects	2,01 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
n-Butyl acetate	Fresh water	0,18 mg/l
	Marine water	0,018 mg/l
	Sewage treatment plant	35,6 mg/l
	Fresh water sediment	0,981 mg/kg dry weight (d.w.)
	Marine sediment	0,098 mg/kg dry weight (d.w.)
	Soil	0,09 mg/kg dry weight (d.w.)
Xylene	Fresh water	0,327 mg/l
	Intermittent use/release	0,327 mg/l
	Marine water	0,327 mg/l
	Sewage treatment plant	6,58 mg/l
	Fresh water sediment	12,46 mg/kg dry weight (d.w.)
	Marine sediment	12,46 mg/kg dry weight (d.w.)
	Soil	2,31 mg/kg dry weight (d.w.)
2-Methoxy-1-methylethyl acetate	Fresh water	0,635 mg/l
	Marine water	0,0635 mg/l
	Intermittent use/release	6,35 mg/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	3,29 mg/kg dry weight (d.w.)
	Marine sediment	0,329 mg/kg dry weight (d.w.)
	Soil	0,29 mg/kg dry weight (d.w.)
2-Butoxyethyl acetate	Fresh water	0,304 mg/l
	Marine water	0,0304 mg/l
	Intermittent use/release	0,56 mg/l
	Sewage treatment plant	90 mg/l
	Fresh water sediment	2,03 mg/kg
	Marine sediment	0,203 mg/kg
	Soil	0,68 mg/kg
	Oral (Secondary Poisoning)	60 mg/kg food
Barite (Ba(SO4))	Fresh water	0,115 mg/l
	Sewage treatment plant	62,2 mg/l
	Fresh water sediment	600,4 mg/kg dry weight (d.w.)
	Soil	207,7 mg/kg dry weight (d.w.)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2C UNIVERSALPRIMER LIGHT GREY - 10 KG

Version 8.0 Revision Date: 06.06.2023 SDS Number: 10713575-00010 Date of last issue: 10.11.2022
Date of first issue: 11.06.2010

Zinc oxide	Fresh water	20,6 µg/l
	Marine water	6,1 µg/l
	Sewage treatment plant	100 µg/l
	Fresh water sediment	117,8 mg/kg dry weight (d.w.)
	Marine sediment	56,5 mg/kg dry weight (d.w.)
	Soil	35,6 mg/kg dry weight (d.w.)
Trizinc bis(orthophosphate)	Fresh water	20,6 µg/l
	Marine water	6,1 µg/l
	Sewage treatment plant	100 µg/l
	Fresh water sediment	117,8 mg/kg
	Marine sediment	56,5 mg/kg
	Soil	35,6 mg/kg
Aluminium orthophosphate	Fresh water	0,032725 mg/l
	Marine water	0,003272 mg/l
	Intermittent use/release	0,32735 mg/l

8.2 Exposure controls

Engineering measures

Minimize workplace exposure concentrations.
If sufficient ventilation is unavailable, use with local exhaust ventilation.
Use explosion-proof electrical, ventilating and lighting equipment.

Personal protective equipment

Eye/face protection : Wear the following personal protective equipment:
Safety glasses
Equipment should conform to DIN EN 166

Hand protection

Material : butyl-rubber
Break through time : 60 min
Glove thickness : $\geq 0,7$ mm
Directive : DIN EN 374
Protective index : Class 2

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2C UNIVERSALPRIMER LIGHT GREY - 10 KG

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10713575-00010	Date of first issue: 11.06.2010

	Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
Respiratory protection	: If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection. Equipment should conform to DIN EN 14387
Filter type	: Combined particulates and organic vapour type (A-P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	: liquid
Colour	: grey
Odour	: characteristic
Odour Threshold	: No data available
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: 124 - 128 °C
Flammability (solid, gas)	: Not applicable
Flammability (liquids)	: Ignitable (see flash point)
Upper explosion limit / Upper flammability limit	: 7,5 %(V)
Lower explosion limit / Lower flammability limit	: 1,2 %(V)
Flash point	: 23 °C Method: DIN 53213
Auto-ignition temperature	: > 350 °C Method: DIN 51794
Decomposition temperature	: No data available
pH	: Solvent mixture; pH value determination not possible, no aqueous solution
Viscosity	
Viscosity, kinematic	: No data available
Flow time	: 125 s at 20 °C

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2C UNIVERSALPRIMER LIGHT GREY - 10 KG

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10713575-00010	Date of first issue: 11.06.2010

Cross section: 6 mm
Method: ISO 2431

Solubility(ies)
Water solubility : immiscible, partly miscible

Partition coefficient: n-
octanol/water : Not applicable

Vapour pressure : < 15 hPa (20 °C)

Density : 1,486 g/cm³ (20 °C)
Method: DIN 53217

Relative vapour density : No data available

Particle characteristics
Particle size : Not applicable

9.2 Other information

Explosives : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Evaporation rate : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Flammable liquid and vapour.
Vapours may form explosive mixture with air.
Can react with strong oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2C UNIVERSALPRIMER LIGHT GREY - 10 KG

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10713575-00010	Date of first issue: 11.06.2010

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure :
Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Components:

n-Butyl acetate:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 21,1 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg
Remarks: Based on data from similar materials

Trizinc bis(orthophosphate):

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2C UNIVERSALPRIMER LIGHT GREY - 10 KG

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10713575-00010	Date of first issue: 11.06.2010

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 5,4 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Remarks: Based on data from similar materials

2-Butoxyethyl acetate:

Acute oral toxicity : LD50 (Rat): 1.880 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Expert judgement
Remarks: Based on national or regional regulation.

Acute dermal toxicity : LD50 (Rabbit): 1.500 mg/kg

2-Methoxy-1-methylethyl acetate:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC0 (Rat): 9,48 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rat): > 5.000 mg/kg

Xylene:

Acute oral toxicity : LD50 (Rat): 3.523 mg/kg
Method: Directive 67/548/EEC, Annex V, B.1.

Acute inhalation toxicity : Acute toxicity estimate: 11 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Expert judgement
Remarks: Based on national or regional regulation.

Acute dermal toxicity : Acute toxicity estimate: 1.100 mg/kg
Method: Expert judgement
Remarks: Based on national or regional regulation.

Zinc oxide:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5,7 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2C UNIVERSALPRIMER LIGHT GREY - 10 KG

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10713575-00010	Date of first issue: 11.06.2010

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Components:

n-Butyl acetate:

Species : Rabbit
Result : No skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Species : Rabbit
Result : Mild skin irritation
Remarks : Based on data from similar materials

Assessment : Repeated exposure may cause skin dryness or cracking.

Trizinc bis(orthophosphate):

Species : Rabbit
Result : No skin irritation
Remarks : Based on data from similar materials

2-Butoxyethyl acetate:

Species : Rabbit
Result : No skin irritation

2-Methoxy-1-methylethyl acetate:

Species : Rabbit
Result : No skin irritation

Xylene:

Species : Rabbit
Result : Skin irritation

Zinc oxide:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2C UNIVERSALPRIMER LIGHT GREY - 10 KG

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10713575-00010	Date of first issue: 11.06.2010

Serious eye damage/eye irritation

Not classified based on available information.

Components:

n-Butyl acetate:

Species	: Rabbit
Method	: OECD Test Guideline 405
Result	: No eye irritation

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Species	: Rabbit
Method	: OECD Test Guideline 405
Result	: No eye irritation
Remarks	: Based on data from similar materials

Trizinc bis(orthophosphate):

Species	: Rabbit
Method	: OECD Test Guideline 405
Result	: No eye irritation

2-Butoxyethyl acetate:

Species	: Rabbit
Result	: No eye irritation

2-Methoxy-1-methylethyl acetate:

Species	: Rabbit
Result	: No eye irritation

Xylene:

Species	: Rabbit
Result	: Irritation to eyes, reversing within 21 days

Zinc oxide:

Species	: Rabbit
Method	: OECD Test Guideline 405
Result	: No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

n-Butyl acetate:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2C UNIVERSALPRIMER LIGHT GREY - 10 KG

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10713575-00010	Date of first issue: 11.06.2010

Test Type	: Maximisation Test
Exposure routes	: Skin contact
Species	: Guinea pig
Result	: negative

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Test Type	: Maximisation Test
Exposure routes	: Skin contact
Species	: Guinea pig
Result	: negative
Remarks	: Based on data from similar materials

Trizinc bis(orthophosphate):

Test Type	: Maximisation Test
Exposure routes	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: negative
Remarks	: Based on data from similar materials

Assessment	: Does not cause skin sensitisation.
------------	--------------------------------------

2-Butoxyethyl acetate:

Test Type	: Buehler Test
Exposure routes	: Skin contact
Species	: Guinea pig
Result	: negative

2-Methoxy-1-methylethyl acetate:

Test Type	: Maximisation Test
Exposure routes	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: negative

Xylene:

Test Type	: Local lymph node assay (LLNA)
Exposure routes	: Skin contact
Species	: Mouse
Result	: negative

Zinc oxide:

Test Type	: Maximisation Test
Exposure routes	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: negative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2C UNIVERSALPRIMER LIGHT GREY - 10 KG

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10713575-00010	Date of first issue: 11.06.2010

Germ cell mutagenicity

Not classified based on available information.

Components:

n-Butyl acetate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test
Result: negative
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)
Species: Rat
Application Route: inhalation (vapour)
Result: negative

Germ cell mutagenicity- Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

Trizinc bis(orthophosphate):

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
Remarks: Based on data from similar materials

2-Butoxyethyl acetate:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative
Remarks: Based on data from similar materials

2-Methoxy-1-methylethyl acetate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2C UNIVERSALPRIMER LIGHT GREY - 10 KG

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10713575-00010	Date of first issue: 11.06.2010

Result: negative

Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: negative

Remarks: Based on data from similar materials

Xylene:

Genotoxicity in vitro

: Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: Chromosome aberration test in vitro

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: negative

Test Type: In vitro sister chromatid exchange assay in mammalian cells

Result: negative

Genotoxicity in vivo

: Test Type: Rodent dominant lethal test (germ cell) (in vivo)
Species: Mouse
Application Route: Skin contact
Result: negative

Zinc oxide:

Genotoxicity in vitro

: Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: equivocal

Test Type: Chromosome aberration test in vitro

Result: equivocal

Genotoxicity in vivo

: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: inhalation (dust/mist/fume)
Method: OECD Test Guideline 474
Result: negative

Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)

Species: Rat

Application Route: inhalation (dust/mist/fume)

Result: positive

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2C UNIVERSALPRIMER LIGHT GREY - 10 KG

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10713575-00010	Date of first issue: 11.06.2010

Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative

Germ cell mutagenicity- Assessment : Weight of evidence does not support classification as a germ cell mutagen.

Carcinogenicity

Not classified based on available information.

Components:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Carcinogenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

2-Butoxyethyl acetate:

Species : Rat
Application Route : inhalation (vapour)
Exposure time : 2 Years
Result : negative
Remarks : Based on data from similar materials

2-Methoxy-1-methylethyl acetate:

Species : Rat
Application Route : inhalation (vapour)
Exposure time : 2 Years
Result : negative
Remarks : Based on data from similar materials

Xylene:

Species : Rat
Application Route : Ingestion
Exposure time : 103 weeks
Result : negative

Zinc oxide:

Species : Mouse
Application Route : Ingestion
Exposure time : 1 Years
Result : negative
Remarks : Based on data from similar materials

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2C UNIVERSALPRIMER LIGHT GREY - 10 KG

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10713575-00010	Date of first issue: 11.06.2010

Reproductive toxicity

Not classified based on available information.

Components:

n-Butyl acetate:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapour)
Method: OECD Test Guideline 416
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Result: negative

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Result: negative
Remarks: Based on data from similar materials

Trizinc bis(orthophosphate):

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

2-Butoxyethyl acetate:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Mouse
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2C UNIVERSALPRIMER LIGHT GREY - 10 KG

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10713575-00010	Date of first issue: 11.06.2010

2-Methoxy-1-methylethyl acetate:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapour)
Method: OECD Test Guideline 416
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Result: negative

Xylene:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapour)
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Result: negative

Zinc oxide:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (dust/mist/fume)
Method: OECD Test Guideline 414
Result: negative
Remarks: Based on data from similar materials

STOT - single exposure

May cause drowsiness or dizziness.

Components:

n-Butyl acetate:

Assessment : May cause drowsiness or dizziness.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Assessment : May cause drowsiness or dizziness.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2C UNIVERSALPRIMER LIGHT GREY - 10 KG

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10713575-00010	Date of first issue: 11.06.2010

2-Methoxy-1-methylethyl acetate:

Assessment : May cause drowsiness or dizziness.

Xylene:

Assessment : May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Components:

Xylene:

Exposure routes : inhalation (vapour)
Target Organs : Auditory system
Assessment : Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg/l/6h/d.

Zinc oxide:

Assessment : No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d or less.

Repeated dose toxicity

Components:

n-Butyl acetate:

Species : Rat
NOAEL : 2,4 mg/l
Application Route : inhalation (vapour)
Exposure time : 90 Days

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Species : Rat
NOAEL : > 100 mg/kg
Application Route : Ingestion
Exposure time : 13 Weeks
Remarks : Based on data from similar materials

Species : Rat
NOAEL : > 1 mg/l
Application Route : inhalation (vapour)
Exposure time : 90 Days
Remarks : Based on data from similar materials

Species : Rat
LOAEL : 500 mg/kg
Application Route : Skin contact
Exposure time : 28 Days

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2C UNIVERSALPRIMER LIGHT GREY - 10 KG

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10713575-00010	Date of first issue: 11.06.2010

Trizinc bis(orthophosphate):

Species	:	Rat
NOAEL	:	31,52 mg/kg
Application Route	:	Ingestion
Exposure time	:	13 Weeks
Method	:	OECD Test Guideline 408
Remarks	:	Based on data from similar materials

2-Butoxyethyl acetate:

Species	:	Rat, male
NOAEL	:	< 69 mg/kg
Application Route	:	Ingestion
Exposure time	:	90 Days

2-Methoxy-1-methylethyl acetate:

Species	:	Rat
NOAEL	:	> 1.000 mg/kg
Application Route	:	Ingestion
Exposure time	:	41 - 45 Days
Method	:	OECD Test Guideline 422

Species	:	Mouse
NOAEL	:	1,62 mg/l
Application Route	:	inhalation (vapour)
Exposure time	:	2 yr
Remarks	:	Based on data from similar materials

Species	:	Rabbit
NOAEL	:	> 1.838 mg/kg
Application Route	:	Skin contact
Exposure time	:	90 Days
Remarks	:	Based on data from similar materials

Xylene:

Species	:	Rat
LOAEL	:	> 0,2 - 1 mg/l
Application Route	:	inhalation (vapour)
Exposure time	:	13 Weeks
Remarks	:	Based on data from similar materials

Species	:	Rat
LOAEL	:	150 mg/kg
Application Route	:	Ingestion
Exposure time	:	90 Days

Zinc oxide:

Species	:	Rat, male
NOAEL	:	0,0015 mg/l
Application Route	:	inhalation (dust/mist/fume)
Exposure time	:	3 Months

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2C UNIVERSALPRIMER LIGHT GREY - 10 KG

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10713575-00010	Date of first issue: 11.06.2010

Method : OECD Test Guideline 413

Aspiration toxicity

Not classified based on available information.

Components:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Xylene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

n-Butyl acetate:

Toxicity to fish	: LC50 (Pimephales promelas (fathead minnow)): 18 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia sp. (water flea)): 44 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	: ErC50 (Pseudokirchneriella subcapitata (green algae)): 397 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: Based on data from similar materials
	NOEC (Pseudokirchneriella subcapitata (green algae)): 196 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2C UNIVERSALPRIMER LIGHT GREY - 10 KG

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10713575-00010	Date of first issue: 11.06.2010

Toxicity to microorganisms : IC50 (Tetrahymena pyriformis): 356 mg/l
Exposure time: 40 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 23,2 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 1.000 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 1.000 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): > 1.000 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

NOELR (Pseudokirchneriella subcapitata (green algae)): 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

Trizinc bis(orthophosphate):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 169 µg/l
Exposure time: 96 h
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Ceriodaphnia dubia (water flea)): 155 µg/l
Exposure time: 48 h
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): 24 µg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

M-Factor (Acute aquatic toxicity) : 1

Toxicity to fish (Chronic toxicity) : NOEC: 39 µg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2C UNIVERSALPRIMER LIGHT GREY - 10 KG

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10713575-00010	Date of first issue: 11.06.2010

icity)
Exposure time: 30 d
Species: Oncorhynchus mykiss (rainbow trout)
Remarks: Based on data from similar materials

Toxicity to daphnia and other : NOEC: 95 µg/l
aquatic invertebrates (Chron- Exposure time: 21 d
ic toxicity) Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

M-Factor (Chronic aquatic : 1
toxicity)

2-Butoxyethyl acetate:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 28 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 37 mg/l
aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic : EC50 (Pseudokirchneriella subcapitata (green algae)): 1.570
plants mg/l
Exposure time: 72 h
Method: ISO 8692

Toxicity to microorganisms : IC50 : 2.800 mg/l
Exposure time: 16 h

Toxicity to daphnia and other : EC10: 30,4 mg/l
aquatic invertebrates (Chron- Exposure time: 7 d
ic toxicity) Species: Ceriodaphnia dubia (water flea)

2-Methoxy-1-methylethyl acetate:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 - 180
mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 500 mg/l
aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic : ErC50 (Pseudokirchneriella subcapitata (green algae)): >
plants 1.000 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (algae)): > 1.000 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC10 : > 1.000 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2C UNIVERSALPRIMER LIGHT GREY - 10 KG

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10713575-00010	Date of first issue: 11.06.2010

Exposure time: 0,5 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: ≥ 100 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

Xylene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 13,5 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): $> 1 - 10$ mg/l
Exposure time: 24 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EC50 (Skeletonema costatum (marine diatom)): 10 mg/l
Exposure time: 72 h

Toxicity to microorganisms : NOEC : > 100 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Toxicity to fish (Chronic toxicity) : NOEC: $> 0,1 - < 1$ mg/l
Exposure time: 35 d
Species: Danio rerio (zebra fish)
Method: OECD Test Guideline 210
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EL10: $> 1 - 10$ mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Zinc oxide:

Toxicity to fish : LC50 : $> 0,1 - 1$ mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 0,136 mg/l
Exposure time: 72 h

NOEC (Pseudokirchneriella subcapitata (green algae)): $> 0,01 - 0,1$ mg/l
Exposure time: 72 h
Remarks: Based on data from similar materials

M-Factor (Acute aquatic toxicity) : 1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2C UNIVERSALPRIMER LIGHT GREY - 10 KG

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10713575-00010	Date of first issue: 11.06.2010

Toxicity to fish (Chronic toxicity) : NOEC: > 0,01 - 0,1 mg/l
Exposure time: 14 Weeks
Species: *Jordanella floridae* (flagfish)
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: > 0,01 - 0,1 mg/l
Exposure time: 7 d
Species: *Ceriodaphnia dubia* (water flea)
Remarks: Based on data from similar materials

M-Factor (Chronic aquatic toxicity) : 1

12.2 Persistence and degradability

Components:

n-Butyl acetate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 83 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 80 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

2-Butoxyethyl acetate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 88 %
Exposure time: 28 d

2-Methoxy-1-methylethyl acetate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 90 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Xylene:

Biodegradability : Result: Readily biodegradable.
Biodegradation: > 70 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2C UNIVERSALPRIMER LIGHT GREY - 10 KG

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10713575-00010	Date of first issue: 11.06.2010

12.3 Bioaccumulative potential

Components:

n-Butyl acetate:

Partition coefficient: n-octanol/water : log Pow: 2,3

2-Butoxyethyl acetate:

Partition coefficient: n-octanol/water : log Pow: 1,51

2-Methoxy-1-methylethyl acetate:

Partition coefficient: n-octanol/water : log Pow: 1,2

Xylene:

Partition coefficient: n-octanol/water : log Pow: 3,16
Remarks: Calculation

Zinc oxide:

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)
Bioconcentration factor (BCF): 78 - 2.060

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2C UNIVERSALPRIMER LIGHT GREY - 10 KG

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10713575-00010	Date of first issue: 11.06.2010

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- | | |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product | : Dispose of in accordance with local regulations.
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.
Do not dispose of waste into sewer. |
| Contaminated packaging | : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product. |
| Waste Code | : The following Waste Codes are only suggestions:

used product
08 01 11, waste paint and varnish containing organic solvents or other hazardous substances

unused product
08 01 11, waste paint and varnish containing organic solvents or other hazardous substances

uncleaned packagings
15 01 10, packaging containing residues of or contaminated by hazardous substances

Acc. Packaging Act properly emptied packaging:
Properly emptied, non-contaminated packaging of non-hazardous products can be supplied to a system for the collection of sales packaging. |

SECTION 14: Transport information

14.1 UN number or ID number

- | | |
|------|-----------|
| ADN | : UN 1263 |
| ADR | : UN 1263 |
| RID | : UN 1263 |
| IMDG | : UN 1263 |
| IATA | : UN 1263 |

14.2 UN proper shipping name

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2C UNIVERSALPRIMER LIGHT GREY - 10 KG

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10713575-00010	Date of first issue: 11.06.2010

ADN	:	PAINT
ADR	:	PAINT
RID	:	PAINT
IMDG	:	PAINT (Trizinc bis(orthophosphate), Zinc oxide)
IATA	:	Paint

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	:	3
ADR	:	3
RID	:	3
IMDG	:	3
IATA	:	3

14.4 Packing group

ADN	
Packing group	: III
Classification Code	: F1
Hazard Identification Number	: 30
Labels	: 3
ADR	
Packing group	: III
Classification Code	: F1
Hazard Identification Number	: 30
Labels	: 3
Tunnel restriction code	: (D/E)
RID	
Packing group	: III
Classification Code	: F1
Hazard Identification Number	: 30
Labels	: 3
IMDG	
Packing group	: III
Labels	: 3
EmS Code	: F-E, <u>S-E</u>
IATA (Cargo)	
Packing instruction (cargo aircraft)	: 366
Packing instruction (LQ)	: Y344
Packing group	: III
Labels	: Flammable Liquids
IATA (Passenger)	
Packing instruction (passenger aircraft)	: 355

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2C UNIVERSALPRIMER LIGHT GREY - 10 KG

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10713575-00010	Date of first issue: 11.06.2010

Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

14.5 Environmental hazards

ADN

Environmentally hazardous : yes

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	: Conditions of restriction for the following entries should be considered: Number on list 75, 3
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	: If you intend to use this product as tattoo ink, please contact your vendor.
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	: Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	: Not applicable
Regulation (EU) 2019/1021 on persistent organic pollutants (recast)	: Not applicable
Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals	: Not applicable
REACH - List of substances subject to authorisation	: Not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2C UNIVERSALPRIMER LIGHT GREY - 10 KG

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10713575-00010	Date of first issue: 11.06.2010

(Annex XIV)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
E2	ENVIRONMENTAL HAZARDS	200 t	500 t
P5c	FLAMMABLE LIQUIDS	5.000 t	50.000 t
34	Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams), (d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)	2.500 t	25.000 t

Water hazard class (Germany) : WGK 2 obviously hazardous to water
Classification according to AwSV, Annex 1 (5.2)

|| Volatile organic compounds : Directive 2004/42/EC
VOC content in g/l: 534 g/l
Product sub-category: Primers
Coatings: Surfacer/filler and general (metal) primer
VOC limit level 1 (2007): 540 g/l

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 27,99 %

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Other information : Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2C UNIVERSALPRIMER LIGHT GREY - 10 KG

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10713575-00010	Date of first issue: 11.06.2010

Full text of H-Statements

H226	: Flammable liquid and vapour.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H373	: May cause damage to organs through prolonged or repeated exposure.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.
EUH066	: Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Skin Irrit.	: Skin irritation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2019/1831/EU	: Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
DE TRGS 900	: Germany. TRGS 900 - Occupational exposure limit values.
TRGS 903	: TRGS 903 - Biological limit values
2000/39/EC / TWA	: Limit Value - eight hours
2000/39/EC / STEL	: Short term exposure limit
2019/1831/EU / TWA	: Limit Value - eight hours
2019/1831/EU / STEL	: Short term exposure limit
DE TRGS 900 / AGW	: Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships car-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878



2C UNIVERSALPRIMER LIGHT GREY - 10 KG

Version	Revision Date:	SDS Number:	Date of last issue: 10.11.2022
8.0	06.06.2023	10713575-00010	Date of first issue: 11.06.2010

rying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Classification of the mixture:

Flam. Liq. 3	H226
STOT SE 3	H336
Aquatic Chronic 2	H411

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN