according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



### PC PRIMER - 250 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.09.2022

 6.0
 08.06.2023
 10620159-00012
 Date of first issue: 20.11.2012

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : PC PRIMER - 250 ML

Product code : 5867000150

Unique Formula Identifier

(UFI)

: XPC0-00N2-V009-TWQ1

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Primers

stance/Mixture Professional use product

Recommended restrictions

on use

: Not applicable

1.3 Details of the supplier of the safety data sheet

Company : Adolf Wuerth GmbH & Co. KG

Reinhold-Würth-Str. 12-17

74653 Künzelsau

Telephone : +49 794015 0

Telefax : +49 794015 10 00

E-mail address of person

responsible for the SDS

: isi@wuerth.com

1.4 Emergency telephone number

+49 (0)6132 - 84463

# **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

# Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Specific target organ toxicity - single ex-

posure, Category 3

H336: May cause drowsiness or dizziness.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



### PC PRIMER - 250 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.09.2022

 6.0
 08.06.2023
 10620159-00012
 Date of first issue: 20.11.2012

#### 2.2 Label elements

# Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms





Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P271 Use only outdoors or in a well-ventilated area.

Storage:

P410 + P412 Protect from sunlight. Do not expose to tem-

peratures exceeding 50 °C/ 122 °F.

### Hazardous components which must be listed on the label:

Dimethyl ether

# 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Components

Chemical name	CAS-No. EC-No.	Classification	Concentration (% w/w)
	Index-No.		

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



# PC PRIMER - 250 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.09.2022

 6.0
 08.06.2023
 10620159-00012
 Date of first issue: 20.11.2012

	Registration number		
Dimethyl ether	115-10-6 204-065-8 603-019-00-8 01-2119472128-37	Flam. Gas 1A; H220 Press. Gas Liquefied gas; H280 STOT SE 3; H336	>= 50 - < 70
Ethanol	64-17-5 200-578-6 603-002-00-5	Flam. Liq. 2; H225 Eye Irrit. 2; H319  specific concentration limit Eye Irrit. 2; H319 >= 50 %	>= 1 - < 10
1-Pentanol	71-41-0 200-752-1 603-200-00-1	Flam. Liq. 3; H226 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H335  Acute toxicity estimate  Acute inhalation toxicity (vapour): 11 mg/l	>=1-<3

For explanation of abbreviations see section 16.

# **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

General advice : In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with plenty of water.

Remove contaminated clothing and shoes.

Get medical attention. Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water

for at least 15 minutes.

If easy to do, remove contact lens, if worn.

Get medical attention.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



# PC PRIMER - 250 ML

Version **Revision Date:** SDS Number: Date of last issue: 06.09.2022 6.0 08.06.2023 10620159-00012 Date of first issue: 20.11.2012

If swallowed If swallowed, DO NOT induce vomiting.

> Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

Risks Causes serious eye irritation.

May cause drowsiness or dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

**Treatment** : Treat symptomatically and supportively.

# **SECTION 5: Firefighting measures**

5.1 Extinguishing media

Suitable extinguishing media Water spray

> Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Flash back possible over considerable distance. Vapours may form explosive mixtures with air.

Exposure to combustion products may be a hazard to health. If the temperature rises there is danger of the vessels bursting

due to the high vapor pressure.

Hazardous combustion prod- : Carbon oxides

ucts

5.3 Advice for firefighters

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



### PC PRIMER - 250 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.09.2022

 6.0
 08.06.2023
 10620159-00012
 Date of first issue: 20.11.2012

#### **SECTION 6: Accidental release measures**

# 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.

Use personal protective equipment.

Follow safe handling advice (see section 7) and personal pro-

tective equipment recommendations (see section 8).

#### 6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g. by containment or oil

barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.

Soak up with inert absorbent material.

Suppress (knock down) gases/vapours/mists with a water

spray jet.

For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor-

bent

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to deter-

mine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

#### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

# **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust

ventilation.

If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventila-

tion.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



### PC PRIMER - 250 ML

Version Revision Date: SDS Number: Date of last issue: 06.09.2022 6.0 08.06.2023 10620159-00012 Date of first issue: 20.11.2012

Advice on safe handling

Do not breathe decomposition products.

Do not get on skin or clothing.

Avoid breathing spray.

Do not swallow.

Do not get in eyes.

Wash skin thoroughly after handling.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as-

sessment

Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

Take precautionary measures against static discharges.

Take care to prevent spills, waste and minimize release to the environment.

Do not spray on an open flame or other ignition source.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye

flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contami-

nated clothing before re-use.

# 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Store locked up. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Do not pierce or burn, even after use. Keep cool. Protect from sun-

light.

Advice on common storage : Do not store with the following product types:

Self-reactive substances and mixtures

Organic peroxides Oxidizing agents Flammable solids Pyrophoric liquids Pyrophoric solids

Self-heating substances and mixtures

Substances and mixtures, which in contact with water, emit

flammable gases

Explosives Gases

Storage class (TRGS 510) : 2B

7.3 Specific end use(s)

Specific use(s) : No data available

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



# PC PRIMER - 250 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.09.2022

 6.0
 08.06.2023
 10620159-00012
 Date of first issue: 20.11.2012

# **SECTION 8: Exposure controls/personal protection**

# 8.1 Control parameters

# **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Dimethyl ether	115-10-6	TWA	1.000 ppm	2000/39/EC
			1.920 mg/m3	
	Further inform	nation: Indicative		
		AGW	1.000 ppm	DE TRGS
			1.900 mg/m3	900
	Peak-limit: excursion factor (category): 8;(II)			
Ethanol	64-17-5	AGW	200 ppm	DE TRGS
			380 mg/m3	900
	Peak-limit: excursion factor (category): 4;(II)			
	Further information: When there is compliance with the OEL and biological			
	tolerance values, there is no risk of harming the unborn child			
1-Pentanol	71-41-0	AGW	20 ppm	DE TRGS
			73 mg/m3	900
	Peak-limit: excursion factor (category): 2;(I)			
	Further information: When there is compliance with the OEL and biological			
	tolerance values, there is no risk of harming the unborn child			

# Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis	
Formaldehyde	50-00-0	TWA	0,3 ppm 0,37 mg/m3	2004/37/EC	
	Further inform	nation: Dermal sensit	tisation, Carcinogens or muta	agens	
		STEL	0,6 ppm 0,74 mg/m3	2004/37/EC	
	Further inform	nation: Dermal sensit	tisation, Carcinogens or muta	agens	
		AGW	0,3 ppm 0,37 mg/m3	DE TRGS 900	
	Peak-limit: ex	Peak-limit: excursion factor (category): 2;(I)			
	Further information: Carcinogenic substance Cat. 1A or 1B or carcinogenic activity or procedure according to § 2 (3) No. 4 of the Hazardous Substances Ordinance - in addition, § 10 GefStoffV must be observed, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child, Substance sensitizing through the skin				
Methanol	67-56-1	TWA	200 ppm 260 mg/m3	2006/15/EC	
		Further information: Indicative, Identifies the possibility of significant uptake through the skin			
		AGW	100 ppm 130 mg/m3	DE TRGS 900	
	Peak-limit: excursion factor (category): 2;(II)				
	Further information: Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child				

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



# PC PRIMER - 250 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.09.2022

 6.0
 08.06.2023
 10620159-00012
 Date of first issue: 20.11.2012

# Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
1-Pentanol	Workers	Inhalation	Long-term local ef- fects	73,16 mg/m3
	Workers	Inhalation	Acute local effects	292 mg/m3
	Consumers	Inhalation	Long-term local ef- fects	13 mg/m3
	Consumers	Inhalation	Acute local effects	218 mg/m3
	Consumers	Ingestion	Long-term systemic effects	12,5 mg/kg bw/day
Ethanol	Workers	Inhalation	Long-term systemic effects	950 mg/m3
	Workers	Skin contact	Long-term systemic effects	343 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	114 mg/m3
	Consumers	Skin contact	Long-term systemic effects	206 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	87 mg/kg bw/day
Dimethyl ether	Workers	Inhalation	Long-term systemic effects	1894 mg/m3
	Consumers	Inhalation	Long-term systemic effects	471 mg/m3

# Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
1-Pentanol	Fresh water	0,12 mg/l
	Marine water	0,012 mg/l
	Intermittent use/release	1,2 mg/l
	Sewage treatment plant	37 mg/l
	Fresh water sediment	0,508 mg/kg dry weight (d.w.)
	Marine sediment	0,051 mg/kg dry weight (d.w.)
	Soil	0,031 mg/kg dry weight (d.w.)
Ethanol	Fresh water	0,96 mg/l
	Freshwater - intermittent	2,75 mg/l
	Marine water	0,79 mg/l
	Sewage treatment plant	580 mg/l
	Fresh water sediment	3,6 mg/kg dry weight (d.w.)
	Marine sediment	2,9 mg/kg dry weight (d.w.)
	Soil	0,63 mg/kg dry weight (d.w.)
	Oral (Secondary Poisoning)	380 mg/kg food
Dimethyl ether	Fresh water	0,155 mg/l
	Marine water	0,016 mg/l
	Intermittent use/release	1,549 mg/l

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



# PC PRIMER - 250 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.09.2022

 6.0
 08.06.2023
 10620159-00012
 Date of first issue: 20.11.2012

Sewage treatment plant	160 mg/l
Fresh water sediment	0,681 mg/kg dry weight (d.w.)
Marine sediment	0,069 mg/kg dry weight (d.w.)
Soil	0,045 mg/kg dry weight (d.w.)

#### 8.2 Exposure controls

#### **Engineering measures**

Processing may form hazardous compounds (see section 10).

Minimize workplace exposure concentrations.

If sufficient ventilation is unavailable, use with local exhaust ventilation.

If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

# Personal protective equipment

Eye/face protection : Wear the following personal protective equipment:

Safety goggles

Equipment should conform to DIN EN 166

Hand protection

Material : butyl-rubber
Break through time : <= 15 min
Glove thickness : 0,7 mm

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Wear the following personal protective equipment:

If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic

protective clothing.

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

Respiratory protection : If adequate local exhaust ventilation is not available or expo-

sure assessment demonstrates exposures outside the rec-

ommended guidelines, use respiratory protection.

Equipment should conform to DIN EN 137

Filter type : Self-contained breathing apparatus

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



# PC PRIMER - 250 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.09.2022

 6.0
 08.06.2023
 10620159-00012
 Date of first issue: 20.11.2012

# **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and chemical properties

Physical state : aerosol

Propellant : Dimethyl ether

Colour : colourless

Odour : characteristic

Odour Threshold : No data available

Melting point/freezing point : Not applicable

Initial boiling point and boiling

range

Not applicable

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper

flammability limit

18,6 %(V)

Lower explosion limit / Lower

flammability limit

3,0 %(V)

Flash point : Not applicable

Auto-ignition temperature : 235 °C

Decomposition temperature : No data available

pH : Solvent mixture; pH value determination not possible, no

aqueous solution

Viscosity

Viscosity, kinematic : Not applicable

Solubility(ies)

Water solubility : partly miscible

Partition coefficient: n-

octanol/water

: Not applicable

Vapour pressure : 3.400 hPa (20 °C)

Relative density : No data available

Relative vapour density : Not applicable

Particle characteristics

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



### PC PRIMER - 250 ML

Version Revision Date: SDS Number: Date of last issue: 06.09.2022 6.0 08.06.2023 10620159-00012 Date of first issue: 20.11.2012

Particle size : Not applicable

9.2 Other information

Explosives : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Evaporation rate : Not applicable

### **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

Not classified as a reactivity hazard.

#### 10.2 Chemical stability

Stable under normal conditions.

# 10.3 Possibility of hazardous reactions

Hazardous reactions : Extremely flammable aerosol.

Vapours may form explosive mixture with air.

If the temperature rises there is danger of the vessels bursting

due to the high vapor pressure.

Can react with strong oxidizing agents.

Hazardous decomposition products will be formed at elevated

temperatures.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

### 10.6 Hazardous decomposition products

Thermal decomposition : Formaldehyde

Methanol

# **SECTION 11: Toxicological information**

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of : Inhalation

exposure Skin contact

Ingestion Eye contact

#### **Acute toxicity**

Not classified based on available information.

# **Product:**

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



### PC PRIMER - 250 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.09.2022

 6.0
 08.06.2023
 10620159-00012
 Date of first issue: 20.11.2012

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

**Components:** 

Dimethyl ether:

Acute inhalation toxicity : LC50 (Rat): 164000 ppm

Exposure time: 4 h
Test atmosphere: gas

**Ethanol:** 

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 124,7 mg/l

Exposure time: 4 h
Test atmosphere: vapour

1-Pentanol:

Acute oral toxicity : LD50 (Rat): 3.645 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 11 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Expert judgement

Remarks: Based on national or regional regulation.

Acute dermal toxicity : LD50 (Rabbit): 2.292 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

Ethanol:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

1-Pentanol:

Species : Rabbit Result : Skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



### PC PRIMER - 250 ML

Version Revision Date: SDS Number: Date of last issue: 06.09.2022 6.0 08.06.2023 10620159-00012 Date of first issue: 20.11.2012

**Components:** 

**Ethanol:** 

Species : Rabbit

Method : OECD Test Guideline 405

Result : Irritation to eyes, reversing within 21 days

1-Pentanol:

Species : Rabbit

Result : Irreversible effects on the eye

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

**Ethanol:** 

Test Type : Local lymph node assay (LLNA)

Exposure routes : Skin contact
Species : Mouse
Result : negative

Germ cell mutagenicity

Not classified based on available information.

**Components:** 

Dimethyl ether:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Genotoxicity in vivo : Test Type: Sex-linked recessive lethal test in Drosophila mel-

anogaster (in vivo)

Application Route: inhalation (gas)

Result: negative

**Ethanol:** 

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



### PC PRIMER - 250 ML

Version Revision Date: SDS Number: Date of last issue: 06.09.2022 6.0 08.06.2023 10620159-00012 Date of first issue: 20.11.2012

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Result: negative

Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)

Species: Mouse

Application Route: Ingestion

Result: equivocal

1-Pentanol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: Chromosomal aberration

Result: negative

Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test

Result: negative

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Ingestion Method: OECD Test Guideline 474

Result: negative

Remarks: Based on data from similar materials

### Carcinogenicity

Not classified based on available information.

### **Components:**

Dimethyl ether:

Species : Rat

Application Route : inhalation (vapour)

Exposure time : 2 Years Result : negative

# Reproductive toxicity

Not classified based on available information.

### **Components:**

Dimethyl ether:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: inhalation (vapour)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



### PC PRIMER - 250 ML

Version Revision Date: SDS Number: Date of last issue: 06.09.2022 6.0 08.06.2023 10620159-00012 Date of first issue: 20.11.2012

Result: negative

Effects on foetal develop-

ment

: Test Type: Embryo-foetal development

Species: Rat

Application Route: inhalation (vapour)

Result: negative

**Ethanol:** 

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Mouse

Application Route: Ingestion

Result: negative

1-Pentanol:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

Remarks: Based on data from similar materials

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: inhalation (vapour)

Result: negative

# STOT - single exposure

May cause drowsiness or dizziness.

# **Components:**

Dimethyl ether:

Assessment : May cause drowsiness or dizziness.

1-Pentanol:

Assessment : May cause respiratory irritation.

#### STOT - repeated exposure

Not classified based on available information.

### Repeated dose toxicity

#### **Components:**

#### Dimethyl ether:

Species : Rat NOAEL : 47,11 mg/l

Application Route : inhalation (vapour)

Exposure time : 2 yr

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



### PC PRIMER - 250 ML

Version Revision Date: SDS Number: Date of last issue: 06.09.2022 6.0 08.06.2023 10620159-00012 Date of first issue: 20.11.2012

**Ethanol:** 

Species : Rat

NOAEL : 1.280 mg/kg LOAEL : 3.156 mg/kg Application Route : Ingestion Exposure time : 90 Days

1-Pentanol:

Species : Rat

NOAEL : > 1.000 mg/kg
Application Route : Ingestion
Exposure time : 13 Weeks

#### **Aspiration toxicity**

Not classified based on available information.

#### Components:

### 1-Pentanol:

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

# 11.2 Information on other hazards

### **Endocrine disrupting properties**

**Product:** 

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

# **SECTION 12: Ecological information**

#### 12.1 Toxicity

#### **Components:**

Dimethyl ether:

Toxicity to fish : LC50 (Poecilia reticulata (guppy)): > 4.100 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 4.400 mg/l

Exposure time: 48 h

Toxicity to microorganisms : EC10 (Pseudomonas putida): > 1.600 mg/l

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



### PC PRIMER - 250 ML

Version Revision Date: SDS Number: Date of last issue: 06.09.2022 6.0 08.06.2023 10620159-00012 Date of first issue: 20.11.2012

**Ethanol:** 

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 1.000 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Ceriodaphnia (water flea)): > 1.000 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

ErC50 (Chlorella vulgaris (Fresh water algae)): 275 mg/l

Exposure time: 72 h

EC10 (Chlorella vulgaris (Fresh water algae)): 11,5 mg/l

Exposure time: 72 h

Toxicity to microorganisms : EC50 (Pseudomonas putida): 6.500 mg/l

Exposure time: 16 h

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

NOEC: 9,6 mg/l Exposure time: 9 d

Species: Daphnia magna (Water flea)

1-Pentanol:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 530 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 341,21 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): > 100

ma/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

EC10 (Pseudokirchneriella subcapitata (green algae)): > 1

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to microorganisms : EC50 : > 1.000 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Remarks: Based on data from similar materials

EC10 : > 100 mg/l Exposure time: 3 h

Method: OECD Test Guideline 209

Remarks: Based on data from similar materials

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



# PC PRIMER - 250 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.09.2022

 6.0
 08.06.2023
 10620159-00012
 Date of first issue: 20.11.2012

#### 12.2 Persistence and degradability

**Components:** 

Dimethyl ether:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 5 % Exposure time: 28 d

Method: OECD Test Guideline 301D

**Ethanol:** 

Biodegradability : Result: Readily biodegradable.

Biodegradation: 84 % Exposure time: 20 d

1-Pentanol:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 80 - 90 % Exposure time: 28 d

### 12.3 Bioaccumulative potential

**Components:** 

Dimethyl ether:

Partition coefficient: n-

octanol/water

log Pow: 0,2

**Ethanol:** 

Partition coefficient: n-

octanol/water

log Pow: -0,35

1-Pentanol:

Partition coefficient: n-

octanol/water

log Pow: 1,44

### 12.4 Mobility in soil

No data available

# 12.5 Results of PBT and vPvB assessment

**Product:** 

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



### PC PRIMER - 250 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.09.2022

 6.0
 08.06.2023
 10620159-00012
 Date of first issue: 20.11.2012

### 12.6 Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

#### 12.7 Other adverse effects

No data available

# **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.

According to the European Waste Catalogue, Waste Codes

are not product specific, but application specific.

Waste codes should be assigned by the user, preferably in

discussion with the waste disposal authorities.

Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product. Please ensure aerosol cans are sprayed completely empty

(including propellant)

Waste Code : The following Waste Codes are only suggestions:

used product

08 01 11, waste paint and varnish containing organic solvents

or other hazardous substances

16 05 04, gases in pressure containers (including halons)

containing hazardous substances

unused product

08 01 11, waste paint and varnish containing organic solvents

or other hazardous substances

16 05 04, gases in pressure containers (including halons)

containing hazardous substances

uncleaned packagings

15 01 10, packaging containing residues of or contaminated

by hazardous substances

Acc. Packaging Act properly emptied packaging: Properly emptied, non-contaminated packaging of non-

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



# PC PRIMER - 250 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.09.2022

 6.0
 08.06.2023
 10620159-00012
 Date of first issue: 20.11.2012

hazardous products can be supplied to a system for the collection of sales packaging.

# **SECTION 14: Transport information**

### 14.1 UN number or ID number

ADN : UN 1950
ADR : UN 1950
RID : UN 1950
IMDG : UN 1950
IATA : UN 1950

# 14.2 UN proper shipping name

ADN : AEROSOLS
ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS

IATA : Aerosols, flammable

# 14.3 Transport hazard class(es)

Class Subsidiary risks

ADN : 2 2.1

ADR : 2 2.1

RID : 2 2.1

IMDG : 2.1

2.1

# 14.4 Packing group

# ADN

**IATA** 

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1

**ADR** 

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1 Tunnel restriction code : (D)

RID

Packing group : Not assigned by regulation

Classification Code : 5F Hazard Identification Number : 23 Labels : 2.1

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



### PC PRIMER - 250 ML

Version Revision Date: SDS Number: Date of last issue: 06.09.2022 6.0 08.06.2023 10620159-00012 Date of first issue: 20.11.2012

**IMDG** 

Packing group : Not assigned by regulation

Labels : 2.1 EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo : 203

aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

IATA (Passenger)

Packing instruction (passen- : 203

ger aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

14.5 Environmental hazards

ADN

Environmentally hazardous : no

**ADR** 

Environmentally hazardous : no

RID

Environmentally hazardous : no

**IMDG** 

Marine pollutant : no

# 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

# 14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

# **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 75

If you intend to use this product as tattoo ink, please contact your ven-

dor.

REACH - Candidate List of Substances of Very High : Not applicable

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



### PC PRIMER - 250 ML

Version Revision Date: SDS Number: Date of last issue: 06.09.2022 6.0 08.06.2023 10620159-00012 Date of first issue: 20.11.2012

Concern for Authorisation (Article 59).

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

: Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

: Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P3a Quantity 1 Quantity 2
FLAMMABLE AEROSOLS 150 t 500 t

Water hazard class (Germa-

nv)

WGK 1 slightly hazardous to water

Classification according to AwSV, Annex 1 (5.2)

Volatile organic compounds : Directive 2004/42/EC

VOC content in g/l: 647 g/l

Product sub-category: Special finishes

Coatings: All types

VOC limit level 1 (2007): 840 g/l

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 60,82 %, 647 g/l

Remarks: VOC content excluding water

#### Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

### 15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

Other information : Items where changes have been made to the previous version

are highlighted in the body of this document by two vertical

lines.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



### PC PRIMER - 250 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.09.2022

 6.0
 08.06.2023
 10620159-00012
 Date of first issue: 20.11.2012

#### **Full text of H-Statements**

H220 : Extremely flammable gas.

H225 : Highly flammable liquid and vapour.
H226 : Flammable liquid and vapour.

H280 : Contains gas under pressure; may explode if heated.

H315 : Causes skin irritation.

H318 : Causes serious eye damage. H319 : Causes serious eye irritation.

H332 : Harmful if inhaled.

H335 : May cause respiratory irritation. H336 : May cause drowsiness or dizziness.

#### Full text of other abbreviations

Acute Tox. : Acute toxicity

Eye Dam. : Serious eye damage

Eye Irrit. : Eye irritation
Flam. Gas : Flammable gases
Flam. Liq. : Flammable liquids
Press. Gas : Gases under pressure

Skin Irrit. : Skin irritation

STOT SE : Specific target organ toxicity - single exposure

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values

2004/37/EC : Europe. Directive 2004/37/EC on the protection of workers

from the risks related to exposure to carcinogens or mutagens

at work

2006/15/EC : Europe. Indicative occupational exposure limit values
DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

2000/39/EC / TWA : Limit Value - eight hours 2004/37/EC / STEL : Short term exposure limit 2004/37/EC / TWA : Long term exposure limit 2006/15/EC / TWA : Limit Value - eight hours DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified;

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



### PC PRIMER - 250 ML

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06.09.2022

 6.0
 08.06.2023
 10620159-00012
 Date of first issue: 20.11.2012

NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

#### **Further information**

Sources of key data used to compile the Safety Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

#### Classification of the mixture:

#### Classification procedure:

Aerosol 1 H222, H229 Based on product data or assessment

Eye Irrit. 2 H319 Calculation method STOT SE 3 H336 Calculation method

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN